ARCHIPELAGO LIGHTING GROUP

DATASHEET

PIR DETECTION	**13FT** MAX HEIGHT
IP20 IP RATING	**10-15Vdc** INPUT VOLTAGE
UL CERTIFICATION	**Bi-Level** PLATFORM

CONTRⒶLS · BI-LEVEL

MSP-HTI/08P1/BLS

Occupancy Sensor | Indoor | PIR | Icarus-III | 1-Pin

Indoor PIR occupancy sensor with Icarus-III form factor. IR remote configurable with 1-pin audio jack connection. Passive infrared detection for standard commercial ceiling heights.

TECHNICAL SPECIFICATIONS

Detection Technology	Passive Infrared (PIR)	IP Rating	IP20
Input Voltage	10-15Vdc	Certification	UL Listed
Max Mounting Height	13FT (4m)	Connector	1-Pin Audio Jack
Detection Range	Adjustable via IR	Commissioning	IR Remote
Hold Time	5s – 30min	Operating Temp	-20°C to +50°C
Daylight Harvesting	Yes (10-2000 Lux)	Finish	White
Stand-by Dimming	10% – 100%	DLC / NLC	No (Standalone)

FEATURES

- Passive infrared motion detection
- Adjustable sensitivity and hold time
- Stand-by dimming level adjustable
- Icarus-III compact form factor
- Heat-based motion detection
- IR remote commissioning (RM-HT series)
- Built-in daylight harvesting sensor
- Plug-and-play 1-pin connection
- No wiring required
- Walk-through test mode

COMPATIBLE LUMINAIRE FAMILIES

lamparⒶRCH (UFO High Bay) | planoⒶRCH (Troffers & Panels) | selectⒶRCH (Strips & Wraps) | LLHB/Tiny-I (Linear High Bay) | LV3P (Vapor Tight)

COMPATIBLE REMOTES

RM-HT/03S · 3-Button | RM-HT/05S · 5-Button Dimming | RM-HT/06S · LCD Full Config

ORDERING INFORMATION

SKU	MSP-HTI/08P1/BLS
UPC	819313024357
Case Quantity	—
Case Dimensions	—
Case Weight	—
Brand	contrⒶLS
Platform	Bi-Level
Manufacturer	Archipelago Lighting Group