ARCHIPELAGO LIGHTING GROUP

DATASHEET

BLE Mesh COMMUNICATION	**13FT** MAX HEIGHT
IP20 IP RATING	**12-24Vdc** INPUT VOLTAGE
UL CERTIFICATION	**SILVAIR** PLATFORM

— CONTRⒶLS · BY SILVAIR

MSP-HTI/08P1/NLC

Occupancy Sensor | Indoor | NLC | Silvair | PIR | 1-Pin

Indoor PIR sensor for Silvair enterprise NLC platform. Icarus-III form factor with BLE mesh networking. 1-pin audio jack connection with unlimited scalability.

TECHNICAL SPECIFICATIONS

Detection Technology	**Passive Infrared (PIR)**	IP Rating	**IP20**
Input Voltage	**12-24Vdc**	Certification	**UL Listed**
Max Mounting Height	**13FT (4m)**	Connector	**1-Pin Audio Jack**
Network	**Bluetooth Mesh (Silvair)**	Commissioning	**Silvair App**
Scalability	**Unlimited nodes**	Operating Temp	**-20°C to +50°C**
DLC NLC	**Qualified**	Finish	**White**
BMS Integration	**Open APIs**	Application	**Fixture**

FEATURES

- Silvair-certified BLE mesh
- Unlimited scalability
- BMS integration via APIs
- Granular zone control
- 1-pin audio jack
- PIR motion detection
- Enterprise NLC platform
- Silvair app commissioning
- Daylight harvesting
- Icarus-III form factor

COMPATIBLE LUMINAIRE FAMILIES

All ALG luminaire families

ORDERING INFORMATION

SKU	MSP-HTI/08P1/NLC
UPC	—
Case Quantity	—
Case Dimensions	—
Case Weight	—
Brand	**contrⒶLS**
Platform	**by SILVAIR**
Manufacturer	**Archipelago Lighting Group**