



Aircraft Flight Dynamics and Control

Flight Course Assignment

Author: James Bray

Registration: 220123839

Contents

Introduction.....	2
Context.....	2
Objectives.....	2
Comparison of Cessna 172 and Beechcraft Starship 2000+.....	3
Design Features.....	3
Stability Aspects.....	4
Longitudinal Stability of the Cessna 172.....	5
Aircraft Dynamic Modes.....	6
Short-Period Mode.....	6
Phugoid Mode.....	7
Dutch Roll Mode.....	8
Effects on real-world handling.....	8
Flight Testing: Purpose and Importance.....	9
Case Study: Beechcraft Bonanza V-Tail.....	9
Conclusions.....	10
References.....	11
Information.....	11
Figures.....	11

Introduction

Context

Aircraft flight dynamics and control is an important field in aerospace that ensures fixed-wing aircraft can fly safely. Stability and control are a primary concern when designing an aircraft as they affect performance and safety. This report focuses on the comparison of two aircraft, the Cessna 172 and the Beechcraft Starship 2000+.



Figure 1.1 - Cessna 172 over a desert



Figure 1.2 - Beechcraft Starship 2000 over a desert

The Cessna 172, introduced in 1956, is one of the most successful aircraft in history, with over 44,000 units produced. Designed as a stable, easy-to-fly training and general aviation plane, its high-wing design, forgiving flight characteristics, and mechanical simplicity made it widely adopted. Its ongoing success is attributed to its reliability, affordability, and adaptability, with updated models still in production. [\[2\]](#)

In contrast, the Beechcraft Starship 2000+, launched in the 1980s, aimed to revolutionise business aviation with its composite airframe, canard design, and advanced avionics. Despite its potential, high production costs and certification challenges led to its commercial failure, with only 53 units built. However, the Starship influenced later aircraft designs by advancing composite materials and aerodynamics. [\[3\]](#)

Objectives

The primary objective of this report is to analyse the longitudinal static stability and manoeuvre stability of the Cessna 172 and Beechcraft Starship 2000+, using theoretical principles, flight test data, and stability calculations. Specifically, this report aims to:

- Compare the design, control systems, and stability characteristics of both aircraft.
- Evaluate longitudinal static stability using the given flight test data and graphs.
- Calculate and analyse the neutral points for stick-fixed stability.
- Discuss manoeuvre stability and its significance in aircraft control.
- Examine the dynamic modes of flight and their key parameters.
- Assess the role and importance of flight testing in aircraft stability analysis.

By conducting these analyses, this report will provide an understanding of how stability principles apply to real-world aircraft and their implications for design and flight operations.

Comparison of Cessna 172 and Beechcraft Starship 2000+

Design Features




Figure 2.1 - Cessna plan view




Figure 2.2 - Starship plan view

The Cessna 172 and Beechcraft Starship 2000+ differ fundamentally in design. The Cessna uses a high-wing, straight-wing configuration with a conventional tail, prioritising passive stability and simplicity. In contrast, the Starship employs a swept-wing, canard layout with fly-by-wire controls to enhance performance at the cost of inherent stability.

Feature	Cessna 172	Beechcraft Starship 2000+
Airframe Layout	High-wing, single-engine aircraft with a conventional tail. Designed for stability and ease of control, ideal for general aviation and training. [2]	Twin-turboprop, canard-configured airframe. The forward wing enhances stall resistance by shifting the CG forward. [6]
Wing Design	Straight wing with moderate aspect ratio, optimised for low-speed stability and predictable stall characteristics. High-wing placement improves roll stability and reduces ground effect.	Delta wing design reduces drag at high speeds and enhances stall resistance. [7] Testing showed some issues with the canard wake interfering with the airflow to the main wings.
Tail Configuration	Conventional horizontal stabiliser positioned at the rear, generating a downward balancing force for pitch stability. Naturally returns to equilibrium after disturbances.	Replaces conventional tail with a canard and twin vertical stabilisers at wingtips. Requires precise aerodynamic balance due to the absence of a traditional stabiliser. [6]
Control System	Mechanical (cables/pulleys), providing direct pilot feedback. Simple and reliable. [6]	Fly-by-wire with mechanical backup. Enhances precision and compensates for reduced inherent stability.

Table 1 - Comparison of design features between the Cessna and the Starship

Stability Aspects




Figure 3.1 - Cessna Moment Diagram




Figure 3.2 - Starship Moment Diagram

The Cessna 172 and Beechcraft Starship 2000+ adopt opposing philosophies in stability design. The Cessna prioritises passive stability through conventional aerodynamic principles: its high static margin, mechanical controls, and dihedral effects ensure predictable recovery from disturbances. Conversely, the Starship sacrifices natural stability for performance, relying on fly-by-wire systems to actively mitigate instability caused by its forward CG, canard configuration, and swept-wing aerodynamics. While the Cessna excels in forgiving handling and passive damping, the Starship's advanced systems enable agility at the cost of increased pilot dependency and system complexity.

Feature	Cessna 172	Beechcraft Starship 2000+
Longitudinal Stability (Pitch)	CG is located near the main wing spar, allowing a natural balance between lift and stability. Its tailplane provides a statically stable downward force. [2]	Low inherent stability, therefore relies on fly-by-wire systems to compensate. Forward CG and canard reduce the static margin.
Lateral Stability (Roll)	High-wing design provides inherent roll stability. Dihedral effect counters disturbances passively.	Swept wings and low-wing placement reduce passive stability. Relies on active control systems for roll damping. [7]
Directional Stability (Yaw)	Large vertical stabiliser and vertical fin ensure strong yaw damping. Dutch roll oscillations dissipate quickly (~10 seconds). [1]	Wingtip-mounted vertical stabilisers reduce yaw damping efficiency. Requires fly-by-wire systems to mitigate oscillations.
Manoeuvre Stability	High "stick force per g" ensures predictable control forces, preventing overcontrol during aggressive maneuvers.	A fly-by-wire system artificially augments stability, enabling rapid responses but requiring precise pilot inputs. [6]
Control Feedback	The mechanical system provides direct feedback, enhancing pilot awareness of stability limits. [6]	Fly-by-wire filters feedback to avoid oscillations, reducing pilot workload but masking inherent instability.

Table 2 - Comparison of stability aspects of the Cessna and the Starship

Longitudinal Stability of the Cessna 172

Longitudinal static stability refers to an aircraft's ability to return to equilibrium after pitch disturbances without pilot input. For the Cessna 172, this stability is quantified by determining its neutral point. The neutral point marks the CG position where longitudinal static stability transitions to neutrality. It was calculated using 5 stick-fixed X-Plane simulations by plotting elevator deflection vs. lift coefficient for multiple CG positions (Figure 4.1), then extrapolating to zero deflection gradient (Figure 4.2). Properties of the aircraft and stability criteria are found using equation set 1.

$$NP = CG - \frac{Cm_{\alpha}}{Cl_{\alpha}} \cdot c$$

Eq. 1.1 - Neutral point

$$\text{Static Margin} = \frac{NP - CG}{c} \times 100$$

Eq. 1.2 - Static Margin

$$\frac{\partial C_m}{\partial \alpha} < 0$$

Eq. 1.3 - Restoring moment

Elevator Deflection vs Lift Coefficient




Figure 4.1 - Elevator deflection vs Lift Coefficient

Deflection Gradient vs CG Position




Figure 4.2 - Deflection Gradient vs CG Position

Group	Deflection Gradient	CG (%MAC)	Static Margin
A	-7.35	29.42%	19.97%
B	-7.5	28.27%	21.13%
C	-7.14	26.18%	23.21%
D	-5.27	33.02%	16.38%
E	-5.73	30.70%	18.70%

Table 3.1 - Static margin calculation [\[1\]](#)

Neutral Point (%MAC)	
49.39%	
CG Limits	
Forward	Aft
25.55%	46.29%

Table 3.3 - CG Limits [\[1\]](#)

Longitudinal static stability ensures that an aircraft naturally counteracts pitch disturbances without pilot input, which is critical for safe flight. The neutral point, where the aircraft becomes neutrally stable, was calculated using five CG positions (Groups A-E). Figure 4.1 shows elevator deflection trends, with negative slopes confirming static stability. A forward CG increases the stabiliser’s restoring moment, as seen in Group D (static margin: 16.38%) versus Group C (23.21%).

Aircraft Dynamic Modes

Aircraft respond to disturbances or control inputs through distinct dynamic modes, either oscillatory or non-oscillatory behaviors governed by their design and flight conditions. These modes are critical for understanding stability, handling qualities, and safety. There are three types of responses covered in this report:

- **Short-Period Mode:** Rapid pitch oscillations (~1s period) driven by elevator inputs. Damping is crucial to prevent pilot-induced oscillations.
- **Phugoid Mode:** Long period (~20–100s) exchanges between altitude and speed, which are lightly damped oscillations.
- **Dutch Roll:** Coupled yaw-roll oscillations requiring quick damping for directional stability.

This section analyses these modes using simulation data (e.g., pitch rate vs. time graphs), calculating damping ratios (ζ) and natural frequencies (ω_n) to quantify stability characteristics. These values are calculated using equation set 2.

$$\delta = \frac{1}{(n-1)} \ln \left(\frac{A_1}{A_n} \right)$$

Eq. 2.1 - logarithmic decrement

$$\zeta = \frac{\delta}{\sqrt{4\pi^2 + \delta^2}}$$

Eq. 2.2 - damping ratio

$$\omega_d = \frac{2\pi(n-1)}{t_n - t_1}$$

Eq. 2.3 - damped frequency

$$\omega_n = \frac{\omega_d}{\sqrt{1 - \zeta^2}}$$

Eq. 2.4 - natural frequency

Short-Period Mode

The short-period mode was analysed using X-Plane flight simulations, which recorded pitch rate responses to elevator inputs. The resulting oscillations (Figure 5) exhibit rapid pitch deviations with a period of ~1–2 seconds, characteristic of this high-frequency mode. The tables and figures below represent the extracted peak amplitudes and time intervals from Flight A, used to calculate damping parameters (ζ , ω_n).

Short Period Oscillations




Figure 5 - Short Period Oscillations

A	
Time (s)	Peak
1.67	2.35
3.70	13.49
5.48	1.43

Table 4.1 - Flight A Peaks [\[1\]](#)

δ	2.244
ζ	0.336
ω_d	3.520
ω_n	3.738

Table 4.2 - Flight A Properties [\[1\]](#)

Due to limited data resolution, only Flight A provided measurable peaks for analysis (Table 4.1). The first peak was excluded from calculations as its amplitude was significantly below the peaks after it. The remaining values confirm strong damping, critical for avoiding pilot-induced oscillations in training aircraft like the Cessna 172.

Phugoid Mode

The analysis of the phugoid state of an aircraft is important as it outlines the longitudinal dynamic behaviour. A lightly damped phugoid mode, while not critical for safety, provides insight into the aircraft's energy exchange between kinetic and potential energy during flight. It also highlights the aircraft's natural tendency to return to equilibrium after disturbances without pilot intervention.

Phugoid States




Figure 6 - Phugoid behaviours recorded on X-Plane

The phugoid mode was analysed using flight data recorded from these X-Plane simulations. The damping ratio (ξ) and natural frequency (ω_n) were calculated using equation set 2, as shown in Table 5. The lightly damped phugoid ($\zeta=0.05-0.08$) confirms expected energy-exchange behavior.

A		B		C		D		E	
Time	Peak	Time	Peak	Time	Peak	Time	Peak	Time	Peak
14.08	9.51	12.18	16.68	12.45	13.60	9.53	10.12	24.30	6.82
37.26	7.43	35.53	8.89	38.07	10.95	33.59	5.96	46.66	5.90
60.24	5.42	58.90	6.79	62.13	7.02	57.35	4.92	70.56	3.30
81.68	3.86	82.03	4.01	87.83	4.95	80.26	2.20	92.39	2.69

Table 5.1 - Pitch peaks extracted from the flight simulations [1]

δ	0.301	δ	0.475	δ	0.337	δ	0.508	δ	0.310
ζ	0.048	ζ	0.075	ζ	0.054	ζ	0.081	ζ	0.049
ω_d	0.279	ω_d	0.270	ω_d	0.250	ω_d	0.267	ω_d	0.277
ω_n	0.279	ω_n	0.271	ω_n	0.250	ω_n	0.267	ω_n	0.277

Table 5.2 - Calculation of frequency and damping ratio via peak detection [1]

While the short-period mode involves rapid pitch oscillations driven by elevator inputs and requires strong damping for controllability, the phugoid mode reflects slow, energy-based exchanges between altitude and airspeed. The Cessna 172's phugoid damping ratios ($\zeta \approx 0.048-0.081$) confirm its lightly damped but benign long-period behavior, typical of conventional aircraft. In contrast, the short-period mode's higher damping ($\zeta = 0.336$) ensures quick recovery from sudden disturbances, highlighting how the aircraft's design prioritises stability across both dynamic regimes.

Dutch Roll Mode

The Dutch roll is a coupled lateral-directional oscillation involving alternating yaw and roll motions, critical for assessing an aircraft's directional stability. For the Cessna 172, this mode is typically well-damped due to its high-wing design and large vertical stabiliser (Figure 3.1), which provides strong passive stability.

Dutch Roll Characteristics




Figure 7 - Dutch roll characteristics recorded on X-Plane

The Cessna's Dutch roll damping is robust (damping ratio $\zeta \approx 0.3\text{--}0.5$), attributed to its large vertical stabiliser and high-wing dihedral effect. Flight tests (Figure 7) show oscillations dissipating within ~ 10 seconds post-disturbance. Conversely, the Starship's wingtip-mounted vertical stabilisers and swept wings reduce yaw damping, necessitating active control systems to mitigate oscillations. Without these systems, the Dutch roll would exhibit weak damping ($\zeta < 0.1$), risking pilot-induced instability.

Additionally, due to the Starship's swept wing design, it is significantly less directionally and laterally stable than the Cessna. This is because when there's a directional disturbance, one of the wings aligns more with the relative wind and increases lift, which causes the aircraft to roll. Without the advanced control systems preventing over-control and damping oscillations, this aircraft would be unflyable. [7]

Effects on real-world handling

The dynamic modes profoundly influence aircraft handling. The Cessna 172's short-period damping ($\zeta = 0.336$) ensures quick pitch recovery, ideal for training. In contrast, the Starship's fly-by-wire compensates for weaker inherent stability, demanding precise inputs. The phugoid's light damping ($\zeta \approx 0.05\text{--}0.08$) requires subtle corrections, affecting steady flight efficiency. Meanwhile, the Cessna's Dutch roll damping ($\zeta \approx 0.3\text{--}0.5$) minimises oscillations passively, whereas the Starship's design risks instability without active systems.

These nuances highlight why simulations alone fall short, as real-world variables like turbulence or control delays (as seen in the Bonanza V-Tail's unanticipated coupling) necessitate flight testing to validate safety and handling.

Flight Testing: Purpose and Importance

Flight testing is a vital phase in aircraft development, offering real-world validation of aerodynamic behaviour, handling qualities, and system performance. While modern simulations and computational tools are powerful, they rely on assumptions and idealised conditions. Flight testing exposes the aircraft to real operational variables, such as turbulence, control surface flexibility, and pilot inputs, which may reveal issues not captured in simulation.

Simulations cannot fully replicate complex phenomena like aeroelasticity, control coupling, or gust response. Therefore, flight testing is essential to confirm theoretical predictions, particularly for stability and control characteristics. For this report, which investigates longitudinal stability, flight data is necessary to validate calculated parameters such as static margin, damping ratio, and trim conditions. It also ensures that safety and handling meet certification standards, making flight testing a cornerstone of responsible aircraft design.

Case Study: Beechcraft Bonanza V-Tail

The Beechcraft Bonanza V-Tail, a light aircraft similar in class to the Cessna 172, experienced multiple in-flight breakups in its early service years. Designed in the 1940s with a distinctive V-tail to reduce drag, it suffered from structural failures, especially in turbulent conditions. The combined rudder and elevator surfaces, called "ruddervators", introduced unexpected pitch-yaw coupling that was not fully understood during initial testing. [\[8\]](#)



Figure 8 - Beechcraft Bonanza V-Tail

These instabilities, often triggered by turbulence or abrupt pilot inputs, revealed insufficient damping and structural stiffness in the tail. Additionally, the aircraft was known for its narrow CG envelope, which perhaps contributed to its many crashes. Many of the issues were not predicted by simulation or wind tunnel testing, highlighting the limitations of early modelling techniques. As a result, modifications were made and stricter operational limits introduced. This case underscores the importance of comprehensive flight testing to identify dynamic stability issues and prevent potentially catastrophic failures. [\[8\]](#)

Conclusions

This report analysed the longitudinal static stability, dynamic modes, and flight testing significance of the Cessna 172 and Beechcraft Starship 2000+. The Cessna 172's conventional design, with a neutral point at 49.39% MAC and static margins of 16–23%, ensures inherent stability, enabling predictable recovery from disturbances. Its mechanical controls and high-wing configuration contribute to strong damping in dynamic modes (e.g. short-period damping ratio $\zeta = 0.336$), critical for pilot training. Conversely, the Starship's canard layout and fly-by-wire system prioritise agility over passive stability, necessitating active control to mitigate weak yaw damping ($\zeta < 0.1$) and reduced static margins.

Flight testing proved indispensable for validating stability parameters, particularly for unconventional designs like the Starship. While simulations provided preliminary data, real-world testing captured nuances such as turbulence effects and control hysteresis, as demonstrated by the Beechcraft Bonanza V-Tail case study. This highlights the limitations of simulations in modeling complex phenomena like aeroelastic coupling.

The findings underscore a fundamental trade-off: conventional designs like the Cessna prioritise safety through passive stability, while innovative configurations like the Starship demand advanced systems to compensate for inherent instability. Future aircraft development must balance these priorities, with flight testing remaining indispensable for ensuring safety and performance.

References

Information

- [1] *Yorkshire Aero Club and the University of Sheffield, "Cessna 172 X-Plane Flight Data"*
Accessed 6 Apr 2025. (*Flight data provided alongside assignment details*)
- [2] *Wikipedia contributors, "Cessna 172," Wikipedia, The Free Encyclopedia*, Accessed 6 Apr 2025.
https://en.wikipedia.org/wiki/Cessna_172
- [3] *Wikipedia contributors, "Beechcraft Starship," Wikipedia, The Free Encyclopedia*, Accessed 6 Apr 2025.
https://en.wikipedia.org/wiki/Beechcraft_Starship
- [4] *Robert Scherer's Starship Resources, "Starship Airplane Flight Manual", Accessed 6 Apr 2025.*
<https://www.bobscherer.com/Files/Starship/Flight%20Deck%20Publications/Starship%20Airplane%20Flight%20Manual.pdf>
- [5] *Cessna, "Information Manual Skyhawk SP, Cessna Model 172S", Accessed 6 Apr 2025.*
<https://longislandaviators.com/wp-content/uploads/2017/10/Cessna-Information-Manual-C172S-Skyhawk-172SIM05.pdf>
- [6] *Barnes McCormack, "Aerodynamics, Aeronautics, and Flight Mechanics", Chapter 9: Static Stability and Control, pp. 478–484, Accessed 6 Apr 2025.*
https://www.academia.edu/39803770/Aerodynamics_Aeronautics_and_Flight_Mechanics_by_Barnes_McCormack?auto=download
- [7] *Beaubien-Taylor, Jared. (2016). "Characteristics & Aspects of Using Delta Wings for Subsonic & Supersonic Aircraft", Accessed 6 Apr 2025.*
https://www.researchgate.net/publication/301202010_Characteristics_Aspects_of_Using_Delta_Wings_for_Subsonic_Supersonic_Aircraft
- [8] *APOA Air Safety Foundation. (1994), "Bonanza Safety Review", Accessed 6 Apr 2025.*
<https://www.aopa.org/news-and-media/all-news/1994/february/pilot/bonanza-safety-review>

Figures

- [1.1] *JetEXE Aviation, "Cessna 172 over a desert", Accessed 6 Apr 2025.*
<https://www.jetexe.com/cessna-desert/>
- [1.2] *Pinterest, "Beechcraft Starship 2000 over a desert", Accessed 6 Apr 2025.*
<https://in.pinterest.com/pin/722968546466406199/>
- [2.1] *PlaneTags, "Cessna plan view", Accessed 6 Apr 2025.*
<https://planetags.com/products/cessna-172-n46373>
- [2.2] *PlaneTags, "Starship plan view", Accessed 6 Apr 2025.*
<https://planetags.com/blogs/planetags-blog/beechnraft-starship-an-aircraft-ahead-of-its-time>
- [3.1] *Wikipedia [1], "Cessna Moment Diagram" Accessed 6 Apr 2025.*
https://en.wikipedia.org/w/index.php?title=Cessna_172&oldid=1279471791
- [3.2] *Robert Scherer's Starship Resources, "Starship Moment Diagram", Accessed 6 Apr 2025.*
<https://www.bobscherer.com/Pages/Starship%20Resources.htm>
- [4] [5] [6] [7] *See information reference [1]*
- [8] *Flying Magazine, "Beechcraft Bonanza V-Tail", Accessed 6 Apr 2025.*
<https://www.flyingmag.com/air-compare-beechcraft-bonanza-vs-bonanza-v-tails/>