

Usage Guideline

HSBC_pain.001.001.03_LowValuePayment_UK BACS

HSBC_pain.001.001.03_LowValuePayment_Europe

This document describes a usage guideline restricting the base message **MX pain.001.001.03**. You can also consult [this information online](#).

Published by SWIFT and generated by [MyStandards](#).

12 December 2018

Table of Contents

Message Functionality 3

1 Restriction summary 4

2 Structure 5

3 Message Building Blocks 6

4 Message Components 8

5 Message Datatypes 139

Legal Notices 183

Message Functionality

Overview

BACS payments are domestic, non-urgent payments (ACH payments) in the United Kingdom of Great Britain and Northern Ireland. Processable amounts are limited by the credit limit set by the BACS clearing system only. If a client has more than one agreement with the BACS clearing system (and consequently multiple ID numbers), the BACS ID needs to be provided in the payment instruction.

The beneficiary account is addressed via the sort code of the beneficiary's bank and the (domestic) account number.

If the beneficiary holds an account with a Building Society that is not part of the BACS clearing, both the account number of the building society with its supporting bank and the "roll number" of the beneficiary account are required.

The reference information that can be passed on to the beneficiary is limited to 18 characters. The EndToEndIdentification is used to transport the reference. No further payment details can be supported with this payment type.

Payment files need to respect the 3-day clearing cycle of the BACS payments. Payment files should be with HSBC at least two working days before the requested execution date

Outline

The HSBC_pain.001.001.03_LowValuePayment_Europe / HSBC_pain.001.001.03_LowValuePayment_UK BACS message is composed of 2 building blocks

a. GroupHeader

Set of characteristics shared by all individual transactions included in the message.

b. PaymentInformation

Set of characteristics that applies to the debit side of the payment transactions included in the credit transfer initiation.

1 Restriction summary

This Usage Guideline restricts the pain.001.001.03 message.

Restriction Type	See page
Removed elements	11, 12, 35, 37, 76, 80, 119, 119, 143, 175
Make mandatory	35, 40, 42, 42, 58, 58, 59, 81, 85, 95, 102, 102, 107, 107
Reduce Multiplicity	70, 76, 76, 77, 77
Ignore	9, 9, 11, 13, 15, 16, 16, 17, 17, 20, 21, 21, 21, 21, 21, 22, 22, 28, 29, 29, 35, 36, 36, 37, 38, 38, 39, 39, 40, 43, 43, 44, 44, 47, 48, 49, 57, 58, 60, 60, 62, 62, 62, 63, 63, 63, 64, 65, 65, 65, 65, 65, 65, 67, 67, 71, 75, 75, 76, 78, 79, 79, 79, 80, 80, 81, 82, 83, 83, 83, 83, 84, 84, 84, 86, 87, 88, 88, 96, 97, 98, 99, 99, 101, 101, 106, 106, 106, 106, 106, 106, 109, 110, 111, 112, 113, 115, 116, 120, 120, 121, 124, 124, 125, 126, 128, 128, 128, 129, 130, 130, 130, 130, 131, 132, 132, 133, 133, 134, 134, 135, 136, 136, 136, 138, 145, 145, 145, 146, 146, 146, 146, 146, 146, 147, 147, 147, 147, 147, 148, 148, 148, 148, 148, 148, 149, 149, 178, 179, 179
Text rules	11, 30, 30, 41, 42, 66, 66, 81, 83, 89, 93, 129
Conditional rules	62, 66, 66
Fixed values	119, 139
Truncates	n.a.
Comments	46, 56, 60, 62, 69, 70, 70, 77, 89, 94, 94, 95, 96, 107, 108, 116, 118, 129, 143
Annotations	n.a.
Changed datatypes	n.a.
Extensions	n.a.
Synonyms	n.a.
Other restrictions	6

2 Structure

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	<i>CustomerCreditTransferInitiationV03</i>	<CstmrCdtTrfInitn>		[1..1]	⚠	6
1.0	GroupHeader	<GrpHdr>		[1..1]		6
1.1	MessageIdentification	<MsgId>		[1..1]	⚠	69
1.2	CreationDateTime	<CreDtTm>		[1..1]		69
1.3	Authorisation	<Authstn>		[0..2]	R[0..1]	69
1.6	NumberOfTransactions	<NbOfTx>		[1..1]	⚠	70
1.7	ControlSum	<CtrlSum>		[0..1]	⚠	70
1.8	InitiatingParty	<InitgPty>		[1..1]		71
1.9	ForwardingAgent	<FwdgAgt>		[0..1]	♦	71
2.0	PaymentInformation	<PmtInf>		[1..*]		6
2.1	PaymentInformationIdentification	<PmtInfId>		[1..1]	⚠	93
2.2	PaymentMethod	<PmtMtd>		[1..1]		93
2.3	BatchBooking	<BtchBookg>		[0..1]	⚠	94
2.4	NumberOfTransactions	<NbOfTx>		[0..1]		94
2.5	ControlSum	<CtrlSum>		[0..1]	⚠	94
2.6	PaymentTypeInformation	<PmtTplnf>		[0..1]	M	94
2.17	RequestedExecutionDate	<ReqdExctnDt>		[1..1]	⚠	95
2.18	PoolingAdjustmentDate	<PoolgAdjstmntDt>		[0..1]	♦	95
2.19	Debtor	<Dbtr>		[1..1]		96
2.20	DebtorAccount	<DbtrAcct>		[1..1]	⚠	96
2.21	DebtorAgent	<DbtrAgt>		[1..1]		97
2.22	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]	♦	97
2.23	UltimateDebtor	<UltmtDbtr>		[0..1]		97
2.24	ChargeBearer	<ChrgBr>		[0..1]	♦	98
2.25	ChargesAccount	<ChrgsAcct>		[0..1]	♦	98
2.26	ChargesAccountAgent	<ChrgsAcctAgt>		[0..1]	♦	99
2.27	CreditTransferTransactionInformation	<CdtTrfTxInf>		[1..*]		99

3 Message Building Blocks

Note The following chapter identifies the building blocks of the HSBC_pain.001.001.03_LowValuePayment_Europe / HSBC_pain.001.001.03_LowValuePayment_UK BACS message definition.

Usage Guideline on Root Node

- on pain.001.001.03/

- HSBC_BACSID_NAME:

For each [CustomerCreditTransferInitiationV03], if the following element(s) [PaymentInformation/UltimateDebtor/Identification/OrganisationIdentification/Other] is (are) present, then the following element(s) [PaymentInformation/UltimateDebtor/Name] must be present

3.1 GroupHeader

XML Tag: GrpHdr

Presence: [1..1]

Definition: Set of characteristics shared by all individual transactions included in the message.

The **GrpHdr** block contains the following elements (see datatype "GroupHeader32" on page 68 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1	MessageIdentification	<MsgId>		[1..1]	⚠	69
1.2	CreationDateTime	<CreDtTm>		[1..1]		69
1.3	Authorisation	<Authstn>		[0..2]	R[0..1]	69
1.6	NumberOfTransactions	<NbOfTx>		[1..1]	⚠	70
1.7	ControlSum	<CtrlSum>		[0..1]	⚠	70
1.8	InitiatingParty	<InitgPty>		[1..1]		71
1.9	ForwardingAgent	<FwdgAgt>		[0..1]	💡	71

3.2 PaymentInformation

XML Tag: PmtInf

Presence: [1..*]

Definition: Set of characteristics that applies to the debit side of the payment transactions included in the credit transfer initiation.

The **PmtInf** block contains the following elements (see datatype "PaymentInstructionInformation3__1" on page 89 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.1	PaymentInformationIdentification	<PmtInfId>		[1..1]	⚠️	93
2.2	PaymentMethod	<PmtMtd>		[1..1]		93
2.3	BatchBooking	<BtchBookg>		[0..1]	⚠️	94
2.4	NumberOfTransactions	<NbOfTx>		[0..1]		94
2.5	ControlSum	<CtrlSum>		[0..1]	⚠️	94
2.6	PaymentTypeInformation	<PmtTpInf>		[0..1]	M	94
2.17	RequestedExecutionDate	<ReqdExctnDt>		[1..1]	⚠️	95
2.18	PoolingAdjustmentDate	<PoolgAdjstmntDt>		[0..1]	💡	95
2.19	Debtor	<Dbtr>		[1..1]		96
2.20	DebtorAccount	<DbtrAcct>		[1..1]	⚠️	96
2.21	DebtorAgent	<DbtrAgt>		[1..1]		97
2.22	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]	💡	97
2.23	UltimateDebtor	<UltmtDbtr>		[0..1]		97
2.24	ChargeBearer	<ChrgBr>		[0..1]	💡	98
2.25	ChargesAccount	<ChrgsAcct>		[0..1]	💡	98
2.26	ChargesAccountAgent	<ChrgsAcctAgt>		[0..1]	💡	99
2.27	CreditTransferTransactionInformation	<CdtTrfTxInf>		[1..*]		99

4 Message Components

Note The following chapter identifies the message components.

4.1 AccountIdentification4Choice

Definition: Specifies the unique identification of an account as assigned by the account servicer.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.1	IBAN	<IBAN>	{Or	[1..1]		8
1.1.2	Other	<Othr>	Or}	[1..1]		8

Used in element(s)

["Identification" on page 18](#)

4.1.1 IBAN

XML Tag: IBAN

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Datatype: ["IBAN2007Identifier" on page 166](#)

4.1.2 Other

XML Tag: Othr

Presence: [1..1]

Definition: Unique identification of an account, as assigned by the account servicer, using an identification scheme.

The **Othr** block contains the following elements (see datatype ["GenericAccountIdentification1" on page 60](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.3	Identification	<Id>		[1..1]		60
1.1.4	SchemeName	<SchmeNm>		[0..1]		61
1.1.7	Issuer	<Issr>		[0..1]		61

4.2 AccountIdentification4Choice__1

Definition: Specifies the unique identification of an account as assigned by the account servicer.

🚫 Removed - ⚡ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.1	IBAN	<IBAN>	{Or	[1..1]	⚡	9
1.1.2	Other	<Othr>	Or}	[1..1]		9

Used in element(s)

"Identification" on page 20

4.2.1 IBAN

XML Tag: IBAN

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Datatype: "IBAN2007Identifier" on page 166

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Identification/IBAN) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgentAccount/Identification/IBAN) will be ignored by the Receiver.

4.2.2 Other

XML Tag: Othr

Presence: [1..1]

Definition: Unique identification of an account, as assigned by the account servicer, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericAccountIdentification1__1" on page 61 for details)

🚫 Removed - ⚡ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.3	Identification	<Id>		[1..1]	⚠	61
1.1.4	SchemeName	<SchmeNm>		[0..1]	⚡	62
1.1.7	Issuer	<Issr>		[0..1]	⚡	62

4.3 AccountSchemeName1Choice

Definition: Sets of elements to identify a name of the identification scheme.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.5	Code	<Cd>	{Or	[1..1]		10
1.1.6	Proprietary	<Prtry>	Or}	[1..1]		10

Used in element(s)

"SchemeName" on page 61, "SchemeName" on page 62

4.3.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalAccountIdentification1Code" on page 159

4.3.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 171

4.4 AmountType3Choice

Definition: Specifies the amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.43	InstructedAmount	<InstdAmt>	{Or	[1..1]	⚠️	10
2.44	EquivalentAmount	<EqvtAmt>	Or}	[1..1]	💡 🚫	11

Used in element(s)

"Amount" on page 35

4.4.1 InstructedAmount

XML Tag: InstdAmt

Presence: [1..1]

Definition: Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 139

Usage Guideline details

- on `pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Amount/InstructedAmount`
 - **HSBC_InstructedAmount:**
Amount must be between 0.01 GBP and 999999999.99 GBP

4.4.2 EquivalentAmount

XML Tag: EqvtAmt

Presence: [1..1]

Definition: Amount of money to be moved between the debtor and creditor, expressed in the currency of the debtor's account, and the currency in which the amount is to be moved.

The **EqvtAmt** block contains the following elements (see datatype "EquivalentAmount2" on page 51 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.45	Amount	<Amt>		[1..1]		52
2.46	CurrencyOfTransfer	<CcyOfTrf>		[1..1]		52

Usage Guideline details

- This element(`pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Amount/EquivalentAmount`) is removed.
- This element(`pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Amount/EquivalentAmount`) will be ignored by the Receiver.

4.5 Authorisation1Choice

Definition: Provides the details on the user identification or any user key that allows to check if the initiating party is allowed to issue the transaction.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.4	Code	<Cd>	{Or	[1..1]		12
1.5	Proprietary	<Prtry>	Or}	[1..1]	🚫	12

Used in element(s)

"Authorisation" on page 69

4.5.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the authorisation, in a coded form.

Datatype: "Authorisation1Code" on page 142

4.5.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the authorisation, in a free text form.

Datatype: "Max128Text" on page 169

Usage Guideline details

- This element(pain.001.001.03/GroupHeader/Authorisation/Proprietary) is removed.

4.6 BranchAndFinancialInstitutionIdentification4

Definition: Set of elements used to uniquely and unambiguously identify a financial institution or a branch of a financial institution.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.0	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		12
6.1.25	BranchIdentification	<BrnchId>		[0..1]	💡	13

Used in element(s)

"ChargesAccountAgent" on page 99, "ForwardingAgent" on page 71, "IntermediaryAgent1" on page 37, "IntermediaryAgent2" on page 38, "IntermediaryAgent3" on page 39

4.6.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "[FinancialInstitutionIdentification7](#)" on page 54 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1	BIC	<BIC>		[0..1]		54
6.1.2	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		54
6.1.7	Name	<Nm>		[0..1]		54
6.1.8	PostalAddress	<PstlAdr>		[0..1]	⚠️	55
6.1.19	Other	<Othr>		[0..1]	💡	57

4.6.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData2](#)" on page 15 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.26	Identification	<Id>		[0..1]		15
6.1.27	Name	<Nm>		[0..1]		15
6.1.28	PostalAddress	<PstlAdr>		[0..1]		16

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent1/BranchIdentification) will be ignored by the Receiver.

4.7 BranchAndFinancialInstitutionIdentification4__1

Definition: Set of elements used to uniquely and unambiguously identify a financial institution or a branch of a financial institution.

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.0	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		14
6.1.25	BranchIdentification	<BrnchId>		[0..1]	✦	14

Used in element(s)

"CreditorAgent" on page 40, "DebtorAgent" on page 97

4.7.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "FinancialInstitutionIdentification7_1" on page 57 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1	BIC	<BIC>		[0..1]	✦	57
6.1.2	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]	M	58
6.1.7	Name	<Nm>		[0..1]		58
6.1.8	PostalAddress	<PstlAdr>		[0..1]	M ⚠	58
6.1.19	Other	<Othr>		[0..1]	✦	60

4.7.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData2](#)" on page 15 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.26	Identification	<Id>		[0..1]		15
6.1.27	Name	<Nm>		[0..1]	✦	15
6.1.28	PostalAddress	<PstlAdr>		[0..1]	✦	16

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/BranchIdentification) will be ignored by the Receiver.

4.8 BranchData2

Definition: Information that locates and identifies a specific branch of a financial institution.

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.26	Identification	<Id>		[0..1]		15
6.1.27	Name	<Nm>		[0..1]	✦	15
6.1.28	PostalAddress	<PstlAdr>		[0..1]	✦	16

Used in element(s)

"[BranchIdentification](#)" on page 13, "[BranchIdentification](#)" on page 14

4.8.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a branch of a financial institution.

Datatype: "[Max35Text](#)" on page 171

4.8.2 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "[Max140Text](#)" on page 169

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/BranchIdentification/Name) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/DebtorAgent/BranchIdentification/Name) will be ignored by the Receiver.

4.8.3 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "[PostalAddress6](#)" on page 104 for details)

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.2 , 6.1.9 , 6.1.29 , 10.1.0	AddressType	<AdrTp>		[0..1]		105
9.1.3 , 6.1.10 , 6.1.30 , 10.1.1	Department	<Dept>		[0..1]		106
9.1.4 , 6.1.11 , 6.1.31 , 10.1.2	SubDepartment	<SubDept>		[0..1]		106
9.1.5 , 6.1.12 , 6.1.32 , 10.1.3	StreetName	<StrtNm>		[0..1]		106
9.1.6 , 6.1.13 , 6.1.33 , 10.1.4	BuildingNumber	<BldgNb>		[0..1]		106
9.1.7 , 6.1.14 , 6.1.34 , 10.1.5	PostCode	<PstCd>		[0..1]		107
9.1.8 , 6.1.15 , 6.1.35 , 10.1.6	TownName	<TwnNm>		[0..1]		107
9.1.9 , 6.1.16 , 6.1.36 , 10.1.7	CountrySubDivision	<CtrySubDvsn>		[0..1]		107
9.1.10 , 6.1.17 , 6.1.37 , 10.1.8	Country	<Ctry>		[0..1]		107
9.1.11 , 6.1.18 , 6.1.38 , 10.1.9	AddressLine	<AdrLine>		[0..7]		108

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/BranchIdentification/PostalAddress) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/DebtorAgent/BranchIdentification/Postal-Address) will be ignored by the Receiver.

4.9 CashAccount16

Definition: Set of elements used to identify an account.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.0	Identification	<Id>		[1..1]		18
1.1.8	Type	<Tp>		[0..1]		18
1.1.11	Currency	<Ccy>		[0..1]		19
1.1.12	Name	<Nm>		[0..1]		19

Used in element(s)

"ChargesAccount" on page 98, "DebtorAgentAccount" on page 97, "IntermediaryAgent1Account" on page 37, "IntermediaryAgent2Account" on page 38, "IntermediaryAgent3Account" on page 39

4.9.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

The **Id** block contains the following elements (see datatype "[AccountIdentification4Choice](#)" on page 8 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.1	IBAN	<IBAN>	{Or	[1..1]		8
1.1.2	Other	<Othr>	Or}	[1..1]		8

4.9.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

The **Tp** block contains the following elements (see datatype "[CashAccountType2](#)" on page 21 for details)

🚫 Removed - ⬜ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.9	Code	<Cd>	{Or	[1..1]		22
1.1.10	Proprietary	<Prtry>	Or}	[1..1]		22

4.9.3 Currency

XML Tag: Ccy

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

Datatype: "[ActiveOrHistoricCurrencyCode](#)" on page 140

4.9.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: "[Max70Text](#)" on page 173

4.10 CashAccount16__1

Definition: Set of elements used to identify an account.

🚫 Removed - ⬜ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.0	Identification	<Id>		[1..1]		20
1.1.8	Type	<Tp>		[0..1]	⬜	20
1.1.11	Currency	<Ccy>		[0..1]	⬜	20
1.1.12	Name	<Nm>		[0..1]	⬜	21

Used in element(s)

"CreditorAccount" on page 42, "CreditorAgentAccount" on page 40, "DebtorAccount" on page 96

4.10.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

The **Id** block contains the following elements (see datatype "AccountIdentification4Choice__1" on page 9 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.1	IBAN	<IBAN>	{Or	[1..1]	💡	9
1.1.2	Other	<Othr>	Or}	[1..1]		9

4.10.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

The **Tp** block contains the following elements (see datatype "CashAccountType2" on page 21 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.9	Code	<Cd>	{Or	[1..1]		22
1.1.10	Proprietary	<Prtry>	Or}	[1..1]	💡	22

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgentAccount/Type) will be ignored by the Receiver.

4.10.3 Currency

XML Tag: Ccy

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

Datatype: "ActiveOrHistoricCurrencyCode" on page 140

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Currency) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgentAccount/Currency) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/DebtorAccount/Currency) will be ignored by the Receiver.

4.10.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: "Max70Text" on page 173

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgentAccount/Name) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/DebtorAccount/Name) will be ignored by the Receiver.

4.11 CashAccountType2

Definition: Nature or use of the account.

🚫 Removed - 💡 Ignored - ⚠️ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.9	Code	<Cd>	{Or	[1..1]		22
1.1.10	Proprietary	<Prtry>	Or}	[1..1]	💡	22

Used in element(s)

["Type" on page 18](#), ["Type" on page 20](#)

4.11.1 Code

XML Tag: Cd

Presence: [1..1]

Warning Either Code or Proprietary must be present, but not both.

Definition: Account type, in a coded form.

Datatype: ["CashAccountType4Code" on page 145](#)

4.11.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Warning Either Code or Proprietary must be present, but not both.

Definition: Nature or use of the account in a proprietary form.

Datatype: ["Max35Text" on page 171](#)

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Proprietary](#)) will be ignored by the Receiver.
- This element([pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Proprietary](#)) will be ignored by the Receiver.

4.12 CategoryPurpose1Choice

Definition: Specifies the high level purpose of the instruction based on a set of pre-defined categories.

Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.

🚫 Removed - 💡 Ignored - ⚠️ Details below - 📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.15 , 2.40	Code	<Cd>	{Or	[1..1]		23
2.16 , 2.41	Proprietary	<Prtry>	Or}	[1..1]		23

Used in element(s)

["CategoryPurpose" on page 102](#)

4.12.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Category purpose, as published in an external category purpose code list.

Datatype: "ExternalCategoryPurpose1Code" on page 160

4.12.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Category purpose, in a proprietary form.

Datatype: "Max35Text" on page 171

4.13 Cheque6

Definition: Set of characteristics related to a cheque instruction, such as cheque type or cheque number.

🚫 Removed - 💡 Ignored - ⚠️ Details below - 📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.53	ChequeType	<ChqTp>		[0..1]		24
2.54	ChequeNumber	<ChqNb>		[0..1]		24
2.55	ChequeFrom	<ChqFr>		[0..1]		24
2.58	DeliveryMethod	<DlvrMtd>		[0..1]		24
2.61	DeliverTo	<DlvrTo>		[0..1]		25
2.64	InstructionPriority	<InstrPrty>		[0..1]		25
2.65	ChequeMaturityDate	<ChqMtrtyDt>		[0..1]		25
2.66	FormsCode	<FrmsCd>		[0..1]		25
2.67	MemoField	<MemoFld>		[0..2]		26
2.68	RegionalClearingZone	<RgnlClrZone>		[0..1]		26
2.69	PrintLocation	<PrtLctn>		[0..1]		26

Rules

R7 ChequeMaturityDateRule ✓

If ChequeMaturityDate is present, then ChequeType must be present and equal to DRFT or EL-DR.

Error handling:

– *Error severity:* Fatal

- *Error Code:* X00101
- *Error Text:* Invalid message content for cheque maturity date.

Used in element(s)

["ChequeInstruction" on page 36](#)

4.13.1 ChequeType

XML Tag: ChqTp

Presence: [0..1]

Definition: Specifies the type of cheque to be issued.

Datatype: ["ChequeType2Code" on page 153](#)

4.13.2 ChequeNumber

XML Tag: ChqNb

Presence: [0..1]

Definition: Unique and unambiguous identifier for a cheque as assigned by the agent.

Datatype: ["Max35Text" on page 171](#)

4.13.3 ChequeFrom

XML Tag: ChqFr

Presence: [0..1]

Definition: Identifies the party that ordered the issuance of the cheque.

The **ChqFr** block contains the following elements (see datatype ["NameAndAddress10" on page 73](#) for details)

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.56 , 2.62 , 2.96	Name	<Nm>		[1..1]		73
2.57 , 2.63 , 2.97	Address	<Adr>		[1..1]		73

4.13.4 DeliveryMethod

XML Tag: DlvryMtd

Presence: [0..1]

Definition: Specifies the delivery method of the cheque by the debtor's agent.

The **DlvryMtd** block contains the following elements (see datatype "[ChequeDeliveryMethod1Choice](#)" on page 26 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.59	Code	<Cd>	{Or	[1..1]		26
2.60	Proprietary	<Prtry>	Or}	[1..1]		27

4.13.5 DeliverTo

XML Tag: DlvrTo

Presence: [0..1]

Definition: Party to whom the debtor's agent needs to send the cheque.

The **DlvrTo** block contains the following elements (see datatype "[NameAndAddress10](#)" on page 73 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.56 , 2.62 , 2.96	Name	<Nm>		[1..1]		73
2.57 , 2.63 , 2.97	Address	<Adr>		[1..1]		73

4.13.6 InstructionPriority

XML Tag: InstrPrty

Presence: [0..1]

Definition: Urgency or order of importance that the originator would like the recipient of the payment instruction to apply to the processing of the payment instruction.

Datatype: "[Priority2Code](#)" on page 176

4.13.7 ChequeMaturityDate

XML Tag: ChqMtrtyDt

Presence: [0..1]

Definition: Date when the draft becomes payable and the debtor's account is debited.

Datatype: "[ISODate](#)" on page 167

4.13.8 FormsCode

XML Tag: FrmsCd

Presence: [0..1]

Definition: Identifies, in a coded form, the cheque layout, company logo and digitised signature to be used to print the cheque, as agreed between the initiating party and the debtor's agent.

Datatype: ["Max35Text" on page 171](#)

4.13.9 MemoField

XML Tag: MemoFld

Presence: [0..2]

Definition: Information that needs to be printed on a cheque, used by the payer to add miscellaneous information.

Datatype: ["Max35Text" on page 171](#)

4.13.10 RegionalClearingZone

XML Tag: RgnlClrZone

Presence: [0..1]

Definition: Regional area in which the cheque can be cleared, when a country has no nation-wide cheque clearing organisation.

Datatype: ["Max35Text" on page 171](#)

4.13.11 PrintLocation

XML Tag: PrtLctn

Presence: [0..1]

Definition: Specifies the print location of the cheque.

Datatype: ["Max35Text" on page 171](#)

4.14 ChequeDeliveryMethod1Choice

Definition: Set of characteristics related to a cheque instruction, such as cheque type or cheque number.

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.59	Code	<Cd>	{Or	[1..1]		26
2.60	Proprietary	<Prtry>	Or}	[1..1]		27

Used in element(s)

["DeliveryMethod" on page 24](#)

4.14.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the delivery method of the cheque by the debtor's agent.

Datatype: ["ChequeDelivery1Code" on page 151](#)

4.14.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies a proprietary delivery method of the cheque by the debtor's agent.

Datatype: ["Max35Text" on page 171](#)

4.15 ClearingSystemIdentification2Choice

Definition: Choice of a clearing system identifier.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.4	Code	<Cd>	{Or	[1..1]		27
6.1.5	Proprietary	<Prtry>	Or}	[1..1]		27

Used in element(s)

["ClearingSystemIdentification" on page 28](#), ["ClearingSystemIdentification" on page 29](#)

4.15.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Identification of a clearing system, in a coded form as published in an external list.

Datatype: ["ExternalClearingSystemIdentification1Code" on page 161](#)

4.15.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Identification code for a clearing system, that has not yet been identified in the list of clearing systems.

Datatype: ["Max35Text" on page 171](#)

4.16 ClearingSystemMemberIdentification2

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

🚫 Removed - ✦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.3	ClearingSystemIdentification	<ClrSysId>		[0..1]	✦	28
6.1.6	MemberIdentification	<Mmbld>		[1..1]		28

Used in element(s)

"ClearingSystemMemberIdentification" on page 54

4.16.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "ClearingSystemIdentification2Choice" on page 27 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.4	Code	<Cd>	{Or	[1..1]		27
6.1.5	Proprietary	<Prtry>	Or}	[1..1]		27

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification) will be ignored by the Receiver.

4.16.2 MemberIdentification

XML Tag: Mmbld

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: "Max35Text" on page 171

4.17 ClearingSystemMemberIdentification2__1

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

 Removed -
  Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.3	ClearingSystemIdentification	<ClrSysId>		[0..1]		29
6.1.6	MemberIdentification	<Mmbld>		[1..1]		29

Used in element(s)

"ClearingSystemMemberIdentification" on page 58

4.17.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "ClearingSystemIdentification2Choice" on page 27 for details)

 Removed -
  Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.4	Code	<Cd>	{Or	[1..1]		27
6.1.5	Proprietary	<Prtry>	Or}	[1..1]		27

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification) will be ignored by the Receiver.

4.17.2 MemberIdentification

XML Tag: Mmbld

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: "Max6Text" on page 172

Usage Guideline details

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification

– **HSBC_MemberIdentification:**

Sort code is required

- on pain.001.001.03/PaymentInformation/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification

– **HSBC_MemberIdentification:**

Sort code is required.

4.18 ContactDetails2

Definition: Communication device number or electronic address used for communication.

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.35	NamePrefix	<NmPrfx>		[0..1]		30
9.1.36	Name	<Nm>		[0..1]		30
9.1.37	PhoneNumber	<PhneNb>		[0..1]		30
9.1.38	MobileNumber	<MobNb>		[0..1]		31
9.1.39	FaxNumber	<FaxNb>		[0..1]		31
9.1.40	EmailAddress	<EmailAdr>		[0..1]		31
9.1.41	Other	<Othr>		[0..1]		31

Used in element(s)

"ContactDetails" on page 83, "ContactDetails" on page 87

4.18.1 NamePrefix

XML Tag: NmPrfx

Presence: [0..1]

Definition: Specifies the terms used to formally address a person.

Datatype: "NamePrefix1Code" on page 173

4.18.2 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 169

4.18.3 PhoneNumber

XML Tag: PhneNb

Presence: [0..1]

Definition: Collection of information that identifies a phone number, as defined by telecom services.

Datatype: ["PhoneNumber" on page 176](#)

4.18.4 MobileNumber

XML Tag: MobNb

Presence: [0..1]

Definition: Collection of information that identifies a mobile phone number, as defined by telecom services.

Datatype: ["PhoneNumber" on page 176](#)

4.18.5 FaxNumber

XML Tag: FaxNb

Presence: [0..1]

Definition: Collection of information that identifies a FAX number, as defined by telecom services.

Datatype: ["PhoneNumber" on page 176](#)

4.18.6 EmailAddress

XML Tag: EmailAdr

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: ["Max2048Text" on page 171](#)

4.18.7 Other

XML Tag: Othr

Presence: [0..1]

Definition: Contact details in another form.

Datatype: ["Max35Text" on page 171](#)

4.19 CreditTransferTransactionInformation10__1

Definition: Set of elements used to provide information specific to the individual transaction(s) included in the message.

Removed -
 Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.28	PaymentIdentification	<PmtId>		[1..1]		34
2.31	PaymentTypeInfo	<PmtTpInf>		[0..1]		34
2.42	Amount	<Amt>		[1..1]		35
2.47	ExchangeRateInformation	<XchgRateInf>		[0..1]		35
2.51	ChargeBearer	<ChrgBr>		[0..1]		36
2.52	ChequeInstruction	<ChqInstr>		[0..1]		36
2.70	UltimateDebtor	<UltmtDbtr>		[0..1]		36
2.71	IntermediaryAgent1	<IntrmyAgt1>		[0..1]		37
2.72	IntermediaryAgent1Account	<IntrmyAgt1Acct>		[0..1]		37
2.73	IntermediaryAgent2	<IntrmyAgt2>		[0..1]		38
2.74	IntermediaryAgent2Account	<IntrmyAgt2Acct>		[0..1]		38
2.75	IntermediaryAgent3	<IntrmyAgt3>		[0..1]		39
2.76	IntermediaryAgent3Account	<IntrmyAgt3Acct>		[0..1]		39
2.77	CreditorAgent	<CdtrAgt>		[0..1]		40
2.78	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		40
2.79	Creditor	<Cdtr>		[0..1]		41
2.80	CreditorAccount	<CdtrAcct>		[0..1]		42
2.81	UltimateCreditor	<UltmtCdtr>		[0..1]		42
2.82	InstructionForCreditorAgent	<InstrForCdtrAgt>		[0..*]		43
2.85	InstructionForDebtorAgent	<InstrForDbtrAgt>		[0..1]		43
2.86	Purpose	<Purp>		[0..1]		44
2.89	RegulatoryReporting	<RgltryRptg>		[0..10]		44
2.90	Tax	<Tax>		[0..1]		45
2.91	RelatedRemittanceInformation	<RltdRmtInf>		[0..10]		45
2.98	RemittanceInformation	<RmtInf>		[0..1]		46

Rules

R19 IntermediaryAgent2Rule ✓

If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present.

Error handling:

– Error severity: Fatal

- *Error Code:* X00056
- *Error Text:* Invalid message content for intermediary agent 2.

R20 IntermediaryAgent3Rule ✓

If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00057
- *Error Text:* Invalid message content for intermediary agent 3.

R21 InstructionForCreditorAgentRule ✓

If InstructionForCreditorAgent/Code contains CHQB, then CreditorAccount is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00051
- *Error Text:* Invalid message content for instruction for creditor agent PayCreditorByCheque

R22 IntermediaryAgent1AccountRule ✓

If IntermediaryAgent1Account is present, then IntermediaryAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00052
- *Error Text:* Invalid message content for intermediary agent 1 account.

R23 IntermediaryAgent2AccountRule ✓

If IntermediaryAgent2Account is present, then IntermediaryAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00053
- *Error Text:* Invalid message content for intermediary agent 2 account.

R24 IntermediaryAgent3AccountRule ✓

If IntermediaryAgent3Account is present, then IntermediaryAgent3 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00054
- *Error Text:* Invalid message content for intermediary agent 3 account.

Guidelines**1. UltimateCreditorGuideline**

UltimateCreditor may only be present if different from Creditor.

2. UltimateDebtorGuideline

UltimateDebtor may only be present if different from Debtor.

Used in element(s)

"CreditTransferTransactionInformation" on page 99

4.19.1 PaymentIdentification

XML Tag: PmtId

Presence: [1..1]

Definition: Set of elements used to reference a payment instruction.

The **PmtId** block contains the following elements (see datatype "PaymentIdentification1__1" on page 88 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.29	InstructionIdentification	<InstrId>		[0..1]		88
2.30	EndToEndIdentification	<EndToEndId>		[1..1]	⚠️	89

4.19.2 PaymentTypeInformation

XML Tag: PmtTpInf

Presence: [0..1]

Definition: Set of elements used to further specify the type of transaction.

The **PmtTpInf** block contains the following elements (see datatype "PaymentTypeInformation19__1" on page 100 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.7 , 2.32	InstructionPriority	<InstrPrty>		[0..1]	💡	101
2.8 , 2.33	ServiceLevel	<SvcLvl>		[0..1]	M	101
2.11 , 2.36	LocalInstrument	<LclInstrm>		[0..1]		102
2.14 , 2.39	CategoryPurpose	<CtgyPurp>		[0..1]		102

Usage Guideline details

- on **pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/PaymentType-Information**

This element is now mandatory, the minimum occurrence has been changed to : 1

4.19.3 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

The **Amt** block contains the following elements (see datatype "[AmountType3Choice](#)" on page 10 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.43	InstructedAmount	<InstdAmt>	{Or	[1..1]	⚠	10
2.44	EquivalentAmount	<EqvtAmt>	Or}	[1..1]	💡 🚫	11

4.19.4 ExchangeRateInformation

XML Tag: XchgRateInf

Presence: [0..1]

Definition: Set of elements used to provide details on the currency exchange rate and contract.

The **XchgRateInf** block contains the following elements (see datatype "[ExchangeRateInformation1](#)" on page 52 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.48	ExchangeRate	<XchgRate>		[0..1]		52
2.49	RateType	<RateTp>		[0..1]		53
2.50	ContractIdentification	<CtrctId>		[0..1]		53

Usage Guideline details

- This element(**pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/ExchangeRateInformation**) is removed.
- This element(**pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/ExchangeRateInformation**) will be ignored by the Receiver.

4.19.5 ChargeBearer

XML Tag: ChrgBr

Presence: [0..1]

Definition: Specifies which party/parties will bear the charges associated with the processing of the payment transaction.

Datatype: ["ChargeBearerType1Code" on page 150](#)

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/ChargeBearer](#)) will be ignored by the Receiver.

4.19.6 ChequeInstruction

XML Tag: ChqInstr

Presence: [0..1]

Definition: Set of elements needed to issue a cheque.

The **ChqInstr** block contains the following elements (see datatype ["Cheque6" on page 23](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - 📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.53	ChequeType	<ChqTp>		[0..1]		24
2.54	ChequeNumber	<ChqNb>		[0..1]		24
2.55	ChequeFrom	<ChqFr>		[0..1]		24
2.58	DeliveryMethod	<DlvryMtd>		[0..1]		24
2.61	DeliverTo	<DlvrTo>		[0..1]		25
2.64	InstructionPriority	<InstrPrty>		[0..1]		25
2.65	ChequeMaturityDate	<ChqMtrtyDt>		[0..1]		25
2.66	FormsCode	<FrmsCd>		[0..1]		25
2.67	MemoField	<MemoFld>		[0..2]		26
2.68	RegionalClearingZone	<RgnlClrZone>		[0..1]		26
2.69	PrintLocation	<PrtLctn>		[0..1]		26

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/ChequeInstruction](#)) will be ignored by the Receiver.

4.19.7 UltimateDebtor

XML Tag: UltmtDbtr

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor.

The **UltmtDbtr** block contains the following elements (see datatype "[PartyIdentification32](#)" on [page 80](#) for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.0	Name	<Nm>		[0..1]	✦	80
9.1.1	PostalAddress	<PstlAdr>		[0..1]	✦	81
9.1.12	Identification	<Id>		[0..1]	✦	82
9.1.33	CountryOfResidence	<CtryOfRes>		[0..1]	✦	83
9.1.34	ContactDetails	<CtctDtls>		[0..1]	✦	83

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor) will be ignored by the Receiver.

4.19.8 IntermediaryAgent1

XML Tag: IntrmyAgt1

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If more than one intermediary agent is present, then IntermediaryAgent1 identifies the agent between the DebtorAgent and the IntermediaryAgent2.

The **IntrmyAgt1** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification4](#)" on [page 12](#) for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.0	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		12
6.1.25	BranchIdentification	<BrnchId>		[0..1]	✦	13

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent1) is removed.

4.19.9 IntermediaryAgent1Account

XML Tag: IntrmyAgt1Acct

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 1 at its servicing agent in the payment chain.

The **IntrmyAgt1Acct** block contains the following elements (see datatype "[CashAccount16](#)" on [page 18](#) for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.0	Identification	<Id>		[1..1]		18
1.1.8	Type	<Tp>		[0..1]		18
1.1.11	Currency	<Ccy>		[0..1]		19
1.1.12	Name	<Nm>		[0..1]		19

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent1Account) will be ignored by the Receiver.

4.19.10 IntermediaryAgent2

XML Tag: IntrmyAgt2

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If more than two intermediary agents are present, then IntermediaryAgent2 identifies the agent between the IntermediaryAgent1 and the IntermediaryAgent3.

The **IntrmyAgt2** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification4](#)" on [page 12](#) for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.0	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		12
6.1.25	BranchIdentification	<BrnchId>		[0..1]		13

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent2) will be ignored by the Receiver.

4.19.11 IntermediaryAgent2Account

XML Tag: IntrmyAgt2Acct

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 2 at its servicing agent in the payment chain.

The **IntrmyAgt2Acct** block contains the following elements (see datatype "[CashAccount16](#)" on [page 18](#) for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.0	Identification	<Id>		[1..1]		18
1.1.8	Type	<Tp>		[0..1]		18
1.1.11	Currency	<Ccy>		[0..1]		19
1.1.12	Name	<Nm>		[0..1]		19

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent2Account) will be ignored by the Receiver.

4.19.12 IntermediaryAgent3

XML Tag: IntrmyAgt3

Presence: [0..1]

Definition: Agent between the debtor's agent and the creditor's agent.

Usage: If IntermediaryAgent3 is present, then it identifies the agent between the IntermediaryAgent 2 and the CreditorAgent.

The **IntrmyAgt3** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification4](#)" on [page 12](#) for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.0	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		12
6.1.25	BranchIdentification	<BrnchId>		[0..1]		13

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent3) will be ignored by the Receiver.

4.19.13 IntermediaryAgent3Account

XML Tag: IntrmyAgt3Acct

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 3 at its servicing agent in the payment chain.

The **IntrmyAgt3Acct** block contains the following elements (see datatype "[CashAccount16](#)" on [page 18](#) for details)

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.0	Identification	<Id>		[1..1]		18
1.1.8	Type	<Tp>		[0..1]		18
1.1.11	Currency	<Ccy>		[0..1]		19
1.1.12	Name	<Nm>		[0..1]		19

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent3Account) will be ignored by the Receiver.

4.19.14 CreditorAgent

XML Tag: CdtrAgt

Presence: [0..1]

Definition: Financial institution servicing an account for the creditor.

The **CdtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification4_1](#)" on [page 13](#) for details)

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.0	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		14
6.1.25	BranchIdentification	<BrnchId>		[0..1]	♦	14

Usage Guideline details

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent
This element is now mandatory, the minimum occurrence has been changed to : 1

4.19.15 CreditorAgentAccount

XML Tag: CdtrAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction.

The **CdtrAgtAcct** block contains the following elements (see datatype "CashAccount16__1" on page 19 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.0	Identification	<Id>		[1..1]		20
1.1.8	Type	<Tp>		[0..1]	✦	20
1.1.11	Currency	<Ccy>		[0..1]	✦	20
1.1.12	Name	<Nm>		[0..1]	✦	21

Usage Guideline details

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgentAccount

– HSBC_Identification:

If the beneficiary account is held at a building society that is not part of the BACS clearing, provide the account number of the building society with its supporting bank in Identification and the roll number of the beneficiary in CreditorAccount. Please note that in this case, it will not be possible to pass through the information provided in the End To End Identification as we will need to pass through the building society member roll number.

4.19.16 Creditor

XML Tag: Cdtr

Presence: [0..1]

Definition: Party to which an amount of money is due.

The **Cdtr** block contains the following elements (see datatype "PartyIdentification32" on page 80 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.0	Name	<Nm>		[0..1]	M ⚠	80
9.1.1	PostalAddress	<PstlAdr>		[0..1]		81
9.1.12	Identification	<Id>		[0..1]		82
9.1.33	CountryOfResidence	<CtryOfRes>		[0..1]	✦	83
9.1.34	ContactDetails	<CtctDtls>		[0..1]	✦	83

Usage Guideline details

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor
This element is now mandatory, the minimum occurrence has been changed to : 1

4.19.17 CreditorAccount

XML Tag: CdtrAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.

The **CdtrAcct** block contains the following elements (see datatype "CashAccount16__1" on page 19 for details)

🚫 Removed - ⬡ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.0	Identification	<Id>		[1..1]		20
1.1.8	Type	<Tp>		[0..1]		20
1.1.11	Currency	<Ccy>		[0..1]	⬡	20
1.1.12	Name	<Nm>		[0..1]		21

Usage Guideline details

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount
This element is now mandatory, the minimum occurrence has been changed to : 1

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount

– **HSBC_Identification:**

If the beneficiary account is held at a building society that is not part of the BACS clearing, provide the account number of the building society with its supporting bank in Identification and the roll number of the beneficiary in CreditorAccount. Please note that in this case, it will not be possible to pass through the information provided in the End To End Identification as we will need to pass through the building society member roll number.

4.19.18 UltimateCreditor

XML Tag: UltmtCdtr

Presence: [0..1]

Definition: Ultimate party to which an amount of money is due.

The **UltmtCdtr** block contains the following elements (see datatype "[PartyIdentification32](#)" on [page 80](#) for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.0	Name	<Nm>		[0..1]		80
9.1.1	PostalAddress	<PstlAdr>		[0..1]		81
9.1.12	Identification	<Id>		[0..1]		82
9.1.33	CountryOfResidence	<CtryOfRes>		[0..1]		83
9.1.34	ContactDetails	<CtctDtls>		[0..1]		83

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateCreditor](#)) will be ignored by the Receiver.

4.19.19 InstructionForCreditorAgent

XML Tag: InstrForCdtrAgt

Presence: [0..*]

Definition: Further information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor agent.

The **InstrForCdtrAgt** block contains the following elements (see datatype "[InstructionForCreditorAgent1](#)" on [page 72](#) for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.83	Code	<Cd>		[0..1]		72
2.84	InstructionInformation	<InstrInf>		[0..1]		72

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/InstructionForCreditorAgent](#)) will be ignored by the Receiver.

4.19.20 InstructionForDebtorAgent

XML Tag: InstrForDbtrAgt

Presence: [0..1]

Definition: Further information related to the processing of the payment instruction, that may need to be acted upon by the debtor agent, depending on agreement between debtor and the debtor agent.

Datatype: "Max140Text" on page 169

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/InstructionForDebtorAgent) will be ignored by the Receiver.

4.19.21 Purpose

XML Tag: Purp

Presence: [0..1]

Definition: Underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

The **Purp** block contains the following elements (see datatype "Purpose2Choice" on page 108 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.87	Code	<Cd>	{Or	[1..1]		108
2.88	Proprietary	<Prtry>	Or}	[1..1]		108

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Purpose) will be ignored by the Receiver.

4.19.22 RegulatoryReporting

XML Tag: RgltryRptg

Presence: [0..10]

Definition: Information needed due to regulatory and statutory requirements.

The **RgltryRptg** block contains the following elements (see datatype "RegulatoryReporting3" on page 112 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
11.1.0	DebitCreditReportingIndicator	<DbtCdtRptgInd>		[0..1]		113
11.1.1	Authority	<Authrty>		[0..1]	💡	113
11.1.4	Details	<Dtls>		[0..*]		113

4.19.23 Tax

XML Tag: Tax

Presence: [0..1]

Definition: Set of elements used to provide details on the tax.

The **Tax** block contains the following elements (see datatype "[TaxInformation3__1](#)" on page 127 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
13.1.0	Creditor	<Cdtr>		[0..1]	💡	127
13.1.4	Debtor	<Dbtr>		[0..1]	💡	128
13.1.11	AdministrationZone	<AdmstnZn>		[0..1]	💡	128
13.1.12	ReferenceNumber	<RefNb>		[0..1]	⚠	128
13.1.13	Method	<Mtd>		[0..1]	💡	129
13.1.14	TotalTaxableBaseAmount	<TtlTaxblBaseAmt>		[0..1]	💡	129
13.1.15	TotalTaxAmount	<TtlTaxAmt>		[0..1]	💡	130
13.1.16	Date	<Dt>		[0..1]	💡	130
13.1.17	SequenceNumber	<SeqNb>		[0..1]	💡	130
13.1.18	Record	<Rcrd>		[0..*]	💡	130

4.19.24 RelatedRemittanceInformation

XML Tag: RltdRmtInf

Presence: [0..10]

Definition: Set of elements used to provide information related to the handling of the remittance information by any of the agents in the transaction processing chain.

The **RltdRmtInf** block contains the following elements (see datatype "[RemittanceLocation2](#)" on page 117 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.92	RemittanceIdentification	<RmtId>		[0..1]	⚠	117
2.93	RemittanceLocationMethod	<RmtLctnMtd>		[0..1]		118
2.94	RemittanceLocationElectronicAddress	<RmtLctnElctrncAdr>		[0..1]		118
2.95	RemittanceLocationPostalAddress	<RmtLctnPstlAdr>		[0..1]		118

Usage Guideline details

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RelatedRemittanceInformation

Comment:

Refer to Advising Product Appendix for further details

4.19.25 RemittanceInformation

XML Tag: RmtInf

Presence: [0..1]

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.

The **RmtInf** block contains the following elements (see datatype "[RemittanceInformation5](#)" on page 116 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.99	Unstructured	<Ustrd>		[0..*]	⚠	116
2.100	Structured	<Strd>		[0..*]		116

4.20 CreditorReferenceInformation2

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.121	Type	<Tp>		[0..1]		46
2.126	Reference	<Ref>		[0..1]	💡	47

Used in element(s)

"[CreditorReferenceInformation](#)" on page 123

4.20.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of creditor reference.

The **Tp** block contains the following elements (see datatype "[CreditorReferenceType2](#)" on page 48 for details)

🚫 Removed - ⬜ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.122	CodeOrProprietary	<CdOrPrtry>		[1..1]		48
2.125	Issuer	<Issr>		[0..1]	⬜	49

4.20.2 Reference

XML Tag: Ref

Presence: [0..1]

Definition: Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction.

Usage: If available, the initiating party should provide this reference in the structured remittance information, to enable reconciliation by the creditor upon receipt of the amount of money.

If the business context requires the use of a creditor reference or a payment remit identification, and only one identifier can be passed through the end-to-end chain, the creditor's reference or payment remittance identification should be quoted in the end-to-end transaction identification.

Datatype: "[Max35Text](#)" on page 171

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/CreditorReferenceInformation/Reference](#)) will be ignored by the Receiver.

4.21 CreditorReferenceType1Choice

Definition: Specifies the type of document referred by the creditor.

🚫 Removed - ⬜ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.123	Code	<Cd>	{Or	[1..1]		47
2.124	Proprietary	<Prtry>	Or}	[1..1]	⬜	48

Used in element(s)

"[CodeOrProprietary](#)" on page 48

4.21.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Type of creditor reference, in a coded form.

Datatype: ["DocumentType3Code" on page 156](#)

4.21.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Creditor reference type, in a proprietary form.

Datatype: ["Max35Text" on page 171](#)

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/CreditorReferenceInformation/Type/CodeOrProprietary/Proprietary](#)) will be ignored by the Receiver.

4.22 CreditorReferenceType2

Definition: Specifies the type of creditor reference.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.122	CodeOrProprietary	<CdOrPrtry>		[1..1]		48
2.125	Issuer	<Issr>		[0..1]	💡	49

Used in element(s)

["Type" on page 46](#)

4.22.1 CodeOrProprietary

XML Tag: CdOrPrtry

Presence: [1..1]

Definition: Coded or proprietary format creditor reference type.

The **CdOrPrtry** block contains the following elements (see datatype ["CreditorReferenceType1Choice" on page 47](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.123	Code	<Cd>	{Or	[1..1]		47
2.124	Proprietary	<Prtry>	Or}	[1..1]	💡	48

4.22.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the credit reference type.

Datatype: "Max35Text" on page 171

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/CreditorReferenceInformation/Type/Issuer) will be ignored by the Receiver.

4.23 DateAndPlaceOfBirth

Definition: Date and place of birth of a person.

🚫 Removed - 💡 Ignored - ⚠️ Details below - 📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.23	BirthDate	<BirthDt>		[1..1]		49
9.1.24	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		49
9.1.25	CityOfBirth	<CityOfBirth>		[1..1]		49
9.1.26	CountryOfBirth	<CtryOfBirth>		[1..1]		50

Used in element(s)

"DateAndPlaceOfBirth" on page 103

4.23.1 BirthDate

XML Tag: BirthDt

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: "ISODate" on page 167

4.23.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: "Max35Text" on page 171

4.23.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: ["Max35Text" on page 171](#)

4.23.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: ["CountryCode" on page 155](#)

4.24 DatePeriodDetails

Definition: Range of time defined by a start date and an end date.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
13.1.29 , 13.1.40	FromDate	<FrDt>		[1..1]		50
13.1.30 , 13.1.41	ToDate	<ToDt>		[1..1]		50

Used in element(s)

["FromToDate" on page 134](#)

4.24.1 FromDate

XML Tag: FrDt

Presence: [1..1]

Definition: Start date of the range.

Datatype: ["ISODate" on page 167](#)

4.24.2 ToDate

XML Tag: ToDt

Presence: [1..1]

Definition: End date of the range.

Datatype: ["ISODate" on page 167](#)

4.25 DocumentAdjustment1

Definition: Set of elements used to provide information on the amount and reason of the document adjustment.

🚫 Removed - ✨ Ignored - ⚠️ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.115	Amount	<Amt>		[1..1]		51
2.116	CreditDebitIndicator	<CdtDbtInd>		[0..1]		51
2.117	Reason	<Rsn>		[0..1]		51
2.118	AdditionalInformation	<AddtlInf>		[0..1]		51

Used in element(s)

"AdjustmentAmountAndReason" on page 115

4.25.1 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money of the document adjustment.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 139

4.25.2 CreditDebitIndicator

XML Tag: CdtDbtInd

Presence: [0..1]

Definition: Specifies whether the adjustment must be subtracted or added to the total amount.

Datatype: "CreditDebitCode" on page 155

4.25.3 Reason

XML Tag: Rsn

Presence: [0..1]

Definition: Specifies the reason for the adjustment.

Datatype: "Max4Text" on page 172

4.25.4 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Provides further details on the document adjustment.

Datatype: "Max140Text" on page 169

4.26 EquivalentAmount2

Definition: Amount of money to be moved between the debtor and creditor, expressed in the currency of the debtor's account, and the currency in which the amount is to be moved.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.45	Amount	<Amt>		[1..1]		52
2.46	CurrencyOfTransfer	<CcyOfTrf>		[1..1]		52

Used in element(s)

["EquivalentAmount" on page 11](#)

4.26.1 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money to be moved between debtor and creditor, before deduction of charges, expressed in the currency of the debtor's account, and to be moved in a different currency.

Usage: The first agent will convert the equivalent amount into the amount to be moved.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 139](#)

4.26.2 CurrencyOfTransfer

XML Tag: CcyOfTrf

Presence: [1..1]

Definition: Specifies the currency of the to be transferred amount, which is different from the currency of the debtor's account.

Datatype: ["ActiveOrHistoricCurrencyCode" on page 140](#)

4.27 ExchangeRateInformation1

Definition: Further detailed information on the exchange rate that has been used in the payment transaction.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.48	ExchangeRate	<XchgRate>		[0..1]		52
2.49	RateType	<RateTp>		[0..1]		53
2.50	ContractIdentification	<CtrctId>		[0..1]		53

Used in element(s)

["ExchangeRateInformation" on page 35](#)

4.27.1 ExchangeRate

XML Tag: XchgRate

Presence: [0..1]

Definition: The factor used for conversion of an amount from one currency to another. This reflects the price at which one currency was bought with another currency.

Datatype: ["BaseOneRate" on page 144](#)

4.27.2 RateType

XML Tag: RateTp

Presence: [0..1]

Definition: Specifies the type used to complete the currency exchange.

Datatype: ["ExchangeRateType1Code" on page 159](#)

4.27.3 ContractIdentification

XML Tag: CtrctId

Presence: [0..1]

Definition: Unique and unambiguous reference to the foreign exchange contract agreed between the initiating party/creditor and the debtor agent.

Datatype: ["Max35Text" on page 171](#)

4.28 FinancialIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.22	Code	<Cd>	{Or	[1..1]		53
6.1.23	Proprietary	<Prtry>	Or}	[1..1]		53

Used in element(s)

["SchemeName" on page 63](#)

4.28.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalFinancialInstitutionIdentification1Code" on page 162](#)

4.28.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 171

4.29 FinancialInstitutionIdentification7

Definition: Set of elements used to identify a financial institution.

🚫 Removed - 💡 Ignored - ⚠️ Details below - 📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1	BIC	<BIC>		[0..1]		54
6.1.2	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		54
6.1.7	Name	<Nm>		[0..1]		54
6.1.8	PostalAddress	<PstlAdr>		[0..1]	⚠️	55
6.1.19	Other	<Othr>		[0..1]	💡	57

Used in element(s)

"FinancialInstitutionIdentification" on page 12

4.29.1 BIC

XML Tag: BIC

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICIdentifier" on page 144

4.29.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2" on page 27 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - 📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.3	ClearingSystemIdentification	<ClrSysId>		[0..1]	💡	28
6.1.6	MemberIdentification	<Mmbld>		[1..1]		28

4.29.3 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 169

4.29.4 **PostalAddress**

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress6" on page 104 for details)

🚫 Removed - ⚡ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.2 , 6.1.9 , 6.1.29 , 10.1.0	AddressType	<AdrTp>		[0..1]	⚡	105
9.1.3 , 6.1.10 , 6.1.30 , 10.1.1	Department	<Dept>		[0..1]		106
9.1.4 , 6.1.11 , 6.1.31 , 10.1.2	SubDepartment	<SubDept>		[0..1]		106
9.1.5 , 6.1.12 , 6.1.32 , 10.1.3	StreetName	<StrtNm>		[0..1]		106
9.1.6 , 6.1.13 , 6.1.33 , 10.1.4	BuildingNumber	<BldgNb>		[0..1]		106
9.1.7 , 6.1.14 , 6.1.34 , 10.1.5	PostCode	<PstCd>		[0..1]		107
9.1.8 , 6.1.15 , 6.1.35 , 10.1.6	TownName	<TwnNm>		[0..1]		107
9.1.9 , 6.1.16 , 6.1.36 , 10.1.7	CountrySubDivision	<CtrySubDvsn>		[0..1]		107
9.1.10 , 6.1.17 , 6.1.37 , 10.1.8	Country	<Ctry>		[0..1]		107
9.1.11 , 6.1.18 , 6.1.38 , 10.1.9	AddressLine	<AdrLine>		[0..7]		108

Usage Guideline details

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress

Comment:

Structured Address recommended

4.29.5 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on page 63 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20	Identification	<Id>		[1..1]		63
6.1.21	SchemeName	<SchmeNm>		[0..1]		63
6.1.24	Issuer	<Issr>		[0..1]		64

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/Other) will be ignored by the Receiver.

4.30 FinancialInstitutionIdentification7__1

Definition: Set of elements used to identify a financial institution.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.1	BIC	<BIC>		[0..1]	💡	57
6.1.2	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]	M	58
6.1.7	Name	<Nm>		[0..1]		58
6.1.8	PostalAddress	<PstlAdr>		[0..1]	M ⚠	58
6.1.19	Other	<Othr>		[0..1]	💡	60

Used in element(s)

"[FinancialInstitutionIdentification](#)" on page 14

4.30.1 BIC

XML Tag: BIC

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICIdentifier" on page 144

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/BIC) will be ignored by the Receiver.

4.30.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2__1" on page 28 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.3	ClearingSystemIdentification	<ClrSysId>		[0..1]	💡	29
6.1.6	MemberIdentification	<Mmbld>		[1..1]	⚠	29

Usage Guideline details

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pain.001.001.03/PaymentInformation/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification
This element is now mandatory, the minimum occurrence has been changed to : 1

4.30.3 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 169

4.30.4 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "[PostalAddress6](#)" on page 104 for details)

🚫 Removed - ♦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.2 , 6.1.9 , 6.1.29 , 10.1.0	AddressType	<AdrTp>		[0..1]	♦	105
9.1.3 , 6.1.10 , 6.1.30 , 10.1.1	Department	<Dept>		[0..1]		106
9.1.4 , 6.1.11 , 6.1.31 , 10.1.2	SubDepartment	<SubDept>		[0..1]		106
9.1.5 , 6.1.12 , 6.1.32 , 10.1.3	StreetName	<StrtNm>		[0..1]		106
9.1.6 , 6.1.13 , 6.1.33 , 10.1.4	BuildingNumber	<BldgNb>		[0..1]		106
9.1.7 , 6.1.14 , 6.1.34 , 10.1.5	PostCode	<PstCd>		[0..1]		107
9.1.8 , 6.1.15 , 6.1.35 , 10.1.6	TownName	<TwnNm>		[0..1]		107
9.1.9 , 6.1.16 , 6.1.36 , 10.1.7	CountrySubDivision	<CtrySubDvsn>		[0..1]		107
9.1.10 , 6.1.17 , 6.1.37 , 10.1.8	Country	<Ctry>		[0..1]	M ⚠	107
9.1.11 , 6.1.18 , 6.1.38 , 10.1.9	AddressLine	<AdrLine>		[0..7]		108

Usage Guideline details

- on **pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress**

This element is now mandatory, the minimum occurrence has been changed to : 1

- on **pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress**

Comment: (empty)

4.30.5 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on page 63 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20	Identification	<Id>		[1..1]		63
6.1.21	SchemeName	<SchmeNm>		[0..1]		63
6.1.24	Issuer	<Issr>		[0..1]		64

Usage Guideline details

- This element(**pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/Other**) will be ignored by the Receiver.
- This element(**pain.001.001.03/PaymentInformation/DebtorAgent/FinancialInstitutionIdentification/Other**) will be ignored by the Receiver.

4.31 GenericAccountIdentification1

Definition: Information related to a generic account identification.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.3	Identification	<Id>		[1..1]		60
1.1.4	SchemeName	<SchmeNm>		[0..1]		61
1.1.7	Issuer	<Issr>		[0..1]		61

Used in element(s)

"Other" on [page 8](#)

4.31.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max34Text" on page 171

4.31.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "AccountSchemeName1Choice" on page 10 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.5	Code	<Cd>	{Or	[1..1]		10
1.1.6	Proprietary	<Prtry>	Or}	[1..1]		10

4.31.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 171

4.32 GenericAccountIdentification1__1

Definition: Information related to a generic account identification.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.3	Identification	<Id>		[1..1]	⚠	61
1.1.4	SchemeName	<SchmeNm>		[0..1]	💡	62
1.1.7	Issuer	<Issr>		[0..1]	💡	62

Used in element(s)

"Other" on page 9

4.32.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max8Text" on page 173

Usage Guideline details

- on **pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Identification/Other/Identification**
 - **HSBC_UKCreditorAccount:**

If
The beneficiary's account is held with a Building Society

Then
Supply the Roll Number in this field

Else
Supply the Beneficiary's Bank Account number
- on **pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgentAccount/Identification/Other/Identification**

Comment:
This is the account number of the building society.

4.32.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "AccountSchemeName1Choice" on page 10 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - 📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.5	Code	<Cd>	{Or	[1..1]		10
1.1.6	Proprietary	<Prtry>	Or}	[1..1]		10

Usage Guideline details

- This element(**pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Identification/Other/SchemeName**) will be ignored by the Receiver.
- This element(**pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgentAccount/Identification/Other/SchemeName**) will be ignored by the Receiver.
- This element(**pain.001.001.03/PaymentInformation/DebtorAccount/Identification/Other/SchemeName**) will be ignored by the Receiver.

4.32.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 171

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Identification/Other/Issuer) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgentAccount/Identification/Other/Issuer) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/DebtorAccount/Identification/Other/Issuer) will be ignored by the Receiver.

4.33 GenericFinancialIdentification1

Definition: Information related to an identification of a financial institution.

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.20	Identification	<Id>		[1..1]		63
6.1.21	SchemeName	<SchmeNm>		[0..1]		63
6.1.24	Issuer	<Issr>		[0..1]		64

Used in element(s)

"Other" on page 57, "Other" on page 60

4.33.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 171

4.33.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[FinancialIdentificationScheme-Name1Choice](#)" on page 53 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.22	Code	<Cd>	{Or	[1..1]		53
6.1.23	Proprietary	<Prtry>	Or}	[1..1]		53

4.33.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "[Max35Text](#)" on page 171

4.34 GenericOrganisationIdentification1

Definition: Information related to an identification of an organisation.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.16	Identification	<Id>		[1..1]	💡	64
9.1.17	SchemeName	<SchmeNm>		[0..1]	💡	64
9.1.20	Issuer	<Issr>		[0..1]	💡	65

Used in element(s)

"Other" on page 75

4.34.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "[Max35Text](#)" on page 171

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/Identification/OrganisationIdentification/Other/Identification) will be ignored by the Receiver.

4.34.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[OrganisationIdentificationSchemeName1Choice](#)" on page 77 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.18	Code	<Cd>	{Or	[1..1]		77
9.1.19	Proprietary	<Prtry>	Or}	[1..1]		77

Usage Guideline details

- This element(pain.001.001.03/GroupHeader/InitiatingParty/Identification/OrganisationIdentification/Other/SchemeName) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/Identification/OrganisationIdentification/Other/SchemeName) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/Identification/OrganisationIdentification/Other/SchemeName) will be ignored by the Receiver.

4.34.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "[Max35Text](#)" on page 171

Usage Guideline details

- This element(pain.001.001.03/GroupHeader/InitiatingParty/Identification/OrganisationIdentification/Other/Issuer) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/Identification/OrganisationIdentification/Other/Issuer) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/Identification/OrganisationIdentification/Other/Issuer) will be ignored by the Receiver.

4.35 GenericOrganisationIdentification1__1

Definition: Information related to an identification of an organisation.

 Removed -
  Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.16	Identification	<Id>		[1..1]		66
9.1.17	SchemeName	<SchmeNm>		[0..1]		67
9.1.20	Issuer	<Issr>		[0..1]		67

Used in element(s)

"Other" on page 76

4.35.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max6Text" on page 172

Usage Guideline details

- on pain.001.001.03/PaymentInformation/Debtor/Identification/OrganisationIdentification/Other/Identification**
 - HSBC_Identification:**

Identification is the BACS ID. If not provided at Debtor or Ultimate Debtor (Batch Level only), BACS ID will be enriched from static data.
- on pain.001.001.03/PaymentInformation/UltimateDebtor/Identification/OrganisationIdentification/Other/Identification**
 - HSBC_Identification:**

Identification is the BACS ID. If not provided, BACS ID will be enriched from static data
- on pain.001.001.03/PaymentInformation/Debtor/Identification/OrganisationIdentification/Other/Identification**
 - HSBC_BACSID:**

If
If BACS ID is supplied in Payment Information/Ultimate Debtor and in Payment Information/Debtor

Then
The BACS ID and Name of the Ultimate Debtor will take precedence over the information supplied at Debtor
- on pain.001.001.03/PaymentInformation/UltimateDebtor/Identification/OrganisationIdentification/Other/Identification**
 - HSBC_BACSID:**

If

If BACS ID is supplied in Payment Information/Ultimate Debtor and in Payment Information/Debtor

Then

The BACS ID and Name of the Ultimate Debtor will take precedence over the information supplied at Debtor

4.35.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[OrganisationIdentificationSchemeName1Choice](#)" on page 77 for details)

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.18	Code	<Cd>	{Or	[1..1]		77
9.1.19	Proprietary	<Prtry>	Or}	[1..1]		77

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/Debtor/Identification/OrganisationIdentification/Other/SchemeName) will be ignored by the Receiver.

4.35.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "[Max35Text](#)" on page 171

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/Debtor/Identification/OrganisationIdentification/Other/Issuer) will be ignored by the Receiver.

4.36 GenericPersonIdentification1

Definition: Information related to an identification of a person.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.28	Identification	<Id>		[1..1]		68
9.1.29	SchemeName	<SchmeNm>		[0..1]		68
9.1.32	Issuer	<Issr>		[0..1]		68

Used in element(s)

"Other" on page 103

4.36.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 171

4.36.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "PersonIdentificationScheme-Name1Choice" on page 104 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.30	Code	<Cd>	{Or	[1..1]		104
9.1.31	Proprietary	<Prtry>	Or}	[1..1]		104

4.36.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 171

4.37 GroupHeader32

Definition: Set of characteristics shared by all individual transactions included in the message.

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1	MessageIdentification	<MsgId>		[1..1]	⚠	69
1.2	CreationDateTime	<CreDtTm>		[1..1]		69
1.3	Authorisation	<Authstn>		[0..2]	R[0..1]	69
1.6	NumberOfTransactions	<NbOfTx>		[1..1]	⚠	70
1.7	ControlSum	<CtrlSum>		[0..1]	⚠	70
1.8	InitiatingParty	<InitgPty>		[1..1]		71
1.9	ForwardingAgent	<FwdgAgt>		[0..1]	♦	71

Used in element(s)

"GroupHeader" on page 6

4.37.1 MessageIdentification

XML Tag: MsgId

Presence: [1..1]

Definition: Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message.

Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period.

Datatype: "Max35Text" on page 171

Usage Guideline details

- on pain.001.001.03/GroupHeader/MessageIdentification

Comment:

Unique message reference used with status messages returned for the processing of this file. HSBC recommends this is unique for a 12 monthly rolling period.

4.37.2 CreationDateTime

XML Tag: CreDtTm

Presence: [1..1]

Definition: Date and time at which the message was created.

Datatype: "ISODateTime" on page 167

4.37.3 Authorisation

XML Tag: Authstn

Presence: [0..2]

Definition: User identification or any user key to be used to check whether the initiating party is allowed to initiate transactions from the account specified in the message.

Usage: The content is not of a technical nature, but reflects the organisational structure at the initiating side.

The authorisation element can typically be used in relay scenarios, payment initiations, payment returns or payment reversals that are initiated on behalf of a party different from the initiating party.

The **Authstn** block contains the following elements (see datatype "[Authorisation1Choice](#)" on [page 11](#) for details)

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.4	Code	<Cd>	{Or	[1..1]		12
1.5	Proprietary	<Prtry>	Or}	[1..1]	🚫	12

Usage Guideline details

- on [pain.001.001.03/GroupHeader/Authorisation](#)

This element has change repeatability, the maximum occurrence has been changed to : 1

4.37.4 NumberOfTransactions

XML Tag: NbOfTxS

Presence: [1..1]

Definition: Number of individual transactions contained in the message.

Datatype: "[Max15NumericText](#)" on [page 169](#)

Usage Guideline details

- on [pain.001.001.03/GroupHeader/NumberOfTransactions](#)

Comment:

This will be verified against the number of occurrences of <CdtTrfTxInf> in the message .

4.37.5 ControlSum

XML Tag: CtrlSum

Presence: [0..1]

Definition: Total of all individual amounts included in the message, irrespective of currencies.

Datatype: "[DecimalNumber](#)" on [page 156](#)

Usage Guideline details

- on [pain.001.001.03/GroupHeader/ControlSum](#)

Comment:

This is the hash total of all payment amounts in the entire message regardless of currency in Instructed Amount. If included amount must have 2 decimal places.

4.37.6 InitiatingParty

XML Tag: InitgPty

Presence: [1..1]

Definition: Party that initiates the payment.

Usage: This can either be the debtor or the party that initiates the credit transfer on behalf of the debtor.

The **InitgPty** block contains the following elements (see datatype "[PartyIdentification32](#)" on page 80 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.0	Name	<Nm>		[0..1]		80
9.1.1	PostalAddress	<PstlAdr>		[0..1]		81
9.1.12	Identification	<Id>		[0..1]	⚠	82
9.1.33	CountryOfResidence	<CtryOfRes>		[0..1]	💡	83
9.1.34	ContactDetails	<CtctDtls>		[0..1]	💡	83

4.37.7 ForwardingAgent

XML Tag: FwdgAgt

Presence: [0..1]

Definition: Financial institution that receives the instruction from the initiating party and forwards it to the next agent in the payment chain for execution.

The **FwdgAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification4](#)" on page 12 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.0	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		12
6.1.25	BranchIdentification	<BrnchId>		[0..1]		13

Usage Guideline details

- This element(pain.001.001.03/GroupHeader/ForwardingAgent) will be ignored by the Receiver.

4.38 InstructionForCreditorAgent1

Definition: Further information related to the processing of the payment instruction that may need to be acted upon by the creditor's agent. The instruction may relate to a level of service, or may be an instruction that has to be executed by the creditor's agent, or may be information required by the creditor's agent.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.83	Code	<Cd>		[0..1]		72
2.84	InstructionInformation	<InstrInf>		[0..1]		72

Used in element(s)

"InstructionForCreditorAgent" on page 43

4.38.1 Code

XML Tag: Cd

Presence: [0..1]

Definition: Coded information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor's agent.

Datatype: "Instruction3Code" on page 167

4.38.2 InstructionInformation

XML Tag: InstrInf

Presence: [0..1]

Definition: Further information complementing the coded instruction or instruction to the creditor's agent that is bilaterally agreed or specific to a user community.

Datatype: "Max140Text" on page 169

4.39 LocalInstrument2Choice

Definition: Set of elements that further identifies the type of local instruments being requested by the initiating party.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.12 , 2.37	Code	<Cd>	{Or	[1..1]		73
2.13 , 2.38	Proprietary	<Prtry>	Or}	[1..1]		73

Used in element(s)

"LocalInstrument" on page 102

4.39.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the local instrument, as published in an external local instrument code list.

Datatype: ["ExternalLocalInstrument1Code" on page 162](#)

4.39.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the local instrument, as a proprietary code.

Datatype: ["Max35Text" on page 171](#)

4.40 NameAndAddress10

Definition: Information that locates and identifies a party.

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.56 , 2.62 , 2.96	Name	<Nm>		[1..1]		73
2.57 , 2.63 , 2.97	Address	<Adr>		[1..1]		73

Used in element(s)

["ChequeFrom" on page 24](#), ["DeliverTo" on page 25](#), ["RemittanceLocationPostalAddress" on page 118](#)

4.40.1 Name

XML Tag: Nm

Presence: [1..1]

Definition: Name by which a party is known and is usually used to identify that party.

Datatype: ["Max140Text" on page 169](#)

4.40.2 Address

XML Tag: Adr

Presence: [1..1]

Definition: Postal address of a party.

The **Adr** block contains the following elements (see datatype "PostalAddress6" on page 104 for details)

🚫 Removed - ⚠ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.2 , 6.1.9 , 6.1.29 , 10.1.0	AddressType	<AdrTp>		[0..1]	⚠	105
9.1.3 , 6.1.10 , 6.1.30 , 10.1.1	Department	<Dept>		[0..1]		106
9.1.4 , 6.1.11 , 6.1.31 , 10.1.2	SubDepartment	<SubDept>		[0..1]		106
9.1.5 , 6.1.12 , 6.1.32 , 10.1.3	StreetName	<StrtNm>		[0..1]		106
9.1.6 , 6.1.13 , 6.1.33 , 10.1.4	BuildingNumber	<BldgNb>		[0..1]		106
9.1.7 , 6.1.14 , 6.1.34 , 10.1.5	PostCode	<PstCd>		[0..1]		107
9.1.8 , 6.1.15 , 6.1.35 , 10.1.6	TownName	<TwnNm>		[0..1]		107
9.1.9 , 6.1.16 , 6.1.36 , 10.1.7	CountrySubDivision	<CtrySubDvsn>		[0..1]		107
9.1.10 , 6.1.17 , 6.1.37 , 10.1.8	Country	<Ctry>		[0..1]		107
9.1.11 , 6.1.18 , 6.1.38 , 10.1.9	AddressLine	<AdrLine>		[0..7]		108

4.41 OrganisationIdentification4

Definition: Unique and unambiguous way to identify an organisation.

🚫 Removed - ✦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.14	BICOrBEI	<BICOrBEI>		[0..1]	✦	75
9.1.15	Other	<Othr>		[0..*]	✦ R[0..1] R[0..1]	75

Used in element(s)

"OrganisationIdentification" on page 78

4.41.1 BICOrBEI

XML Tag: BICOrBEI

Presence: [0..1]

Definition: Code allocated to a financial institution or non financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "AnyBICIdentifier" on page 142

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/Identification/OrganisationIdentification/BICOrBEI) will be ignored by the Receiver.

4.41.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericOrganisationIdentification1" on page 64 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.16	Identification	<Id>		[1..1]	✦	64
9.1.17	SchemeName	<SchmeNm>		[0..1]	✦	64
9.1.20	Issuer	<Issr>		[0..1]	✦	65

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/Identification/OrganisationIdentification/Other) will be ignored by the Receiver.

- on pain.001.001.03/GroupHeader/InitiatingParty/Identification/OrganisationIdentification/Other
This element has change repeatability, the maximum occurrence has been changed to : 1
- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/Identification/OrganisationIdentification/Other
This element has change repeatability, the maximum occurrence has been changed to : 1

4.42 OrganisationIdentification4__1

Definition: Unique and unambiguous way to identify an organisation.

🚫 Removed - 💡 Ignored - ⚠️ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.14	BICOrBEI	<BICOrBEI>		[0..1]	💡 🚫	76
9.1.15	Other	<Othr>		[0..*]	⚠️ R[0..1] R[0..1]	76

Used in element(s)

"OrganisationIdentification" on page 79

4.42.1 BICOrBEI

XML Tag: BICOrBEI

Presence: [0..1]

Definition: Code allocated to a financial institution or non financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "AnyBICIdentifier" on page 142

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/Debtor/Identification/OrganisationIdentification/BICOrBEI) is removed.
- This element(pain.001.001.03/PaymentInformation/UltimateDebtor/Identification/OrganisationIdentification/BICOrBEI) will be ignored by the Receiver.

4.42.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericOrganisationIdentification1__1](#)" on page 65 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.16	Identification	<Id>		[1..1]	⚠	66
9.1.17	SchemeName	<SchmeNm>		[0..1]	💡	67
9.1.20	Issuer	<Issr>		[0..1]	💡	67

Usage Guideline details

- on **pain.001.001.03/PaymentInformation/Debtor/Identification/OrganisationIdentification/Other**
This element has change repeatability, the maximum occurrence has been changed to : 1
- on **pain.001.001.03/PaymentInformation/UltimateDebtor/Identification/OrganisationIdentification/Other**
This element has change repeatability, the maximum occurrence has been changed to : 1
- on **pain.001.001.03/PaymentInformation/Debtor/Identification/OrganisationIdentification/Other**
Comment:
BACS ID. If not provided, BACS ID will be enriched from static data.

4.43 OrganisationIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.18	Code	<Cd>	{Or	[1..1]		77
9.1.19	Proprietary	<Prtry>	Or}	[1..1]		77

Used in element(s)

"SchemeName" on page 64, "SchemeName" on page 67

4.43.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "[ExternalOrganisationIdentification1Code](#)" on page 163

4.43.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 171

4.44 Party6Choice

Definition: Nature or use of the account.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.13	OrganisationIdentification	<OrgId>	{Or	[1..1]	💡	78
9.1.21	PrivateIdentification	<PrvtId>	Or}	[1..1]	💡	78

Used in element(s)

"Identification" on page 82

4.44.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "OrganisationIdentification4" on page 74 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.14	BICOrBEI	<BICOrBEI>		[0..1]	💡	75
9.1.15	Other	<Othr>		[0..*]	💡 R[0..1] R[0..1]	75

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/Identification/OrganisationIdentification) will be ignored by the Receiver.

4.44.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "[PersonIdentification5](#)" on page 103 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.22	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		103
9.1.27	Other	<Othr>		[0..*]		103

Usage Guideline details

- This element(pain.001.001.03/GroupHeader/InitiatingParty/Identification/PrivateIdentification) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/Identification/PrivateIdentification) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/Identification/PrivateIdentification) will be ignored by the Receiver.

4.45 Party6Choice__1

Definition: Nature or use of the account.

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.13	OrganisationIdentification	<OrgId>	{Or	[1..1]		79
9.1.21	PrivateIdentification	<PrvtId>	Or}	[1..1]	✦ 🚫	80

Used in element(s)

"Identification" on page 86

4.45.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "[OrganisationIdentification4__1](#)" on page 76 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.14	BICOrBEI	<BICOrBEI>		[0..1]	✦ 🚫	76
9.1.15	Other	<Othr>		[0..*]	⚠ R[0..1] R[0..1]	76

4.45.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "PersonIdentification5" on page 103 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.22	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		103
9.1.27	Other	<Othr>		[0..*]		103

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/Debtor/Identification/PrivateIdentification) is removed.
- This element(pain.001.001.03/PaymentInformation/Debtor/Identification/PrivateIdentification) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/UltimateDebtor/Identification/PrivateIdentification) will be ignored by the Receiver.

4.46 PartyIdentification32

Definition: Set of elements used to identify a person or an organisation.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.0	Name	<Nm>		[0..1]	M 💡 ⚠️	80
9.1.1	PostalAddress	<PstlAdr>		[0..1]	💡	81
9.1.12	Identification	<Id>		[0..1]	💡 ⚠️	82
9.1.33	CountryOfResidence	<CtryOfRes>		[0..1]	💡	83
9.1.34	ContactDetails	<CtctDtls>		[0..1]	💡	83

Used in element(s)

"Creditor" on page 41, "InitiatingParty" on page 71, "Invoicee" on page 124, "Invoicer" on page 123, "UltimateCreditor" on page 42, "UltimateDebtor" on page 36

4.46.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max140Text" on page 169

Usage Guideline details

- **This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/Name) will be ignored by the Receiver.**
- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/Name**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/Name**
 - **HSBC_Name:**

If name is longer than 18 characters, it will be truncated.

4.46.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress6" on page 104 for details)

🚫 Removed - ⚠ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.2 , 6.1.9 , 6.1.29 , 10.1.0	AddressType	<AdrTp>		[0..1]	⚠	105
9.1.3 , 6.1.10 , 6.1.30 , 10.1.1	Department	<Dept>		[0..1]		106
9.1.4 , 6.1.11 , 6.1.31 , 10.1.2	SubDepartment	<SubDept>		[0..1]		106
9.1.5 , 6.1.12 , 6.1.32 , 10.1.3	StreetName	<StrtNm>		[0..1]		106
9.1.6 , 6.1.13 , 6.1.33 , 10.1.4	BuildingNumber	<BldgNb>		[0..1]		106
9.1.7 , 6.1.14 , 6.1.34 , 10.1.5	PostCode	<PstCd>		[0..1]		107
9.1.8 , 6.1.15 , 6.1.35 , 10.1.6	TownName	<TwnNm>		[0..1]		107
9.1.9 , 6.1.16 , 6.1.36 , 10.1.7	CountrySubDivision	<CtrySubDvsn>		[0..1]		107
9.1.10 , 6.1.17 , 6.1.37 , 10.1.8	Country	<Ctry>		[0..1]		107
9.1.11 , 6.1.18 , 6.1.38 , 10.1.9	AddressLine	<AdrLine>		[0..7]		108

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/PostalAddress) will be ignored by the Receiver.

4.46.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "Party6Choice" on page 78 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.13	OrganisationIdentification	<OrgId>	{Or	[1..1]	💡	78
9.1.21	PrivateIdentification	<PrvtId>	Or}	[1..1]	💡	78

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/Identification) will be ignored by the Receiver.
- on pain.001.001.03/GroupHeader/InitiatingParty/Identification
 - **HSBC_InitiatingParty:**

Provide HSBC Connect Customer ID under /InitgPty/Id/OrgId/Othr/Id/. Alternatively, provide: BIC under /InitgPty/Id/OrgId/BICOrBEI/ or SIRET ID under /InitgPty/Id/OrgId/Othr/Id/

Please note that this information is mandatory for Host to Host and Swiftnet File Act submissions. While this information is not mandatory for HSBCnet File Upload we strongly encourage including it.

4.46.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "CountryCode" on page 155

Usage Guideline details

- This element(pain.001.001.03/GroupHeader/InitiatingParty/CountryOfResidence) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/CountryOfResidence) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/CountryOfResidence) will be ignored by the Receiver.

4.46.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "[ContactDetails2](#)" on page 30 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.35	NamePrefix	<NmPrfx>		[0..1]		30
9.1.36	Name	<Nm>		[0..1]		30
9.1.37	PhoneNumber	<PhneNb>		[0..1]		30
9.1.38	MobileNumber	<MobNb>		[0..1]		31
9.1.39	FaxNumber	<FaxNb>		[0..1]		31
9.1.40	EmailAddress	<EmailAdr>		[0..1]		31
9.1.41	Other	<Othr>		[0..1]		31

Usage Guideline details

- This element(pain.001.001.03/GroupHeader/InitiatingParty/ContactDetails) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/ContactDetails) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/ContactDetails) will be ignored by the Receiver.

4.47 PartyIdentification32__1

Definition: Set of elements used to identify a person or an organisation.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.0	Name	<Nm>		[0..1]	M	85
9.1.1	PostalAddress	<PstlAdr>		[0..1]	💡	85
9.1.12	Identification	<Id>		[0..1]		86
9.1.33	CountryOfResidence	<CtryOfRes>		[0..1]	💡	87
9.1.34	ContactDetails	<CtctDtls>		[0..1]	💡	87

Used in element(s)

"Debtor" on page 96, "UltimateDebtor" on page 97

4.47.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max18Text__1" on page 170

Usage Guideline details

- on pain.001.001.03/PaymentInformation/Debtor/Name

This element is now mandatory, the minimum occurrence has been changed to : 1

4.47.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress6" on page 104 for details)

🚫 Removed - ⚡ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.2 , 6.1.9 , 6.1.29 , 10.1.0	AddressType	<AdrTp>		[0..1]	⚡	105
9.1.3 , 6.1.10 , 6.1.30 , 10.1.1	Department	<Dept>		[0..1]		106
9.1.4 , 6.1.11 , 6.1.31 , 10.1.2	SubDepartment	<SubDept>		[0..1]		106
9.1.5 , 6.1.12 , 6.1.32 , 10.1.3	StreetName	<StrtNm>		[0..1]		106
9.1.6 , 6.1.13 , 6.1.33 , 10.1.4	BuildingNumber	<BldgNb>		[0..1]		106
9.1.7 , 6.1.14 , 6.1.34 , 10.1.5	PostCode	<PstCd>		[0..1]		107
9.1.8 , 6.1.15 , 6.1.35 , 10.1.6	TownName	<TwnNm>		[0..1]		107
9.1.9 , 6.1.16 , 6.1.36 , 10.1.7	CountrySubDivision	<CtrySubDvsn>		[0..1]		107
9.1.10 , 6.1.17 , 6.1.37 , 10.1.8	Country	<Ctry>		[0..1]		107
9.1.11 , 6.1.18 , 6.1.38 , 10.1.9	AddressLine	<AdrLine>		[0..7]		108

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/UltimateDebtor/PostalAddress) will be ignored by the Receiver.

4.47.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "[Party6Choice__1](#)" on page 79 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.13	OrganisationIdentification	<OrgId>	{Or	[1..1]		79
9.1.21	PrivateIdentification	<PrvtId>	Or}	[1..1]	💡 🚫	80

4.47.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "[CountryCode](#)" on page 155

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/UltimateDebtor/CountryOfResidence](#)) will be ignored by the Receiver.

4.47.5 ContactDetails

XML Tag: CtctDtIs

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "[ContactDetails2](#)" on page 30 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.35	NamePrefix	<NmPrfx>		[0..1]		30
9.1.36	Name	<Nm>		[0..1]		30
9.1.37	PhoneNumber	<PhneNb>		[0..1]		30
9.1.38	MobileNumber	<MobNb>		[0..1]		31
9.1.39	FaxNumber	<FaxNb>		[0..1]		31
9.1.40	EmailAddress	<EmailAdr>		[0..1]		31
9.1.41	Other	<Othr>		[0..1]		31

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/Debtor/ContactDetails](#)) will be ignored by the Receiver.
- This element([pain.001.001.03/PaymentInformation/UltimateDebtor/ContactDetails](#)) will be ignored by the Receiver.

4.48 PaymentIdentification1__1

Definition: Set of elements used to provide further means of referencing a payment transaction.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.29	InstructionIdentification	<InstrId>		[0..1]		88
2.30	EndToEndIdentification	<EndToEndId>		[1..1]	⚠	89

Used in element(s)

["PaymentIdentification"](#) on page 34

4.48.1 InstructionIdentification

XML Tag: InstrId

Presence: [0..1]

Definition: Unique identification as assigned by an instructing party for an instructed party to unambiguously identify the instruction.

Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction.

Datatype: "Max35Text" on page 171

4.48.2 EndToEndIdentification

XML Tag: EndToEndId

Presence: [1..1]

Definition: Unique identification assigned by the initiating party to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.

Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction.

Datatype: "Max18Text" on page 170

Usage Guideline details

- on `pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/PaymentIdentification/EndToEndIdentification`

– HSBC_EndToEndIdentification:

A maximum length of 18 chars is supported by BACS; if a longer ID is provided it will be truncated. Please note that for building society payments no ID can be transmitted to the beneficiary

- on `pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/PaymentIdentification/EndToEndIdentification`

Comment:

A maximum length of 18 chars is supported by BACS; if a longer ID is provided it will be truncated. Please note that for building society payments the roll number will be populated therefore no ID can be transmitted to the beneficiary.

4.49 PaymentInstructionInformation3__1

Definition: Set of characteristics that apply to the debit side of the payment transactions included in the credit transfer initiation.

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.1	PaymentInformationIdentification	<PmtInfId>		[1..1]	⚠	93
2.2	PaymentMethod	<PmtMtd>		[1..1]		93
2.3	BatchBooking	<BtchBookg>		[0..1]	⚠	94
2.4	NumberOfTransactions	<NbOfTxS>		[0..1]		94
2.5	ControlSum	<CtrlSum>		[0..1]	⚠	94
2.6	PaymentTypeInformation	<PmtTplnf>		[0..1]	M	94
2.17	RequestedExecutionDate	<ReqdExctnDt>		[1..1]	⚠	95
2.18	PoolingAdjustmentDate	<PoolgAdjstmntDt>		[0..1]	♦	95
2.19	Debtor	<Dbtr>		[1..1]		96
2.20	DebtorAccount	<DbtrAcct>		[1..1]	⚠	96
2.21	DebtorAgent	<DbtrAgt>		[1..1]		97
2.22	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]	♦	97
2.23	UltimateDebtor	<UltmtDbtr>		[0..1]		97
2.24	ChargeBearer	<ChrgBr>		[0..1]	♦	98
2.25	ChargesAccount	<ChrgsAcct>		[0..1]	♦	98
2.26	ChargesAccountAgent	<ChrgsAcctAgt>		[0..1]	♦	99
2.27	CreditTransferTransactionInformation	<CdtTrfTxInf>		[1..*]		99

Rules

R8 PaymentTypeInformationRule ✓

If PaymentTypeInformation is present, then CreditTransferTransactionInformation/PaymentTypeInformation is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00009
- *Error Text:* Invalid message content for payment type information.

R9 ChequeInstructionRule ✓

If PaymentMethod is different from CHK, then CreditTransferTransactionInformation/ChequeInstruction is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00100

- *Error Text:* Invalid message content for cheque instruction.

R10 ChargesAccountRule ✓

If ChargesAccountAgent is present, then ChargesAccount must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00099
- *Error Text:* Invalid message content for charges agent account.

R11 ChargesAccountAgentRule

If ChargesAccountAgent is present, then it must contain a branch of the DebtorAgent. It must not contain a completely different agent.

Error handling: Undefined

R12 ChargeBearerRule ✓

If ChargeBearer is present, then CreditTransferTransactionInformation/ChargeBearer is not allowed.

If CreditTransferTransactionInformation/ChargeBearer is present, then ChargeBearer is not allowed.

CreditTransferTransactionInformation/ChargeBearer and ChargeBearer may both be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00112
- *Error Text:* Invalid message content for charge bearer.

R13 UltimateDebtorRule ✓

If UltimateDebtor is present, then CreditTransferTransactionInformation/UltimateDebtor is not allowed.

If CreditTransferTransactionInformation/UltimateDebtor is present, then UltimateDebtor is not allowed.

CreditTransferTransactionInformation/UltimateDebtor and UltimateDebtor may both be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00097
- *Error Text:* Invalid message content for ultimate debtor.

R14 ChequeAndCreditorAccountRule ✓

If PaymentMethod is CHK, then CreditTransferTransactionInformation/CreditorAccount is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00107
- *Error Text:* Invalid message content for cheque payment method.

R15 ChequeDeliveryAndCreditorAgentRule ✓

If PaymentMethod is CHK and CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod/Code is present and is equal to MLFA, CRFA, RGFA or PUFA, then CreditTransferTransactionInformation/CreditorAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00109
- *Error Text:* Invalid message content for cheque payment with creditor agent.

R16 ChequeDeliveryAndNoCreditorAgentRule ✓

If PaymentMethod is CHK and CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod/Code is present and different from MLFA, CRFA, RGFA or PUFA, then CreditTransferTransactionInformation/CreditorAgent is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00110
- *Error Text:* Invalid message content for cheque payment without creditor agent.

R17 NonChequePaymentMethodRule

If PaymentMethod is different from CHK and CreditTransferTransactionInformation/Creditor is not present, then CreditTransferTransactionInformation/CreditorAccount must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00108
- *Error Text:* Invalid message content for non cheque payment method.

R18 ChequeNoDeliveryAndNoCreditorAgentRule ✓

If PaymentMethod is CHK and CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is not present, then CreditTransferTransactionInformation/CreditorAgent is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00111
- *Error Text:* Invalid message content for cheque payment without delivery method.

Guidelines

1. UltimateDebtorGuideline

UltimateDebtor may only be present if different from Debtor.

2. ChequeInstructionDeliverToDebtorGuideline

If CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and if CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod/Code is CRDB, MLDB, PUDB or RGDB, then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different from Debtor.

3. ChequeInstructionDeliverToCreditorGuideline

If PaymentInformation/CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and is CRCD, MLCD, PUCD or RGCD, then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different from CreditTransferTransactionInformation/Creditor.

4. ChequeInstructionDeliverToCreditorAgentGuideline

If CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and is CRFA, MLFA, PUFA or RGFA, then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different from CreditTransferTransactionInformation/Creditor.

5. ChequeFromGuideline

CreditTransferTransactionInformation/ChequeInstruction/ChequeFrom may only be present if different from CreditTransferTransactionInformation/UltimateDebtor or Debtor.

Used in element(s)

"PaymentInformation" on page 6

4.49.1 PaymentInformationIdentification

XML Tag: PmtInfId

Presence: [1..1]

Definition: Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message.

Datatype: "Max18Text" on page 170

Usage Guideline details

- on pain.001.001.03/PaymentInformation/PaymentInformationIdentification

– HSBC_PaymentInformationIdentification:

Payment Information Identification is the Batch Reference Number

4.49.2 PaymentMethod

XML Tag: PmtMtd

Presence: [1..1]

Definition: Specifies the means of payment that will be used to move the amount of money.

Datatype: ["PaymentMethod3Code" on page 175](#)

4.49.3 BatchBooking

XML Tag: BtchBookg

Presence: [0..1]

Definition: Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested.

Usage: Batch booking is used to request and not order a possible batch booking.

Datatype: ["BatchBookingIndicator" on page 145](#)

Usage Guideline details

- on pain.001.001.03/PaymentInformation/BatchBooking

Comment:

TRUE = Single entry on the Bank Statement for total value of Batch.
False= All transactions will be reported individually on Bank Statement.
Default is True.

4.49.4 NumberOfTransactions

XML Tag: NbOfTxS

Presence: [0..1]

Definition: Number of individual transactions contained in the paymnet information group.

Datatype: ["Max15NumericText" on page 169](#)

4.49.5 ControlSum

XML Tag: CtrlSum

Presence: [0..1]

Definition: Total of all individual amounts included in the group, irrespective of currencies.

Datatype: ["DecimalNumber" on page 156](#)

Usage Guideline details

- on pain.001.001.03/PaymentInformation/ControlSum

Comment:

This is the hash total of all payment amounts within a Payment Information batch regardless of currency in Instructed Amount. If included this value will be checked and must have 2 decimal places.

4.49.6 PaymentTypeInformation

XML Tag: PmtTpInf

Presence: [0..1]

Definition: Set of elements used to further specify the type of transaction.

The **PmtTpInf** block contains the following elements (see datatype "[PaymentTypeInformation19__1](#)" on [page 100](#) for details)

🚫 Removed - ⚠ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.7 , 2.32	InstructionPriority	<InstrPrty>		[0..1]	⚠	101
2.8 , 2.33	ServiceLevel	<SvcLv>		[0..1]	M	101
2.11 , 2.36	LocalInstrument	<LclInstrm>		[0..1]		102
2.14 , 2.39	CategoryPurpose	<CtgyPurp>		[0..1]		102

Usage Guideline details

- on [pain.001.001.03/PaymentInformation/PaymentTypeInformation](#)
This element is now mandatory, the minimum occurrence has been changed to : 1

4.49.7 RequestedExecutionDate

XML Tag: ReqdExctnDt

Presence: [1..1]

Definition: Date at which the initiating party requests the clearing agent to process the payment.

Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank.

Datatype: "[ISODate](#)" on [page 167](#)

Usage Guideline details

- on [pain.001.001.03/PaymentInformation/RequestedExecutionDate](#)
Comment:
Work day on which the payment should be initiated.

4.49.8 PoolingAdjustmentDate

XML Tag: PoolgAdjstmntDt

Presence: [0..1]

Definition: Date used for the correction of the value date of a cash pool movement that has been posted with a different value date.

Datatype: "[ISODate](#)" on [page 167](#)

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/PoolingAdjustmentDate](#)) will be ignored by the Receiver.

4.49.9 Debtor

XML Tag: Dbtr

Presence: [1..1]

Definition: Party that owes an amount of money to the (ultimate) creditor.

The **Dbtr** block contains the following elements (see datatype "[PartyIdentification32__1](#)" on page 84 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.0	Name	<Nm>		[0..1]	M	85
9.1.1	PostalAddress	<PstlAdr>		[0..1]		85
9.1.12	Identification	<Id>		[0..1]		86
9.1.33	CountryOfResidence	<CtryOfRes>		[0..1]		87
9.1.34	ContactDetails	<CtctDtls>		[0..1]	💡	87

4.49.10 DebtorAccount

XML Tag: DbtrAcct

Presence: [1..1]

Definition: Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.

The **DbtrAcct** block contains the following elements (see datatype "[CashAccount16__1](#)" on page 19 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.0	Identification	<Id>		[1..1]		20
1.1.8	Type	<Tp>		[0..1]		20
1.1.11	Currency	<Ccy>		[0..1]	💡	20
1.1.12	Name	<Nm>		[0..1]	💡	21

Usage Guideline details

- on [pain.001.001.03/PaymentInformation/DebtorAccount](#)
- Comment:**

Debit account must be provided as 8 characters domestic account number or IBAN

4.49.11 DebtorAgent

XML Tag: DbtrAgt

Presence: [1..1]

Definition: Financial institution servicing an account for the debtor.

The **DbtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification4__1](#)" on page 13 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.0	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		14
6.1.25	BranchIdentification	<BrnchId>		[0..1]		14

4.49.12 DebtorAgentAccount

XML Tag: DbtrAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain.

The **DbtrAgtAcct** block contains the following elements (see datatype "[CashAccount16](#)" on page 18 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.0	Identification	<Id>		[1..1]		18
1.1.8	Type	<Tp>		[0..1]		18
1.1.11	Currency	<Ccy>		[0..1]		19
1.1.12	Name	<Nm>		[0..1]		19

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/DebtorAgentAccount) will be ignored by the Receiver.

4.49.13 UltimateDebtor

XML Tag: UltmtDbtr

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor.

The **UltmtDbtr** block contains the following elements (see datatype "[PartyIdentification32__1](#)" on [page 84](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.0	Name	<Nm>		[0..1]		85
9.1.1	PostalAddress	<PstlAdr>		[0..1]	💡	85
9.1.12	Identification	<Id>		[0..1]		86
9.1.33	CountryOfResidence	<CtryOfRes>		[0..1]	💡	87
9.1.34	ContactDetails	<CtctDtls>		[0..1]	💡	87

4.49.14 ChargeBearer

XML Tag: ChrgBr

Presence: [0..1]

Definition: Specifies which party/parties will bear the charges associated with the processing of the payment transaction.

Datatype: "[ChargeBearerType1Code](#)" on [page 150](#)

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/ChargeBearer](#)) will be ignored by the Receiver.

4.49.15 ChargesAccount

XML Tag: ChrgsAcct

Presence: [0..1]

Definition: Account used to process charges associated with a transaction.

Usage: Charges account should be used when charges have to be booked to an account different from the account identified in debtor's account.

The **ChrgsAcct** block contains the following elements (see datatype "[CashAccount16](#)" on [page 18](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.0	Identification	<Id>		[1..1]		18
1.1.8	Type	<Tp>		[0..1]		18
1.1.11	Currency	<Ccy>		[0..1]		19
1.1.12	Name	<Nm>		[0..1]		19

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/ChargesAccount](#)) will be ignored by the Receiver.

4.49.16 ChargesAccountAgent

XML Tag: ChrgsAcctAgt

Presence: [0..1]

Definition: Agent that services a charges account.

Usage: Charges account agent should only be used when the charges account agent is different from the debtor agent.

The **ChrgsAcctAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification4](#)" on [page 12](#) for details)

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
6.1.0	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		12
6.1.25	BranchIdentification	<BrnchId>		[0..1]		13

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/ChargesAccountAgent](#)) will be ignored by the Receiver.

4.49.17 CreditTransferTransactionInformation

XML Tag: CdtTrfTxInf

Presence: [1..*]

Definition: Set of elements used to provide information on the individual transaction(s) included in the message.

The **CdtTrfTxInf** block contains the following elements (see datatype "CreditTransferTransactionInformation10__1" on page 31 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.28	PaymentIdentification	<PmtId>		[1..1]		34
2.31	PaymentTypeInformation	<PmtTplnf>		[0..1]	M	34
2.42	Amount	<Amt>		[1..1]		35
2.47	ExchangeRateInformation	<XchgRateInf>		[0..1]	💡 🚫	35
2.51	ChargeBearer	<ChrgBr>		[0..1]	💡	36
2.52	ChequeInstruction	<ChqInstr>		[0..1]	💡	36
2.70	UltimateDebtor	<UltmtDbtr>		[0..1]	💡	36
2.71	IntermediaryAgent1	<IntrmyAgt1>		[0..1]	🚫	37
2.72	IntermediaryAgent1Account	<IntrmyAgt1Acct>		[0..1]	💡	37
2.73	IntermediaryAgent2	<IntrmyAgt2>		[0..1]	💡	38
2.74	IntermediaryAgent2Account	<IntrmyAgt2Acct>		[0..1]	💡	38
2.75	IntermediaryAgent3	<IntrmyAgt3>		[0..1]	💡	39
2.76	IntermediaryAgent3Account	<IntrmyAgt3Acct>		[0..1]	💡	39
2.77	CreditorAgent	<CdtrAgt>		[0..1]	M	40
2.78	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]	⚠️	40
2.79	Creditor	<Cdtr>		[0..1]	M	41
2.80	CreditorAccount	<CdtrAcct>		[0..1]	M ⚠️	42
2.81	UltimateCreditor	<UltmtCdtr>		[0..1]	💡	42
2.82	InstructionForCreditorAgent	<InstrForCdtrAgt>		[0..*]	💡	43
2.85	InstructionForDebtorAgent	<InstrForDbtrAgt>		[0..1]	💡	43
2.86	Purpose	<Purp>		[0..1]	💡	44
2.89	RegulatoryReporting	<RgltryRptg>		[0..10]		44
2.90	Tax	<Tax>		[0..1]		45
2.91	RelatedRemittanceInformation	<RltdRmtInf>		[0..10]	⚠️	45
2.98	RemittanceInformation	<RmtInf>		[0..1]		46

4.50 PaymentTypeInformation19__1

Definition: Set of elements used to provide further details of the type of payment.

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.7 , 2.32	InstructionPriority	<InstrPrty>		[0..1]	♦	101
2.8 , 2.33	ServiceLevel	<SvcLvl>		[0..1]	M	101
2.11 , 2.36	LocalInstrument	<LclInstrm>		[0..1]		102
2.14 , 2.39	CategoryPurpose	<CtgyPurp>		[0..1]		102

Used in element(s)

"PaymentTypeInformation" on page 94, "PaymentTypeInformation" on page 34

4.50.1 InstructionPriority

XML Tag: InstrPrty

Presence: [0..1]

Definition: Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction.

Datatype: "Priority2Code" on page 176

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/PaymentTypeInformation/InstructionPriority) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/PaymentTypeInformation/InstructionPriority) will be ignored by the Receiver.

4.50.2 ServiceLevel

XML Tag: SvcLvl

Presence: [0..1]

Definition: Agreement under which or rules under which the transaction should be processed.

The **SvcLvl** block contains the following elements (see datatype "ServiceLevel8Choice__1" on page 118 for details)

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.9 , 2.34	Code	<Cd>	{Or	[1..1]	⚠	119
2.10 , 2.35	Proprietary	<Prtry>	Or}	[1..1]	🚫	119

Usage Guideline details

- on **pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/PaymentType-Information/ServiceLevel**

This element is now mandatory, the minimum occurrence has been changed to : 1

- on **pain.001.001.03/PaymentInformation/PaymentTypeInformation/ServiceLevel**

This element is now mandatory, the minimum occurrence has been changed to : 1

4.50.3 LocalInstrument

XML Tag: LclInstrm

Presence: [0..1]

Definition: User community specific instrument.

Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level.

The **LclInstrm** block contains the following elements (see datatype "[LocalInstrument2Choice](#)" on page 72 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.12 , 2.37	Code	<Cd>	{Or}	[1..1]		73
2.13 , 2.38	Proprietary	<Prtry>	Or}	[1..1]		73

4.50.4 CategoryPurpose

XML Tag: Ctgypurp

Presence: [0..1]

Definition: Specifies the high level purpose of the instruction based on a set of pre-defined categories.

Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.

The **Ctgypurp** block contains the following elements (see datatype "[CategoryPurpose1Choice](#)" on page 22 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.15 , 2.40	Code	<Cd>	{Or}	[1..1]		23
2.16 , 2.41	Proprietary	<Prtry>	Or}	[1..1]		23

4.51 PersonIdentification5

Definition: Unique and unambiguous way to identify a person.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.22	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		103
9.1.27	Other	<Othr>		[0..*]		103

Used in element(s)

"PrivateIdentification" on page 78, "PrivateIdentification" on page 80

4.51.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "DateAndPlaceOfBirth" on page 49 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.23	BirthDate	<BirthDt>		[1..1]		49
9.1.24	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		49
9.1.25	CityOfBirth	<CityOfBirth>		[1..1]		49
9.1.26	CountryOfBirth	<CtryOfBirth>		[1..1]		50

4.51.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericPersonIdentification1" on page 67 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.28	Identification	<Id>		[1..1]		68
9.1.29	SchemeName	<SchmeNm>		[0..1]		68
9.1.32	Issuer	<Issr>		[0..1]		68

4.52 PersonIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the identification scheme.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.30	Code	<Cd>	{Or	[1..1]		104
9.1.31	Proprietary	<Prtry>	Or}	[1..1]		104

Used in element(s)

"SchemeName" on page 68

4.52.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalPersonIdentification1Code" on page 164

4.52.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 171

4.53 PostalAddress6

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.2 , 6.1.9 , 6.1.29 , 10.1.0	AddressType	<AdrTp>		[0..1]		105
9.1.3 , 6.1.10 , 6.1.30 , 10.1.1	Department	<Dept>		[0..1]		106
9.1.4 , 6.1.11 , 6.1.31 , 10.1.2	SubDepartment	<SubDept>		[0..1]		106
9.1.5 , 6.1.12 , 6.1.32 , 10.1.3	StreetName	<StrtNm>		[0..1]		106
9.1.6 , 6.1.13 , 6.1.33 , 10.1.4	BuildingNumber	<BldgNb>		[0..1]		106
9.1.7 , 6.1.14 , 6.1.34 , 10.1.5	PostCode	<PstCd>		[0..1]		107
9.1.8 , 6.1.15 , 6.1.35 , 10.1.6	TownName	<TwnNm>		[0..1]		107
9.1.9 , 6.1.16 , 6.1.36 , 10.1.7	CountrySubDivision	<CtrySubDvsn>		[0..1]		107
9.1.10 , 6.1.17 , 6.1.37 , 10.1.8	Country	<Ctry>		[0..1]	 	107
9.1.11 , 6.1.18 , 6.1.38 , 10.1.9	AddressLine	<AdrLine>		[0..7]		108

Used in element(s)

"Address" on page 73, "PostalAddress" on page 16, "PostalAddress" on page 81, "PostalAddress" on page 55, "PostalAddress" on page 85, "PostalAddress" on page 58

4.53.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

Datatype: ["AddressType2Code" on page 140](#)

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/PostalAddress/AddressType](#)) will be ignored by the Receiver.
- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) will be ignored by the Receiver.
- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) will be ignored by the Receiver.
- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RelatedRemittanceInformation/RemittanceLocationPostalAddress/Address/AddressType](#)) will be ignored by the Receiver.
- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/PostalAddress/AddressType](#)) will be ignored by the Receiver.
- This element([pain.001.001.03/PaymentInformation/Debtor/PostalAddress/AddressType](#)) will be ignored by the Receiver.

4.53.2 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: ["Max70Text" on page 173](#)

4.53.3 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: ["Max70Text" on page 173](#)

4.53.4 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: ["Max70Text" on page 173](#)

4.53.5 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: "Max16Text" on page 170

4.53.6 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: "Max16Text" on page 170

4.53.7 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "Max35Text" on page 171

4.53.8 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: "Max35Text" on page 171

4.53.9 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: "CountryCode" on page 155

Usage Guideline details

- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/Country**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.001.001.03/PaymentInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Country**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/Country**
Comment:

The creditor agent's country code should be provided in this field. Please note that for Building Society payments it is mandatory to provide the country code in this field.

- on pain.001.001.03/PaymentInformation/DebtorAgent/FinancialInstitutionIdentification/Postal-Address/Country

Comment:

The debtor agent's country code should be provided in this field. Please note that for Building Society payments it is mandatory to provide the country code in this field.

4.53.10 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "Max70Text" on page 173

4.54 Purpose2Choice

Definition: Specifies the underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.87	Code	<Cd>	{Or	[1..1]		108
2.88	Proprietary	<Prtry>	Or}	[1..1]		108

Used in element(s)

"Purpose" on page 44

4.54.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Underlying reason for the payment transaction, as published in an external purpose code list.

Datatype: "ExternalPurpose1Code" on page 165

4.54.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Purpose, in a proprietary form.

Datatype: ["Max35Text" on page 171](#)

4.55 ReferredDocumentInformation3

Definition: Set of elements used to identify the documents referred to in the remittance information.

🚫 Removed - 💡 Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.102	Type	<Tp>		[0..1]		109
2.107	Number	<Nb>		[0..1]	💡	109
2.108	RelatedDate	<RltdDt>		[0..1]	💡	110

Used in element(s)

["ReferredDocumentInformation" on page 122](#)

4.55.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of referred document.

The **Tp** block contains the following elements (see datatype ["ReferredDocumentType2" on page 111](#) for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.103	CodeOrProprietary	<CdOrPrtry>		[1..1]		111
2.106	Issuer	<Issr>		[0..1]	💡	111

4.55.2 Number

XML Tag: Nb

Presence: [0..1]

Definition: Unique and unambiguous identification of the referred document.

Datatype: ["Max35Text" on page 171](#)

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/ReferredDocumentInformation/Number](#)) will be ignored by the Receiver.

4.55.3 RelatedDate

XML Tag: RltdDt

Presence: [0..1]

Definition: Date associated with the referred document.

Datatype: ["ISODate" on page 167](#)

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/ReferredDocumentInformation/RelatedDate](#)) will be ignored by the Receiver.

4.56 ReferredDocumentType1Choice

Definition: Specifies the type of the document referred in the remittance information.

🚫 Removed - ♦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.104	Code	<Cd>	{Or	[1..1]		110
2.105	Proprietary	<Prtry>	Or}	[1..1]	♦	110

Used in element(s)

["CodeOrProprietary" on page 111](#)

4.56.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Document type in a coded form.

Datatype: ["DocumentType5Code" on page 156](#)

4.56.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Proprietary identification of the type of the remittance document.

Datatype: ["Max35Text" on page 171](#)

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/ReferredDocumentInformation/Type/CodeOrProprietary/Proprietary) will be ignored by the Receiver.

4.57 ReferredDocumentType2

Definition: Specifies the type of the document referred in the remittance information.

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.103	CodeOrProprietary	<CdOrPrtry>		[1..1]		111
2.106	Issuer	<Issr>		[0..1]	✦	111

Used in element(s)

"Type" on page 109

4.57.1 CodeOrProprietary

XML Tag: CdOrPrtry

Presence: [1..1]

Definition: Provides the type details of the referred document.

The **CdOrPrtry** block contains the following elements (see datatype "[ReferredDocumentType1Choice](#)" on page 110 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.104	Code	<Cd>	{Or	[1..1]		110
2.105	Proprietary	<Prtry>	Or}	[1..1]	✦	110

4.57.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Identification of the issuer of the reference document type.

Datatype: "[Max35Text](#)" on page 171

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/ReferredDocumentInformation/Type/Issuer](#)) will be ignored by the Receiver.

4.58 RegulatoryAuthority2

Definition: Entity requiring the regulatory reporting information.

Removed - Ignored - Details below - Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
11.1.2	Name	<Nm>		[0..1]		112
11.1.3	Country	<Ctry>		[0..1]		112

Used in element(s)

"Authority" on page 113

4.58.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the entity requiring the regulatory reporting information.

Datatype: "Max140Text" on page 169

4.58.2 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Country of the entity that requires the regulatory reporting information.

Datatype: "CountryCode" on page 155

4.59 RegulatoryReporting3

Definition: Information needed due to regulatory and/or statutory requirements.

Removed - Ignored - Details below - Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
11.1.0	DebitCreditReportingIndicator	<DbtCdtRptgInd>		[0..1]		113
11.1.1	Authority	<Authrty>		[0..1]	Ignored	113
11.1.4	Details	<Dtls>		[0..*]		113

Used in element(s)

["RegulatoryReporting" on page 44](#)

4.59.1 DebitCreditReportingIndicator

XML Tag: DbtCdtRptgInd

Presence: [0..1]

Definition: Identifies whether the regulatory reporting information applies to the debit side, to the credit side or to both debit and credit sides of the transaction.

Datatype: ["RegulatoryReportingType1Code" on page 177](#)

4.59.2 Authority

XML Tag: Authrty

Presence: [0..1]

Definition: Entity requiring the regulatory reporting information.

The **Authrty** block contains the following elements (see datatype ["RegulatoryAuthority2" on page 112](#) for details)

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
11.1.2	Name	<Nm>		[0..1]		112
11.1.3	Country	<Ctry>		[0..1]		112

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RegulatoryReporting/Authority) will be ignored by the Receiver.

4.59.3 Details

XML Tag: Dtls

Presence: [0..*]

Definition: Set of elements used to provide details on the regulatory reporting information.

The **Dtls** block contains the following elements (see datatype "[StructuredRegulatoryReporting3](#)" on page 119 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
11.1.5	Type	<Tp>		[0..1]	💡	120
11.1.6	Date	<Dt>		[0..1]	💡	120
11.1.7	Country	<Ctry>		[0..1]	💡	120
11.1.8	Code	<Cd>		[0..1]		121
11.1.9	Amount	<Amt>		[0..1]		121
11.1.10	Information	<Inf>		[0..*]		121

4.60 RemittanceAmount1

Definition: Nature of the amount and currency on a document referred to in the remittance section, typically either the original amount due/payable or the amount actually remitted for the referenced document.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.110	DuePayableAmount	<DuePyblAmt>		[0..1]		114
2.111	DiscountAppliedAmount	<DscntApldAmt>		[0..1]		114
2.112	CreditNoteAmount	<CdtNoteAmt>		[0..1]		115
2.113	TaxAmount	<TaxAmt>		[0..1]	💡	115
2.114	AdjustmentAmountAndReason	<AdjstmntAmtAndRsn>		[0..*]	💡	115
2.119	RemittedAmount	<RmtdAmt>		[0..1]		116

Used in element(s)

"[ReferredDocumentAmount](#)" on page 122

4.60.1 DuePayableAmount

XML Tag: DuePyblAmt

Presence: [0..1]

Definition: Amount specified is the exact amount due and payable to the creditor.

Datatype: "[ActiveOrHistoricCurrencyAndAmount](#)" on page 139

4.60.2 DiscountAppliedAmount

XML Tag: DscntApldAmt

Presence: [0..1]

Definition: Amount of money that results from the application of an agreed discount to the amount due and payable to the creditor.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 139](#)

4.60.3 CreditNoteAmount

XML Tag: CdtNoteAmt

Presence: [0..1]

Definition: Amount specified for the referred document is the amount of a credit note.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 139](#)

4.60.4 TaxAmount

XML Tag: TaxAmt

Presence: [0..1]

Definition: Quantity of cash resulting from the calculation of the tax.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 139](#)

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/ReferredDocumentAmount/TaxAmount](#)) will be ignored by the Receiver.

4.60.5 AdjustmentAmountAndReason

XML Tag: AdjstmntAmtAndRsn

Presence: [0..*]

Definition: Set of elements used to provide information on the amount and reason of the document adjustment.

The **AdjstmntAmtAndRsn** block contains the following elements (see datatype ["DocumentAdjustment1"](#) on page 50 for details)

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.115	Amount	<Amt>		[1..1]		51
2.116	CreditDebitIndicator	<CdtDbtInd>		[0..1]		51
2.117	Reason	<Rsn>		[0..1]		51
2.118	AdditionalInformation	<AddtlInf>		[0..1]		51

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/ReferredDocumentAmount/AdjustmentAmountAndReason) will be ignored by the Receiver.

4.60.6 RemittedAmount

XML Tag: RmtdAmt

Presence: [0..1]

Definition: Amount of money remitted for the referred document.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 139

4.61 RemittanceInformation5

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system.

🚫 Removed - 💡 Ignored - ⚠️ Details below - 📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.99	Unstructured	<Ustrd>		[0..*]	⚠️	116
2.100	Structured	<Strd>		[0..*]		116

Used in element(s)

"RemittanceInformation" on page 46

4.61.1 Unstructured

XML Tag: Ustrd

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form.

Datatype: "Max140Text" on page 169

Usage Guideline details

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Unstructured

Comment:

This is depending on payment instrument..

4.61.2 Structured

XML Tag: Strd

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

The **Strd** block contains the following elements (see datatype "StructuredRemittanceInformation7" on page 121 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.101	ReferredDocumentInformation	<RfrdDocInf>		[0..*]		122
2.109	ReferredDocumentAmount	<RfrdDocAmt>		[0..1]		122
2.120	CreditorReferenceInformation	<CdtrRefInf>		[0..1]		123
2.127	Invoicer	<Invcr>		[0..1]	💡	123
2.128	Invoicee	<Invcee>		[0..1]	💡	124
2.129	AdditionalRemittanceInformation	<AddtlRmtInf>		[0..3]	💡	124

4.62 RemittanceLocation2

Definition: Set of elements used to provide information on the remittance advice.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.92	RemittanceIdentification	<RmtId>		[0..1]	⚠	117
2.93	RemittanceLocationMethod	<RmtLctnMtd>		[0..1]		118
2.94	RemittanceLocationElectronicAddress	<RmtLctnElctrncAdr>		[0..1]		118
2.95	RemittanceLocationPostalAddress	<RmtLctnPstlAdr>		[0..1]		118

Used in element(s)

"RelatedRemittanceInformation" on page 45

4.62.1 RemittanceIdentification

XML Tag: RmtId

Presence: [0..1]

Definition: Unique identification, as assigned by the initiating party, to unambiguously identify the remittance information sent separately from the payment instruction, such as a remittance advice.

Datatype: "Max35Text" on page 171

Usage Guideline details

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RelatedRemittanceInformation/RemittanceIdentification

Comment:

Refer to Advising Appendix

4.62.2 RemittanceLocationMethod

XML Tag: RmtLctnMtd

Presence: [0..1]

Definition: Method used to deliver the remittance advice information.

Datatype: "RemittanceLocationMethod2Code" on page 178

4.62.3 RemittanceLocationElectronicAddress

XML Tag: RmtLctnElctrncAdr

Presence: [0..1]

Definition: Electronic address to which an agent is to send the remittance information.

Datatype: "Max2048Text" on page 171

4.62.4 RemittanceLocationPostalAddress

XML Tag: RmtLctnPstlAdr

Presence: [0..1]

Definition: Postal address to which an agent is to send the remittance information.

The **RmtLctnPstlAdr** block contains the following elements (see datatype "NameAndAddress10" on page 73 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.56 , 2.62 , 2.96	Name	<Nm>		[1..1]		73
2.57 , 2.63 , 2.97	Address	<Adr>		[1..1]		73

4.63 ServiceLevel8Choice__1

Definition: Specifies the service level of the transaction.

 Removed -
  Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.9 , 2.34	Code	<Cd>	{Or	[1..1]		119
2.10 , 2.35	Proprietary	<Prtry>	Or}	[1..1]		119

Used in element(s)

["ServiceLevel" on page 101](#)

4.63.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list.

Datatype: ["HSBC_UKBACS_ServiceLevel.Code" on page 166](#)

Usage Guideline details

- on [pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/PaymentTypeInformation/ServiceLevel/Code](#)

Single value: NURG

4.63.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as a proprietary code.

Datatype: ["Max35Text" on page 171](#)

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/PaymentTypeInformation/ServiceLevel/Proprietary](#)) is removed.
- This element([pain.001.001.03/PaymentInformation/PaymentTypeInformation/ServiceLevel/Proprietary](#)) is removed.

4.64 StructuredRegulatoryReporting3

Definition: Information needed due to regulatory and statutory requirements.

🚫 Removed - ✦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
11.1.5	Type	<Tp>		[0..1]	✦	120
11.1.6	Date	<Dt>		[0..1]	✦	120
11.1.7	Country	<Ctry>		[0..1]	✦	120
11.1.8	Code	<Cd>		[0..1]		121
11.1.9	Amount	<Amt>		[0..1]		121
11.1.10	Information	<Inf>		[0..*]		121

Used in element(s)

"Details" on page 113

4.64.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of the information supplied in the regulatory reporting details.

Datatype: "Max35Text" on page 171

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RegulatoryReporting/Details/Type) will be ignored by the Receiver.

4.64.2 Date

XML Tag: Dt

Presence: [0..1]

Definition: Date related to the specified type of regulatory reporting details.

Datatype: "ISODate" on page 167

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RegulatoryReporting/Details/Date) will be ignored by the Receiver.

4.64.3 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Country related to the specified type of regulatory reporting details.

Datatype: ["CountryCode" on page 155](#)

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RegulatoryReporting/Details/Country](#)) will be ignored by the Receiver.

4.64.4 Code

XML Tag: Cd

Presence: [0..1]

Definition: Specifies the nature, purpose, and reason for the transaction to be reported for regulatory and statutory requirements in a coded form.

Datatype: ["Max10Text" on page 169](#)

4.64.5 Amount

XML Tag: Amt

Presence: [0..1]

Definition: Amount of money to be reported for regulatory and statutory requirements.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 139](#)

4.64.6 Information

XML Tag: Inf

Presence: [0..*]

Definition: Additional details that cater for specific domestic regulatory requirements.

Datatype: ["Max35Text" on page 171](#)

4.65 StructuredRemittanceInformation7

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

🚫 Removed - ✦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.101	ReferredDocumentInformation	<RfrdDocInf>		[0..*]		122
2.109	ReferredDocumentAmount	<RfrdDocAmt>		[0..1]		122
2.120	CreditorReferenceInformation	<CdtrRefInf>		[0..1]		123
2.127	Invoicer	<Invcr>		[0..1]	✦	123
2.128	Invoicee	<Invcee>		[0..1]	✦	124
2.129	AdditionalRemittanceInformation	<AddtlRmtInf>		[0..3]	✦	124

Used in element(s)

"Structured" on page 116

4.65.1 ReferredDocumentInformation

XML Tag: RfrdDocInf

Presence: [0..*]

Definition: Set of elements used to identify the documents referred to in the remittance information.

The **RfrdDocInf** block contains the following elements (see datatype "[ReferredDocumentInformation3](#)" on page 109 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.102	Type	<Tp>		[0..1]		109
2.107	Number	<Nb>		[0..1]	✦	109
2.108	RelatedDate	<RltdDt>		[0..1]	✦	110

4.65.2 ReferredDocumentAmount

XML Tag: RfrdDocAmt

Presence: [0..1]

Definition: Set of elements used to provide details on the amounts of the referred document.

The **RfrdDocAmt** block contains the following elements (see datatype "[RemittanceAmount1](#)" on [page 114](#) for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.110	DuePayableAmount	<DuePyblAmt>		[0..1]		114
2.111	DiscountAppliedAmount	<DscntApldAmt>		[0..1]		114
2.112	CreditNoteAmount	<CdtNoteAmt>		[0..1]		115
2.113	TaxAmount	<TaxAmt>		[0..1]	💡	115
2.114	AdjustmentAmountAndReason	<AdjstmntAmtAndRsn>		[0..*]	💡	115
2.119	RemittedAmount	<RmtdAmt>		[0..1]		116

4.65.3 CreditorReferenceInformation

XML Tag: CdtrRefInf

Presence: [0..1]

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

The **CdtrRefInf** block contains the following elements (see datatype "[CreditorReferenceInformation2](#)" on [page 46](#) for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.121	Type	<Tp>		[0..1]		46
2.126	Reference	<Ref>		[0..1]	💡	47

4.65.4 Invoicer

XML Tag: Invcr

Presence: [0..1]

Definition: Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor.

The **Invcr** block contains the following elements (see datatype "[PartyIdentification32](#)" on page 80 for details)

Removed - Ignored - Details below - Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.0	Name	<Nm>		[0..1]		80
9.1.1	PostalAddress	<PstlAdr>		[0..1]		81
9.1.12	Identification	<Id>		[0..1]		82
9.1.33	CountryOfResidence	<CtryOfRes>		[0..1]		83
9.1.34	ContactDetails	<CtctDtls>		[0..1]		83

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/Invoicer](#)) will be ignored by the Receiver.

4.65.5 Invoicee

XML Tag: Invcee

Presence: [0..1]

Definition: Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor.

The **Invcee** block contains the following elements (see datatype "[PartyIdentification32](#)" on page 80 for details)

Removed - Ignored - Details below - Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
9.1.0	Name	<Nm>		[0..1]		80
9.1.1	PostalAddress	<PstlAdr>		[0..1]		81
9.1.12	Identification	<Id>		[0..1]		82
9.1.33	CountryOfResidence	<CtryOfRes>		[0..1]		83
9.1.34	ContactDetails	<CtctDtls>		[0..1]		83

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/Invoicee](#)) will be ignored by the Receiver.

4.65.6 AdditionalRemittanceInformation

XML Tag: AddtlRmtInf

Presence: [0..3]

Definition: Additional information, in free text form, to complement the structured remittance information.

Datatype: ["Max140Text" on page 169](#)

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/AdditionalRemittanceInformation](#)) will be ignored by the Receiver.

4.66 TaxAmount1

Definition: Set of elements used to provide information on the tax amount(s) of tax record.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
13.1.32	Rate	<Rate>		[0..1]		125
13.1.33	TaxableBaseAmount	<TaxblBaseAmt>		[0..1]		125
13.1.34	TotalAmount	<TtlAmt>		[0..1]	💡	125
13.1.35	Details	<Dtls>		[0..*]		126

Used in element(s)

["TaxAmount" on page 137](#)

4.66.1 Rate

XML Tag: Rate

Presence: [0..1]

Definition: Rate used to calculate the tax.

Datatype: ["PercentageRate" on page 176](#)

4.66.2 TaxableBaseAmount

XML Tag: TaxblBaseAmt

Presence: [0..1]

Definition: Amount of money on which the tax is based.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 139](#)

4.66.3 TotalAmount

XML Tag: TtlAmt

Presence: [0..1]

Definition: Total amount that is the result of the calculation of the tax for the record.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 139

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Record/TaxAmount/TotalAmount) will be ignored by the Receiver.

4.66.4 Details

XML Tag: Dtls

Presence: [0..*]

Definition: Set of elements used to provide details on the tax period and amount.

The **Dtls** block contains the following elements (see datatype "TaxRecordDetails1" on page 138 for details)

🚫 Removed - ⬜ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
13.1.36	Period	<Prd>		[0..1]		138
13.1.42	Amount	<Amt>		[1..1]	⬜	138

4.67 TaxAuthorisation1

Definition: Details of the authorised tax paying party.

🚫 Removed - ⬜ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
13.1.9	Title	<Titl>		[0..1]		126
13.1.10	Name	<Nm>		[0..1]		126

Used in element(s)

"Authorisation" on page 133

4.67.1 Title

XML Tag: Titl

Presence: [0..1]

Definition: Title or position of debtor or the debtor's authorised representative.

Datatype: "Max35Text" on page 171

4.67.2 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the debtor or the debtor's authorised representative.

Datatype: "Max140Text" on page 169

4.68 TaxInformation3__1

Definition: Details about tax paid, or to be paid, to the government in accordance with the law, including pre-defined parameters such as thresholds and type of account.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
13.1.0	Creditor	<Cdtr>		[0..1]	💡	127
13.1.4	Debtor	<Dbtr>		[0..1]	💡	128
13.1.11	AdministrationZone	<AdmstnZn>		[0..1]	💡	128
13.1.12	ReferenceNumber	<RefNb>		[0..1]	⚠	128
13.1.13	Method	<Mtd>		[0..1]	💡	129
13.1.14	TotalTaxableBaseAmount	<TtlTaxblBaseAmt>		[0..1]	💡	129
13.1.15	TotalTaxAmount	<TtlTaxAmt>		[0..1]	💡	130
13.1.16	Date	<Dt>		[0..1]	💡	130
13.1.17	SequenceNumber	<SeqNb>		[0..1]	💡	130
13.1.18	Record	<Rcrd>		[0..*]	💡	130

Used in element(s)

"Tax" on page 45

4.68.1 Creditor

XML Tag: Cdtr

Presence: [0..1]

Definition: Party on the credit side of the transaction to which the tax applies.

The **Cdtr** block contains the following elements (see datatype "TaxParty1" on page 131 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
13.1.1	TaxIdentification	<TaxId>		[0..1]		131
13.1.2	RegistrationIdentification	<RegnId>		[0..1]	💡	132
13.1.3	TaxType	<TaxTp>		[0..1]	💡	132

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Creditor) will be ignored by the Receiver.

4.68.2 Debtor

XML Tag: Dbtr

Presence: [0..1]

Definition: Set of elements used to identify the party on the debit side of the transaction to which the tax applies.

The **Dbtr** block contains the following elements (see datatype "[TaxParty2](#)" on page 132 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
13.1.5	TaxIdentification	<TaxId>		[0..1]		132
13.1.6	RegistrationIdentification	<RegnId>		[0..1]	💡	133
13.1.7	TaxType	<TaxTp>		[0..1]	💡	133
13.1.8	Authorisation	<Authstn>		[0..1]		133

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Debtor) will be ignored by the Receiver.

4.68.3 AdministrationZone

XML Tag: AdmstnZn

Presence: [0..1]

Definition: Territorial part of a country to which the tax payment is related.

Datatype: "[Max35Text](#)" on page 171

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/AdministrationZone) will be ignored by the Receiver.

4.68.4 ReferenceNumber

XML Tag: RefNb

Presence: [0..1]

Definition: Tax reference information that is specific to a taxing agency.

Datatype: "Max3Text" on page 172

Usage Guideline details

- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/ReferenceNumber**
 - **HSBC_ReferenceNumber:**

RTI - Real Time Information
Where the Originator of the Payroll BACS file is an employer making payments to which Income Tax (PAYE - Pay As You Earn) regulations apply, then the 3 character code (used as part of the algorithm to calculate the Unique Reference Number that forms part of the employers' RTI submission direct to HMRC) must be quoted preceded by '/'.
This request is only applicable to Bacs Direct submitters, therefore customers/employers using their own Service User Number
- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/ReferenceNumber**

Comment:
RTI - Real Time Information
Where the Originator of the Payroll BACS file is an employer making payments to which Income Tax (PAYE - Pay As You Earn) regulations apply, then the 3 character code (used as part of the algorithm to calculate the Unique Reference Number that forms part of the employers' RTI submission direct to HMRC) must be quoted preceded by '/'.
This request is only applicable to Bacs Direct submitters, therefore customers/employers using their own Service User Number.

4.68.5 Method

XML Tag: Mtd

Presence: [0..1]

Definition: Method used to indicate the underlying business or how the tax is paid.

Datatype: "Max35Text" on page 171

Usage Guideline details

- **This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Method) will be ignored by the Receiver.**

4.68.6 TotalTaxableBaseAmount

XML Tag: TtlTaxblBaseAmt

Presence: [0..1]

Definition: Total amount of money on which the tax is based.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 139

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/TotalTaxableBaseAmount](#)) will be ignored by the Receiver.

4.68.7 TotalTaxAmount

XML Tag: TtlTaxAmt

Presence: [0..1]

Definition: Total amount of money as result of the calculation of the tax.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 139](#)

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/TotalTaxAmount](#)) will be ignored by the Receiver.

4.68.8 Date

XML Tag: Dt

Presence: [0..1]

Definition: Date by which tax is due.

Datatype: ["ISODate" on page 167](#)

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Date](#)) will be ignored by the Receiver.

4.68.9 SequenceNumber

XML Tag: SeqNb

Presence: [0..1]

Definition: Sequential number of the tax report.

Datatype: ["Number" on page 174](#)

Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/SequenceNumber](#)) will be ignored by the Receiver.

4.68.10 Record

XML Tag: Rcrd

Presence: [0..*]

Definition: Record of tax details.

The **Rcrd** block contains the following elements (see datatype "[TaxRecord1](#)" on page 135 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
13.1.19	Type	<Tp>		[0..1]		135
13.1.20	Category	<Ctgy>		[0..1]	✦	136
13.1.21	CategoryDetails	<CtgyDtls>		[0..1]	✦	136
13.1.22	DebtorStatus	<DbtrSts>		[0..1]	✦	136
13.1.23	CertificateIdentification	<CertId>		[0..1]		136
13.1.24	FormsCode	<FrmsCd>		[0..1]		137
13.1.25	Period	<Prd>		[0..1]		137
13.1.31	TaxAmount	<TaxAmt>		[0..1]		137
13.1.43	AdditionalInformation	<AddtlInf>		[0..1]		137

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Record) will be ignored by the Receiver.

4.69 TaxParty1

Definition: Details about the entity involved in the tax paid or to be paid.

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
13.1.1	TaxIdentification	<TaxId>		[0..1]		131
13.1.2	RegistrationIdentification	<RegnId>		[0..1]	✦	132
13.1.3	TaxType	<TaxTp>		[0..1]	✦	132

Used in element(s)

"[Creditor](#)" on page 127

4.69.1 TaxIdentification

XML Tag: TaxId

Presence: [0..1]

Definition: Tax identification number of the creditor.

Datatype: "Max35Text" on page 171

4.69.2 RegistrationIdentification

XML Tag: RegnId

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: "Max35Text" on page 171

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Creditor/RegistrationIdentification) will be ignored by the Receiver.

4.69.3 TaxType

XML Tag: TaxTp

Presence: [0..1]

Definition: Type of tax payer.

Datatype: "Max35Text" on page 171

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Creditor/TaxType) will be ignored by the Receiver.

4.70 TaxParty2

Definition: Details about the entity involved in the tax paid or to be paid.

🚫 Removed - 💡 Ignored - ⚠️ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
13.1.5	TaxIdentification	<TaxId>		[0..1]		132
13.1.6	RegistrationIdentification	<RegnId>		[0..1]	💡	133
13.1.7	TaxType	<TaxTp>		[0..1]	💡	133
13.1.8	Authorisation	<Authstn>		[0..1]		133

Used in element(s)

"Debtor" on page 128

4.70.1 TaxIdentification

XML Tag: TaxId

Presence: [0..1]

Definition: Tax identification number of the debtor.

Datatype: "Max35Text" on page 171

4.70.2 RegistrationIdentification

XML Tag: RegnId

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: "Max35Text" on page 171

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Debtor/RegistrationIdentification) will be ignored by the Receiver.

4.70.3 TaxType

XML Tag: TaxTp

Presence: [0..1]

Definition: Type of tax payer.

Datatype: "Max35Text" on page 171

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Debtor/TaxType) will be ignored by the Receiver.

4.70.4 Authorisation

XML Tag: Authstn

Presence: [0..1]

Definition: Details of the authorised tax paying party.

The **Authstn** block contains the following elements (see datatype "TaxAuthorisation1" on page 126 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
13.1.9	Title	<Tit/>		[0..1]		126
13.1.10	Name	<Nm>		[0..1]		126

4.71 TaxPeriod1

Definition: Period of time details related to the tax payment.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
13.1.26 , 13.1.37	Year	<Yr>		[0..1]		134
13.1.27 , 13.1.38	Type	<Tp>		[0..1]	💡	134
13.1.28 , 13.1.39	FromToDate	<FrToDt>		[0..1]	💡	134

Used in element(s)

"Period" on page 138, "Period" on page 137

4.71.1 Year

XML Tag: Yr

Presence: [0..1]

Definition: Year related to the tax payment.

Datatype: "ISODate" on page 167

4.71.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Identification of the period related to the tax payment.

Datatype: "TaxRecordPeriod1Code" on page 180

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Record/Period/Type) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Record/TaxAmount/Details/Period/Type) will be ignored by the Receiver.

4.71.3 FromToDate

XML Tag: FrToDt

Presence: [0..1]

Definition: Range of time between a start date and an end date for which the tax report is provided.

The **FrToDt** block contains the following elements (see datatype "[DatePeriodDetails](#)" on page 50 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
13.1.29 , 13.1.40	FromDate	<FrDt>		[1..1]		50
13.1.30 , 13.1.41	ToDate	<ToDt>		[1..1]		50

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Record/TaxAmount/Details/Period/FromToDate) will be ignored by the Receiver.

4.72 TaxRecord1

Definition: Set of elements used to define the tax record.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
13.1.19	Type	<Tp>		[0..1]		135
13.1.20	Category	<Ctgy>		[0..1]	💡	136
13.1.21	CategoryDetails	<CtgyDtls>		[0..1]	💡	136
13.1.22	DebtorStatus	<DbtrSts>		[0..1]	💡	136
13.1.23	CertificateIdentification	<CertId>		[0..1]		136
13.1.24	FormsCode	<FrmsCd>		[0..1]		137
13.1.25	Period	<Prd>		[0..1]		137
13.1.31	TaxAmount	<TaxAmt>		[0..1]		137
13.1.43	AdditionalInformation	<AddtlInf>		[0..1]		137

Used in element(s)

"Record" on page 130

4.72.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: High level code to identify the type of tax details.

Datatype: "[Max35Text](#)" on page 171

4.72.2 Category

XML Tag: CtgY

Presence: [0..1]

Definition: Specifies the tax code as published by the tax authority.

Datatype: "Max35Text" on page 171

Usage Guideline details

- This element(**pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Record/Category**) will be ignored by the Receiver.

4.72.3 CategoryDetails

XML Tag: CtgYDtIs

Presence: [0..1]

Definition: Provides further details of the category tax code.

Datatype: "Max35Text" on page 171

Usage Guideline details

- This element(**pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Record/CategoryDetails**) will be ignored by the Receiver.

4.72.4 DebtorStatus

XML Tag: DbtrSts

Presence: [0..1]

Definition: Code provided by local authority to identify the status of the party that has drawn up the settlement document.

Datatype: "Max35Text" on page 171

Usage Guideline details

- This element(**pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Record/DebtorStatus**) will be ignored by the Receiver.

4.72.5 CertificateIdentification

XML Tag: CertId

Presence: [0..1]

Definition: Identification number of the tax report as assigned by the taxing authority.

Datatype: "Max35Text" on page 171

4.72.6 FormsCode

XML Tag: FrmsCd

Presence: [0..1]

Definition: Identifies, in a coded form, on which template the tax report is to be provided.

Datatype: "Max35Text" on page 171

4.72.7 Period

XML Tag: Prd

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

The **Prd** block contains the following elements (see datatype "TaxPeriod1" on page 133 for details)

🚫 Removed - ✨ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
13.1.26 , 13.1.37	Year	<Yr>		[0..1]		134
13.1.27 , 13.1.38	Type	<Tp>		[0..1]	✨	134
13.1.28 , 13.1.39	FromDate	<FrToDt>		[0..1]		134

4.72.8 TaxAmount

XML Tag: TaxAmt

Presence: [0..1]

Definition: Set of elements used to provide information on the amount of the tax record.

The **TaxAmt** block contains the following elements (see datatype "TaxAmount1" on page 125 for details)

🚫 Removed - ✨ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
13.1.32	Rate	<Rate>		[0..1]		125
13.1.33	TaxableBaseAmount	<TaxblBaseAmt>		[0..1]		125
13.1.34	TotalAmount	<TtlAmt>		[0..1]	✨	125
13.1.35	Details	<Dtls>		[0..*]		126

4.72.9 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Further details of the tax record.

Datatype: "Max140Text" on page 169

4.73 TaxRecordDetails1

Definition: Provides information on the individual tax amount(s) per period of the tax record.

🚫 Removed - 💡 Ignored - ⚠️ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
13.1.36	Period	<Prd>		[0..1]		138
13.1.42	Amount	<Amt>		[1..1]	💡	138

Used in element(s)

"Details" on page 126

4.73.1 Period

XML Tag: Prd

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

The **Prd** block contains the following elements (see datatype "TaxPeriod1" on page 133 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
13.1.26 , 13.1.37	Year	<Yr>		[0..1]		134
13.1.27 , 13.1.38	Type	<Tp>		[0..1]	💡	134
13.1.28 , 13.1.39	FromToDate	<FrToDt>		[0..1]	💡	134

4.73.2 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Underlying tax amount related to the specified period.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 139

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Record/TaxAmount/Details/Amount) will be ignored by the Receiver.

5 Message Datatypes

Note The following chapter identifies the datatypes that are used in the message.

5.1 ActiveOrHistoricCurrencyAndAmount

Definition: A number of monetary units specified in an active or a historic currency where the unit of currency is explicit and compliant with ISO 4217.

Type: Amount

This data type must be used with the following XML Attributes:

Attribute	Tag	Datatype
Currency	Ccy	"ActiveOrHistoricCurrencyCode" on page 140 Usage Guideline restrictions for this attribute on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Amount/InstructedAmount/Currency Single value: GBP

Format

minInclusive	0
totalDigits	18
fractionDigits	5

Rules

R6 CurrencyAmount ✓

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

Used in element(s)

"Amount" on page 51, "Amount" on page 138, "Amount" on page 52, "Amount" on page 121, "CreditNoteAmount" on page 115, "DiscountAppliedAmount" on page 114, "DuePayableAmount" on page 114, "InstructedAmount" on page 10, "RemittedAmount" on page 116, "TaxAmount" on page 115, "Taxable-

[BaseAmount](#)" on page 125, [TotalAmount](#)" on page 125, [TotalTaxAmount](#)" on page 130, [TotalTaxableBaseAmount](#)" on page 129

5.2 ActiveOrHistoricCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme, as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: Code

Format

pattern [A-Z]{3,3}

Rules

R4 ActiveOrHistoricCurrency ✓

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

Used in element(s)

["Currency"](#) on page 19, ["Currency"](#) on page 20, ["CurrencyOfTransfer"](#) on page 52

Used in attribute(s)

["ActiveOrHistoricCurrencyAndAmount"](#) on page 139

Restricts

["ParentCurrencyCode"](#) on page 174

5.3 AddressType2Code

Definition: Specifies the type of address.

Type: Code

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.

Code	Name	Definition
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Used in element(s)

["AddressType" on page 105](#)

Restricts

["AddressTypeCode" on page 141](#)

5.4 AddressTypeCode

Definition: Specifies the type of address.

Type: Code

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Is restricted by

["AddressType2Code" on page 140](#)

5.5 AmountDirectionCode

Definition: Specifies if an operation is an increase or a decrease or the result of a reversal operation.

Type: Code

Code	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.
RVCD	ReversalCredit	Debit entry used to reverse a previously booked credit entry.
RVDB	ReversalDebit	Credit entry used to reverse a previously booked debit entry.

Is restricted by

["CreditDebitCode" on page 155](#)

5.6 AnyBICIdentifier

Definition: Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}

Rules

R3 AnyBIC ✓

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consists of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC.

Used in element(s)

"BICOrBEI" on page 75, "BICOrBEI" on page 76

5.7 Authorisation1Code

Definition: Specifies the level of approval depending on a number of factors, including payment type, threshold amount or local country or operations practice.

Type: Code

Code	Name	Definition
AUTH	PreAuthorisedFile	Indicates a file has been pre authorised or approved within the originating customer environment and no further approval is required.
FDET	FileLevelAuthorisationDetails	Indicates that a file requires additional file level approval, with the ability to view both the payment information block and supporting customer credit transaction detail.
FSUM	FileLevelAuthorisationSummary	Indicates that a file requires additional file level approval, with the ability to view only the payment information block level information.

Code	Name	Definition
		Usage Guideline restrictions for this code • on pain.001.001.03/GroupHeader/Authorisation/Code/FileLevelAuthorisationSummary Comment: PaymentInformationId is mandatory at this authorisation level and should be unique within a file if multiple batches are used.
ILEV	InstructionLevelAuthorisation	Indicates that a file requires all customer transactions to be authorised or approved. Usage Guideline restrictions for this code • This code(pain.001.001.03/GroupHeader/Authorisation/Code/InstructionLevelAuthorisation) is removed.

Used in element(s)

["Code" on page 12](#)

Restricts

["AuthorisationCode" on page 143](#)

5.8 AuthorisationCode

Definition: Specifies the level of approval depending on a number of factors, including payment type, threshold amount or local country or operations practice.

Type: Code

Code	Name	Definition
AUTH	PreAuthorisedFile	Indicates a file has been pre authorised or approved within the originating customer environment and no further approval is required.
FDET	FileLevelAuthorisationDetails	Indicates that a file requires additional file level approval, with the ability to view both the payment information block and supporting customer credit transaction detail.
FSUM	FileLevelAuthorisationSummary	Indicates that a file requires additional file level approval, with the ability to view

Code	Name	Definition
		only the payment information block level information.
ILEV	InstructionLevelAuthorisation	Indicates that a file requires all customer transactions to be authorised or approved.

Is restricted by

"Authorisation1Code" on page 142

5.9 BICIdentifier

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}

Rules

R5 BIC ✓

Valid BICs for financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consist of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid BIC Code

Used in element(s)

"BIC" on page 54, "BIC" on page 57

5.10 BaseOneRate

Definition: Rate expressed as a decimal, eg, 0.7 is 7/10 and 70%.

Type: Rate

Format

totalDigits	11
fractionDigits	10

Used in element(s)

"ExchangeRate" on page 52

5.11 BatchBookingIndicator

Definition: Identifies whether the sending party requests a single debit or credit entry per individual transaction or a batch entry for the sum of the amounts of all transactions.

Type: Indicator

Meaning When True: Identifies that a batch entry for the sum of the amounts of all transactions in the batch or message is requested.

Meaning When False: Identifies that a single entry for each of the transactions in the batch or message is requested.

Used in element(s)

["BatchBooking" on page 94](#)

5.12 CashAccountType4Code

Definition: Specifies the nature, or use, of the cash account.

Type: Code

Code	Name	Definition
CACC	Current	Account used to post debits and credits when no specific account has been nominated.
CASH	CashPayment	Account used for the payment of cash. Usage Guideline restrictions for this code • This code(pain.001.001.03/PaymentInformation/CreditTransfer-TransactionInformation/CreditorAccount/Type/xor/Code/CashPayment) will be ignored by the Receiver. • This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/CashPayment) will be ignored by the Receiver.
CHAR	Charges	Account used for charges if different from the account for payment. Usage Guideline restrictions for this code • This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Code/Charges) will be ignored by the Receiver.

Code	Name	Definition
		This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/Charges) will be ignored by the Receiver.
CISH	CashIncome	Account used for payment of income if different from the current cash account. Usage Guideline restrictions for this code - This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Code/CashIncome) will be ignored by the Receiver. - This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/CashIncome) will be ignored by the Receiver.
COMM	Commission	Account used for commission if different from the account for payment. Usage Guideline restrictions for this code - This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Code/Commission) will be ignored by the Receiver. - This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/Commission) will be ignored by the Receiver.
LOAN	Loan	Account used for loans.
MGLD	MarginalLending	Account used for a marginal lending facility. Usage Guideline restrictions for this code This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Code/MarginalLending) will be ignored by the Receiver.

Code	Name	Definition
		This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/MarginalLending) will be ignored by the Receiver.
MOMA	MoneyMarket	Account used for money markets if different from the cash account. Usage Guideline restrictions for this code - This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Code/MoneyMarket) will be ignored by the Receiver. - This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/MoneyMarket) will be ignored by the Receiver.
NREX	NonResidentExternal	Account used for non-resident external. Usage Guideline restrictions for this code - This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Code/NonResidentExternal) will be ignored by the Receiver. - This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/NonResidentExternal) will be ignored by the Receiver.
ODFT	Overdraft	Account is used for overdrafts. Usage Guideline restrictions for this code This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Code/Overdraft) will be ignored by the Receiver.

Code	Name	Definition
		This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/Overdraft) will be ignored by the Receiver.
ONDP	OverNightDeposit	Account used for overnight deposits.
SACC	Settlement	Account used to post debit and credit entries, as a result of transactions cleared and settled through a specific clearing and settlement system. Usage Guideline restrictions for this code - This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Code/Settlement) will be ignored by the Receiver. - This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/Settlement) will be ignored by the Receiver.
SLRY	Salary	Accounts used for salary payments. Usage Guideline restrictions for this code - This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Code/Salary) will be ignored by the Receiver. - This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/Salary) will be ignored by the Receiver.
SVGS	Savings	Account used for savings.
TAXE	Tax	Account used for taxes if different from the account for payment. Usage Guideline restrictions for this code This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAc-

Code	Name	Definition
		count/Type/xor/Code/Tax) will be ignored by the Receiver. This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/Tax) will be ignored by the Receiver.
TRAS	CashTrading	Account used for trading if different from the current cash account. Usage Guideline restrictions for this code This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/CashTrading) will be ignored by the Receiver.

Used in element(s)

"Code" on page 22

Restricts

"CashAccountTypeCode" on page 149

5.13 CashAccountTypeCode

Definition: Specifies the nature, or use, of the cash account.

Type: Code

Code	Name	Definition
CACC	Current	Account used to post debits and credits when no specific account has been nominated.
CASH	CashPayment	Account used for the payment of cash.
CHAR	Charges	Account used for charges if different from the account for payment.
CISH	CashIncome	Account used for payment of income if different from the current cash account.
COLL	Collateral	Account is for collateral.
COMM	Commission	Account used for commission if different from the account for payment.
LEND	Lending	Account is for the coverage of lending.
LOAN	Loan	Account used for loans.
MARR	MarginReturn	Account is for margin returns.

Code	Name	Definition
MGLD	MarginalLending	Account used for a marginal lending facility.
MOMA	MoneyMarket	Account used for money markets if different from the cash account.
NREX	NonResidentExternal	Account used for non-resident external.
ODFT	Overdraft	Account is used for overdrafts.
ONDP	OverNightDeposit	Account used for overnight deposits.
SACC	Settlement	Account used to post debit and credit entries, as a result of transactions cleared and settled through a specific clearing and settlement system.
SEGT	Segregated	Account is an segregated account.
SETT	FinancialSettlement	Account is for financial settlements.
SLRY	Salary	Accounts used for salary payments.
SVGS	Savings	Account used for savings.
TAXE	Tax	Account used for taxes if different from the account for payment.
TRAS	CashTrading	Account used for trading if different from the current cash account.

Is restricted by

"CashAccountType4Code" on page 145

5.14 ChargeBearerType1Code

Definition: Specifies which party(ies) will pay charges due for processing of the instruction.

Type: Code

Code	Name	Definition
CRED	BorneByCreditor	All transaction charges are to be borne by the creditor.
DEBT	BorneByDebtor	All transaction charges are to be borne by the debtor.
SHAR	Shared	In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor, transaction charges on the receiver side are to be borne by the debtor.
SLEV	FollowingServiceLevel	Charges are to be applied following the rules agreed in the service level and/or scheme.

Used in element(s)

["ChargeBearer" on page 98](#), ["ChargeBearer" on page 36](#)

Restricts

["ChargeBearerTypeCode" on page 151](#)

5.15 ChargeBearerTypeCode

Definition: Specifies which party(ies) will pay charges due for processing of the instruction.

Type: Code

Code	Name	Definition
CRED	BorneByCreditor	All transaction charges are to be borne by the creditor.
DEBT	BorneByDebtor	All transaction charges are to be borne by the debtor.
SHAR	Shared	In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor, transaction charges on the receiver side are to be borne by the debtor.
SLEV	FollowingServiceLevel	Charges are to be applied following the rules agreed in the service level and/or scheme.

Is restricted by

["ChargeBearerType1Code" on page 150](#)

5.16 ChequeDelivery1Code

Definition: Specifies the method to be used in delivering a cheque to a party.

Type: Code

Code	Name	Definition
CRCD	CourierToCreditor	Cheque is to be sent through courier services to creditor.
CRDB	CourierToDebtor	Cheque is to be sent through courier services to debtor.
CRFA	CourierToFinalAgent	Cheque is to be sent through courier services to creditor agent.
MLCD	MailToCreditor	Cheque is to be sent through mail services to creditor.
MLDB	MailToDebtor	Cheque is to be sent through mail services to debtor.

Code	Name	Definition
MLFA	MailToFinalAgent	Cheque is to be sent through mail services to creditor agent.
PUCD	PickUpByCreditor	Cheque will be picked up by the creditor.
PUDB	PickUpByDebtor	Cheque will be picked up by the debtor.
PUFA	PickUpByFinalAgent	Cheque will be picked up by the creditor agent.
RGCD	RegisteredMailToCreditor	Cheque is to be sent through registered mail services to creditor.
RGDB	RegisteredMailToDebtor	Cheque is to be sent through registered mail services to debtor.
RGFA	RegisteredMailToFinalAgent	Cheque is to be sent through registered mail services to creditor agent.

Used in element(s)

"Code" on page 26

Restricts

"ChequeDeliveryCode" on page 152

5.17 ChequeDeliveryCode

Definition: Specifies the method to be used in delivering a cheque to a party.

Type: Code

Code	Name	Definition
CRCD	CourierToCreditor	Cheque is to be sent through courier services to creditor.
CRDB	CourierToDebtor	Cheque is to be sent through courier services to debtor.
CRFA	CourierToFinalAgent	Cheque is to be sent through courier services to creditor agent.
MLCD	MailToCreditor	Cheque is to be sent through mail services to creditor.
MLDB	MailToDebtor	Cheque is to be sent through mail services to debtor.
MLFA	MailToFinalAgent	Cheque is to be sent through mail services to creditor agent.
PUCD	PickUpByCreditor	Cheque will be picked up by the creditor.
PUDB	PickUpByDebtor	Cheque will be picked up by the debtor.
PUFA	PickUpByFinalAgent	Cheque will be picked up by the creditor agent.
RGCD	RegisteredMailToCreditor	Cheque is to be sent through registered mail services to creditor.

Code	Name	Definition
RGDB	RegisteredMailToDebtor	Cheque is to be sent through registered mail services to debtor.
RGFA	RegisteredMailToFinalAgent	Cheque is to be sent through registered mail services to creditor agent.

Is restricted by

["ChequeDelivery1Code" on page 151](#)

5.18 ChequeType2Code

Definition: Specifies the type of cheque.

Type: Code

Code	Name	Definition
BCHQ	BankCheque	Cheque drawn on the account of the debtor's financial institution, which is debited on the debtor's account when the cheque is issued. These cheques are printed by the debtor's financial institution and payment is guaranteed by the financial institution. Synonym is 'cashier's cheque'.
CCCH	CertifiedCustomerCheque	Cheque drawn on the account of the debtor, and debited on the debtor's account when the cheque is cashed. The financial institution prints and certifies the cheque, guaranteeing the payment.
CCHQ	CustomerCheque	Cheque drawn on the account of the debtor, and debited on the debtor's account when the cheque is cashed. Synonym is 'corporate cheque'.
DRFT	Draft	A guaranteed bank cheque with a future value date (do not pay before), which in commercial terms is a 'negotiable instrument': the beneficiary can receive early payment from any bank under subtraction of a discount. The ordering customer's account is debited on value date.
ELDR	ElectronicDraft	An instrument with a future value date (do not pay before), which in commercial terms is a 'negotiable instrument': the beneficiary can receive early payment from any bank under subtraction of a discount. The ordering customer's account is debited on value date.

Used in element(s)

["ChequeType" on page 24](#)

Restricts

["ChequeTypeCode" on page 154](#)

5.19 ChequeTypeCode

Definition: Specifies the type of cheque.

Type: Code

Code	Name	Definition
BCHQ	BankCheque	Cheque drawn on the account of the debtor's financial institution, which is debited on the debtor's account when the cheque is issued. These cheques are printed by the debtor's financial institution and payment is guaranteed by the financial institution. Synonym is 'cashier's cheque'.
BKDF	BankDraft	Cheque drawn by a bank on itself or its agent. A person who owes money to another buys the draft from a bank for cash and hands it to the creditor who need have no fear that it might be dishonoured. A bank draft is also called a banker's cheque, banker's draft, bank check, or treasurer's check.
CCCH	CertifiedCustomerCheque	Cheque drawn on the account of the debtor, and debited on the debtor's account when the cheque is cashed. The financial institution prints and certifies the cheque, guaranteeing the payment.
CCHQ	CustomerCheque	Cheque drawn on the account of the debtor, and debited on the debtor's account when the cheque is cashed. Synonym is 'corporate cheque'.
CLCQ	CircularCheque	An instruction from a bank to its correspondent bank to pay the creditor a stated sum upon the presentation of a means of identification.
CRCQ	CrossedCheque	Cheque that must be paid into an account and not cashed over the counter. There are two parallel lines across the face of a crossed cheque.
DRFT	Draft	A guaranteed bank cheque with a future value date (do not pay before), which in commercial terms is a 'negotiable instrument': the beneficiary can receive early payment from any bank under subtraction of a discount. The ordering customer's account is debited on value date.
ELDR	ElectronicDraft	An instrument with a future value date (do not pay before), which in commercial terms is a 'negotiable instrument': the beneficiary can receive early payment from any bank under subtraction of a discount. The ordering customer's account is debited on value date.
OCHQ	OnlineCheque	Cheque initiated or completed through an online service.

Code	Name	Definition
OPCQ	OpenCheque	Cheque that may only be cashed at the bank of origin.
ORCQ	OrderCheque	Cheque made payable to a named recipient 'or order'. The payee can either deposit the cheque in an account or endorse it to a third party.

Is restricted by

"ChequeType2Code" on page 153

5.20 CountryCode

Definition: Code to identify a country, a dependency, or another area of particular geopolitical interest, on the basis of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Type: Code

Format

pattern [A-Z]{2,2}

Rules

R1 Country ✓

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

Used in element(s)

"Country" on page 107, "Country" on page 112, "Country" on page 120, "CountryOfBirth" on page 50, "CountryOfResidence" on page 83, "CountryOfResidence" on page 87

5.21 CreditDebitCode

Definition: Specifies if an operation is an increase or a decrease.

Type: Code

Code	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

Used in element(s)

"CreditDebitIndicator" on page 51

Restricts

["AmountDirectionCode" on page 141](#)

5.22 DecimalNumber

Definition: Number of objects represented as a decimal number, for example 0.75 or 45.6.

Type: Quantity

Format

totalDigits	18
fractionDigits	17

Used in element(s)

["ControlSum" on page 70](#), ["ControlSum" on page 94](#)

5.23 DocumentType3Code

Definition: Specifies a type of financial or commercial document.

Type: Code

Code	Name	Definition
DISP	DispatchAdvice	Document is a dispatch advice.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
PUOR	PurchaseOrder	Document is a purchase order.
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, eg, in a cover scenario.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.

Used in element(s)

["Code" on page 47](#)

Restricts

["DocumentTypeCode" on page 157](#)

5.24 DocumentType5Code

Definition: Specifies a type of financial or commercial document.

Type: Code

Code	Name	Definition
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
BOLD	BillOfLading	Document is a shipping notice.
CINV	CommercialInvoice	Document is an invoice.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
DISP	DispatchAdvice	Document is a dispatch advice.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.
VCHR	Voucher	Document is an electronic payment document.

Used in element(s)

"Code" on page 110

Restricts

"DocumentTypeCode" on page 157

5.25 DocumentTypeCode

Definition: Specifies a type of financial or commercial document.

Type: Code

Code	Name	Definition
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
BOLD	BillOfLading	Document is a shipping notice.
CINV	CommercialInvoice	Document is an invoice.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
DISP	DispatchAdvice	Document is a dispatch advice.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
PUOR	PurchaseOrder	Document is a purchase order.
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, eg, in a cover scenario.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.
VCHR	Voucher	Document is an electronic payment document.

Is restricted by

["DocumentType3Code" on page 156](#), ["DocumentType5Code" on page 156](#)

5.26 ExchangeRateType1Code

Definition: Specifies a type of financial or commercial document.

Type: Code

Code	Name	Definition
AGRD	Agreed	Exchange rate applied is the rate agreed between the parties.
SALE	Sale	Exchange rate applied is the market rate at the time of the sale.
SPOT	Spot	Exchange rate applied is the spot rate.

Used in element(s)

["RateType" on page 53](#)

Restricts

["ExchangeRateTypeCode" on page 159](#)

5.27 ExchangeRateTypeCode

Definition: Code used to define the type of the currency exchange.

Type: Code

Code	Name	Definition
AGRD	Agreed	Exchange rate applied is the rate agreed between the parties.
SALE	Sale	Exchange rate applied is the market rate at the time of the sale.
SPOT	Spot	Exchange rate applied is the spot rate.

Is restricted by

["ExchangeRateType1Code" on page 159](#)

5.28 ExternalAccountIdentification1Code

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: Code

Format

minLength	1
maxLength	4

Used in element(s)

["Code" on page 10](#)

Restricts

["ExternalAccountIdentificationCode" on page 160](#)

5.29 ExternalAccountIdentificationCode

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: Code

Format

minLength	1
maxLength	4

Is restricted by

["ExternalAccountIdentification1Code" on page 159](#)

5.30 ExternalCategoryPurpose1Code

Definition: Specifies the category purpose, as published in an external category purpose code list.

External code sets can be downloaded from www.iso20022.org.

Type: Code

Format

minLength	1
maxLength	4

Used in element(s)

["Code" on page 23](#)

Restricts

["ExternalCategoryPurposeCode" on page 161](#)

5.31 ExternalCategoryPurposeCode

Definition: Specifies the category purpose, as published in an external category purpose code list.

External code sets can be downloaded from www.iso20022.org.

Type: Code

Format

minLength	1
maxLength	4

Is restricted by

"ExternalCategoryPurpose1Code" on page 160

5.32 ExternalClearingSystemIdentification1Code

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: Code

Format

minLength	1
maxLength	5

Used in element(s)

"Code" on page 27

Restricts

"ExternalClearingSystemIdentificationCode" on page 161

5.33 ExternalClearingSystemIdentificationCode

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: Code

Format

minLength	1
maxLength	5

Is restricted by

["ExternalClearingSystemIdentification1Code" on page 161](#)

5.34 ExternalFinancialInstitutionIdentification1Code

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: Code

Format

minLength	1
maxLength	4

Used in element(s)

["Code" on page 53](#)

Restricts

["ExternalFinancialInstitutionIdentificationCode" on page 162](#)

5.35 ExternalFinancialInstitutionIdentificationCode

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: Code

Format

minLength	1
maxLength	4

Is restricted by

["ExternalFinancialInstitutionIdentification1Code" on page 162](#)

5.36 ExternalLocalInstrument1Code

Definition: Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: Code

Format

minLength	1
maxLength	35

Used in element(s)

"Code" on page 73

Restricts

"ExternalLocalInstrumentCode" on page 163

5.37 ExternalLocalInstrumentCode

Definition: Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: Code

Format

minLength	1
maxLength	35

Is restricted by

"ExternalLocalInstrument1Code" on page 162

5.38 ExternalOrganisationIdentification1Code

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: Code

Format

minLength	1
maxLength	4

Used in element(s)

["Code" on page 77](#)

Restricts

["ExternalOrganisationIdentificationCode" on page 164](#)

5.39 ExternalOrganisationIdentificationCode

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: Code

Format

minLength	1
maxLength	4

Is restricted by

["ExternalOrganisationIdentification1Code" on page 163](#)

5.40 ExternalPersonIdentification1Code

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: Code

Format

minLength	1
maxLength	4

Used in element(s)

["Code" on page 104](#)

Restricts

["ExternalPersonIdentificationCode" on page 164](#)

5.41 ExternalPersonIdentificationCode

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: Code

Format

minLength	1
maxLength	4

Is restricted by

"ExternalPersonIdentification1Code" on page 164

5.42 ExternalPurpose1Code

Definition: Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: Code

Format

minLength	1
maxLength	4

Used in element(s)

"Code" on page 108

Restricts

"ExternalPurposeCode" on page 165

5.43 ExternalPurposeCode

Definition: Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: Code

Format

minLength	1
maxLength	4

Is restricted by

"ExternalPurpose1Code" on page 165

5.44 HSBC_UKBACS_ServiceLevel.Code

Definition:

This datatype has been created by the Publisher of this Usage Guideline.

Type: Code

Format

minLength	1
maxLength	4

Code	Name	Definition
NURG	Non Urgent Payment	Non Urgent Payment

Used in element(s)

"Code" on page 119

5.45 IBAN2007Identifier

Definition: An identifier used internationally by financial institutions to uniquely identify the account of a customer at a financial institution, as described in the latest edition of the international standard ISO 13616: 2007 - "Banking and related financial services - International Bank Account Number (IBAN)".

Type: IdentifierSet

Format

pattern	[A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}
---------	---------------------------------------

Rules**R2 IBAN ✓**

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

Error handling:

- Error severity: Fatal
- Error Code: D00003

– *Error Text:* Invalid IBAN format or invalid check digits.

Used in element(s)

"IBAN" on page 8, "IBAN" on page 9

5.46 ISODate

Definition: A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Type: Date

Used in element(s)

"BirthDate" on page 49, "ChequeMaturityDate" on page 25, "Date" on page 120, "Date" on page 130, "FromDate" on page 50, "PoolingAdjustmentDate" on page 95, "RelatedDate" on page 110, "RequestedExecutionDate" on page 95, "ToDate" on page 50, "Year" on page 134

5.47 ISODateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in either UTC time format (YYYY-MM-DDThh:mm:ss.sssZ), local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm), or local time format (YYYY-MM-DDThh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: DateTime

Used in element(s)

"CreationDateTime" on page 69

5.48 Instruction3Code

Definition: Specifies further instructions concerning the processing of a payment instruction, provided by the sending clearing agent to the next agent(s).

Type: Code

Code	Name	Definition
CHQB	PayCreditorByCheque	(Ultimate) creditor must be paid by cheque.
HOLD	HoldCashForCreditor	Amount of money must be held for the (ultimate) creditor, who will call. Pay on identification.
PHOB	PhoneBeneficiary	Please advise/contact (ultimate) creditor/claimant by phone.
TELB	Telecom	Please advise/contact (ultimate) creditor/claimant by the most efficient means of telecommunication.

Used in element(s)

"Code" on page 72

Restricts

"InstructionCode" on page 168

5.49 InstructionCode

Definition: Specifies further instructions concerning the processing of a payment instruction.

Type: Code

Code	Name	Definition
CHQB	PayCreditorByCheque	(Ultimate) creditor must be paid by cheque.
HOLD	HoldCashForCreditor	Amount of money must be held for the (ultimate) creditor, who will call. Pay on identification.
PBEN	PayTheBeneficiary	(Ultimate) creditor to be paid only after verification of identity.
PHOA	PhoneNextAgent	Please advise/contact next agent by phone.
PHOB	PhoneBeneficiary	Please advise/contact (ultimate) creditor/claimant by phone.
TELA	TelecomNextAgent	Please advise/contact next agent by the most efficient means of telecommunication.
TELB	Telecom	Please advise/contact (ultimate) creditor/claimant by the most efficient means of telecommunication.
TFRO	TimeFrom	Payment instruction will be valid and eligible for execution from the date and time stipulated.
TTIL	TimeTill	Payment instruction is valid and eligible for execution until the date and time stipulated. Otherwise, the payment instruction will be rejected.

Is restricted by

["Instruction3Code" on page 167](#)

5.50 Max10Text

Definition: Specifies a character string with a maximum length of 10 characters.

Type: Text

Format

minLength	1
maxLength	10

Used in element(s)

["Code" on page 121](#)

5.51 Max128Text

Definition: Specifies a character string with a maximum length of 128 characters.

Type: Text

Format

minLength	1
maxLength	128

Used in element(s)

["Proprietary" on page 12](#)

5.52 Max140Text

Definition: Specifies a character string with a maximum length of 140 characters.

Type: Text

Format

minLength	1
maxLength	140

Used in element(s)

["AdditionalInformation" on page 51](#), ["AdditionalInformation" on page 137](#), ["AdditionalRemittanceInformation" on page 124](#), ["InstructionForDebtorAgent" on page 43](#), ["InstructionInformation" on page 72](#), ["Name" on page 15](#), ["Name" on page 30](#), ["Name" on page 80](#), ["Name" on page 54](#), ["Name" on page 73](#), ["Name" on page 126](#), ["Name" on page 112](#), ["Name" on page 58](#), ["Unstructured" on page 116](#)

5.53 Max15NumericText

Definition: Specifies a numeric string with a maximum length of 15 digits.

Type: Text

Format

pattern	[0-9]{1,15}
---------	-------------

Used in element(s)

"NumberOfTransactions" on page 70, "NumberOfTransactions" on page 94

5.54 Max16Text

Definition: Specifies a character string with a maximum length of 16 characters.

Type: Text

Format

minLength	1
maxLength	16

Used in element(s)

"BuildingNumber" on page 106, "PostCode" on page 107

5.55 Max18Text

Definition:

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

minLength	1
maxLength	18

Used in element(s)

"EndToEndIdentification" on page 89, "PaymentInformationIdentification" on page 93

5.56 Max18Text__1

Definition:

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

minLength	1
maxLength	18

Used in element(s)

"Name" on page 85

5.57 Max2048Text

Definition: Specifies a character string with a maximum length of 2048 characters.

Type: Text

Format

minLength	1
maxLength	2048

Used in element(s)

"EmailAddress" on page 31, "RemittanceLocationElectronicAddress" on page 118

5.58 Max34Text

Definition: Specifies a character string with a maximum length of 34 characters.

Type: Text

Format

minLength	1
maxLength	34

Used in element(s)

"Identification" on page 60

5.59 Max35Text

Definition: Specifies a character string with a maximum length of 35 characters.

Type: Text

Format

minLength	1
maxLength	35

Used in element(s)

"AdministrationZone" on page 128, "Category" on page 136, "CategoryDetails" on page 136, "CertificateIdentification" on page 136, "ChequeNumber" on page 24, "CityOfBirth" on page 49, "ContractIden-

tification" on page 53, "CountrySubDivision" on page 107, "DebtorStatus" on page 136, "FormsCode" on page 137, "FormsCode" on page 25, "Identification" on page 63, "Identification" on page 15, "Identification" on page 64, "Identification" on page 68, "Information" on page 121, "InstructionIdentification" on page 88, "Issuer" on page 64, "Issuer" on page 61, "Issuer" on page 65, "Issuer" on page 68, "Issuer" on page 111, "Issuer" on page 49, "Issuer" on page 67, "Issuer" on page 62, "MemberIdentification" on page 28, "MemoField" on page 26, "MessageIdentification" on page 69, "Method" on page 129, "Number" on page 109, "Other" on page 31, "PrintLocation" on page 26, "Proprietary" on page 27, "Proprietary" on page 53, "Proprietary" on page 10, "Proprietary" on page 22, "Proprietary" on page 77, "Proprietary" on page 104, "Proprietary" on page 108, "Proprietary" on page 110, "Proprietary" on page 48, "Proprietary" on page 27, "Proprietary" on page 73, "Proprietary" on page 23, "Proprietary" on page 119, "ProvinceOfBirth" on page 49, "Reference" on page 47, "RegionalClearingZone" on page 26, "RegistrationIdentification" on page 132, "RegistrationIdentification" on page 133, "RemittanceIdentification" on page 117, "TaxIdentification" on page 131, "TaxIdentification" on page 132, "TaxType" on page 132, "TaxType" on page 133, "Title" on page 126, "TownName" on page 107, "Type" on page 135, "Type" on page 120

5.60 Max3Text

Definition: Specifies a character string with a maximum length of 3 characters.

Type: Text

Format

minLength	1
maxLength	3

Used in element(s)

"ReferenceNumber" on page 128

5.61 Max4Text

Definition: Specifies a character string with a maximum length of 4 characters.

Type: Text

Format

minLength	1
maxLength	4

Used in element(s)

"Reason" on page 51

5.62 Max6Text

Definition: Specifies a character string with a maximum length of 6 characters.

Type: Text

Format

minLength	1
maxLength	6

Used in element(s)

"Identification" on page 66, "MemberIdentification" on page 29

5.63 Max70Text

Definition: Specifies a character string with a maximum length of 70characters.

Type: Text

Format

minLength	1
maxLength	70

Used in element(s)

"AddressLine" on page 108, "Department" on page 106, "Name" on page 19, "Name" on page 21, "StreetName" on page 106, "SubDepartment" on page 106

5.64 Max8Text

Definition: Specifies a character string with a maximum length of 8 characters.

Type: Text

Format

minLength	1
maxLength	8

Used in element(s)

"Identification" on page 61

5.65 NamePrefix1Code

Definition: Specifies the terms used to formally address a person.

Type: Code

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Used in element(s)

["NamePrefix" on page 30](#)

Restricts

["NamePrefixCode" on page 174](#)

5.66 NamePrefixCode

Definition: Specifies the terms used to formally address a person.

Type: Code

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Is restricted by

["NamePrefix1Code" on page 173](#)

5.67 Number

Definition: Number of objects represented as an integer.

Type: Quantity

Format

totalDigits	18
fractionDigits	0

Used in element(s)

["SequenceNumber" on page 130](#)

5.68 ParentCurrencyCode

Definition: Code allocated to a currency, by a maintenance agency, under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds". Valid currency codes are registered with the ISO 4217 Maintenance Agency, and consist of three contiguous letters.

Type: Code

Format

pattern	[A-Z]{3,3}
---------	------------

Is restricted by

["ActiveOrHistoricCurrencyCode" on page 140](#)

5.69 PaymentMethod3Code

Definition: Specifies the transfer method that will be used to transfer an amount of money.

Type: Code

Code	Name	Definition
CHK	Cheque	Written order to a bank to pay a certain amount of money from one person to another person. Usage Guideline restrictions for this code • This code(pain.001.001.03/PaymentInformation/PaymentMethod/Cheque) is removed.
TRA	TransferAdvice	Transfer of an amount of money in the books of the account servicer. An advice should be sent back to the account owner.
TRF	CreditTransfer	Transfer of an amount of money in the books of the account servicer.

Used in element(s)

["PaymentMethod" on page 93](#)

Restricts

["PaymentMethodCode" on page 175](#)

5.70 PaymentMethodCode

Definition: Specifies the transfer method that will be used to transfer the cash.

Type: Code

Code	Name	Definition
CHK	Cheque	Written order to a bank to pay a certain amount of money from one person to another person.
CLAS	Classical	Classical method.
DD	DirectDebit	Collection of an amount of money from the debtor's bank account by the creditor. The amount of money and dates of collections may vary.
DIRE	Direct	Direct method.

Code	Name	Definition
TRA	TransferAdvice	Transfer of an amount of money in the books of the account servicer. An advice should be sent back to the account owner.
TRF	CreditTransfer	Transfer of an amount of money in the books of the account servicer.

Is restricted by

"PaymentMethod3Code" on page 175

5.71 PercentageRate

Definition: Rate expressed as a percentage, ie, in hundredths, for example, 0.7 is 7/10 of a percent, and 7.0 is 7%.

Type: Rate

Format

totalDigits	11
fractionDigits	10

Used in element(s)

"Rate" on page 125

5.72 PhoneNumber

Definition: The collection of information which identifies a specific phone or FAX number as defined by telecom services.

It consists of a "+" followed by the country code (from 1 to 3 characters) then a "-" and finally, any combination of numbers, "(", ")", "+ and "-" (up to 30 characters).

Type: Text

Format

pattern	\+[0-9]{1,3}-[0-9()+\-]{1,30}
---------	-------------------------------

Used in element(s)

"FaxNumber" on page 31, "MobileNumber" on page 31, "PhoneNumber" on page 30

5.73 Priority2Code

Definition: Specifies the priority level of an event.

Type: Code

Code	Name	Definition
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

Used in element(s)

["InstructionPriority" on page 25](#), ["InstructionPriority" on page 101](#)

Restricts

["PriorityCode" on page 177](#)

5.74 PriorityCode

Definition: Specifies the priority level of an event.

Type: Code

Code	Name	Definition
HIGH	High	Priority level is high.
LOWW	Low	Priority level is low.
NORM	Normal	Priority level is normal.
URGT	Urgent	Priority level is urgent (highest priority possible).

Is restricted by

["Priority2Code" on page 176](#)

5.75 RegulatoryReportingType1Code

Definition: Identifies whether the regulatory reporting information applies to the debit side, to the credit side or to both debit and credit sides of the transaction.

Type: Code

Code	Name	Definition
BOTH	Both	Regulatory information applies to both credit and debit sides.
CRED	Credit	Regulatory information applies to the credit side.
DEBT	Debit	Regulatory information applies to the debit side.

Used in element(s)

["DebitCreditReportingIndicator" on page 113](#)

Restricts

["RegulatoryReportingTypeCode" on page 178](#)

5.76 RegulatoryReportingTypeCode

Definition: Identifies whether the regulatory reporting information applies to the debit side, to the credit side or to both debit and credit sides of the transaction.

Type: Code

Code	Name	Definition
BOTH	Both	Regulatory information applies to both credit and debit sides.
CRED	Credit	Regulatory information applies to the credit side.
DEBT	Debit	Regulatory information applies to the debit side.

Is restricted by

"RegulatoryReportingType1Code" on page 177

5.77 RemittanceLocationMethod2Code

Definition: Specifies the method used to deliver the remittance advice information.

Type: Code

Code	Name	Definition
EDIC	ElectronicDataInterchange	Remittance advice information must be sent through Electronic Data Interchange (EDI). Usage Guideline restrictions for this code • This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RelatedRemittanceInformation/RemittanceLocationMethod/ElectronicDataInterchange) will be ignored by the Receiver.
EMAL	EMail	Remittance advice information must be sent through e-mail.
FAXI	Fax	Remittance advice information must be faxed.
POST	Post	Remittance advice information must be sent through postal services.
SMSM	SMS	Remittance advice information must be sent through by phone as a short message service (SMS).

Code	Name	Definition
		Usage Guideline restrictions for this code • This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RelatedRemittanceInformation/RemittanceLocationMethod/SMS) will be ignored by the Receiver.
URID	UniformResourceIdentifier	Remittance advice information needs to be sent to a Uniform Resource Identifier (URI). URI is a compact string of characters that uniquely identify an abstract or physical resource. URI's are the super-set of identifiers, such as URLs, email addresses, ftp sites, etc, and as such, provide the syntax for all of the identification schemes. Usage Guideline restrictions for this code • This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RelatedRemittanceInformation/RemittanceLocationMethod/UniformResourceIdentifier) will be ignored by the Receiver.

Used in element(s)

"RemittanceLocationMethod" on page 118

Restricts

"RemittanceLocationMethodCode" on page 179

5.78 RemittanceLocationMethodCode

Definition: Specifies the method used to deliver the remittance advice information.

Type: Code

Code	Name	Definition
EDIC	ElectronicDataInterchange	Remittance advice information must be sent through Electronic Data Interchange (EDI).
EMAL	EMail	Remittance advice information must be sent through e-mail.

Code	Name	Definition
FAXI	Fax	Remittance advice information must be faxed.
POST	Post	Remittance advice information must be sent through postal services.
SMSM	SMS	Remittance advice information must be sent through by phone as a short message service (SMS).
URID	UniformResourceIdentifier	Remittance advice information needs to be sent to a Uniform Resource Identifier (URI). URI is a compact string of characters that uniquely identify an abstract or physical resource. URI's are the super-set of identifiers, such as URLs, email addresses, ftp sites, etc, and as such, provide the syntax for all of the identification schemes.

Is restricted by

"RemittanceLocationMethod2Code" on page 178

5.79 TaxRecordPeriod1Code

Definition: Specifies the period related to the tax payment.

Type: Code

Code	Name	Definition
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.

Code	Name	Definition
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.

Used in element(s)

"Type" on page 134

Restricts

"TaxRecordPeriodCode" on page 181

5.80 TaxRecordPeriodCode

Definition: Specifies the period related to the tax payment.

Type: Code

Code	Name	Definition
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.

Code	Name	Definition
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.

Is restricted by

"TaxRecordPeriod1Code" on page 180

Legal Notices

Copyright

SWIFT © 2018. All rights reserved.

This material is a component of MyStandards, the SWIFT collaborative Web application used to manage standards definitions and industry usage. It can only be used and distributed in accordance with MyStandards Terms of Use.

Unless otherwise agreed in writing with SWIFT SCRL, you have no right to:

- authorise external end users to use this component for other purposes than their internal use.
- remove, alter, cover, obfuscate or cancel from view any copyright or other proprietary rights notices appearing in this physical medium.
- re-sell or authorise another party e.g. software and service providers, to re-sell this component.

Confidentiality

This publication may contain SWIFT or third-party confidential information. Only disclose it outside your organisation in accordance with MyStandards Terms of Use and your related license rights.

This component is provided 'AS IS'. SWIFT does not give and excludes any express or implied warranties with respect to this component such as but not limited to any guarantee as to its quality, supply or availability.

Any and all rights, including title, ownership rights, copyright, trademark, patents, and any other intellectual property rights of whatever nature in this component will remain the exclusive property of SWIFT or its licensors.

Trademarks and Patents

SWIFT is the trade name of S.W.I.F.T. SCRL. The following are registered trademarks of SWIFT: SWIFT, the SWIFT logo, 3SKey, Innotribe, Sibos, SWIFTNet, MyStandards, SWIFTReady, and Accord. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.