

## Usage Guideline

# HSBC\_pain.001.001.03\_TARGETandInternationalPayments\_UnitedKingdom

## HSBC\_pain.001.001.03\_HighValuePayment\_Europe

This document describes a usage guideline restricting the base message **MX pain.001.001.03**. You can also consult [this information online](#).

Published by SWIFT and generated by [MyStandards](#).

29 June 2018

# Table of Contents

**Message Functionality** ..... 3

**1    Restriction summary** ..... 4

**2    Structure** ..... 5

**3    Message Building Blocks** ..... 6

**4    Message Components** ..... 8

**5    Message Datatypes** ..... 138

**Legal Notices** ..... 182

## Message Functionality

### Overview

CHAPS payments are high-value, domestic sterling payments in the United Kingdom of Great Britain and Northern Ireland.. The beneficiary account should be addressed by providing the sort code of the beneficiary's bank and the domestic account number. For any other currency or beneficiary accounts outside the United Kingdom, international payments are initiated (clearing via Swift or bilateral agreements). The Swift BIC of the beneficiary's bank should be provided wherever known. For European countries that support IBAN, the beneficiary account should be provided as an IBAN, in all other cases as the domestic account number. An intermediary bank may be used for international payments. It should only be provided if requested by the beneficiary, i.e. if it is part of the account information supplied by the beneficiary. HSBC maintains a directory of relevant bank relationships and will enrich this information if not provided in the payment instruction

Characters must be encoded using UTF-8. ISO 20022 has decided to restrict to only UTF-8 based on the fact that it is the most efficient (length-wise) way to transport characters. Only SWIFT supported characters can be supplied, see below.

| Character | Description                                 |
|-----------|---------------------------------------------|
| "a" - "z" | 26 small characters of the Latin alphabet   |
| "A" - "Z" | 26 capital characters of the Latin alphabet |
| "0" - "9" | 10 numeric characters                       |
| "/"       | Solidus (slash)                             |
| "-"       | Hyphen                                      |
| "?"       | Question mark                               |
| ":"       | Colon                                       |
| "("       | Opening parenthesis                         |
| ")"       | Closing parenthesis                         |
| ","       | Full stop                                   |
| ","       | Comma                                       |
| "' "      | Apostrophe                                  |
| "+"       | Plus                                        |
| " "       | Space                                       |

### Outline

The HSBC\_pain.001.001.03\_HighValuePayment\_Europe / HSBC\_pain.001.001.03\_TARGETandInternationalPayments\_UnitedKingdom message is composed of 2 building blocks

#### a. GroupHeader

Set of characteristics shared by all individual transactions included in the message.

#### b. PaymentInformation

Set of characteristics that applies to the debit side of the payment transactions included in the credit transfer initiation.

# 1 Restriction summary

This Usage Guideline restricts the pain.001.001.03 message.

| Restriction Type    | See page                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Removed elements    | 24, 49, 53, 84, 92, 101, 101, 101, 101, 107, 107, 107, 107, 118, 118, 142, 150, 174, 174                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Make mandatory      | 36, 37, 37, 52, 53, 63, 68, 68, 74, 74, 74, 74, 75, 76, 77, 77, 85, 98, 98, 105, 105, 105, 105, 105, 105, 105, 105, 106, 106, 106, 106                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Reduce Multiplicity | 38, 60, 68, 68, 68, 107, 107, 107, 107, 129                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Ignore              | 9, 11, 12, 16, 16, 16, 16, 17, 17, 17, 24, 31, 33, 34, 34, 35, 35, 38, 43, 44, 45, 53, 53, 54, 54, 54, 54, 55, 55, 55, 57, 57, 57, 57, 57, 58, 58, 58, 58, 62, 67, 67, 69, 69, 70, 70, 70, 72, 73, 77, 77, 78, 78, 78, 78, 86, 88, 90, 90, 92, 93, 94, 97, 97, 97, 97, 97, 101, 101, 101, 101, 101, 101, 101, 101, 102, 102, 102, 102, 102, 109, 109, 110, 111, 112, 112, 114, 115, 118, 118, 119, 119, 120, 120, 120, 123, 123, 124, 125, 127, 128, 128, 128, 130, 130, 131, 131, 132, 132, 132, 133, 134, 134, 134, 137, 144, 144, 144, 144, 144, 145, 145, 145, 145, 145, 145, 146, 146, 146, 146, 146, 146, 146, 147, 147, 147, 147, 148, 148, 150, 177, 178 |
| Text rules          | 12, 39, 39, 49, 49, 54, 63, 63, 63, 72, 79, 87, 115, 120                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Conditional rules   | 7, 32, 74, 74, 74, 74, 86, 89, 102, 102, 102, 103, 103, 103, 103, 103, 104, 104, 104, 104, 105, 106, 106, 106                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Fixed values        | n.a.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Truncates           | n.a.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Comments            | 12, 15, 24, 30, 38, 41, 56, 57, 60, 61, 61, 76, 76, 76, 76, 83, 84, 85, 87, 89, 93, 93, 116, 117, 141                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Annotations         | n.a.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Changed datatypes   | n.a.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Extensions          | n.a.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Synonyms            | n.a.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Other restrictions  | 6                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

## 2 Structure

⊘ Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                               | <XML Tag>          | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------------------------------------|--------------------|----|--------|------------------|------|
|       | <i>CustomerCreditTransferInitiationV03</i> | <CstmrCdtTrfInitn> |    | [1..1] | ⚠                | 6    |
| 1.0   | <b>GroupHeader</b>                         | <GrpHdr>           |    | [1..1] |                  | 6    |
| 1.1   | MessageIdentification                      | <MsgId>            |    | [1..1] | ⚠                | 59   |
| 1.2   | CreationDateTime                           | <CreDtTm>          |    | [1..1] |                  | 60   |
| 1.3   | Authorisation                              | <Authstn>          |    | [0..2] | R[0..1]          | 60   |
| 1.6   | NumberOfTransactions                       | <NbOfTx>           |    | [1..1] | ⚠                | 60   |
| 1.7   | ControlSum                                 | <CtrlSum>          |    | [0..1] | ⚠                | 61   |
| 1.8   | InitiatingParty                            | <InitgPty>         |    | [1..1] |                  | 61   |
| 1.9   | ForwardingAgent                            | <FwdgAgt>          |    | [0..1] | ♦                | 62   |
| 2.0   | <b>PaymentInformation</b>                  | <PmtInf>           |    | [1..*] | ⚠                | 6    |
| 2.1   | PaymentInformationIdentification           | <PmtInfId>         |    | [1..1] | ⚠                | 83   |
| 2.2   | PaymentMethod                              | <PmtMtd>           |    | [1..1] |                  | 83   |
| 2.3   | BatchBooking                               | <BtchBookg>        |    | [0..1] | ⊘                | 84   |
| 2.4   | NumberOfTransactions                       | <NbOfTx>           |    | [0..1] |                  | 84   |
| 2.5   | ControlSum                                 | <CtrlSum>          |    | [0..1] | ⚠                | 84   |
| 2.6   | PaymentTypeInformation                     | <PmtTplnf>         |    | [0..1] | M                | 84   |
| 2.17  | RequestedExecutionDate                     | <ReqdExctnDt>      |    | [1..1] | ⚠                | 85   |
| 2.18  | PoolingAdjustmentDate                      | <PoolgAdjstmntDt>  |    | [0..1] | ♦                | 85   |
| 2.19  | Debtor                                     | <Dbtr>             |    | [1..1] | ⚠                | 86   |
| 2.20  | DebtorAccount                              | <DbtrAcct>         |    | [1..1] | ⚠                | 86   |
| 2.21  | DebtorAgent                                | <DbtrAgt>          |    | [1..1] | ⚠                | 87   |
| 2.22  | DebtorAgentAccount                         | <DbtrAgtAcct>      |    | [0..1] | ♦                | 88   |
| 2.23  | UltimateDebtor                             | <UltmtDbtr>        |    | [0..1] | ⚠                | 88   |
| 2.24  | ChargeBearer                               | <ChrgBr>           |    | [0..1] | ⚠                | 89   |
| 2.25  | ChargesAccount                             | <ChrgsAcct>        |    | [0..1] | ♦                | 89   |
| 2.26  | ChargesAccountAgent                        | <ChrgsAcctAgt>     |    | [0..1] | ♦                | 90   |
| 2.27  | CreditTransferTransactionInformation       | <CdtTrfTxInf>      |    | [1..*] |                  | 90   |

## 3 Message Building Blocks

**Note** The following chapter identifies the building blocks of the HSBC\_pain.001.001.03\_HighValuePayment\_Europe / HSBC\_pain.001.001.03\_TARGETandInternationalPayments\_United-Kingdom message definition.

### Usage Guideline on Root Node

- on pain.001.001.03/

- **MutuallyExclusive:**

For each [CustomerCreditTransferInitiationV03], the following elements are mutually exclusive: [PaymentInformation/UltimateDebtor] , [PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor] and all may be absent

### 3.1 GroupHeader

*XML Tag:* GrpHdr

*Presence:* [1..1]

*Definition:* Set of characteristics shared by all individual transactions included in the message.

The **GrpHdr** block contains the following elements (see datatype "GroupHeader32" on page 59 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item          | <XML Tag>  | Or | Mult.  | Usage Guidelines | Page |
|-------|-----------------------|------------|----|--------|------------------|------|
| 1.1   | MessageIdentification | <MsgId>    |    | [1..1] | ⚠️               | 59   |
| 1.2   | CreationDateTime      | <CreDtTm>  |    | [1..1] |                  | 60   |
| 1.3   | Authorisation         | <Authstn>  |    | [0..2] | R[0..1]          | 60   |
| 1.6   | NumberOfTransactions  | <NbOfTxs>  |    | [1..1] | ⚠️               | 60   |
| 1.7   | ControlSum            | <CtrlSum>  |    | [0..1] | ⚠️               | 61   |
| 1.8   | InitiatingParty       | <InitgPty> |    | [1..1] |                  | 61   |
| 1.9   | ForwardingAgent       | <FwdgAgt>  |    | [0..1] | 💡                | 62   |

### 3.2 PaymentInformation

*XML Tag:* PmtInf

*Presence:* [1..\*]

*Definition:* Set of characteristics that applies to the debit side of the payment transactions included in the credit transfer initiation.

The **PmtInf** block contains the following elements (see datatype "PaymentInstructionInformation3\_\_1" on page 79 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                         | <XML Tag>         | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------------------------------|-------------------|----|--------|------------------|------|
| 2.1   | PaymentInformationIdentification     | <PmtInfId>        |    | [1..1] | ⚠                | 83   |
| 2.2   | PaymentMethod                        | <PmtMtd>          |    | [1..1] |                  | 83   |
| 2.3   | BatchBooking                         | <BtchBookg>       |    | [0..1] | 🚫                | 84   |
| 2.4   | NumberOfTransactions                 | <NbOfTx>          |    | [0..1] |                  | 84   |
| 2.5   | ControlSum                           | <CtrlSum>         |    | [0..1] | ⚠                | 84   |
| 2.6   | PaymentTypeInformation               | <PmtTpInf>        |    | [0..1] | M                | 84   |
| 2.17  | RequestedExecutionDate               | <ReqdExctnDt>     |    | [1..1] | ⚠                | 85   |
| 2.18  | PoolingAdjustmentDate                | <PoolgAdjstmntDt> |    | [0..1] | ✦                | 85   |
| 2.19  | Debtor                               | <Dbtr>            |    | [1..1] | ⚠                | 86   |
| 2.20  | DebtorAccount                        | <DbtrAcct>        |    | [1..1] | ⚠                | 86   |
| 2.21  | DebtorAgent                          | <DbtrAgt>         |    | [1..1] | ⚠                | 87   |
| 2.22  | DebtorAgentAccount                   | <DbtrAgtAcct>     |    | [0..1] | ✦                | 88   |
| 2.23  | UltimateDebtor                       | <UltmtDbtr>       |    | [0..1] | ⚠                | 88   |
| 2.24  | ChargeBearer                         | <ChrgBr>          |    | [0..1] | ⚠                | 89   |
| 2.25  | ChargesAccount                       | <ChrgsAcct>       |    | [0..1] | ✦                | 89   |
| 2.26  | ChargesAccountAgent                  | <ChrgsAcctAgt>    |    | [0..1] | ✦                | 90   |
| 2.27  | CreditTransferTransactionInformation | <CdtTrfTxInf>     |    | [1..*] |                  | 90   |

#### Usage Guideline details

- on pain.001.001.03/PaymentInformation

- HSBC\_ServiceLevel:

Provide Service Level only at either Payment-Information or Transaction level

**If**

'Service Level' is present at 'Payment Information'

**Then**

'Service Level' is not allowed at 'Credit Transfer Transaction Information'

## 4 Message Components

**Note** The following chapter identifies the message components.

### 4.1 AccountIdentification4Choice

*Definition:* Specifies the unique identification of an account as assigned by the account servicer.

🚫 Removed - ⬡ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
| 1.1.1 | IBAN         | <IBAN>    | {Or | [1..1] |                  | 8    |
| 1.1.2 | Other        | <Othr>    | Or} | [1..1] | ⬡                | 8    |

**Used in element(s)**

["Identification" on page 15](#)

#### 4.1.1 IBAN

*XML Tag:* IBAN

*Presence:* [1..1]

*Definition:* International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

*Datatype:* ["IBAN2007Identifier" on page 166](#)

#### 4.1.2 Other

*XML Tag:* Othr

*Presence:* [1..1]

*Definition:* Unique identification of an account, as assigned by the account servicer, using an identification scheme.

The **Othr** block contains the following elements (see datatype ["GenericAccountIdentification1" on page 53](#) for details)

🚫 Removed - ⬡ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
| 1.1.3 | Identification | <Id>      |    | [1..1] | ⬡ ⚠              | 54   |
| 1.1.4 | SchemeName     | <SchmeNm> |    | [0..1] | ⬡                | 54   |
| 1.1.7 | Issuer         | <Issr>    |    | [0..1] | ⬡                | 54   |

## Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgentAccount/Identification/Other](#)) will be ignored by the Receiver.

## 4.2 AccountSchemeName1Choice

*Definition:* Sets of elements to identify a name of the identification scheme.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
| 1.1.5 | Code         | <Cd>      | {Or | [1..1] |                  | 9    |
| 1.1.6 | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 9    |

Used in element(s)

"SchemeName" on page 54

### 4.2.1 Code

*XML Tag:* Cd

*Presence:* [1..1]

*Definition:* Name of the identification scheme, in a coded form as published in an external list.

*Datatype:* ["ExternalAccountIdentification1Code"](#) on page 159

### 4.2.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Name of the identification scheme, in a free text form.

*Datatype:* ["Max35Text"](#) on page 171

## 4.3 AmountType3Choice

*Definition:* Specifies the amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item     | <XML Tag>  | Or  | Mult.  | Usage Guidelines | Page |
|-------|------------------|------------|-----|--------|------------------|------|
| 2.43  | InstructedAmount | <InstdAmt> | {Or | [1..1] |                  | 10   |
| 2.44  | EquivalentAmount | <EqvtAmt>  | Or} | [1..1] |                  | 10   |

**Used in element(s)**["Amount" on page 29](#)

### 4.3.1 InstructedAmount

*XML Tag:* InstdAmt*Presence:* [1..1]*Definition:* Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.*Datatype:* ["ActiveOrHistoricCurrencyAndAmount" on page 138](#)

### 4.3.2 EquivalentAmount

*XML Tag:* EqvtAmt*Presence:* [1..1]*Definition:* Amount of money to be moved between the debtor and creditor, expressed in the currency of the debtor's account, and the currency in which the amount is to be moved.The **EqvtAmt** block contains the following elements (see datatype ["EquivalentAmount2" on page 47](#) for details)
 Removed - 
  Ignored - 
  Details below - 
  Mandatory - 
 R[x..x] Repeatability[details]

| Index | Message Item       | <XML Tag>  | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------------|------------|----|--------|------------------|------|
| 2.45  | Amount             | <Amt>      |    | [1..1] |                  | 48   |
| 2.46  | CurrencyOfTransfer | <CcyOfTrf> |    | [1..1] |                  | 48   |

## 4.4 Authorisation1Choice

*Definition:* Provides the details on the user identification or any user key that allows to check if the initiating party is allowed to issue the transaction.
 Removed - 
  Ignored - 
  Details below - 
  Mandatory - 
 R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines                                                                      | Page |
|-------|--------------|-----------|-----|--------|---------------------------------------------------------------------------------------|------|
| 1.4   | Code         | <Cd>      | {Or | [1..1] |                                                                                       | 10   |
| 1.5   | Proprietary  | <Prtry>   | Or} | [1..1] |  | 11   |

**Used in element(s)**["Authorisation" on page 60](#)

### 4.4.1 Code

*XML Tag:* Cd*Presence:* [1..1]*Definition:* Specifies the authorisation, in a coded form.

Datatype: ["Authorisation1Code" on page 141](#)

## 4.4.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the authorisation, in a free text form.

Datatype: ["Max128Text" on page 168](#)

### Usage Guideline details

- This element([pain.001.001.03/GroupHeader/Authorisation/Proprietary](#)) will be ignored by the Receiver.

## 4.5 BranchAndFinancialInstitutionIdentification4

Definition: Set of elements used to uniquely and unambiguously identify a financial institution or a branch of a financial institution.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item                       | <XML Tag>    | Or | Mult.  | Usage Guidelines | Page |
|--------|------------------------------------|--------------|----|--------|------------------|------|
| 6.1.0  | FinancialInstitutionIdentification | <FinInstnId> |    | [1..1] | ⚠️               | 11   |
| 6.1.25 | BranchIdentification               | <BrnchId>    |    | [0..1] | 💡 ⚠️             | 12   |

### Used in element(s)

"ChargesAccountAgent" on page 90, "CreditorAgent" on page 35, "DebtorAgent" on page 87, "ForwardingAgent" on page 62, "IntermediaryAgent1" on page 32, "IntermediaryAgent2" on page 33, "IntermediaryAgent3" on page 34

### 4.5.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "[FinancialInstitutionIdentification7](#)" on page 50 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item                       | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|--------|------------------------------------|---------------|----|--------|------------------|------|
| 6.1.1  | BIC                                | <BIC>         |    | [0..1] |                  | 50   |
| 6.1.2  | ClearingSystemMemberIdentification | <ClrSysMmbld> |    | [0..1] |                  | 51   |
| 6.1.7  | Name                               | <Nm>          |    | [0..1] |                  | 51   |
| 6.1.8  | PostalAddress                      | <PstlAdr>     |    | [0..1] | <b>M</b>         | 51   |
| 6.1.19 | Other                              | <Othr>        |    | [0..1] | 💡 🚫              | 53   |

#### Usage Guideline details

- on **pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification**
  - **HSBC\_FinancialInstitutionIdentification:**  
SWIFT BIC or routing code are the preferred options

## 4.5.2 BranchIdentification

*XML Tag:* BrnchId

*Presence:* [0..1]

*Definition:* Identifies a specific branch of a financial institution.

*Usage:* This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData2](#)" on page 13 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|----------------|-----------|----|--------|------------------|------|
| 6.1.26 | Identification | <Id>      |    | [0..1] |                  | 13   |
| 6.1.27 | Name           | <Nm>      |    | [0..1] |                  | 13   |
| 6.1.28 | PostalAddress  | <PstlAdr> |    | [0..1] |                  | 13   |

#### Usage Guideline details

- This element(**pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent1/BranchIdentification**) will be ignored by the Receiver.
- on **pain.001.001.03/PaymentInformation/DebtorAgent/BranchIdentification**

**Comment:** (empty)

## 4.6 BranchData2

*Definition:* Information that locates and identifies a specific branch of a financial institution.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|----------------|-----------|----|--------|------------------|------|
| 6.1.26 | Identification | <Id>      |    | [0..1] |                  | 13   |
| 6.1.27 | Name           | <Nm>      |    | [0..1] |                  | 13   |
| 6.1.28 | PostalAddress  | <PstlAdr> |    | [0..1] |                  | 13   |

**Used in element(s)**

"BranchIdentification" on page 12

### 4.6.1 Identification

*XML Tag:* Id

*Presence:* [0..1]

*Definition:* Unique and unambiguous identification of a branch of a financial institution.

*Datatype:* "Max35Text" on page 171

### 4.6.2 Name

*XML Tag:* Nm

*Presence:* [0..1]

*Definition:* Name by which an agent is known and which is usually used to identify that agent.

*Datatype:* "Max140Text" on page 169

### 4.6.3 PostalAddress

*XML Tag:* PstlAdr

*Presence:* [0..1]

*Definition:* Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress6" on page 96 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index                                      | Message Item       | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|--------------------------------------------|--------------------|---------------|----|--------|------------------|------|
| 9.1.2 ,<br>6.1.9 ,<br>6.1.29 ,<br>10.1.0   | AddressType        | <AdrTp>       |    | [0..1] | ✦                | 96   |
| 9.1.3 ,<br>6.1.10 ,<br>6.1.30 ,<br>10.1.1  | Department         | <Dept>        |    | [0..1] |                  | 97   |
| 9.1.4 ,<br>6.1.11 ,<br>6.1.31 ,<br>10.1.2  | SubDepartment      | <SubDept>     |    | [0..1] |                  | 97   |
| 9.1.5 ,<br>6.1.12 ,<br>6.1.32 ,<br>10.1.3  | StreetName         | <StrtNm>      |    | [0..1] |                  | 97   |
| 9.1.6 ,<br>6.1.13 ,<br>6.1.33 ,<br>10.1.4  | BuildingNumber     | <BldgNb>      |    | [0..1] |                  | 97   |
| 9.1.7 ,<br>6.1.14 ,<br>6.1.34 ,<br>10.1.5  | PostCode           | <PstCd>       |    | [0..1] |                  | 98   |
| 9.1.8 ,<br>6.1.15 ,<br>6.1.35 ,<br>10.1.6  | TownName           | <TwnNm>       |    | [0..1] |                  | 98   |
| 9.1.9 ,<br>6.1.16 ,<br>6.1.36 ,<br>10.1.7  | CountrySubDivision | <CtrySubDvsn> |    | [0..1] |                  | 98   |
| 9.1.10 ,<br>6.1.17 ,<br>6.1.37 ,<br>10.1.8 | Country            | <Ctry>        |    | [0..1] |                  | 98   |
| 9.1.11 ,<br>6.1.18 ,<br>6.1.38 ,<br>10.1.9 | AddressLine        | <AdrLine>     |    | [0..7] |                  | 99   |

## 4.7 CashAccount16

*Definition:* Set of elements used to identify an account.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|----------------|-----------|----|--------|------------------|------|
| 1.1.0  | Identification | <Id>      |    | [1..1] | ⚠                | 15   |
| 1.1.8  | Type           | <Tp>      |    | [0..1] | 💡                | 15   |
| 1.1.11 | Currency       | <Ccy>     |    | [0..1] | 💡                | 16   |
| 1.1.12 | Name           | <Nm>      |    | [0..1] | 💡                | 16   |

#### Used in element(s)

"ChargesAccount" on page 89, "CreditorAccount" on page 37, "CreditorAgentAccount" on page 36, "DebtorAccount" on page 86, "DebtorAgentAccount" on page 88, "IntermediaryAgent1Account" on page 33, "IntermediaryAgent2Account" on page 34, "IntermediaryAgent3Account" on page 35

## 4.7.1 Identification

XML Tag: Id

Presence: [1..1]

**Definition:** Unique and unambiguous identification for the account between the account owner and the account servicer.

The **Id** block contains the following elements (see datatype "AccountIdentification4Choice" on page 8 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
| 1.1.1 | IBAN         | <IBAN>    | {Or | [1..1] |                  | 8    |
| 1.1.2 | Other        | <Othr>    | Or} | [1..1] | 💡                | 8    |

#### Usage Guideline details

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Identification

**Comment:**

May be provided as IBAN or domestic account number.

## 4.7.2 Type

XML Tag: Tp

Presence: [0..1]

**Definition:** Specifies the nature, or use of the account.

The **Tp** block contains the following elements (see datatype "[CashAccountType2](#)" on page 17 for details)

🚫 Removed - ♦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|--------|--------------|-----------|-----|--------|------------------|------|
| 1.1.9  | Code         | <Cd>      | {Or | [1..1] |                  | 17   |
| 1.1.10 | Proprietary  | <Prtry>   | Or} | [1..1] | ♦                | 17   |

#### Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgentAccount/Type](#)) will be ignored by the Receiver.

### 4.7.3 Currency

*XML Tag:* Ccy

*Presence:* [0..1]

*Definition:* Identification of the currency in which the account is held.

*Usage:* Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

*Datatype:* "[ActiveOrHistoricCurrencyCode](#)" on page 138

#### Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/DebtorAccount/Currency](#)) will be ignored by the Receiver.
- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgentAccount/Currency](#)) will be ignored by the Receiver.
- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Currency](#)) will be ignored by the Receiver.

### 4.7.4 Name

*XML Tag:* Nm

*Presence:* [0..1]

*Definition:* Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

*Usage:* The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

*Datatype:* "[Max70Text](#)" on page 172

## Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgentAccount/Name](#)) will be ignored by the Receiver.

## 4.8 CashAccountType2

*Definition:* Nature or use of the account.

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|--------|--------------|-----------|-----|--------|------------------|------|
| 1.1.9  | Code         | <Cd>      | {Or | [1..1] |                  | 17   |
| 1.1.10 | Proprietary  | <Prtry>   | Or} | [1..1] | ✦                | 17   |

Used in element(s)

["Type" on page 15](#)

### 4.8.1 Code

*XML Tag:* Cd

*Presence:* [1..1]

**Warning** Either Code or Proprietary must be present, but not both.

*Definition:* Account type, in a coded form.

*Datatype:* ["CashAccountType4Code" on page 143](#)

### 4.8.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

**Warning** Either Code or Proprietary must be present, but not both.

*Definition:* Nature or use of the account in a proprietary form.

*Datatype:* ["Max35Text" on page 171](#)

## Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Proprietary](#)) will be ignored by the Receiver.
- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Proprietary](#)) will be ignored by the Receiver.

## 4.9 CategoryPurpose1Choice

*Definition:* Specifies the high level purpose of the instruction based on a set of pre-defined categories.

*Usage:* This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index          | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|----------------|--------------|-----------|-----|--------|------------------|------|
| 2.15 ,<br>2.40 | Code         | <Cd>      | {Or | [1..1] |                  | 18   |
| 2.16 ,<br>2.41 | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 18   |

Used in element(s)

"CategoryPurpose" on page 93

### 4.9.1 Code

*XML Tag:* Cd

*Presence:* [1..1]

*Definition:* Category purpose, as published in an external category purpose code list.

*Datatype:* "ExternalCategoryPurpose1Code" on page 160

### 4.9.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Category purpose, in a proprietary form.

*Datatype:* "Max35Text" on page 171

## 4.10 Cheque6

*Definition:* Set of characteristics related to a cheque instruction, such as cheque type or cheque number.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item         | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------------|---------------|----|--------|------------------|------|
| 2.53  | ChequeType           | <ChqTp>       |    | [0..1] |                  | 19   |
| 2.54  | ChequeNumber         | <ChqNb>       |    | [0..1] |                  | 19   |
| 2.55  | ChequeFrom           | <ChqFr>       |    | [0..1] |                  | 20   |
| 2.58  | DeliveryMethod       | <DlvryMtd>    |    | [0..1] |                  | 20   |
| 2.61  | DeliverTo            | <DlvrTo>      |    | [0..1] |                  | 20   |
| 2.64  | InstructionPriority  | <InstrPrty>   |    | [0..1] |                  | 21   |
| 2.65  | ChequeMaturityDate   | <ChqMtrtyDt>  |    | [0..1] |                  | 21   |
| 2.66  | FormsCode            | <FrmsCd>      |    | [0..1] |                  | 21   |
| 2.67  | MemoField            | <MemoFld>     |    | [0..2] |                  | 21   |
| 2.68  | RegionalClearingZone | <RgnlClrZone> |    | [0..1] |                  | 21   |
| 2.69  | PrintLocation        | <PrtLctn>     |    | [0..1] |                  | 22   |

## Rules

### R24 ChequeMaturityDateRule ✓

If ChequeMaturityDate is present, then ChequeType must be present and equal to DRFT or EL-DR.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00101
- *Error Text:* Invalid message content for cheque maturity date.

## Used in element(s)

["ChequeInstruction" on page 31](#)

## 4.10.1 ChequeType

*XML Tag:* ChqTp

*Presence:* [0..1]

*Definition:* Specifies the type of cheque to be issued.

*Datatype:* ["ChequeType2Code" on page 152](#)

## 4.10.2 ChequeNumber

*XML Tag:* ChqNb

*Presence:* [0..1]

*Definition:* Unique and unambiguous identifier for a cheque as assigned by the agent.

Datatype: "Max35Text" on page 171

### 4.10.3 ChequeFrom

XML Tag: ChqFr

Presence: [0..1]

Definition: Identifies the party that ordered the issuance of the cheque.

The **ChqFr** block contains the following elements (see datatype "NameAndAddress10" on page 64 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index                    | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------------------------|--------------|-----------|----|--------|------------------|------|
| 2.56 ,<br>2.62 ,<br>2.96 | Name         | <Nm>      |    | [1..1] |                  | 65   |
| 2.57 ,<br>2.63 ,<br>2.97 | Address      | <Adr>     |    | [1..1] |                  | 65   |

### 4.10.4 DeliveryMethod

XML Tag: DlvryMtd

Presence: [0..1]

Definition: Specifies the delivery method of the cheque by the debtor's agent.

The **DlvryMtd** block contains the following elements (see datatype "ChequeDeliveryMethod1Choice" on page 22 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
| 2.59  | Code         | <Cd>      | {Or | [1..1] |                  | 22   |
| 2.60  | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 22   |

### 4.10.5 DeliverTo

XML Tag: DlvrTo

Presence: [0..1]

Definition: Party to whom the debtor's agent needs to send the cheque.

The **DlvrTo** block contains the following elements (see datatype "[NameAndAddress10](#)" on page 64 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index                    | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------------------------|--------------|-----------|----|--------|------------------|------|
| 2.56 ,<br>2.62 ,<br>2.96 | Name         | <Nm>      |    | [1..1] |                  | 65   |
| 2.57 ,<br>2.63 ,<br>2.97 | Address      | <Adr>     |    | [1..1] |                  | 65   |

## 4.10.6 InstructionPriority

XML Tag: InstrPrty

Presence: [0..1]

*Definition:* Urgency or order of importance that the originator would like the recipient of the payment instruction to apply to the processing of the payment instruction.

Datatype: "[Priority2Code](#)" on page 175

## 4.10.7 ChequeMaturityDate

XML Tag: ChqMtrtyDt

Presence: [0..1]

*Definition:* Date when the draft becomes payable and the debtor's account is debited.

Datatype: "[ISODate](#)" on page 166

## 4.10.8 FormsCode

XML Tag: FrmsCd

Presence: [0..1]

*Definition:* Identifies, in a coded form, the cheque layout, company logo and digitised signature to be used to print the cheque, as agreed between the initiating party and the debtor's agent.

Datatype: "[Max35Text](#)" on page 171

## 4.10.9 MemoField

XML Tag: MemoFld

Presence: [0..2]

*Definition:* Information that needs to be printed on a cheque, used by the payer to add miscellaneous information.

Datatype: "[Max35Text](#)" on page 171

## 4.10.10 RegionalClearingZone

XML Tag: RgnlClrZone

*Presence:* [0..1]

*Definition:* Regional area in which the cheque can be cleared, when a country has no nation-wide cheque clearing organisation.

*Datatype:* ["Max35Text" on page 171](#)

## 4.10.11 PrintLocation

*XML Tag:* PrtLctn

*Presence:* [0..1]

*Definition:* Specifies the print location of the cheque.

*Datatype:* ["Max35Text" on page 171](#)

## 4.11 ChequeDeliveryMethod1Choice

*Definition:* Set of characteristics related to a cheque instruction, such as cheque type or cheque number.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
| 2.59  | Code         | <Cd>      | {Or | [1..1] |                  | 22   |
| 2.60  | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 22   |

**Used in element(s)**

["DeliveryMethod" on page 20](#)

### 4.11.1 Code

*XML Tag:* Cd

*Presence:* [1..1]

*Definition:* Specifies the delivery method of the cheque by the debtor's agent.

*Datatype:* ["ChequeDelivery1Code" on page 151](#)

### 4.11.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Specifies a proprietary delivery method of the cheque by the debtor's agent.

*Datatype:* ["Max35Text" on page 171](#)

## 4.12 ClearingSystemIdentification2Choice

*Definition:* Choice of a clearing system identifier.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
| 6.1.4 | Code         | <Cd>      | {Or | [1..1] |                  | 23   |
| 6.1.5 | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 23   |

#### Used in element(s)

"ClearingSystemIdentification" on page 23

## 4.12.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Identification of a clearing system, in a coded form as published in an external list.

Datatype: "ExternalClearingSystemIdentification1Code" on page 160

## 4.12.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Identification code for a clearing system, that has not yet been identified in the list of clearing systems.

Datatype: "Max35Text" on page 171

## 4.13 ClearingSystemMemberIdentification2

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                 | <XML Tag>  | Or | Mult.  | Usage Guidelines | Page |
|-------|------------------------------|------------|----|--------|------------------|------|
| 6.1.3 | ClearingSystemIdentification | <ClrSysId> |    | [0..1] | 💡 🚫 ⚠            | 23   |
| 6.1.6 | MemberIdentification         | <Mmbld>    |    | [1..1] |                  | 24   |

#### Used in element(s)

"ClearingSystemMemberIdentification" on page 51

## 4.13.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "[ClearingSystemIdentification2Choice](#)" on page 22 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
| 6.1.4 | Code         | <Cd>      | {Or | [1..1] |                  | 23   |
| 6.1.5 | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 23   |

#### Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification](#)) is removed.
- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification](#)) will be ignored by the Receiver.
- on [pain.001.001.03/PaymentInformation/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification](#)

**Comment:**

Domestic routing code is required if domestic account number is quoted.

## 4.13.2 MemberIdentification

*XML Tag:* Mmbld

*Presence:* [1..1]

*Definition:* Identification of a member of a clearing system.

*Datatype:* "[Max35Text](#)" on page 171

## 4.14 ContactDetails2

*Definition:* Communication device number or electronic address used for communication.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item | <XML Tag>  | Or | Mult.  | Usage Guidelines | Page |
|--------|--------------|------------|----|--------|------------------|------|
| 9.1.35 | NamePrefix   | <NmPrfx>   |    | [0..1] |                  | 25   |
| 9.1.36 | Name         | <Nm>       |    | [0..1] |                  | 25   |
| 9.1.37 | PhoneNumber  | <PhneNb>   |    | [0..1] |                  | 25   |
| 9.1.38 | MobileNumber | <MobNb>    |    | [0..1] |                  | 25   |
| 9.1.39 | FaxNumber    | <FaxNb>    |    | [0..1] |                  | 25   |
| 9.1.40 | EmailAddress | <EmailAdr> |    | [0..1] |                  | 25   |
| 9.1.41 | Other        | <Othr>     |    | [0..1] |                  | 26   |

**Used in element(s)**

["ContactDetails" on page 77](#), ["ContactDetails" on page 72](#)

## 4.14.1      **NamePrefix**

*XML Tag:* NmPrfx

*Presence:* [0..1]

*Definition:* Specifies the terms used to formally address a person.

*Datatype:* ["NamePrefix1Code" on page 172](#)

## 4.14.2      **Name**

*XML Tag:* Nm

*Presence:* [0..1]

*Definition:* Name by which a party is known and which is usually used to identify that party.

*Datatype:* ["Max140Text" on page 169](#)

## 4.14.3      **PhoneNumber**

*XML Tag:* PhneNb

*Presence:* [0..1]

*Definition:* Collection of information that identifies a phone number, as defined by telecom services.

*Datatype:* ["PhoneNumber" on page 175](#)

## 4.14.4      **MobileNumber**

*XML Tag:* MobNb

*Presence:* [0..1]

*Definition:* Collection of information that identifies a mobile phone number, as defined by telecom services.

*Datatype:* ["PhoneNumber" on page 175](#)

## 4.14.5      **FaxNumber**

*XML Tag:* FaxNb

*Presence:* [0..1]

*Definition:* Collection of information that identifies a FAX number, as defined by telecom services.

*Datatype:* ["PhoneNumber" on page 175](#)

## 4.14.6      **EmailAddress**

*XML Tag:* EmailAdr

*Presence:* [0..1]

*Definition:* Address for electronic mail (e-mail).

*Datatype:* ["Max2048Text" on page 170](#)

#### 4.14.7 Other

*XML Tag:* Othr

*Presence:* [0..1]

*Definition:* Contact details in another form.

*Datatype:* "Max35Text" on page 171

### 4.15 CreditTransferTransactionInformation10\_\_1

*Definition:* Set of elements used to provide information specific to the individual transaction(s) included in the message.

Removed - 
 Ignored - 
 Details below - 
 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                 | <XML Tag>         | Or | Mult.   | Usage Guidelines | Page |
|-------|------------------------------|-------------------|----|---------|------------------|------|
| 2.28  | PaymentIdentification        | <PmtId>           |    | [1..1]  |                  | 29   |
| 2.31  | PaymentTypeInfo              | <PmtTplnf>        |    | [0..1]  |                  | 29   |
| 2.42  | Amount                       | <Amt>             |    | [1..1]  |                  | 29   |
| 2.47  | ExchangeRateInformation      | <XchgRateInf>     |    | [0..1]  |                  | 30   |
| 2.51  | ChargeBearer                 | <ChrgBr>          |    | [0..1]  |                  | 30   |
| 2.52  | ChequeInstruction            | <ChqInstr>        |    | [0..1]  |                  | 31   |
| 2.70  | UltimateDebtor               | <UltmtDbtr>       |    | [0..1]  |                  | 31   |
| 2.71  | IntermediaryAgent1           | <IntrmyAgt1>      |    | [0..1]  |                  | 32   |
| 2.72  | IntermediaryAgent1Account    | <IntrmyAgt1Acct>  |    | [0..1]  |                  | 33   |
| 2.73  | IntermediaryAgent2           | <IntrmyAgt2>      |    | [0..1]  |                  | 33   |
| 2.74  | IntermediaryAgent2Account    | <IntrmyAgt2Acct>  |    | [0..1]  |                  | 34   |
| 2.75  | IntermediaryAgent3           | <IntrmyAgt3>      |    | [0..1]  |                  | 34   |
| 2.76  | IntermediaryAgent3Account    | <IntrmyAgt3Acct>  |    | [0..1]  |                  | 35   |
| 2.77  | CreditorAgent                | <CdtrAgt>         |    | [0..1]  |                  | 35   |
| 2.78  | CreditorAgentAccount         | <CdtrAgtAcct>     |    | [0..1]  |                  | 36   |
| 2.79  | Creditor                     | <Cdtr>            |    | [0..1]  |                  | 36   |
| 2.80  | CreditorAccount              | <CdtrAcct>        |    | [0..1]  |                  | 37   |
| 2.81  | UltimateCreditor             | <UltmtCdtr>       |    | [0..1]  |                  | 37   |
| 2.82  | InstructionForCreditorAgent  | <InstrForCdtrAgt> |    | [0..*]  | R[0..5]          | 38   |
| 2.85  | InstructionForDebtorAgent    | <InstrForDbtrAgt> |    | [0..1]  |                  | 39   |
| 2.86  | Purpose                      | <Purp>            |    | [0..1]  |                  | 40   |
| 2.89  | RegulatoryReporting          | <RgltryRptg>      |    | [0..10] |                  | 40   |
| 2.90  | Tax                          | <Tax>             |    | [0..1]  |                  | 40   |
| 2.91  | RelatedRemittanceInformation | <RltdRmtInf>      |    | [0..10] |                  | 41   |
| 2.98  | RemittanceInformation        | <RmtInf>          |    | [0..1]  |                  | 42   |

## Rules

### R13 IntermediaryAgent2Rule ✓

If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present.

Error handling:

– *Error severity: Fatal*

- *Error Code:* X00056
- *Error Text:* Invalid message content for intermediary agent 2.

**R14 IntermediaryAgent3Rule ✓**

If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00057
- *Error Text:* Invalid message content for intermediary agent 3.

**R15 InstructionForCreditorAgentRule ✓**

If InstructionForCreditorAgent/Code contains CHQB, then CreditorAccount is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00051
- *Error Text:* Invalid message content for instruction for creditor agent PayCreditorByCheque

**R16 IntermediaryAgent1AccountRule ✓**

If IntermediaryAgent1Account is present, then IntermediaryAgent1 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00052
- *Error Text:* Invalid message content for intermediary agent 1 account.

**R17 IntermediaryAgent2AccountRule ✓**

If IntermediaryAgent2Account is present, then IntermediaryAgent2 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00053
- *Error Text:* Invalid message content for intermediary agent 2 account.

**R18 IntermediaryAgent3AccountRule ✓**

If IntermediaryAgent3Account is present, then IntermediaryAgent3 must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00054
- *Error Text:* Invalid message content for intermediary agent 3 account.

**Guidelines****1. UltimateCreditorGuideline**

UltimateCreditor may only be present if different from Creditor.

**2. UltimateDebtorGuideline**

UltimateDebtor may only be present if different from Debtor.

**Used in element(s)**

"CreditTransferTransactionInformation" on page 90

## 4.15.1 PaymentIdentification

*XML Tag:* PmtId

*Presence:* [1..1]

*Definition:* Set of elements used to reference a payment instruction.

The **PmtId** block contains the following elements (see datatype "PaymentIdentification1\_1" on page 78 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item              | <XML Tag>    | Or | Mult.  | Usage Guidelines | Page |
|-------|---------------------------|--------------|----|--------|------------------|------|
| 2.29  | InstructionIdentification | <InstrId>    |    | [0..1] |                  | 78   |
| 2.30  | EndToEndIdentification    | <EndToEndId> |    | [1..1] | ⚠                | 79   |

## 4.15.2 PaymentTypeInformation

*XML Tag:* PmtTpInf

*Presence:* [0..1]

*Definition:* Set of elements used to further specify the type of transaction.

The **PmtTpInf** block contains the following elements (see datatype "PaymentTypeInformation19\_1" on page 91 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index          | Message Item        | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|----------------|---------------------|-------------|----|--------|------------------|------|
| 2.7 ,<br>2.32  | InstructionPriority | <InstrPrty> |    | [0..1] | 🚫                | 92   |
| 2.8 ,<br>2.33  | ServiceLevel        | <SvcLvl>    |    | [0..1] | ⚠                | 92   |
| 2.11 ,<br>2.36 | LocalInstrument     | <LclInstrm> |    | [0..1] |                  | 93   |
| 2.14 ,<br>2.39 | CategoryPurpose     | <CtgyPurp>  |    | [0..1] |                  | 93   |

## 4.15.3 Amount

*XML Tag:* Amt

*Presence:* [1..1]

*Definition:* Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

The **Amt** block contains the following elements (see datatype "[AmountType3Choice](#)" on page 9 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item     | <XML Tag>  | Or   | Mult.  | Usage Guidelines | Page |
|-------|------------------|------------|------|--------|------------------|------|
| 2.43  | InstructedAmount | <InstdAmt> | {Or} | [1..1] |                  | 10   |
| 2.44  | EquivalentAmount | <EqvtAmt>  | Or}  | [1..1] |                  | 10   |

## 4.15.4 ExchangeRateInformation

*XML Tag:* XchgRateInf

*Presence:* [0..1]

*Definition:* Set of elements used to provide details on the currency exchange rate and contract.

The **XchgRateInf** block contains the following elements (see datatype "[ExchangeRateInformation1\\_\\_1](#)" on page 48 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item           | <XML Tag>  | Or | Mult.  | Usage Guidelines | Page |
|-------|------------------------|------------|----|--------|------------------|------|
| 2.48  | ExchangeRate           | <XchgRate> |    | [0..1] | ⚠                | 48   |
| 2.49  | RateType               | <RateTp>   |    | [0..1] | 🚫                | 49   |
| 2.50  | ContractIdentification | <CtrctId>  |    | [0..1] | ⚠                | 49   |

## 4.15.5 ChargeBearer

*XML Tag:* ChrgBr

*Presence:* [0..1]

*Definition:* Specifies which party/parties will bear the charges associated with the processing of the payment transaction.

*Datatype:* "[ChargeBearerType1Code](#)" on page 149

### Usage Guideline details

- on [pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/ChargeBearer](#)  
**Comment:**  
 From 6th January 2018, as part of the PSD2 regulation for all payments where the originator and beneficiary are in EEA countries the only option available for the charge indicator will be "Shared". The only exception is for payments debiting a German account, where the charge indicator can be 'Shared' or 'Our' (debit account). If the "Shared" or 'Our' option, as appropriate, is not supplied the HSBC

back office systems will default the charge indicator to "Shared" before the payment is processed.

## 4.15.6 ChequeInstruction

*XML Tag:* ChqInstr

*Presence:* [0..1]

*Definition:* Set of elements needed to issue a cheque.

The **ChqInstr** block contains the following elements (see datatype "[Cheque6](#)" on [page 18](#) for details)

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item         | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------------|---------------|----|--------|------------------|------|
| 2.53  | ChequeType           | <ChqTp>       |    | [0..1] |                  | 19   |
| 2.54  | ChequeNumber         | <ChqNb>       |    | [0..1] |                  | 19   |
| 2.55  | ChequeFrom           | <ChqFr>       |    | [0..1] |                  | 20   |
| 2.58  | DeliveryMethod       | <DlvryMtd>    |    | [0..1] |                  | 20   |
| 2.61  | DeliverTo            | <DlvrTo>      |    | [0..1] |                  | 20   |
| 2.64  | InstructionPriority  | <InstrPrty>   |    | [0..1] |                  | 21   |
| 2.65  | ChequeMaturityDate   | <ChqMtrtyDt>  |    | [0..1] |                  | 21   |
| 2.66  | FormsCode            | <FrmsCd>      |    | [0..1] |                  | 21   |
| 2.67  | MemoField            | <MemoFld>     |    | [0..2] |                  | 21   |
| 2.68  | RegionalClearingZone | <RgnlClrZone> |    | [0..1] |                  | 21   |
| 2.69  | PrintLocation        | <PrtLctn>     |    | [0..1] |                  | 22   |

### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/ChequeInstruction) will be ignored by the Receiver.

## 4.15.7 UltimateDebtor

*XML Tag:* UltmtDbtr

*Presence:* [0..1]

*Definition:* Ultimate party that owes an amount of money to the (ultimate) creditor.

The **UltmtDbtr** block contains the following elements (see datatype "PartyIdentification32\_\_1" on page 73 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item       | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|--------|--------------------|-------------|----|--------|------------------|------|
| 9.1.0  | Name               | <Nm>        |    | [0..1] | <b>M</b> ⚠️      | 73   |
| 9.1.1  | PostalAddress      | <PstlAdr>   |    | [0..1] | ⚠️               | 74   |
| 9.1.12 | Identification     | <Id>        |    | [0..1] | <b>M</b>         | 76   |
| 9.1.33 | CountryOfResidence | <CtryOfRes> |    | [0..1] | 💡                | 77   |
| 9.1.34 | ContactDetails     | <CtctDtls>  |    | [0..1] | 💡                | 77   |

#### Usage Guideline details

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor

- **HSBC\_OnBehalfOf:**

It is Mandatory to provide the name, address and an account or identification of the ultimate debtor if a priority payment is being made on behalf of someone apart from the account holder and should be supplied in the Ultimate Debtor block.

The address should include, as a minimum, the city or town name; the state or county; and the country.

The Debtor Account <DbtrAcct> block should always be used to supply the HSBC account to be debited.

**If**

The payment is being made on behalf of someone apart from the account holder.

**Then**

The Ultimate Debtor block <UltmtDbtr> should be used to supply the name, address and an account or identification of the ultimate debtor

**Else**

The Debtor <Dbtr> block should be used to supply the name and address of the ultimate debtor.

## 4.15.8 IntermediaryAgent1

*XML Tag:* IntrmyAgt1

*Presence:* [0..1]

*Definition:* Agent between the debtor's agent and the creditor's agent.

*Usage:* If more than one intermediary agent is present, then IntermediaryAgent1 identifies the agent between the DebtorAgent and the IntermediaryAgent2.

The **IntrmyAgt1** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification4](#)" on [page 11](#) for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item                       | <XML Tag>    | Or | Mult.  | Usage Guidelines | Page |
|--------|------------------------------------|--------------|----|--------|------------------|------|
| 6.1.0  | FinancialInstitutionIdentification | <FinInstnId> |    | [1..1] |                  | 11   |
| 6.1.25 | BranchIdentification               | <BrnchId>    |    | [0..1] | 💡                | 12   |

## 4.15.9 IntermediaryAgent1Account

*XML Tag:* IntrmyAgt1Acct

*Presence:* [0..1]

*Definition:* Unambiguous identification of the account of the intermediary agent 1 at its servicing agent in the payment chain.

The **IntrmyAgt1Acct** block contains the following elements (see datatype "[CashAccount16](#)" on [page 14](#) for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|----------------|-----------|----|--------|------------------|------|
| 1.1.0  | Identification | <Id>      |    | [1..1] |                  | 15   |
| 1.1.8  | Type           | <Tp>      |    | [0..1] |                  | 15   |
| 1.1.11 | Currency       | <Ccy>     |    | [0..1] |                  | 16   |
| 1.1.12 | Name           | <Nm>      |    | [0..1] |                  | 16   |

### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent1Account) will be ignored by the Receiver.

## 4.15.10 IntermediaryAgent2

*XML Tag:* IntrmyAgt2

*Presence:* [0..1]

*Definition:* Agent between the debtor's agent and the creditor's agent.

*Usage:* If more than two intermediary agents are present, then IntermediaryAgent2 identifies the agent between the IntermediaryAgent1 and the IntermediaryAgent3.

The **IntrmyAgt2** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification4](#)" on [page 11](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item                       | <XML Tag>    | Or | Mult.  | Usage Guidelines | Page |
|--------|------------------------------------|--------------|----|--------|------------------|------|
| 6.1.0  | FinancialInstitutionIdentification | <FinInstnId> |    | [1..1] |                  | 11   |
| 6.1.25 | BranchIdentification               | <BrnchId>    |    | [0..1] |                  | 12   |

#### Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent2](#)) will be ignored by the Receiver.

## 4.15.11 IntermediaryAgent2Account

*XML Tag:* IntrmyAgt2Acct

*Presence:* [0..1]

*Definition:* Unambiguous identification of the account of the intermediary agent 2 at its servicing agent in the payment chain.

The **IntrmyAgt2Acct** block contains the following elements (see datatype "[CashAccount16](#)" on [page 14](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|----------------|-----------|----|--------|------------------|------|
| 1.1.0  | Identification | <Id>      |    | [1..1] |                  | 15   |
| 1.1.8  | Type           | <Tp>      |    | [0..1] |                  | 15   |
| 1.1.11 | Currency       | <Ccy>     |    | [0..1] |                  | 16   |
| 1.1.12 | Name           | <Nm>      |    | [0..1] |                  | 16   |

#### Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent2Account](#)) will be ignored by the Receiver.

## 4.15.12 IntermediaryAgent3

*XML Tag:* IntrmyAgt3

*Presence:* [0..1]

*Definition:* Agent between the debtor's agent and the creditor's agent.

*Usage:* If IntermediaryAgent3 is present, then it identifies the agent between the IntermediaryAgent 2 and the CreditorAgent.

The **IntrmyAgt3** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification4](#)" on [page 11](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item                       | <XML Tag>    | Or | Mult.  | Usage Guidelines | Page |
|--------|------------------------------------|--------------|----|--------|------------------|------|
| 6.1.0  | FinancialInstitutionIdentification | <FinInstnId> |    | [1..1] |                  | 11   |
| 6.1.25 | BranchIdentification               | <BrnchId>    |    | [0..1] |                  | 12   |

#### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent3) will be ignored by the Receiver.

## 4.15.13 IntermediaryAgent3Account

*XML Tag:* IntrmyAgt3Acct

*Presence:* [0..1]

*Definition:* Unambiguous identification of the account of the intermediary agent 3 at its servicing agent in the payment chain.

The **IntrmyAgt3Acct** block contains the following elements (see datatype "[CashAccount16](#)" on [page 14](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|----------------|-----------|----|--------|------------------|------|
| 1.1.0  | Identification | <Id>      |    | [1..1] |                  | 15   |
| 1.1.8  | Type           | <Tp>      |    | [0..1] |                  | 15   |
| 1.1.11 | Currency       | <Ccy>     |    | [0..1] |                  | 16   |
| 1.1.12 | Name           | <Nm>      |    | [0..1] |                  | 16   |

#### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent3Account) will be ignored by the Receiver.

## 4.15.14 CreditorAgent

*XML Tag:* CdtrAgt

*Presence:* [0..1]

*Definition:* Financial institution servicing an account for the creditor.

The **CdtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification4](#)" on page 11 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item                       | <XML Tag>    | Or | Mult.  | Usage Guidelines | Page |
|--------|------------------------------------|--------------|----|--------|------------------|------|
| 6.1.0  | FinancialInstitutionIdentification | <FinInstnId> |    | [1..1] | ⚠                | 11   |
| 6.1.25 | BranchIdentification               | <BrnchId>    |    | [0..1] |                  | 12   |

#### Usage Guideline details

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent  
*This element is now mandatory, the minimum occurrence has been changed to : 1*

## 4.15.15 CreditorAgentAccount

XML Tag: CdtrAgtAcct

Presence: [0..1]

**Definition:** Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction.

The **CdtrAgtAcct** block contains the following elements (see datatype "[CashAccount16](#)" on page 14 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|----------------|-----------|----|--------|------------------|------|
| 1.1.0  | Identification | <Id>      |    | [1..1] |                  | 15   |
| 1.1.8  | Type           | <Tp>      |    | [0..1] | ✦                | 15   |
| 1.1.11 | Currency       | <Ccy>     |    | [0..1] | ✦                | 16   |
| 1.1.12 | Name           | <Nm>      |    | [0..1] | ✦                | 16   |

## 4.15.16 Creditor

XML Tag: Cdtr

Presence: [0..1]

**Definition:** Party to which an amount of money is due.

The **Cdtr** block contains the following elements (see datatype "PartyIdentification32\_\_1" on page 73 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item       | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|--------|--------------------|-------------|----|--------|------------------|------|
| 9.1.0  | Name               | <Nm>        |    | [0..1] | <b>M</b> ⚠       | 73   |
| 9.1.1  | PostalAddress      | <PstlAdr>   |    | [0..1] | <b>M</b> ⚠       | 74   |
| 9.1.12 | Identification     | <Id>        |    | [0..1] |                  | 76   |
| 9.1.33 | CountryOfResidence | <CtryOfRes> |    | [0..1] |                  | 77   |
| 9.1.34 | ContactDetails     | <CtctDtls>  |    | [0..1] | 💡                | 77   |

#### Usage Guideline details

- on **pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor**  
This element is now mandatory, the minimum occurrence has been changed to : 1

## 4.15.17 CreditorAccount

XML Tag: CdtrAcct

Presence: [0..1]

**Definition:** Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.

The **CdtrAcct** block contains the following elements (see datatype "CashAccount16" on page 14 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|----------------|-----------|----|--------|------------------|------|
| 1.1.0  | Identification | <Id>      |    | [1..1] | ⚠                | 15   |
| 1.1.8  | Type           | <Tp>      |    | [0..1] |                  | 15   |
| 1.1.11 | Currency       | <Ccy>     |    | [0..1] | 💡                | 16   |
| 1.1.12 | Name           | <Nm>      |    | [0..1] |                  | 16   |

#### Usage Guideline details

- on **pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount**  
This element is now mandatory, the minimum occurrence has been changed to : 1

## 4.15.18 UltimateCreditor

XML Tag: UltmtCdtr

*Presence:* [0..1]

*Definition:* Ultimate party to which an amount of money is due.

The **UltmtCdtr** block contains the following elements (see datatype "[PartyIdentification32](#)" on page 70 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item       | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|--------|--------------------|-------------|----|--------|------------------|------|
| 9.1.0  | Name               | <Nm>        |    | [0..1] |                  | 70   |
| 9.1.1  | PostalAddress      | <PstlAdr>   |    | [0..1] |                  | 70   |
| 9.1.12 | Identification     | <Id>        |    | [0..1] |                  | 71   |
| 9.1.33 | CountryOfResidence | <CtryOfRes> |    | [0..1] |                  | 72   |
| 9.1.34 | ContactDetails     | <CtctDtls>  |    | [0..1] |                  | 72   |

#### Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateCreditor](#)) will be ignored by the Receiver.

## 4.15.19 InstructionForCreditorAgent

*XML Tag:* InstrForCdtrAgt

*Presence:* [0..\*]

*Definition:* Further information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor agent.

The **InstrForCdtrAgt** block contains the following elements (see datatype "[InstructionForCreditorAgent1](#)" on page 62 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item           | <XML Tag>  | Or | Mult.  | Usage Guidelines | Page |
|-------|------------------------|------------|----|--------|------------------|------|
| 2.83  | Code                   | <Cd>       |    | [0..1] |                  | 62   |
| 2.84  | InstructionInformation | <InstrInf> |    | [0..1] | <b>M</b> ⚠️      | 62   |

#### Usage Guideline details

- on [pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/InstructionForCreditorAgent](#)  
This element has change repeatability, the maximum occurrence has been changed to : 5
- on [pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/InstructionForCreditorAgent](#)  
Comment:

Instruction for Creditor Agent is used to provide instructions to the beneficiary bank both in a coded form (Tag 23E in SWIFT) and in free text form (Tag 72 in SWIFT).

## 4.15.20 InstructionForDebtorAgent

*XML Tag:* InstrForDbtrAgt

*Presence:* [0..1]

*Definition:* Further information related to the processing of the payment instruction, that may need to be acted upon by the debtor agent, depending on agreement between debtor and the debtor agent.

*Datatype:* "Max140Text" on page 169

### Usage Guideline details

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Instruction-ForDebtorAgent

#### – HSBC\_Instruction\_for\_Debtor\_Agent:

You may provide Instruction for Debtor Agent with the codeword /REC/. You may provide 30 characters of text (after the codeword) for the first line and 33 characters of text for each subsequent line totalling a maximum of 140 characters (including the codeword).

If you choose not to provide the codeword you may provide 30 characters of text (after the codeword) for the first line and 33 characters of text for each subsequent line totalling a maximum of 140 characters (including the codeword).

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Instruction-ForDebtorAgent

#### – HSBC\_Tag\_72:

Instruction for Creditor Agent and Instruction for Debtor Agent are both used to populate Tag 72 on a SWIFT message.

A maximum of 5 lines of 35 characters may be provided to provide instruction to either the creditor bank or the debtor bank (or both). Check Instruction for Creditor Agent and Debtor Agent comments for further instructions on how to structure the text.

In some countries, there are a maximum of 4 lines available. Please check your country MIG.

If you are providing exchange rate contract information in <XchgRateInf><CtrctId> then the total number of lines will be reduced by one.

If you are providing a Purpose of Payment code in <RgltryRptg><RgltryDtls><Inf> then the total number of lines will be reduced by one.

If you are using the Authorisation Type of ILA and using Get Rate functionality, then the total number of lines will be reduced by one.

If you are providing both Instruction for Debtor Agent AND Instruction for Creditor Agent THEN the debtor agent instruction will take precedence.

## 4.15.21 Purpose

*XML Tag:* Purp

*Presence:* [0..1]

*Definition:* Underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

The **Purp** block contains the following elements (see datatype "[Purpose2Choice](#)" on page 107 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
| 2.87  | Code         | <Cd>      | {Or | [1..1] |                  | 108  |
| 2.88  | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 108  |

## 4.15.22 RegulatoryReporting

*XML Tag:* RgltryRptg

*Presence:* [0..10]

*Definition:* Information needed due to regulatory and statutory requirements.

The **RgltryRptg** block contains the following elements (see datatype "[RegulatoryReporting3](#)" on page 111 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item                  | <XML Tag>       | Or | Mult.  | Usage Guidelines | Page |
|--------|-------------------------------|-----------------|----|--------|------------------|------|
| 11.1.0 | DebitCreditReportingIndicator | <DbtCdtRptgInd> |    | [0..1] | 💡                | 112  |
| 11.1.1 | Authority                     | <Authrty>       |    | [0..1] | 💡                | 112  |
| 11.1.4 | Details                       | <Dtls>          |    | [0..*] |                  | 112  |

## 4.15.23 Tax

*XML Tag:* Tax

*Presence:* [0..1]

*Definition:* Set of elements used to provide details on the tax.

The **Tax** block contains the following elements (see datatype "[TaxInformation3](#)" on page 126 for details)

🚫 Removed - ⚠ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index   | Message Item           | <XML Tag>         | Or | Mult.  | Usage Guidelines | Page |
|---------|------------------------|-------------------|----|--------|------------------|------|
| 13.1.0  | Creditor               | <Cdtr>            |    | [0..1] |                  | 126  |
| 13.1.4  | Debtor                 | <Dbtr>            |    | [0..1] |                  | 126  |
| 13.1.11 | AdministrationZone     | <AdmstnZn>        |    | [0..1] | ⚠                | 127  |
| 13.1.12 | ReferenceNumber        | <RefNb>           |    | [0..1] |                  | 127  |
| 13.1.13 | Method                 | <Mtd>             |    | [0..1] |                  | 127  |
| 13.1.14 | TotalTaxableBaseAmount | <TtlTaxblBaseAmt> |    | [0..1] | ⚠                | 127  |
| 13.1.15 | TotalTaxAmount         | <TtlTaxAmt>       |    | [0..1] | ⚠                | 128  |
| 13.1.16 | Date                   | <Dt>              |    | [0..1] | ⚠                | 128  |
| 13.1.17 | SequenceNumber         | <SeqNb>           |    | [0..1] |                  | 128  |
| 13.1.18 | Record                 | <Rcrd>            |    | [0..*] | R[0..10]         | 128  |

## 4.15.24 RelatedRemittanceInformation

*XML Tag:* RltdRmtInf

*Presence:* [0..10]

*Definition:* Set of elements used to provide information related to the handling of the remittance information by any of the agents in the transaction processing chain.

The **RltdRmtInf** block contains the following elements (see datatype "[RemittanceLocation2](#)" on page 116 for details)

🚫 Removed - ⚠ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                        | <XML Tag>           | Or | Mult.  | Usage Guidelines | Page |
|-------|-------------------------------------|---------------------|----|--------|------------------|------|
| 2.92  | RemittanceIdentification            | <RmtId>             |    | [0..1] | ⚠                | 116  |
| 2.93  | RemittanceLocationMethod            | <RmtLctnMtd>        |    | [0..1] |                  | 117  |
| 2.94  | RemittanceLocationElectronicAddress | <RmtLctnElctrcnAdr> |    | [0..1] |                  | 117  |
| 2.95  | RemittanceLocationPostalAddress     | <RmtLctnPstlAdr>    |    | [0..1] |                  | 117  |

### Usage Guideline details

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RelatedRemittanceInformation

**Comment:**

Refer to Advising Product Appendix for further details

## 4.15.25 RemittanceInformation

*XML Tag:* RmtInf

*Presence:* [0..1]

*Definition:* Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.

The **RmtInf** block contains the following elements (see datatype "RemittanceInformation5" on page 115 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|----|--------|------------------|------|
| 2.99  | Unstructured | <Ustrd>   |    | [0..*] | ⚠️               | 115  |
| 2.100 | Structured   | <Strd>    |    | [0..*] |                  | 116  |

## 4.16 CreditorReferenceInformation2

*Definition:* Reference information provided by the creditor to allow the identification of the underlying documents.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|----|--------|------------------|------|
| 2.121 | Type         | <Tp>      |    | [0..1] |                  | 42   |
| 2.126 | Reference    | <Ref>     |    | [0..1] | 💡                | 42   |

**Used in element(s)**

"CreditorReferenceInformation" on page 122

### 4.16.1 Type

*XML Tag:* Tp

*Presence:* [0..1]

*Definition:* Specifies the type of creditor reference.

The **Tp** block contains the following elements (see datatype "CreditorReferenceType2" on page 44 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item      | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|-------|-------------------|-------------|----|--------|------------------|------|
| 2.122 | CodeOrProprietary | <CdOrPrtry> |    | [1..1] |                  | 44   |
| 2.125 | Issuer            | <Issr>      |    | [0..1] | 💡                | 44   |

### 4.16.2 Reference

*XML Tag:* Ref

*Presence:* [0..1]

*Definition:* Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction.

*Usage:* If available, the initiating party should provide this reference in the structured remittance information, to enable reconciliation by the creditor upon receipt of the amount of money.

If the business context requires the use of a creditor reference or a payment remit identification, and only one identifier can be passed through the end-to-end chain, the creditor's reference or payment remittance identification should be quoted in the end-to-end transaction identification.

*Datatype:* "Max35Text" on page 171

#### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/CreditorReferenceInformation/Reference) will be ignored by the Receiver.

## 4.17 CreditorReferenceType1Choice

*Definition:* Specifies the type of document referred by the creditor.

🚫 Removed - 💡 Ignored - ⚠️ Details below - 📌 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
| 2.123 | Code         | <Cd>      | {Or | [1..1] |                  | 43   |
| 2.124 | Proprietary  | <Prtry>   | Or} | [1..1] | 💡                | 43   |

#### Used in element(s)

"CodeOrProprietary" on page 44

### 4.17.1 Code

*XML Tag:* Cd

*Presence:* [1..1]

*Definition:* Type of creditor reference, in a coded form.

*Datatype:* "DocumentType3Code" on page 155

### 4.17.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Creditor reference type, in a proprietary form.

*Datatype:* "Max35Text" on page 171

## Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/CreditorReferenceInformation/Type/CodeOrProprietary/Proprietary) will be ignored by the Receiver.

## 4.18 CreditorReferenceType2

*Definition:* Specifies the type of creditor reference.

Removed - Ignored - Details below - Mandatory - R[x..x] Repeatability[details]

| Index | Message Item      | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|-------|-------------------|-------------|----|--------|------------------|------|
| 2.122 | CodeOrProprietary | <CdOrPrtry> |    | [1..1] |                  | 44   |
| 2.125 | Issuer            | <Issr>      |    | [0..1] | Ignored          | 44   |

Used in element(s)

"Type" on page 42

### 4.18.1 CodeOrProprietary

*XML Tag:* CdOrPrtry

*Presence:* [1..1]

*Definition:* Coded or proprietary format creditor reference type.

The **CdOrPrtry** block contains the following elements (see datatype "[CreditorReferenceType1Choice](#)" on page 43 for details)

Removed - Ignored - Details below - Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
| 2.123 | Code         | <Cd>      | {Or | [1..1] |                  | 43   |
| 2.124 | Proprietary  | <Prtry>   | Or} | [1..1] | Ignored          | 43   |

### 4.18.2 Issuer

*XML Tag:* Issr

*Presence:* [0..1]

*Definition:* Entity that assigns the credit reference type.

*Datatype:* "[Max35Text](#)" on page 171

## Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/CreditorReferenceInformation/Type/Issuer](#)) will be ignored by the Receiver.

## 4.19 DateAndPlaceOfBirth

*Definition:* Date and place of birth of a person.

🚫 Removed - ♦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item    | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|--------|-----------------|---------------|----|--------|------------------|------|
| 9.1.23 | BirthDate       | <BirthDt>     |    | [1..1] |                  | 45   |
| 9.1.24 | ProvinceOfBirth | <PrvcOfBirth> |    | [0..1] |                  | 45   |
| 9.1.25 | CityOfBirth     | <CityOfBirth> |    | [1..1] |                  | 45   |
| 9.1.26 | CountryOfBirth  | <CtryOfBirth> |    | [1..1] |                  | 45   |

### Used in element(s)

["DateAndPlaceOfBirth" on page 94](#)

### 4.19.1 BirthDate

*XML Tag:* BirthDt

*Presence:* [1..1]

*Definition:* Date on which a person is born.

*Datatype:* ["ISODate" on page 166](#)

### 4.19.2 ProvinceOfBirth

*XML Tag:* PrvcOfBirth

*Presence:* [0..1]

*Definition:* Province where a person was born.

*Datatype:* ["Max35Text" on page 171](#)

### 4.19.3 CityOfBirth

*XML Tag:* CityOfBirth

*Presence:* [1..1]

*Definition:* City where a person was born.

*Datatype:* ["Max35Text" on page 171](#)

### 4.19.4 CountryOfBirth

*XML Tag:* CtryOfBirth

*Presence:* [1..1]

*Definition:* Country where a person was born.

*Datatype:* "CountryCode" on page 154

## 4.20 DatePeriodDetails

*Definition:* Range of time defined by a start date and an end date.

🚫 Removed - 💡 Ignored - ⚠️ Details below - 📌 Mandatory - R[x..x] Repeatability[details]

| Index                | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|----------------------|--------------|-----------|----|--------|------------------|------|
| 13.1.29 ,<br>13.1.40 | FromDate     | <FrDt>    |    | [1..1] |                  | 46   |
| 13.1.30 ,<br>13.1.41 | ToDate       | <ToDt>    |    | [1..1] |                  | 46   |

**Used in element(s)**

"FromToDate" on page 132

### 4.20.1 FromDate

*XML Tag:* FrDt

*Presence:* [1..1]

*Definition:* Start date of the range.

*Datatype:* "ISODate" on page 166

### 4.20.2 ToDate

*XML Tag:* ToDt

*Presence:* [1..1]

*Definition:* End date of the range.

*Datatype:* "ISODate" on page 166

## 4.21 DocumentAdjustment1

*Definition:* Set of elements used to provide information on the amount and reason of the document adjustment.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item          | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|-------|-----------------------|-------------|----|--------|------------------|------|
| 2.115 | Amount                | <Amt>       |    | [1..1] |                  | 47   |
| 2.116 | CreditDebitIndicator  | <CdtDbtInd> |    | [0..1] |                  | 47   |
| 2.117 | Reason                | <Rsn>       |    | [0..1] |                  | 47   |
| 2.118 | AdditionalInformation | <AddtlInf>  |    | [0..1] |                  | 47   |

#### Used in element(s)

"AdjustmentAmountAndReason" on page 114

## 4.21.1 Amount

*XML Tag:* Amt

*Presence:* [1..1]

*Definition:* Amount of money of the document adjustment.

*Datatype:* "ActiveOrHistoricCurrencyAndAmount" on page 138

## 4.21.2 CreditDebitIndicator

*XML Tag:* CdtDbtInd

*Presence:* [0..1]

*Definition:* Specifies whether the adjustment must be subtracted or added to the total amount.

*Datatype:* "CreditDebitCode" on page 155

## 4.21.3 Reason

*XML Tag:* Rsn

*Presence:* [0..1]

*Definition:* Specifies the reason for the adjustment.

*Datatype:* "Max4Text" on page 171

## 4.21.4 AdditionalInformation

*XML Tag:* AddtlInf

*Presence:* [0..1]

*Definition:* Provides further details on the document adjustment.

*Datatype:* "Max140Text" on page 169

## 4.22 EquivalentAmount2

*Definition:* Amount of money to be moved between the debtor and creditor, expressed in the currency of the debtor's account, and the currency in which the amount is to be moved.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item       | <XML Tag>  | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------------|------------|----|--------|------------------|------|
| 2.45  | Amount             | <Amt>      |    | [1..1] |                  | 48   |
| 2.46  | CurrencyOfTransfer | <CcyOfTrf> |    | [1..1] |                  | 48   |

Used in element(s)

"EquivalentAmount" on page 10

## 4.22.1 Amount

XML Tag: Amt

Presence: [1..1]

*Definition:* Amount of money to be moved between debtor and creditor, before deduction of charges, expressed in the currency of the debtor's account, and to be moved in a different currency.

Usage: The first agent will convert the equivalent amount into the amount to be moved.

*Datatype:* "ActiveOrHistoricCurrencyAndAmount" on page 138

## 4.22.2 CurrencyOfTransfer

XML Tag: CcyOfTrf

Presence: [1..1]

*Definition:* Specifies the currency of the to be transferred amount, which is different from the currency of the debtor's account.

*Datatype:* "ActiveOrHistoricCurrencyCode" on page 138

## 4.23 ExchangeRateInformation1\_\_1

*Definition:* Further detailed information on the exchange rate that has been used in the payment transaction.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item           | <XML Tag>  | Or | Mult.  | Usage Guidelines | Page |
|-------|------------------------|------------|----|--------|------------------|------|
| 2.48  | ExchangeRate           | <XchgRate> |    | [0..1] | ⚠️               | 48   |
| 2.49  | RateType               | <RateTp>   |    | [0..1] | 🚫                | 49   |
| 2.50  | ContractIdentification | <CtrctId>  |    | [0..1] | ⚠️               | 49   |

Used in element(s)

"ExchangeRateInformation" on page 30

## 4.23.1 ExchangeRate

XML Tag: XchgRate

*Presence:* [0..1]

*Definition:* The factor used for conversion of an amount from one currency to another. This reflects the price at which one currency was bought with another currency.

*Datatype:* ["Max12Text" on page 169](#)

#### Usage Guideline details

- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/ExchangeRateInformation/ExchangeRate**
  - **HSBC\_ExchangeRate:**

Agreed exchange rate if EquivalentAmount is used

## 4.23.2 RateType

*XML Tag:* RateTp

*Presence:* [0..1]

*Definition:* Specifies the type used to complete the currency exchange.

*Datatype:* ["ExchangeRateType1Code" on page 158](#)

#### Usage Guideline details

- **This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/ExchangeRateInformation/RateType) is removed.**

## 4.23.3 ContractIdentification

*XML Tag:* CtrctId

*Presence:* [0..1]

*Definition:* Unique and unambiguous reference to the foreign exchange contract agreed between the initiating party/creditor and the debtor agent.

*Datatype:* ["Max28Text" on page 170](#)

#### Usage Guideline details

- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/ExchangeRateInformation/ContractIdentification**
  - **HSBC\_Contractidentification:**

Deal reference for an FX contract. Use only if EquivalentAmount is used

## 4.24 FinancialIdentificationSchemeName1Choice

*Definition:* Sets of elements to identify a name of the organisation identification scheme.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item | <XML Tag> | Or   | Mult.  | Usage Guidelines | Page |
|--------|--------------|-----------|------|--------|------------------|------|
| 6.1.22 | Code         | <Cd>      | {Or} | [1..1] |                  | 50   |
| 6.1.23 | Proprietary  | <Prtry>   | Or}  | [1..1] |                  | 50   |

Used in element(s)

"SchemeName" on page 55

## 4.24.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalFinancialInstitutionIdentification1Code" on page 161

## 4.24.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 171

## 4.25 FinancialInstitutionIdentification7

Definition: Set of elements used to identify a financial institution.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item                       | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|--------|------------------------------------|---------------|----|--------|------------------|------|
| 6.1.1  | BIC                                | <BIC>         |    | [0..1] |                  | 50   |
| 6.1.2  | ClearingSystemMemberIdentification | <ClrSysMmbld> |    | [0..1] |                  | 51   |
| 6.1.7  | Name                               | <Nm>          |    | [0..1] |                  | 51   |
| 6.1.8  | PostalAddress                      | <PstlAdr>     |    | [0..1] | <b>M</b>         | 51   |
| 6.1.19 | Other                              | <Othr>        |    | [0..1] | 💡 🚫              | 53   |

Used in element(s)

"FinancialInstitutionIdentification" on page 11

## 4.25.1 BIC

XML Tag: BIC

Presence: [0..1]

*Definition:* Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

*Datatype:* "BICIdentifier" on page 142

## 4.25.2 ClearingSystemMemberIdentification

*XML Tag:* ClrSysMmbld

*Presence:* [0..1]

*Definition:* Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2" on page 23 for details)

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                 | <XML Tag>  | Or | Mult.  | Usage Guidelines                                                                                                                                                                                                                                            | Page |
|-------|------------------------------|------------|----|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| 6.1.3 | ClearingSystemIdentification | <ClrSysId> |    | [0..1] |    | 23   |
| 6.1.6 | MemberIdentification         | <Mmbld>    |    | [1..1] |                                                                                                                                                                                                                                                             | 24   |

## 4.25.3 Name

*XML Tag:* Nm

*Presence:* [0..1]

*Definition:* Name by which an agent is known and which is usually used to identify that agent.

*Datatype:* "Max140Text" on page 169

## 4.25.4 PostalAddress

*XML Tag:* PstlAdr

*Presence:* [0..1]

*Definition:* Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress6" on page 96 for details)

🚫 Removed - ⚡ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index                                      | Message Item       | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|--------------------------------------------|--------------------|---------------|----|--------|------------------|------|
| 9.1.2 ,<br>6.1.9 ,<br>6.1.29 ,<br>10.1.0   | AddressType        | <AdrTp>       |    | [0..1] | ⚡                | 96   |
| 9.1.3 ,<br>6.1.10 ,<br>6.1.30 ,<br>10.1.1  | Department         | <Dept>        |    | [0..1] |                  | 97   |
| 9.1.4 ,<br>6.1.11 ,<br>6.1.31 ,<br>10.1.2  | SubDepartment      | <SubDept>     |    | [0..1] |                  | 97   |
| 9.1.5 ,<br>6.1.12 ,<br>6.1.32 ,<br>10.1.3  | StreetName         | <StrtNm>      |    | [0..1] |                  | 97   |
| 9.1.6 ,<br>6.1.13 ,<br>6.1.33 ,<br>10.1.4  | BuildingNumber     | <BldgNb>      |    | [0..1] |                  | 97   |
| 9.1.7 ,<br>6.1.14 ,<br>6.1.34 ,<br>10.1.5  | PostCode           | <PstCd>       |    | [0..1] |                  | 98   |
| 9.1.8 ,<br>6.1.15 ,<br>6.1.35 ,<br>10.1.6  | TownName           | <TwnNm>       |    | [0..1] |                  | 98   |
| 9.1.9 ,<br>6.1.16 ,<br>6.1.36 ,<br>10.1.7  | CountrySubDivision | <CtrySubDvsn> |    | [0..1] |                  | 98   |
| 9.1.10 ,<br>6.1.17 ,<br>6.1.37 ,<br>10.1.8 | Country            | <Ctry>        |    | [0..1] | <b>M</b>         | 98   |
| 9.1.11 ,<br>6.1.18 ,<br>6.1.38 ,<br>10.1.9 | AddressLine        | <AdrLine>     |    | [0..7] |                  | 99   |

#### Usage Guideline details

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress

*This element is now mandatory, the minimum occurrence has been changed to : 1*

- on **pain.001.001.03/PaymentInformation/DebtorAgent/FinancialInstitutionIdentification/Postal-Address**

*This element is now mandatory, the minimum occurrence has been changed to : 1*

## 4.25.5 Other

XML Tag: Othr

Presence: [0..1]

**Definition:** Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericFinancialIdentification1](#)" on page 55 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|----------------|-----------|----|--------|------------------|------|
| 6.1.20 | Identification | <Id>      |    | [1..1] |                  | 55   |
| 6.1.21 | SchemeName     | <SchmeNm> |    | [0..1] |                  | 55   |
| 6.1.24 | Issuer         | <Issr>    |    | [0..1] |                  | 56   |

### Usage Guideline details

- This element(**pain.001.001.03/PaymentInformation/DebtorAgent/FinancialInstitutionIdentification/Other**) is removed.
- This element(**pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/Other**) will be ignored by the Receiver.
- This element(**pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/Other**) will be ignored by the Receiver.

## 4.26 GenericAccountIdentification1

**Definition:** Information related to a generic account identification.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
| 1.1.3 | Identification | <Id>      |    | [1..1] | 💡 ⚠              | 54   |
| 1.1.4 | SchemeName     | <SchmeNm> |    | [0..1] | 💡                | 54   |
| 1.1.7 | Issuer         | <Issr>    |    | [0..1] | 💡                | 54   |

**Used in element(s)**

"Other" on page 8

## 4.26.1 Identification

*XML Tag:* Id

*Presence:* [1..1]

*Definition:* Identification assigned by an institution.

*Datatype:* "Max34Text" on page 170

### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgentAccount/Identification/Other/Identification) will be ignored by the Receiver.
- on pain.001.001.03/PaymentInformation/DebtorAccount/Identification/Other/Identification
  - HSBC\_Identification:  
Debit account should be provided as domestic account number.

## 4.26.2 SchemeName

*XML Tag:* SchmeNm

*Presence:* [0..1]

*Definition:* Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "AccountSchemeName1Choice" on page 9 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
| 1.1.5 | Code         | <Cd>      | {Or | [1..1] |                  | 9    |
| 1.1.6 | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 9    |

### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Identification/Other/SchemeName) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgentAccount/Identification/Other/SchemeName) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/DebtorAccount/Identification/Other/SchemeName) will be ignored by the Receiver.

## 4.26.3 Issuer

*XML Tag:* Issr

*Presence:* [0..1]

*Definition:* Entity that assigns the identification.

*Datatype:* "Max35Text" on page 171

#### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/DebtorAccount/Identification/Other/Issuer) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Identification/Other/Issuer) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgentAccount/Identification/Other/Issuer) will be ignored by the Receiver.

## 4.27 GenericFinancialIdentification1

*Definition:* Information related to an identification of a financial institution.

🚫 Removed - 💡 Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|----------------|-----------|----|--------|------------------|------|
| 6.1.20 | Identification | <Id>      |    | [1..1] |                  | 55   |
| 6.1.21 | SchemeName     | <SchmeNm> |    | [0..1] |                  | 55   |
| 6.1.24 | Issuer         | <Issr>    |    | [0..1] |                  | 56   |

#### Used in element(s)

"Other" on page 53

### 4.27.1 Identification

*XML Tag:* Id

*Presence:* [1..1]

*Definition:* Unique and unambiguous identification of a person.

*Datatype:* "Max35Text" on page 171

### 4.27.2 SchemeName

*XML Tag:* SchmeNm

*Presence:* [0..1]

*Definition:* Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[FinancialIdentificationScheme-Name1Choice](#)" on page 49 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|--------|--------------|-----------|-----|--------|------------------|------|
| 6.1.22 | Code         | <Cd>      | {Or | [1..1] |                  | 50   |
| 6.1.23 | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 50   |

## 4.27.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "[Max35Text](#)" on page 171

## 4.28 GenericOrganisationIdentification1

Definition: Information related to an identification of an organisation.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|----------------|-----------|----|--------|------------------|------|
| 9.1.16 | Identification | <Id>      |    | [1..1] | ⚠️               | 56   |
| 9.1.17 | SchemeName     | <SchmeNm> |    | [0..1] | 💡                | 57   |
| 9.1.20 | Issuer         | <Issr>    |    | [0..1] | 💡                | 57   |

Used in element(s)

"Other" on page 67

### 4.28.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "[Max35Text](#)" on page 171

Usage Guideline details

- on [pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/Identification/OrganisationIdentification/Other/Identification](#)

**Comment:**

For payments on behalf of other than the debit account owner and where the source of funds is another account, that account number should be provided here. Where no account exists, a unique identifier for the originator should be provided.

- on pain.001.001.03/PaymentInformation/UltimateDebtor/Identification/OrganisationIdentification/Other/Identification

**Comment:**

For payments on behalf of other than the debit account owner and where the source of funds is another account, that account number should be provided here. Where no account exists, a unique identifier for the originator should be provided.

## 4.28.2 SchemeName

*XML Tag:* SchmeNm

*Presence:* [0..1]

*Definition:* Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[OrganisationIdentificationSchemeName1Choice](#)" on page 68 for details)

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|--------|--------------|-----------|-----|--------|------------------|------|
| 9.1.18 | Code         | <Cd>      | {Or | [1..1] |                  | 68   |
| 9.1.19 | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 68   |

### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/Identification/OrganisationIdentification/Other/SchemeName) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/Debtor/Identification/OrganisationIdentification/Other/SchemeName) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/UltimateDebtor/Identification/OrganisationIdentification/Other/SchemeName) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/Identification/OrganisationIdentification/Other/SchemeName) will be ignored by the Receiver.
- This element(pain.001.001.03/GroupHeader/InitiatingParty/Identification/OrganisationIdentification/Other/SchemeName) will be ignored by the Receiver.

## 4.28.3 Issuer

*XML Tag:* Issr

*Presence:* [0..1]

*Definition:* Entity that assigns the identification.

*Datatype:* "[Max35Text](#)" on page 171

## Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/Identification/OrganisationIdentification/Other/Issuer](#)) will be ignored by the Receiver.
- This element([pain.001.001.03/PaymentInformation/UltimateDebtor/Identification/OrganisationIdentification/Other/Issuer](#)) will be ignored by the Receiver.
- This element([pain.001.001.03/PaymentInformation/Debtor/Identification/OrganisationIdentification/Other/Issuer](#)) will be ignored by the Receiver.
- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/Identification/OrganisationIdentification/Other/Issuer](#)) will be ignored by the Receiver.
- This element([pain.001.001.03/GroupHeader/InitiatingParty/Identification/OrganisationIdentification/Other/Issuer](#)) will be ignored by the Receiver.

## 4.29 GenericPersonIdentification1

*Definition:* Information related to an identification of a person.

Removed - Ignored - Details below - Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|----------------|-----------|----|--------|------------------|------|
| 9.1.28 | Identification | <Id>      |    | [1..1] |                  | 58   |
| 9.1.29 | SchemeName     | <SchmeNm> |    | [0..1] |                  | 58   |
| 9.1.32 | Issuer         | <Issr>    |    | [0..1] |                  | 59   |

Used in element(s)

["Other" on page 95](#)

### 4.29.1 Identification

*XML Tag:* Id

*Presence:* [1..1]

*Definition:* Unique and unambiguous identification of a person.

*Datatype:* ["Max35Text" on page 171](#)

### 4.29.2 SchemeName

*XML Tag:* SchmeNm

*Presence:* [0..1]

*Definition:* Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[PersonIdentificationScheme-Name1Choice](#)" on page 95 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|--------|--------------|-----------|-----|--------|------------------|------|
| 9.1.30 | Code         | <Cd>      | {Or | [1..1] |                  | 95   |
| 9.1.31 | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 95   |

## 4.29.3 Issuer

*XML Tag:* Issr

*Presence:* [0..1]

*Definition:* Entity that assigns the identification.

*Datatype:* "[Max35Text](#)" on page 171

## 4.30 GroupHeader32

*Definition:* Set of characteristics shared by all individual transactions included in the message.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item          | <XML Tag>  | Or | Mult.  | Usage Guidelines | Page |
|-------|-----------------------|------------|----|--------|------------------|------|
| 1.1   | MessageIdentification | <MsgId>    |    | [1..1] | ⚠️               | 59   |
| 1.2   | CreationDateTime      | <CreDtTm>  |    | [1..1] |                  | 60   |
| 1.3   | Authorisation         | <Authstn>  |    | [0..2] | R[0..1]          | 60   |
| 1.6   | NumberOfTransactions  | <NbOfTx>   |    | [1..1] | ⚠️               | 60   |
| 1.7   | ControlSum            | <CtrlSum>  |    | [0..1] | ⚠️               | 61   |
| 1.8   | InitiatingParty       | <InitgPty> |    | [1..1] |                  | 61   |
| 1.9   | ForwardingAgent       | <FwdgAgt>  |    | [0..1] | 💡                | 62   |

**Used in element(s)**

"[GroupHeader](#)" on page 6

### 4.30.1 MessageIdentification

*XML Tag:* MsgId

*Presence:* [1..1]

*Definition:* Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message.

*Usage:* The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period.

Datatype: ["Max35Text" on page 171](#)

#### Usage Guideline details

- on [pain.001.001.03/GroupHeader/MessageIdentification](#)

**Comment:**

Unique message reference used with status messages returned for the processing of this file. HSBC recommends this is unique for a 12 monthly rolling period.

## 4.30.2 CreationDateTime

XML Tag: CreDtTm

Presence: [1..1]

Definition: Date and time at which the message was created.

Datatype: ["ISODatetime" on page 166](#)

## 4.30.3 Authorisation

XML Tag: Authstn

Presence: [0..2]

Definition: User identification or any user key to be used to check whether the initiating party is allowed to initiate transactions from the account specified in the message.

Usage: The content is not of a technical nature, but reflects the organisational structure at the initiating side.

The authorisation element can typically be used in relay scenarios, payment initiations, payment returns or payment reversals that are initiated on behalf of a party different from the initiating party.

The **Authstn** block contains the following elements (see datatype ["Authorisation1Choice" on page 10](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
| 1.4   | Code         | <Cd>      | {Or | [1..1] |                  | 10   |
| 1.5   | Proprietary  | <Prtry>   | Or} | [1..1] | 💡                | 11   |

#### Usage Guideline details

- on [pain.001.001.03/GroupHeader/Authorisation](#)

*This element has change repeatability, the maximum occurrence has been changed to : 1*

## 4.30.4 NumberOfTransactions

XML Tag: NbOfTxS

Presence: [1..1]

*Definition:* Number of individual transactions contained in the message.

*Datatype:* ["Max15NumericText" on page 169](#)

#### Usage Guideline details

- on [pain.001.001.03/GroupHeader/NumberOfTransactions](#)

**Comment:**

This will be verified against the number of occurrences of <CdtTrfTxInf> in the message .

## 4.30.5 ControlSum

*XML Tag:* CtrlSum

*Presence:* [0..1]

*Definition:* Total of all individual amounts included in the message, irrespective of currencies.

*Datatype:* ["DecimalNumber" on page 155](#)

#### Usage Guideline details

- on [pain.001.001.03/GroupHeader/ControlSum](#)

**Comment:**

This is the hash total of all payment amounts in the entire message regardless of currency in Instructed Amount and Equivalent amount. If included amount must have 2 decimal places.

## 4.30.6 InitiatingParty

*XML Tag:* InitgPty

*Presence:* [1..1]

*Definition:* Party that initiates the payment.

Usage: This can either be the debtor or the party that initiates the credit transfer on behalf of the debtor.

The **InitgPty** block contains the following elements (see datatype ["PartyIdentification32" on page 70](#) for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item       | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|--------|--------------------|-------------|----|--------|------------------|------|
| 9.1.0  | Name               | <Nm>        |    | [0..1] |                  | 70   |
| 9.1.1  | PostalAddress      | <PstlAdr>   |    | [0..1] |                  | 70   |
| 9.1.12 | Identification     | <Id>        |    | [0..1] | ⚠                | 71   |
| 9.1.33 | CountryOfResidence | <CtryOfRes> |    | [0..1] | 💡                | 72   |
| 9.1.34 | ContactDetails     | <CtctDtls>  |    | [0..1] | 💡                | 72   |

## 4.30.7 ForwardingAgent

XML Tag: FwdgAgt

Presence: [0..1]

*Definition:* Financial institution that receives the instruction from the initiating party and forwards it to the next agent in the payment chain for execution.

The **FwdgAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification4](#)" on page 11 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item                       | <XML Tag>    | Or | Mult.  | Usage Guidelines | Page |
|--------|------------------------------------|--------------|----|--------|------------------|------|
| 6.1.0  | FinancialInstitutionIdentification | <FinInstnId> |    | [1..1] |                  | 11   |
| 6.1.25 | BranchIdentification               | <BrnchId>    |    | [0..1] |                  | 12   |

### Usage Guideline details

- This element(pain.001.001.03/GroupHeader/ForwardingAgent) will be ignored by the Receiver.

## 4.31 InstructionForCreditorAgent1

*Definition:* Further information related to the processing of the payment instruction that may need to be acted upon by the creditor's agent. The instruction may relate to a level of service, or may be an instruction that has to be executed by the creditor's agent, or may be information required by the creditor's agent.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item           | <XML Tag>  | Or | Mult.  | Usage Guidelines | Page |
|-------|------------------------|------------|----|--------|------------------|------|
| 2.83  | Code                   | <Cd>       |    | [0..1] |                  | 62   |
| 2.84  | InstructionInformation | <InstrInf> |    | [0..1] | <b>M</b> ⚠️      | 62   |

### Used in element(s)

"[InstructionForCreditorAgent](#)" on page 38

### 4.31.1 Code

XML Tag: Cd

Presence: [0..1]

*Definition:* Coded information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor's agent.

*Datatype:* "[Instruction3Code](#)" on page 167

### 4.31.2 InstructionInformation

XML Tag: InstrInf

Presence: [0..1]

**Definition:** Further information complementing the coded instruction or instruction to the creditor's agent that is bilaterally agreed or specific to a user community.

**Datatype:** "Max140Text" on page 169

#### Usage Guideline details

- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/InstructionFor-CreditorAgent/InstructionInformation**

*This element is now mandatory, the minimum occurrence has been changed to : 1*

- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/InstructionFor-CreditorAgent/InstructionInformation**

#### – HSBC\_Instructed Information:

If using Instruction Information in free text form (i.e. Tag 72) then each instance of Instruction Information must start with a valid codeword followed by the text:

/ACC/ - information for the account with institution (beneficiary bank)

/INS/ - details of the instructing institution

/INT/ - information for the intermediary bank

You may provide 30 characters of text (after the codeword) for the first line and 33 characters of text for each subsequent line totalling a maximum of 140 characters (including the codeword).

If using instruction information in coded form (i.e. Tag 23E) then Instruction Information must be no greater than 30 characters.

- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/InstructionFor-CreditorAgent/InstructionInformation**

#### – HSBC\_Tag\_23E:

- Up to four instances of Instruction for Creditor Agent can be used to provide coded instructions. The code must be provided in <InstrForCdtrAgt><Code> and accompanying text instructions in <InstrForCdtrAgt><InstrInf>

- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/InstructionFor-CreditorAgent/InstructionInformation**

#### – HSBC\_Tag\_72:

Instruction for Creditor Agent and Instruction for Debtor Agent are both used to populate Tag 72 on a SWIFT message.

A maximum of 5 lines of 35 characters may be provided to provide instruction to either the creditor bank or the debtor bank (or both). Check Instruction for Creditor Agent and Debtor Agent comments for further instructions on how to structure the text.

In some countries, there are a maximum of 4 lines available. Please check your country MIG.

If you are providing exchange rate contract information in <XchgRateInf><Ctrc-tId> then the total number of lines will be reduced by one.

If you are providing a Purpose of Payment code in <RgltryRptg><RgltryDtls><Inf> then the total number of lines will be reduced by one.

If you are using the Authorisation Type of ILA and using Get Rate functionality, then the total number of lines will be reduced by one.

If you are providing both Instruction for Debtor Agent AND Instruction for Creditor Agent THEN the debtor agent instruction will take precedence.

## 4.32 LocalInstrument2Choice

*Definition:* Set of elements that further identifies the type of local instruments being requested by the initiating party.

🚫 Removed - 💡 Ignored - ⚠️ Details below - 📌 Mandatory - R[x..x] Repeatability[details]

| Index          | Message Item | <XML Tag> | Or   | Mult.  | Usage Guidelines | Page |
|----------------|--------------|-----------|------|--------|------------------|------|
| 2.12 ,<br>2.37 | Code         | <Cd>      | {Or} | [1..1] |                  | 64   |
| 2.13 ,<br>2.38 | Proprietary  | <Prtry>   | Or}  | [1..1] |                  | 64   |

Used in element(s)

"LocalInstrument" on page 93

### 4.32.1 Code

*XML Tag:* Cd

*Presence:* [1..1]

*Definition:* Specifies the local instrument, as published in an external local instrument code list.

*Datatype:* ["ExternalLocalInstrument1Code" on page 162](#)

### 4.32.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Specifies the local instrument, as a proprietary code.

*Datatype:* ["Max35Text" on page 171](#)

## 4.33 NameAndAddress10

*Definition:* Information that locates and identifies a party.

 Removed - 
  Ignored - 
  Details below - 
  Mandatory - 
 R[x..x] Repeatability[details]

| Index                    | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------------------------|--------------|-----------|----|--------|------------------|------|
| 2.56 ,<br>2.62 ,<br>2.96 | Name         | <Nm>      |    | [1..1] |                  | 65   |
| 2.57 ,<br>2.63 ,<br>2.97 | Address      | <Adr>     |    | [1..1] |                  | 65   |

#### Used in element(s)

["ChequeFrom" on page 20](#), 
 ["DeliverTo" on page 20](#), 
 ["RemittanceLocationPostalAddress" on page 117](#)

### 4.33.1 Name

*XML Tag:* Nm

*Presence:* [1..1]

*Definition:* Name by which a party is known and is usually used to identify that party.

*Datatype:* ["Max140Text" on page 169](#)

### 4.33.2 Address

*XML Tag:* Adr

*Presence:* [1..1]

*Definition:* Postal address of a party.

The **Adr** block contains the following elements (see datatype "PostalAddress6" on page 96 for details)

🚫 Removed - ⬜ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index                                      | Message Item       | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|--------------------------------------------|--------------------|---------------|----|--------|------------------|------|
| 9.1.2 ,<br>6.1.9 ,<br>6.1.29 ,<br>10.1.0   | AddressType        | <AdrTp>       |    | [0..1] | ⬜                | 96   |
| 9.1.3 ,<br>6.1.10 ,<br>6.1.30 ,<br>10.1.1  | Department         | <Dept>        |    | [0..1] |                  | 97   |
| 9.1.4 ,<br>6.1.11 ,<br>6.1.31 ,<br>10.1.2  | SubDepartment      | <SubDept>     |    | [0..1] |                  | 97   |
| 9.1.5 ,<br>6.1.12 ,<br>6.1.32 ,<br>10.1.3  | StreetName         | <StrtNm>      |    | [0..1] |                  | 97   |
| 9.1.6 ,<br>6.1.13 ,<br>6.1.33 ,<br>10.1.4  | BuildingNumber     | <BldgNb>      |    | [0..1] |                  | 97   |
| 9.1.7 ,<br>6.1.14 ,<br>6.1.34 ,<br>10.1.5  | PostCode           | <PstCd>       |    | [0..1] |                  | 98   |
| 9.1.8 ,<br>6.1.15 ,<br>6.1.35 ,<br>10.1.6  | TownName           | <TwnNm>       |    | [0..1] |                  | 98   |
| 9.1.9 ,<br>6.1.16 ,<br>6.1.36 ,<br>10.1.7  | CountrySubDivision | <CtrySubDvsn> |    | [0..1] |                  | 98   |
| 9.1.10 ,<br>6.1.17 ,<br>6.1.37 ,<br>10.1.8 | Country            | <Ctry>        |    | [0..1] |                  | 98   |
| 9.1.11 ,<br>6.1.18 ,<br>6.1.38 ,<br>10.1.9 | AddressLine        | <AdrLine>     |    | [0..7] |                  | 99   |

## 4.34 OrganisationIdentification4

*Definition:* Unique and unambiguous way to identify an organisation.

🚫 Removed - ✨ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item | <XML Tag>  | Or | Mult.  | Usage Guidelines                 | Page |
|--------|--------------|------------|----|--------|----------------------------------|------|
| 9.1.14 | BICOrBEI     | <BICOrBEI> |    | [0..1] | ✨                                | 67   |
| 9.1.15 | Other        | <Othr>     |    | [0..*] | <b>M</b> R[1..1] R[1..1] R[0..1] | 67   |

Used in element(s)

"OrganisationIdentification" on page 69

## 4.34.1 BICOrBEI

XML Tag: BICOrBEI

Presence: [0..1]

**Definition:** Code allocated to a financial institution or non financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

**Datatype:** "AnyBICIdentifier" on page 140

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/Identification/OrganisationIdentification/BICOrBEI) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/UltimateDebtor/Identification/OrganisationIdentification/BICOrBEI) will be ignored by the Receiver.

## 4.34.2 Other

XML Tag: Othr

Presence: [0..\*]

**Definition:** Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericOrganisationIdentification1" on page 56 for details)

🚫 Removed - ✨ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|----------------|-----------|----|--------|------------------|------|
| 9.1.16 | Identification | <Id>      |    | [1..1] | ⚠                | 56   |
| 9.1.17 | SchemeName     | <SchmeNm> |    | [0..1] | ✨                | 57   |
| 9.1.20 | Issuer         | <Issr>    |    | [0..1] | ✨                | 57   |

## Usage Guideline details

- **on pain.001.001.03/GroupHeader/InitiatingParty/Identification/OrganisationIdentification/Other**  
*This element has change repeatability, the maximum occurrence has been changed to : 1*
- **on pain.001.001.03/PaymentInformation/UltimateDebtor/Identification/OrganisationIdentification/Other**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*  
*This element has change repeatability, the maximum occurrence has been changed to : 1*
- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/Identification/OrganisationIdentification/Other**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*  
*This element has change repeatability, the maximum occurrence has been changed to : 1*

## 4.35 OrganisationIdentificationSchemeName1Choice

*Definition:* Sets of elements to identify a name of the organisation identification scheme.

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|--------|--------------|-----------|-----|--------|------------------|------|
| 9.1.18 | Code         | <Cd>      | {Or | [1..1] |                  | 68   |
| 9.1.19 | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 68   |

Used in element(s)

["SchemeName" on page 57](#)

### 4.35.1 Code

*XML Tag:* Cd

*Presence:* [1..1]

*Definition:* Name of the identification scheme, in a coded form as published in an external list.

*Datatype:* ["ExternalOrganisationIdentification1Code" on page 163](#)

### 4.35.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Name of the identification scheme, in a free text form.

*Datatype:* ["Max35Text" on page 171](#)

## 4.36 Party6Choice

*Definition:* Nature or use of the account.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item               | <XML Tag> | Or   | Mult.  | Usage Guidelines | Page |
|--------|----------------------------|-----------|------|--------|------------------|------|
| 9.1.13 | OrganisationIdentification | <OrgId>   | {Or} | [1..1] |                  | 69   |
| 9.1.21 | PrivateIdentification      | <PrvtId>  | Or}  | [1..1] | 💡                | 69   |

Used in element(s)

"Identification" on page 76, "Identification" on page 71

## 4.36.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "[OrganisationIdentification4](#)" on page 66 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item | <XML Tag>  | Or | Mult.  | Usage Guidelines                 | Page |
|--------|--------------|------------|----|--------|----------------------------------|------|
| 9.1.14 | BICOrBEI     | <BICOrBEI> |    | [0..1] | 💡                                | 67   |
| 9.1.15 | Other        | <Othr>     |    | [0..*] | <b>M</b> R[1..1] R[1..1] R[0..1] | 67   |

## 4.36.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "[PersonIdentification5](#)" on page 94 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item        | <XML Tag>         | Or | Mult.  | Usage Guidelines | Page |
|--------|---------------------|-------------------|----|--------|------------------|------|
| 9.1.22 | DateAndPlaceOfBirth | <DtAndPlcOfBirth> |    | [0..1] |                  | 94   |
| 9.1.27 | Other               | <Othr>            |    | [0..*] |                  | 95   |

### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/Identification/PrivateIdentification) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/Debtor/Identification/PrivateIdentification) will be ignored by the Receiver.

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/Identification/PrivateIdentification) will be ignored by the Receiver.
- This element(pain.001.001.03/GroupHeader/InitiatingParty/Identification/PrivateIdentification) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/UltimateDebtor/Identification/PrivateIdentification) will be ignored by the Receiver.

## 4.37 PartyIdentification32

*Definition:* Set of elements used to identify a person or an organisation.

🚫 Removed - 💡 Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item       | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|--------|--------------------|-------------|----|--------|------------------|------|
| 9.1.0  | Name               | <Nm>        |    | [0..1] |                  | 70   |
| 9.1.1  | PostalAddress      | <PstlAdr>   |    | [0..1] |                  | 70   |
| 9.1.12 | Identification     | <Id>        |    | [0..1] | ⚠                | 71   |
| 9.1.33 | CountryOfResidence | <CtryOfRes> |    | [0..1] | 💡                | 72   |
| 9.1.34 | ContactDetails     | <CtctDtls>  |    | [0..1] | 💡                | 72   |

**Used in element(s)**

"InitiatingParty" on page 61, "Invoicee" on page 123, "Invoicer" on page 122, "UltimateCreditor" on page 37

### 4.37.1 Name

*XML Tag:* Nm

*Presence:* [0..1]

*Definition:* Name by which a party is known and which is usually used to identify that party.

*Datatype:* "Max140Text" on page 169

### 4.37.2 PostalAddress

*XML Tag:* PstlAdr

*Presence:* [0..1]

*Definition:* Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "[PostalAddress6](#)" on page 96 for details)

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

| Index                                      | Message Item       | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|--------------------------------------------|--------------------|---------------|----|--------|------------------|------|
| 9.1.2 ,<br>6.1.9 ,<br>6.1.29 ,<br>10.1.0   | AddressType        | <AdrTp>       |    | [0..1] |                  | 96   |
| 9.1.3 ,<br>6.1.10 ,<br>6.1.30 ,<br>10.1.1  | Department         | <Dept>        |    | [0..1] |                  | 97   |
| 9.1.4 ,<br>6.1.11 ,<br>6.1.31 ,<br>10.1.2  | SubDepartment      | <SubDept>     |    | [0..1] |                  | 97   |
| 9.1.5 ,<br>6.1.12 ,<br>6.1.32 ,<br>10.1.3  | StreetName         | <StrtNm>      |    | [0..1] |                  | 97   |
| 9.1.6 ,<br>6.1.13 ,<br>6.1.33 ,<br>10.1.4  | BuildingNumber     | <BldgNb>      |    | [0..1] |                  | 97   |
| 9.1.7 ,<br>6.1.14 ,<br>6.1.34 ,<br>10.1.5  | PostCode           | <PstCd>       |    | [0..1] |                  | 98   |
| 9.1.8 ,<br>6.1.15 ,<br>6.1.35 ,<br>10.1.6  | TownName           | <TwnNm>       |    | [0..1] |                  | 98   |
| 9.1.9 ,<br>6.1.16 ,<br>6.1.36 ,<br>10.1.7  | CountrySubDivision | <CtrySubDvsn> |    | [0..1] |                  | 98   |
| 9.1.10 ,<br>6.1.17 ,<br>6.1.37 ,<br>10.1.8 | Country            | <Ctry>        |    | [0..1] |                  | 98   |
| 9.1.11 ,<br>6.1.18 ,<br>6.1.38 ,<br>10.1.9 | AddressLine        | <AdrLine>     |    | [0..7] |                  | 99   |

## 4.37.3 Identification

*XML Tag:* Id

*Presence:* [0..1]

*Definition:* Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "[Party6Choice](#)" on page 68 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item               | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|--------|----------------------------|-----------|-----|--------|------------------|------|
| 9.1.13 | OrganisationIdentification | <OrgId>   | {Or | [1..1] |                  | 69   |
| 9.1.21 | PrivateIdentification      | <PrvtId>  | Or} | [1..1] | 💡                | 69   |

#### Usage Guideline details

- on **pain.001.001.03/GroupHeader/InitiatingParty/Identification**

- **HSBC\_InitiatingParty:**

Provide HSBC Connect Customer ID under /InitgPty/Id/OrgId/Othr/Id/. Alternatively, provide: BIC under /InitgPty/Id/OrgId/BICOrBEI/ or SIRET ID under /InitgPty/Id/OrgId/Othr/Id/

Please note that this information is mandatory for Host to Host and Swiftnet File Act submissions. While this information is not mandatory for HSBCnet File Upload we strongly encourage including it.

## 4.37.4 CountryOfResidence

*XML Tag:* CtryOfRes

*Presence:* [0..1]

*Definition:* Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

*Datatype:* "[CountryCode](#)" on page 154

#### Usage Guideline details

- This element(**pain.001.001.03/GroupHeader/InitiatingParty/CountryOfResidence**) will be ignored by the Receiver.

## 4.37.5 ContactDetails

*XML Tag:* CtctDtls

*Presence:* [0..1]

*Definition:* Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "[ContactDetails2](#)" on page 24 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item | <XML Tag>  | Or | Mult.  | Usage Guidelines | Page |
|--------|--------------|------------|----|--------|------------------|------|
| 9.1.35 | NamePrefix   | <NmPrfx>   |    | [0..1] |                  | 25   |
| 9.1.36 | Name         | <Nm>       |    | [0..1] |                  | 25   |
| 9.1.37 | PhoneNumber  | <PhneNb>   |    | [0..1] |                  | 25   |
| 9.1.38 | MobileNumber | <MobNb>    |    | [0..1] |                  | 25   |
| 9.1.39 | FaxNumber    | <FaxNb>    |    | [0..1] |                  | 25   |
| 9.1.40 | EmailAddress | <EmailAdr> |    | [0..1] |                  | 25   |
| 9.1.41 | Other        | <Othr>     |    | [0..1] |                  | 26   |

#### Usage Guideline details

- This element([pain.001.001.03/GroupHeader/InitiatingParty/ContactDetails](#)) will be ignored by the Receiver.

## 4.38 PartyIdentification32\_\_1

*Definition:* Set of elements used to identify a person or an organisation.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item       | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|--------|--------------------|-------------|----|--------|------------------|------|
| 9.1.0  | Name               | <Nm>        |    | [0..1] | <b>M</b> ⚠️      | 73   |
| 9.1.1  | PostalAddress      | <PstlAdr>   |    | [0..1] | <b>M</b> ⚠️      | 74   |
| 9.1.12 | Identification     | <Id>        |    | [0..1] | <b>M</b>         | 76   |
| 9.1.33 | CountryOfResidence | <CtryOfRes> |    | [0..1] | 💡                | 77   |
| 9.1.34 | ContactDetails     | <CtctDtls>  |    | [0..1] | 💡                | 77   |

#### Used in element(s)

"Creditor" on page 36, "Debtor" on page 86, "UltimateDebtor" on page 88, "UltimateDebtor" on page 31

### 4.38.1 Name

*XML Tag:* Nm

*Presence:* [0..1]

*Definition:* Name by which a party is known and which is usually used to identify that party.

*Datatype:* "[Max70Text](#)" on page 172

## Usage Guideline details

- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/Name**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- **on pain.001.001.03/PaymentInformation/Debtor/Name**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/Name**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- **on pain.001.001.03/PaymentInformation/UltimateDebtor/Name**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- **on pain.001.001.03/PaymentInformation/Debtor/Name**
  - **HSBC\_Name\_Address:**
    - If**  
Name of greater than 35 characters is supplied
    - Then**  
Postal Address>Street Name and Building Number will be ignored
- **on pain.001.001.03/PaymentInformation/UltimateDebtor/Name**
  - **HSBC\_Name\_Address:**
    - If**  
Name of greater than 35 characters is supplied
    - Then**  
Postal Address>Street Name and Building Number will be ignored
- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/Name**
  - **HSBC\_Name\_Address:**
    - If**  
Name of greater than 35 characters is supplied
    - Then**  
Postal Address>Street Name and Building Number will be ignored
- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/Name**
  - **HSBC\_Name\_Address:**
    - If**  
Name of greater than 35 characters is supplied
    - Then**  
Postal Address>Street Name and Building Number will be ignored

## 4.38.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

**Definition:** Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress6\_\_1" on page 99 for details)

🚫 Removed - ⬜ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index                                      | Message Item       | <XML Tag>     | Or | Mult.  | Usage Guidelines                  | Page |
|--------------------------------------------|--------------------|---------------|----|--------|-----------------------------------|------|
| 9.1.2 ,<br>6.1.9 ,<br>6.1.29 ,<br>10.1.0   | AddressType        | <AdrTp>       |    | [0..1] | ⬜ 🚫                               | 100  |
| 9.1.3 ,<br>6.1.10 ,<br>6.1.30 ,<br>10.1.1  | Department         | <Dept>        |    | [0..1] | ⬜                                 | 101  |
| 9.1.4 ,<br>6.1.11 ,<br>6.1.31 ,<br>10.1.2  | SubDepartment      | <SubDept>     |    | [0..1] | ⬜                                 | 101  |
| 9.1.5 ,<br>6.1.12 ,<br>6.1.32 ,<br>10.1.3  | StreetName         | <StrtNm>      |    | [0..1] | ⚠                                 | 102  |
| 9.1.6 ,<br>6.1.13 ,<br>6.1.33 ,<br>10.1.4  | BuildingNumber     | <BldgNb>      |    | [0..1] | ⚠                                 | 103  |
| 9.1.7 ,<br>6.1.14 ,<br>6.1.34 ,<br>10.1.5  | PostCode           | <PstCd>       |    | [0..1] | ⚠                                 | 104  |
| 9.1.8 ,<br>6.1.15 ,<br>6.1.35 ,<br>10.1.6  | TownName           | <TwnNm>       |    | [0..1] | <b>M</b>                          | 104  |
| 9.1.9 ,<br>6.1.16 ,<br>6.1.36 ,<br>10.1.7  | CountrySubDivision | <CtrySubDvsn> |    | [0..1] | <b>M</b> ⚠                        | 105  |
| 9.1.10 ,<br>6.1.17 ,<br>6.1.37 ,<br>10.1.8 | Country            | <Ctry>        |    | [0..1] | <b>M</b>                          | 106  |
| 9.1.11 ,<br>6.1.18 ,<br>6.1.38 ,<br>10.1.9 | AddressLine        | <AdrLine>     |    | [0..7] | 🚫 R[0..3] R[0..3] R[0..3] R[0..3] | 106  |

#### Usage Guideline details

- on pain.001.001.03/PaymentInformation/Debtor/PostalAddress

*This element is now mandatory, the minimum occurrence has been changed to : 1*

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/PostalAddress

*This element is now mandatory, the minimum occurrence has been changed to : 1*

- on pain.001.001.03/PaymentInformation/Debtor/PostalAddress

**Comment:**

If Name is greater than 35 characters only 70 characters of Address is supported  
if Name is 35 characters or less then 105 characters is supported for Address.

The Clearing system for Priority Payments, Cross border/currency payments only supports a maximum of 140 characters for Name and Address.

The address must be as complete as possible, be provided in a structured format and must always include in Town Name, Country Sub Division and Country.

- on pain.001.001.03/PaymentInformation/UltimateDebtor/PostalAddress

**Comment:**

If Name is greater than 35 characters only 70 characters of Address is supported  
if Name is 35 characters or less then 105 characters is supported for Address.

The Clearing system for Priority Payments, Cross border/currency payments only supports a maximum of 140 characters for Name and Address.

The address must be as complete as possible, be provided in a structured format and must always include in Town Name, Country Sub Division and Country.

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/PostalAddress

**Comment:**

If Name is greater than 35 characters only 70 characters of Address is supported  
if Name is 35 characters or less then 105 characters is supported for Address.

The Clearing system for Priority Payments, Cross border/currency payments only supports a maximum of 140 characters for Name and Address.

The address must be as complete as possible, be provided in a structured format and must always include in Town Name, Country Sub Division and Country.

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/PostalAddress

**Comment:**

If Name is greater than 35 characters only 70 characters of Address is supported  
if Name is 35 characters or less then 105 characters is supported for Address.

The Clearing system for Priority Payments, Cross border/currency payments only supports a maximum of 140 characters for Name and Address.

The address must be as complete as possible, be provided in a structured format and must always include in Town Name, Country Sub Division and Country.

## 4.38.3 Identification

*XML Tag:* Id

*Presence:* [0..1]

*Definition:* Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "[Party6Choice](#)" on page 68 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item               | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|--------|----------------------------|-----------|-----|--------|------------------|------|
| 9.1.13 | OrganisationIdentification | <OrgId>   | {Or | [1..1] |                  | 69   |
| 9.1.21 | PrivateIdentification      | <PrvtId>  | Or} | [1..1] | 💡                | 69   |

#### Usage Guideline details

- on **pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/Identification**

*This element is now mandatory, the minimum occurrence has been changed to : 1*

- on **pain.001.001.03/PaymentInformation/UltimateDebtor/Identification**

*This element is now mandatory, the minimum occurrence has been changed to : 1*

## 4.38.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

*Definition:* Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

*Datatype:* "[CountryCode](#)" on page 154

#### Usage Guideline details

- This element(**pain.001.001.03/PaymentInformation/UltimateDebtor/CountryOfResidence**) will be ignored by the Receiver.
- This element(**pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/CountryOfResidence**) will be ignored by the Receiver.

## 4.38.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

*Definition:* Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "[ContactDetails2](#)" on page 24 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item | <XML Tag>  | Or | Mult.  | Usage Guidelines | Page |
|--------|--------------|------------|----|--------|------------------|------|
| 9.1.35 | NamePrefix   | <NmPrfx>   |    | [0..1] |                  | 25   |
| 9.1.36 | Name         | <Nm>       |    | [0..1] |                  | 25   |
| 9.1.37 | PhoneNumber  | <PhneNb>   |    | [0..1] |                  | 25   |
| 9.1.38 | MobileNumber | <MobNb>    |    | [0..1] |                  | 25   |
| 9.1.39 | FaxNumber    | <FaxNb>    |    | [0..1] |                  | 25   |
| 9.1.40 | EmailAddress | <EmailAdr> |    | [0..1] |                  | 25   |
| 9.1.41 | Other        | <Othr>     |    | [0..1] |                  | 26   |

#### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/ContactDetails) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/Debtor/ContactDetails) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/UltimateDebtor/ContactDetails) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/ContactDetails) will be ignored by the Receiver.

## 4.39 PaymentIdentification1\_\_1

*Definition:* Set of elements used to provide further means of referencing a payment transaction.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item              | <XML Tag>    | Or | Mult.  | Usage Guidelines | Page |
|-------|---------------------------|--------------|----|--------|------------------|------|
| 2.29  | InstructionIdentification | <InstrId>    |    | [0..1] |                  | 78   |
| 2.30  | EndToEndIdentification    | <EndToEndId> |    | [1..1] | ⚠                | 79   |

Used in element(s)

"[PaymentIdentification](#)" on page 29

### 4.39.1 InstructionIdentification

*XML Tag:* InstrId

*Presence:* [0..1]

*Definition:* Unique identification as assigned by an instructing party for an instructed party to unambiguously identify the instruction.

*Usage:* The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction.

*Datatype:* "Max35Text" on page 171

## 4.39.2 EndToEndIdentification

*XML Tag:* EndToEndId

*Presence:* [1..1]

*Definition:* Unique identification assigned by the initiating party to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.

*Usage:* The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction.

*Datatype:* "Max16Text" on page 170

### Usage Guideline details

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/PaymentIdentification/EndToEndIdentification
  - HSBC\_EndToEndIdentification:
 

End To End Identification is a unique transaction reference. While 35 characters can be sent to the beneficiary, the debit reference is limited to 16 characters

## 4.40 PaymentInstructionInformation3\_\_1

*Definition:* Set of characteristics that apply to the debit side of the payment transactions included in the credit transfer initiation.

Removed - 
 Ignored - 
 Details below - 
 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                         | <XML Tag>         | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------------------------------|-------------------|----|--------|------------------|------|
| 2.1   | PaymentInformationIdentification     | <PmtInId>         |    | [1..1] |                  | 83   |
| 2.2   | PaymentMethod                        | <PmtMtd>          |    | [1..1] |                  | 83   |
| 2.3   | BatchBooking                         | <BtchBookg>       |    | [0..1] |                  | 84   |
| 2.4   | NumberOfTransactions                 | <NbOfTxS>         |    | [0..1] |                  | 84   |
| 2.5   | ControlSum                           | <CtrlSum>         |    | [0..1] |                  | 84   |
| 2.6   | PaymentTypeInformation               | <PmtTplnf>        |    | [0..1] |                  | 84   |
| 2.17  | RequestedExecutionDate               | <ReqdExctnDt>     |    | [1..1] |                  | 85   |
| 2.18  | PoolingAdjustmentDate                | <PoolgAdjstmntDt> |    | [0..1] |                  | 85   |
| 2.19  | Debtor                               | <Dbtr>            |    | [1..1] |                  | 86   |
| 2.20  | DebtorAccount                        | <DbtrAcct>        |    | [1..1] |                  | 86   |
| 2.21  | DebtorAgent                          | <DbtrAgt>         |    | [1..1] |                  | 87   |
| 2.22  | DebtorAgentAccount                   | <DbtrAgtAcct>     |    | [0..1] |                  | 88   |
| 2.23  | UltimateDebtor                       | <UltmtDbtr>       |    | [0..1] |                  | 88   |
| 2.24  | ChargeBearer                         | <ChrgBr>          |    | [0..1] |                  | 89   |
| 2.25  | ChargesAccount                       | <ChrgsAcct>       |    | [0..1] |                  | 89   |
| 2.26  | ChargesAccountAgent                  | <ChrgsAcctAgt>    |    | [0..1] |                  | 90   |
| 2.27  | CreditTransferTransactionInformation | <CdtTrfTxInf>     |    | [1..*] |                  | 90   |

## Rules

### R1 PaymentTypeInformationRule ✓

If PaymentTypeInformation is present, then CreditTransferTransactionInformation/PaymentTypeInformation is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00009
- *Error Text:* Invalid message content for payment type information.

### R2 ChequeInstructionRule ✓

If PaymentMethod is different from CHK, then CreditTransferTransactionInformation/ChequeInstruction is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00100

- *Error Text:* Invalid message content for cheque instruction.

### **R3 ChargesAccountRule ✓**

If ChargesAccountAgent is present, then ChargesAccount must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00099
- *Error Text:* Invalid message content for charges agent account.

### **R4 ChargesAccountAgentRule**

If ChargesAccountAgent is present, then it must contain a branch of the DebtorAgent. It must not contain a completely different agent.

Error handling: Undefined

### **R5 ChargeBearerRule ✓**

If ChargeBearer is present, then CreditTransferTransactionInformation/ChargeBearer is not allowed.

If CreditTransferTransactionInformation/ChargeBearer is present, then ChargeBearer is not allowed.

CreditTransferTransactionInformation/ChargeBearer and ChargeBearer may both be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00112
- *Error Text:* Invalid message content for charge bearer.

### **R6 UltimateDebtorRule ✓**

If UltimateDebtor is present, then CreditTransferTransactionInformation/UltimateDebtor is not allowed.

If CreditTransferTransactionInformation/UltimateDebtor is present, then UltimateDebtor is not allowed.

CreditTransferTransactionInformation/UltimateDebtor and UltimateDebtor may both be absent.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00097
- *Error Text:* Invalid message content for ultimate debtor.

### **R7 ChequeAndCreditorAccountRule ✓**

If PaymentMethod is CHK, then CreditTransferTransactionInformation/CreditorAccount is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00107
- *Error Text:* Invalid message content for cheque payment method.

**R8 ChequeDeliveryAndCreditorAgentRule ✓**

If PaymentMethod is CHK and CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod/Code is present and is equal to MLFA, CRFA, RGFA or PUFA, then CreditTransferTransactionInformation/CreditorAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00109
- *Error Text:* Invalid message content for cheque payment with creditor agent.

**R9 ChequeDeliveryAndNoCreditorAgentRule ✓**

If PaymentMethod is CHK and CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod/Code is present and different from MLFA, CRFA, RGFA or PUFA, then CreditTransferTransactionInformation/CreditorAgent is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00110
- *Error Text:* Invalid message content for cheque payment without creditor agent.

**R10 NonChequePaymentMethodRule**

If PaymentMethod is different from CHK and CreditTransferTransactionInformation/Creditor is not present, then CreditTransferTransactionInformation/CreditorAccount must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00108
- *Error Text:* Invalid message content for non cheque payment method.

**R11 ChequeNoDeliveryAndNoCreditorAgentRule ✓**

If PaymentMethod is CHK and CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is not present, then CreditTransferTransactionInformation/CreditorAgent is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00111
- *Error Text:* Invalid message content for cheque payment without delivery method.

## Guidelines

### 1. UltimateDebtorGuideline

UltimateDebtor may only be present if different from Debtor.

### 2. ChequeInstructionDeliverToDebtorGuideline

If CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and if CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod/Code is CRDB, MLDB, PUDB or RGDB, then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different from Debtor.

### 3. ChequeInstructionDeliverToCreditorGuideline

If PaymentInformation/CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and is CRCD, MLCD, PUCD or RGCD, then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different from CreditTransferTransactionInformation/Creditor.

### 4. ChequeInstructionDeliverToCreditorAgentGuideline

If CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and is CRFA, MLFA, PUFA or RGFA, then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different from CreditTransferTransactionInformation/Creditor.

### 5. ChequeFromGuideline

CreditTransferTransactionInformation/ChequeInstruction/ChequeFrom may only be present if different from CreditTransferTransactionInformation/UltimateDebtor or Debtor.

## Used in element(s)

"PaymentInformation" on page 6

## 4.40.1 PaymentInformationIdentification

*XML Tag:* PmtInfId

*Presence:* [1..1]

*Definition:* Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message.

*Datatype:* "Max35Text" on page 171

## Usage Guideline details

- on pain.001.001.03/PaymentInformation/PaymentInformationIdentification

### Comment:

This will be reported in Payment Status Report.

## 4.40.2 PaymentMethod

*XML Tag:* PmtMtd

*Presence:* [1..1]

*Definition:* Specifies the means of payment that will be used to move the amount of money.

Datatype: ["PaymentMethod3Code" on page 173](#)

### 4.40.3 BatchBooking

XML Tag: BtchBookg

Presence: [0..1]

*Definition:* Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested.

Usage: Batch booking is used to request and not order a possible batch booking.

Datatype: ["BatchBookingIndicator" on page 143](#)

#### Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/BatchBooking](#)) is removed.

### 4.40.4 NumberOfTransactions

XML Tag: NbOfTxS

Presence: [0..1]

*Definition:* Number of individual transactions contained in the paymnet information group.

Datatype: ["Max15NumericText" on page 169](#)

### 4.40.5 ControlSum

XML Tag: CtrlSum

Presence: [0..1]

*Definition:* Total of all individual amounts included in the group, irrespective of currencies.

Datatype: ["DecimalNumber" on page 155](#)

#### Usage Guideline details

- on [pain.001.001.03/PaymentInformation/ControlSum](#)

**Comment:**

This is the hash total of all payment amounts in the entire message regardless of currency in Instructed Amount and Equivalent amount. If included amount must have 2 decimal places.

### 4.40.6 PaymentTypeInformation

XML Tag: PmtTpInf

Presence: [0..1]

*Definition:* Set of elements used to further specify the type of transaction.

The **PmtTpInf** block contains the following elements (see datatype "[PaymentTypeInformation19\\_\\_1](#)" on [page 91](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index          | Message Item        | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|----------------|---------------------|-------------|----|--------|------------------|------|
| 2.7 ,<br>2.32  | InstructionPriority | <InstrPrty> |    | [0..1] | 💡                | 92   |
| 2.8 ,<br>2.33  | ServiceLevel        | <SvcLvl>    |    | [0..1] | ⚠️               | 92   |
| 2.11 ,<br>2.36 | LocalInstrument     | <LclInstrm> |    | [0..1] | 💡                | 93   |
| 2.14 ,<br>2.39 | CategoryPurpose     | <CtgyPurp>  |    | [0..1] | 💡                | 93   |

#### Usage Guideline details

- **on pain.001.001.03/PaymentInformation/PaymentTypeInformation**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*

## 4.40.7 RequestedExecutionDate

XML Tag: ReqdExctnDt

Presence: [1..1]

Definition: Date at which the initiating party requests the clearing agent to process the payment.

Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank.

Datatype: "[ISODate](#)" on [page 166](#)

#### Usage Guideline details

- **on pain.001.001.03/PaymentInformation/RequestedExecutionDate**  
**Comment:**  
Work day on which the payment should be initiated

## 4.40.8 PoolingAdjustmentDate

XML Tag: PoolgAdjstmntDt

Presence: [0..1]

Definition: Date used for the correction of the value date of a cash pool movement that has been posted with a different value date.

Datatype: "[ISODate](#)" on [page 166](#)

## Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/PoolingAdjustmentDate](#)) will be ignored by the Receiver.

## 4.40.9 Debtor

*XML Tag:* Dbtr

*Presence:* [1..1]

*Definition:* Party that owes an amount of money to the (ultimate) creditor.

The **Dbtr** block contains the following elements (see datatype "[PartyIdentification32\\_\\_1](#)" on page 73 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item       | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|--------|--------------------|-------------|----|--------|------------------|------|
| 9.1.0  | Name               | <Nm>        |    | [0..1] | <b>M</b> ⚠️      | 73   |
| 9.1.1  | PostalAddress      | <PstlAdr>   |    | [0..1] | <b>M</b> ⚠️      | 74   |
| 9.1.12 | Identification     | <Id>        |    | [0..1] |                  | 76   |
| 9.1.33 | CountryOfResidence | <CtryOfRes> |    | [0..1] |                  | 77   |
| 9.1.34 | ContactDetails     | <CtctDtls>  |    | [0..1] | 💡                | 77   |

## Usage Guideline details

- on [pain.001.001.03/PaymentInformation/Debtor](#)

### – HSBC\_OnBehalfOf:

It is Mandatory to provide the name, address and an account or identification of the ultimate debtor if a priority payment is being made on behalf of someone apart from the account holder and should be supplied in the Ultimate Debtor block.

The address should include, as a minimum, the city or town name; the state or county; and the country.

The Debtor Account <DbtrAcct> block should always be used to supply the HSBC account to be debited.

#### If

The payment is being made on behalf of someone apart from the account holder.

#### Then

The Ultimate Debtor block <UltmtDbtr> should be used to supply the name, address and an account or identification of the ultimate debtor

#### Else

The Debtor <Dbtr> block should be used to supply the name and address of the ultimate debtor.

## 4.40.10 DebtorAccount

*XML Tag:* DbtrAcct

*Presence:* [1..1]

*Definition:* Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.

The **DbtrAcct** block contains the following elements (see datatype "[CashAccount16](#)" on page 14 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|----------------|-----------|----|--------|------------------|------|
| 1.1.0  | Identification | <Id>      |    | [1..1] |                  | 15   |
| 1.1.8  | Type           | <Tp>      |    | [0..1] |                  | 15   |
| 1.1.11 | Currency       | <Ccy>     |    | [0..1] | 💡                | 16   |
| 1.1.12 | Name           | <Nm>      |    | [0..1] |                  | 16   |

#### Usage Guideline details

- on [pain.001.001.03/PaymentInformation/DebtorAccount](#)

**Comment:**

Debit account should be provided as domestic account number under Other or IBAN.

## 4.40.11 DebtorAgent

*XML Tag:* DbtrAgt

*Presence:* [1..1]

*Definition:* Financial institution servicing an account for the debtor.

The **DbtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification4](#)" on page 11 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item                       | <XML Tag>    | Or | Mult.  | Usage Guidelines | Page |
|--------|------------------------------------|--------------|----|--------|------------------|------|
| 6.1.0  | FinancialInstitutionIdentification | <FinInstnId> |    | [1..1] |                  | 11   |
| 6.1.25 | BranchIdentification               | <BrnchId>    |    | [0..1] | ⚠                | 12   |

#### Usage Guideline details

- on [pain.001.001.03/PaymentInformation/DebtorAgent](#)

– **HSBC\_DebtorAgent:**

Debtor agent can be supplied as BIC or domestic routing code.  
Domestic routing code is required if domestic account number is quoted

## 4.40.12 DebtorAgentAccount

*XML Tag:* DbtrAgtAcct

*Presence:* [0..1]

*Definition:* Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain.

The **DbtrAgtAcct** block contains the following elements (see datatype "CashAccount16" on page 14 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|----------------|-----------|----|--------|------------------|------|
| 1.1.0  | Identification | <Id>      |    | [1..1] |                  | 15   |
| 1.1.8  | Type           | <Tp>      |    | [0..1] |                  | 15   |
| 1.1.11 | Currency       | <Ccy>     |    | [0..1] |                  | 16   |
| 1.1.12 | Name           | <Nm>      |    | [0..1] |                  | 16   |

### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/DebtorAgentAccount) will be ignored by the Receiver.

## 4.40.13 UltimateDebtor

*XML Tag:* UltmtDbtr

*Presence:* [0..1]

*Definition:* Ultimate party that owes an amount of money to the (ultimate) creditor.

The **UltmtDbtr** block contains the following elements (see datatype "PartyIdentification32\_\_1" on page 73 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item       | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|--------|--------------------|-------------|----|--------|------------------|------|
| 9.1.0  | Name               | <Nm>        |    | [0..1] | <b>M</b> ⚠️      | 73   |
| 9.1.1  | PostalAddress      | <PstlAdr>   |    | [0..1] | ⚠️               | 74   |
| 9.1.12 | Identification     | <Id>        |    | [0..1] | <b>M</b>         | 76   |
| 9.1.33 | CountryOfResidence | <CtryOfRes> |    | [0..1] | 💡                | 77   |
| 9.1.34 | ContactDetails     | <CtctDtls>  |    | [0..1] | 💡                | 77   |

### Usage Guideline details

- on pain.001.001.03/PaymentInformation/UltimateDebtor

– **HSBC\_OnBehalfOf:**

It is Mandatory to provide the name, address and an account or identification of the ultimate debtor if a priority payment is being made on behalf of someone apart from the account holder and should be supplied in the Ultimate Debtor block.

The address should include, as a minimum, the city or town name; the state or county; and the country.

The Debtor Account <DbtrAcct> block should always be used to supply the HSBC account to be debited.

**If**

The payment is being made on behalf of someone apart from the account holder.

**Then**

The Ultimate Debtor block <UltmtDbtr> should be used to supply the name, address and an account or identification of the ultimate debtor

**Else**

The Debtor <Dbtr> block should be used to supply the name and address of the ultimate debtor.

## 4.40.14 ChargeBearer

*XML Tag:* ChrgBr

*Presence:* [0..1]

*Definition:* Specifies which party/parties will bear the charges associated with the processing of the payment transaction.

*Datatype:* ["ChargeBearerType1Code" on page 149](#)

### Usage Guideline details

- on pain.001.001.03/PaymentInformation/ChargeBearer

**Comment:**

From 6th January 2018, as part of the PSD2 regulation for all payments where the originator and beneficiary are in EEA countries the only option available for the charge indicator will be "Shared". The only exception is for payments debiting a German account, where the charge indicator can be 'Shared' or 'Our' (debit account). If the "Shared" or 'Our' option, as appropriate, is not supplied the HSBC back office systems will default the charge indicator to "Shared" before the payment is processed.

## 4.40.15 ChargesAccount

*XML Tag:* ChrgsAcct

*Presence:* [0..1]

*Definition:* Account used to process charges associated with a transaction.

*Usage:* Charges account should be used when charges have to be booked to an account different from the account identified in debtor's account.

The **ChrgsAcct** block contains the following elements (see datatype "[CashAccount16](#)" on page 14 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|----------------|-----------|----|--------|------------------|------|
| 1.1.0  | Identification | <Id>      |    | [1..1] |                  | 15   |
| 1.1.8  | Type           | <Tp>      |    | [0..1] |                  | 15   |
| 1.1.11 | Currency       | <Ccy>     |    | [0..1] |                  | 16   |
| 1.1.12 | Name           | <Nm>      |    | [0..1] |                  | 16   |

#### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/ChargesAccount) will be ignored by the Receiver.

## 4.40.16 ChargesAccountAgent

XML Tag: ChrgsAcctAgt

Presence: [0..1]

Definition: Agent that services a charges account.

Usage: Charges account agent should only be used when the charges account agent is different from the debtor agent.

The **ChrgsAcctAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification4](#)" on page 11 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item                       | <XML Tag>    | Or | Mult.  | Usage Guidelines | Page |
|--------|------------------------------------|--------------|----|--------|------------------|------|
| 6.1.0  | FinancialInstitutionIdentification | <FinInstnId> |    | [1..1] |                  | 11   |
| 6.1.25 | BranchIdentification               | <BrnchId>    |    | [0..1] |                  | 12   |

#### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/ChargesAccountAgent) will be ignored by the Receiver.

## 4.40.17 CreditTransferTransactionInformation

XML Tag: CdtTrfTxInf

Presence: [1..\*]

Definition: Set of elements used to provide information on the individual transaction(s) included in the message.

The **CdtTrfTxInf** block contains the following elements (see datatype "CreditTransferTransactionInformation10\_\_1" on page 26 for details)

🚫 Removed - ✨ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                 | <XML Tag>         | Or | Mult.   | Usage Guidelines | Page |
|-------|------------------------------|-------------------|----|---------|------------------|------|
| 2.28  | PaymentIdentification        | <PmtId>           |    | [1..1]  |                  | 29   |
| 2.31  | PaymentTypeInformation       | <PmtTplnf>        |    | [0..1]  |                  | 29   |
| 2.42  | Amount                       | <Amt>             |    | [1..1]  |                  | 29   |
| 2.47  | ExchangeRateInformation      | <XchgRateInf>     |    | [0..1]  |                  | 30   |
| 2.51  | ChargeBearer                 | <ChrgBr>          |    | [0..1]  | ⚠                | 30   |
| 2.52  | ChequeInstruction            | <ChqInstr>        |    | [0..1]  | ✨                | 31   |
| 2.70  | UltimateDebtor               | <UltmtDbtr>       |    | [0..1]  | ⚠                | 31   |
| 2.71  | IntermediaryAgent1           | <IntrmyAgt1>      |    | [0..1]  |                  | 32   |
| 2.72  | IntermediaryAgent1Account    | <IntrmyAgt1Acct>  |    | [0..1]  | ✨                | 33   |
| 2.73  | IntermediaryAgent2           | <IntrmyAgt2>      |    | [0..1]  | ✨                | 33   |
| 2.74  | IntermediaryAgent2Account    | <IntrmyAgt2Acct>  |    | [0..1]  | ✨                | 34   |
| 2.75  | IntermediaryAgent3           | <IntrmyAgt3>      |    | [0..1]  | ✨                | 34   |
| 2.76  | IntermediaryAgent3Account    | <IntrmyAgt3Acct>  |    | [0..1]  | ✨                | 35   |
| 2.77  | CreditorAgent                | <CdtrAgt>         |    | [0..1]  | <b>M</b>         | 35   |
| 2.78  | CreditorAgentAccount         | <CdtrAgtAcct>     |    | [0..1]  |                  | 36   |
| 2.79  | Creditor                     | <Cdtr>            |    | [0..1]  | <b>M</b>         | 36   |
| 2.80  | CreditorAccount              | <CdtrAcct>        |    | [0..1]  | <b>M</b>         | 37   |
| 2.81  | UltimateCreditor             | <UltmtCdtr>       |    | [0..1]  | ✨                | 37   |
| 2.82  | InstructionForCreditorAgent  | <InstrForCdtrAgt> |    | [0..*]  | ⚠ R[0..5]        | 38   |
| 2.85  | InstructionForDebtorAgent    | <InstrForDbtrAgt> |    | [0..1]  | ⚠                | 39   |
| 2.86  | Purpose                      | <Purp>            |    | [0..1]  |                  | 40   |
| 2.89  | RegulatoryReporting          | <RgltryRptg>      |    | [0..10] |                  | 40   |
| 2.90  | Tax                          | <Tax>             |    | [0..1]  |                  | 40   |
| 2.91  | RelatedRemittanceInformation | <RltdRmtInf>      |    | [0..10] | ⚠                | 41   |
| 2.98  | RemittanceInformation        | <RmtInf>          |    | [0..1]  |                  | 42   |

## 4.41 PaymentTypeInformation19\_\_1

*Definition:* Set of elements used to provide further details of the type of payment.

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index          | Message Item        | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|----------------|---------------------|-------------|----|--------|------------------|------|
| 2.7 ,<br>2.32  | InstructionPriority | <InstrPrty> |    | [0..1] | ✦ 🚫              | 92   |
| 2.8 ,<br>2.33  | ServiceLevel        | <SvcLvl>    |    | [0..1] | ⚠                | 92   |
| 2.11 ,<br>2.36 | LocalInstrument     | <LclInstrm> |    | [0..1] | ✦                | 93   |
| 2.14 ,<br>2.39 | CategoryPurpose     | <CtgyPurp>  |    | [0..1] | ✦                | 93   |

#### Used in element(s)

"PaymentTypeInformation" on page 84, "PaymentTypeInformation" on page 29

### 4.41.1 InstructionPriority

XML Tag: InstrPrty

Presence: [0..1]

**Definition:** Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction.

**Datatype:** "Priority2Code" on page 175

#### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/PaymentTypeInformation/InstructionPriority) is removed.
- This element(pain.001.001.03/PaymentInformation/PaymentTypeInformation/InstructionPriority) will be ignored by the Receiver.

### 4.41.2 ServiceLevel

XML Tag: SvcLvl

Presence: [0..1]

**Definition:** Agreement under which or rules under which the transaction should be processed.

The **SvcLvl** block contains the following elements (see datatype "ServiceLevel8Choice\_\_1" on page 117 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index          | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|----------------|--------------|-----------|-----|--------|------------------|------|
| 2.9 ,<br>2.34  | Code         | <Cd>      | {Or | [1..1] |                  | 118  |
| 2.10 ,<br>2.35 | Proprietary  | <Prtry>   | Or} | [1..1] | ✦ 🚫              | 118  |

## Usage Guideline details

- **on pain.001.001.03/PaymentInformation/PaymentTypeInformation/ServiceLevel**  
**Comment:**  
It is mandatory to provide service level code at either payment level or transaction level. Recommended at Payment Level
- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/PaymentTypeInformation/ServiceLevel**  
**Comment:**  
It is mandatory to provide service level code at either payment level or transaction level.

## 4.41.3 LocalInstrument

*XML Tag:* LclInstrm

*Presence:* [0..1]

*Definition:* User community specific instrument.

Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level.

The **LclInstrm** block contains the following elements (see datatype "[LocalInstrument2Choice](#)" on page 64 for details)

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

| Index          | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|----------------|--------------|-----------|-----|--------|------------------|------|
| 2.12 ,<br>2.37 | Code         | <Cd>      | {Or | [1..1] |                  | 64   |
| 2.13 ,<br>2.38 | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 64   |

## Usage Guideline details

- **This element(pain.001.001.03/PaymentInformation/PaymentTypeInformation/LocalInstrument) will be ignored by the Receiver.**

## 4.41.4 CategoryPurpose

*XML Tag:* CtgPurp

*Presence:* [0..1]

*Definition:* Specifies the high level purpose of the instruction based on a set of pre-defined categories.

Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.

The **CtgyPurp** block contains the following elements (see datatype "[CategoryPurpose1Choice](#)" on [page 18](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index          | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|----------------|--------------|-----------|-----|--------|------------------|------|
| 2.15 ,<br>2.40 | Code         | <Cd>      | {Or | [1..1] |                  | 18   |
| 2.16 ,<br>2.41 | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 18   |

#### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/PaymentTypeInformation/CategoryPurpose) will be ignored by the Receiver.

## 4.42 PersonIdentification5

*Definition:* Unique and unambiguous way to identify a person.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item        | <XML Tag>         | Or | Mult.  | Usage Guidelines | Page |
|--------|---------------------|-------------------|----|--------|------------------|------|
| 9.1.22 | DateAndPlaceOfBirth | <DtAndPlcOfBirth> |    | [0..1] |                  | 94   |
| 9.1.27 | Other               | <Othr>            |    | [0..*] |                  | 95   |

#### Used in element(s)

"[PrivateIdentification](#)" on [page 69](#)

### 4.42.1 DateAndPlaceOfBirth

*XML Tag:* DtAndPlcOfBirth

*Presence:* [0..1]

*Definition:* Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "[DateAndPlaceOfBirth](#)" on [page 45](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item    | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|--------|-----------------|---------------|----|--------|------------------|------|
| 9.1.23 | BirthDate       | <BirthDt>     |    | [1..1] |                  | 45   |
| 9.1.24 | ProvinceOfBirth | <PrvcOfBirth> |    | [0..1] |                  | 45   |
| 9.1.25 | CityOfBirth     | <CityOfBirth> |    | [1..1] |                  | 45   |
| 9.1.26 | CountryOfBirth  | <CtryOfBirth> |    | [1..1] |                  | 45   |

## 4.42.2 Other

*XML Tag:* Othr

*Presence:* [0..\*]

*Definition:* Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericPersonIdentification1](#)" on page 58 for details)

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item   | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|----------------|-----------|----|--------|------------------|------|
| 9.1.28 | Identification | <Id>      |    | [1..1] |                  | 58   |
| 9.1.29 | SchemeName     | <SchmeNm> |    | [0..1] |                  | 58   |
| 9.1.32 | Issuer         | <Issr>    |    | [0..1] |                  | 59   |

## 4.43 PersonIdentificationSchemeName1Choice

*Definition:* Sets of elements to identify a name of the identification scheme.

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|--------|--------------|-----------|-----|--------|------------------|------|
| 9.1.30 | Code         | <Cd>      | {Or | [1..1] |                  | 95   |
| 9.1.31 | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 95   |

**Used in element(s)**

"[SchemeName](#)" on page 58

### 4.43.1 Code

*XML Tag:* Cd

*Presence:* [1..1]

*Definition:* Name of the identification scheme, in a coded form as published in an external list.

*Datatype:* "[ExternalPersonIdentification1Code](#)" on page 164

### 4.43.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Name of the identification scheme, in a free text form.

*Datatype:* "[Max35Text](#)" on page 171

## 4.44 PostalAddress6

*Definition:* Information that locates and identifies a specific address, as defined by postal services.

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index                                      | Message Item       | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|--------------------------------------------|--------------------|---------------|----|--------|------------------|------|
| 9.1.2 ,<br>6.1.9 ,<br>6.1.29 ,<br>10.1.0   | AddressType        | <AdrTp>       |    | [0..1] | ✦                | 96   |
| 9.1.3 ,<br>6.1.10 ,<br>6.1.30 ,<br>10.1.1  | Department         | <Dept>        |    | [0..1] |                  | 97   |
| 9.1.4 ,<br>6.1.11 ,<br>6.1.31 ,<br>10.1.2  | SubDepartment      | <SubDept>     |    | [0..1] |                  | 97   |
| 9.1.5 ,<br>6.1.12 ,<br>6.1.32 ,<br>10.1.3  | StreetName         | <StrtNm>      |    | [0..1] |                  | 97   |
| 9.1.6 ,<br>6.1.13 ,<br>6.1.33 ,<br>10.1.4  | BuildingNumber     | <BldgNb>      |    | [0..1] |                  | 97   |
| 9.1.7 ,<br>6.1.14 ,<br>6.1.34 ,<br>10.1.5  | PostCode           | <PstCd>       |    | [0..1] |                  | 98   |
| 9.1.8 ,<br>6.1.15 ,<br>6.1.35 ,<br>10.1.6  | TownName           | <TwnNm>       |    | [0..1] |                  | 98   |
| 9.1.9 ,<br>6.1.16 ,<br>6.1.36 ,<br>10.1.7  | CountrySubDivision | <CtrySubDvsn> |    | [0..1] |                  | 98   |
| 9.1.10 ,<br>6.1.17 ,<br>6.1.37 ,<br>10.1.8 | Country            | <Ctry>        |    | [0..1] | <b>M</b>         | 98   |
| 9.1.11 ,<br>6.1.18 ,<br>6.1.38 ,<br>10.1.9 | AddressLine        | <AdrLine>     |    | [0..7] |                  | 99   |

Used in element(s)

"Address" on page 65, "PostalAddress" on page 13, "PostalAddress" on page 70, "PostalAddress" on page 51

### 4.44.1 AddressType

*XML Tag:* AdrTp

*Presence:* [0..1]

*Definition:* Identifies the nature of the postal address.

*Datatype:* ["AddressType2Code" on page 139](#)

#### Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/BranchIdentification/PostalAddress/AddressType](#)) will be ignored by the Receiver.
- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RelatedRemittanceInformation/RemittanceLocationPostalAddress/Address/AddressType](#)) will be ignored by the Receiver.
- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) will be ignored by the Receiver.
- This element([pain.001.001.03/PaymentInformation/DebtorAgent/BranchIdentification/PostalAddress/AddressType](#)) will be ignored by the Receiver.
- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent1/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) will be ignored by the Receiver.

## 4.44.2 Department

*XML Tag:* Dept

*Presence:* [0..1]

*Definition:* Identification of a division of a large organisation or building.

*Datatype:* ["Max70Text" on page 172](#)

## 4.44.3 SubDepartment

*XML Tag:* SubDept

*Presence:* [0..1]

*Definition:* Identification of a sub-division of a large organisation or building.

*Datatype:* ["Max70Text" on page 172](#)

## 4.44.4 StreetName

*XML Tag:* StrtNm

*Presence:* [0..1]

*Definition:* Name of a street or thoroughfare.

*Datatype:* ["Max70Text" on page 172](#)

## 4.44.5 BuildingNumber

*XML Tag:* BldgNb

*Presence:* [0..1]

*Definition:* Number that identifies the position of a building on a street.

*Datatype:* "Max16Text" on page 170

## 4.44.6 PostCode

*XML Tag:* PstCd

*Presence:* [0..1]

*Definition:* Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

*Datatype:* "Max16Text" on page 170

## 4.44.7 TownName

*XML Tag:* TwnNm

*Presence:* [0..1]

*Definition:* Name of a built-up area, with defined boundaries, and a local government.

*Datatype:* "Max35Text" on page 171

## 4.44.8 CountrySubDivision

*XML Tag:* CtrySubDvsn

*Presence:* [0..1]

*Definition:* Identifies a subdivision of a country such as state, region, county.

*Datatype:* "Max35Text" on page 171

## 4.44.9 Country

*XML Tag:* Ctry

*Presence:* [0..1]

*Definition:* Nation with its own government.

*Datatype:* "CountryCode" on page 154

### Usage Guideline details

- on **pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/PostalAddress/Country**

*This element is now mandatory, the minimum occurrence has been changed to : 1*

- on **pain.001.001.03/PaymentInformation/DebtorAgent/FinancialInstitutionIdentification/PostalAddress/Country**

*This element is now mandatory, the minimum occurrence has been changed to : 1*

## 4.44.10      **AddressLine**

*XML Tag:* AdrLine

*Presence:* [0..7]

*Definition:* Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

*Datatype:* "Max70Text" on page 172

## 4.45      **PostalAddress6\_\_1**

*Definition:* Information that locates and identifies a specific address, as defined by postal services.

Removed - 
 Ignored - 
 Details below - 
 Mandatory - R[x..x] Repeatability[details]

| Index                                      | Message Item       | <XML Tag>     | Or | Mult.  | Usage Guidelines                | Page |
|--------------------------------------------|--------------------|---------------|----|--------|---------------------------------|------|
| 9.1.2 ,<br>6.1.9 ,<br>6.1.29 ,<br>10.1.0   | AddressType        | <AdrTp>       |    | [0..1] |                                 | 100  |
| 9.1.3 ,<br>6.1.10 ,<br>6.1.30 ,<br>10.1.1  | Department         | <Dept>        |    | [0..1] |                                 | 101  |
| 9.1.4 ,<br>6.1.11 ,<br>6.1.31 ,<br>10.1.2  | SubDepartment      | <SubDept>     |    | [0..1] |                                 | 101  |
| 9.1.5 ,<br>6.1.12 ,<br>6.1.32 ,<br>10.1.3  | StreetName         | <StrtNm>      |    | [0..1] |                                 | 102  |
| 9.1.6 ,<br>6.1.13 ,<br>6.1.33 ,<br>10.1.4  | BuildingNumber     | <BldgNb>      |    | [0..1] |                                 | 103  |
| 9.1.7 ,<br>6.1.14 ,<br>6.1.34 ,<br>10.1.5  | PostCode           | <PstCd>       |    | [0..1] |                                 | 104  |
| 9.1.8 ,<br>6.1.15 ,<br>6.1.35 ,<br>10.1.6  | TownName           | <TwnNm>       |    | [0..1] |                                 | 104  |
| 9.1.9 ,<br>6.1.16 ,<br>6.1.36 ,<br>10.1.7  | CountrySubDivision | <CtrySubDvsn> |    | [0..1] |                                 | 105  |
| 9.1.10 ,<br>6.1.17 ,<br>6.1.37 ,<br>10.1.8 | Country            | <Ctry>        |    | [0..1] |                                 | 106  |
| 9.1.11 ,<br>6.1.18 ,<br>6.1.38 ,<br>10.1.9 | AddressLine        | <AdrLine>     |    | [0..7] | R[0..3] R[0..3] R[0..3] R[0..3] | 106  |

#### Used in element(s)

"PostalAddress" on page 74

## 4.45.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

Datatype: ["AddressType2Code" on page 139](#)

#### Usage Guideline details

- This element(`pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/PostalAddress/AddressType`) is removed.
- This element(`pain.001.001.03/PaymentInformation/Debtor/PostalAddress/AddressType`) is removed.
- This element(`pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/PostalAddress/AddressType`) is removed.
- This element(`pain.001.001.03/PaymentInformation/UltimateDebtor/PostalAddress/AddressType`) is removed.
- This element(`pain.001.001.03/PaymentInformation/UltimateDebtor/PostalAddress/AddressType`) will be ignored by the Receiver.
- This element(`pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/PostalAddress/AddressType`) will be ignored by the Receiver.
- This element(`pain.001.001.03/PaymentInformation/Debtor/PostalAddress/AddressType`) will be ignored by the Receiver.
- This element(`pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/PostalAddress/AddressType`) will be ignored by the Receiver.

## 4.45.2 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: ["Max70Text" on page 172](#)

#### Usage Guideline details

- This element(`pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/PostalAddress/Department`) will be ignored by the Receiver.
- This element(`pain.001.001.03/PaymentInformation/Debtor/PostalAddress/Department`) will be ignored by the Receiver.
- This element(`pain.001.001.03/PaymentInformation/UltimateDebtor/PostalAddress/Department`) will be ignored by the Receiver.
- This element(`pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/PostalAddress/Department`) will be ignored by the Receiver.

## 4.45.3 SubDepartment

XML Tag: SubDept

Presence: [0..1]

*Definition:* Identification of a sub-division of a large organisation or building.

*Datatype:* "Max70Text" on page 172

#### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/PostalAddress/SubDepartment) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/Debtor/PostalAddress/SubDepartment) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/UltimateDebtor/PostalAddress/SubDepartment) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/PostalAddress/SubDepartment) will be ignored by the Receiver.

## 4.45.4 StreetName

*XML Tag:* StrtNm

*Presence:* [0..1]

*Definition:* Name of a street or thoroughfare.

*Datatype:* "Max35Text" on page 171

#### Usage Guideline details

- on pain.001.001.03/PaymentInformation/Debtor/PostalAddress/StreetName
  - HSBC\_Name\_Address:
    - If**  
Name of greater than 35 characters is supplied
    - Then**  
Postal Address>Street Name and Building Number will be ignored
- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/PostalAddress/StreetName
  - HSBC\_Name\_Address:
    - If**  
Name of greater than 35 characters is supplied
    - Then**  
Postal Address>Street Name and Building Number will be ignored
- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/PostalAddress/StreetName
  - HSBC\_Name\_Address:
    - If**  
Name of greater than 35 characters is supplied
    - Then**  
Postal Address>Street Name and Building Number will be ignored

- on pain.001.001.03/PaymentInformation/UltimateDebtor/PostalAddress/StreetName

- HSBC\_Name\_Address:

**If**

Name of greater than 35 characters is supplied

**Then**

Postal Address>Street Name and Building Number will be ignored

## 4.45.5 BuildingNumber

*XML Tag:* BldgNb

*Presence:* [0..1]

*Definition:* Number that identifies the position of a building on a street.

*Datatype:* "Max16Text" on page 170

### Usage Guideline details

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/PostalAddress/BuildingNumber

- HSBC\_Name\_Address:

**If**

Name of greater than 35 characters is supplied

**Then**

Postal Address>Street Name and Building Number will be ignored

- on pain.001.001.03/PaymentInformation/Debtor/PostalAddress/BuildingNumber

- HSBC\_Name\_Address:

**If**

Name of greater than 35 characters is supplied

**Then**

Postal Address>Street Name and Building Number will be ignored

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/PostalAddress/BuildingNumber

- HSBC\_Name\_Address:

**If**

Name of greater than 35 characters is supplied

**Then**

Postal Address>Street Name and Building Number will be ignored

- on pain.001.001.03/PaymentInformation/UltimateDebtor/PostalAddress/BuildingNumber

- HSBC\_Name\_Address:

**If**

Name of greater than 35 characters is supplied

**Then**

Postal Address>Street Name and Building Number will be ignored

## 4.45.6 PostCode

*XML Tag:* PstCd

*Presence:* [0..1]

*Definition:* Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

*Datatype:* "Max16Text" on page 170

### Usage Guideline details

- **on pain.001.001.03/PaymentInformation/Debtor/PostalAddress/PostCode**
  - **HSBC\_CountrySubDivision\_PostCode:**
    - If**  
Country Sub Division is supplied
    - Then**  
Post Code is ignored
- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/PostalAddress/PostCode**
  - **HSBC\_CountrySubDivision\_PostCode:**
    - If**  
Country Sub Division is supplied
    - Then**  
Post Code is ignored
- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/PostalAddress/PostCode**
  - **HSBC\_CountrySubDivision\_PostCode:**
    - If**  
Country Sub Division is supplied
    - Then**  
Post Code is ignored
- **on pain.001.001.03/PaymentInformation/UltimateDebtor/PostalAddress/PostCode**
  - **HSBC\_CountrySubDivision\_PostCode:**
    - If**  
Country Sub Division is supplied
    - Then**  
Post Code is ignored

## 4.45.7 TownName

*XML Tag:* TwnNm

*Presence:* [0..1]

*Definition:* Name of a built-up area, with defined boundaries, and a local government.

*Datatype:* "Max35Text" on page 171

## Usage Guideline details

- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/PostalAddress/TownName**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/PostalAddress/TownName**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- **on pain.001.001.03/PaymentInformation/UltimateDebtor/PostalAddress/TownName**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- **on pain.001.001.03/PaymentInformation/Debtor/PostalAddress/TownName**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*

## 4.45.8 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: "Max35Text" on page 171

## Usage Guideline details

- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/PostalAddress/CountrySubDivision**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/PostalAddress/CountrySubDivision**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- **on pain.001.001.03/PaymentInformation/Debtor/PostalAddress/CountrySubDivision**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- **on pain.001.001.03/PaymentInformation/UltimateDebtor/PostalAddress/CountrySubDivision**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/PostalAddress/CountrySubDivision**
  - **HSBC\_CountrySubDivision\_PostCode:**
    - If**  
Country Sub Division is supplied
    - Then**  
Post Code is ignored
- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/PostalAddress/CountrySubDivision**

- **HSBC\_CountrySubDivision\_PostCode:**
  - If**  
Country Sub Division is supplied
  - Then**  
Post Code is ignored
- **on pain.001.001.03/PaymentInformation/Debtor/PostalAddress/CountrySubDivision**
  - **HSBC\_CountrySubDivision\_PostCode:**
    - If**  
Country Sub Division is supplied
    - Then**  
Post Code is ignored
- **on pain.001.001.03/PaymentInformation/UltimateDebtor/PostalAddress/CountrySubDivision**
  - **HSBC\_CountrySubDivision\_PostCode:**
    - If**  
Country Sub Division is supplied
    - Then**  
Post Code is ignored

## 4.45.9 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: "CountryCode" on page 154

### Usage Guideline details

- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/PostalAddress/Country**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- **on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/PostalAddress/Country**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- **on pain.001.001.03/PaymentInformation/Debtor/PostalAddress/Country**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- **on pain.001.001.03/PaymentInformation/UltimateDebtor/PostalAddress/Country**  
*This element is now mandatory, the minimum occurrence has been changed to : 1*

## 4.45.10 AddressLine

XML Tag: AdrLine

*Presence:* [0..7]

*Definition:* Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

*Datatype:* ["Max35Text" on page 171](#)

#### Usage Guideline details

- This element(**pain.001.001.03/PaymentInformation/Debtor/PostalAddress/AddressLine**) is removed.
- This element(**pain.001.001.03/PaymentInformation/UltimateDebtor/PostalAddress/AddressLine**) is removed.
- This element(**pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/PostalAddress/AddressLine**) is removed.
- This element(**pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/PostalAddress/AddressLine**) is removed.
- on **pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/PostalAddress/AddressLine**  
*This element has change repeatability, the maximum occurrence has been changed to : 3*
- on **pain.001.001.03/PaymentInformation/Debtor/PostalAddress/AddressLine**  
*This element has change repeatability, the maximum occurrence has been changed to : 3*
- on **pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Creditor/PostalAddress/AddressLine**  
*This element has change repeatability, the maximum occurrence has been changed to : 3*
- on **pain.001.001.03/PaymentInformation/UltimateDebtor/PostalAddress/AddressLine**  
*This element has change repeatability, the maximum occurrence has been changed to : 3*

## 4.46 Purpose2Choice

*Definition:* Specifies the underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
| 2.87  | Code         | <Cd>      | {Or | [1..1] |                  | 108  |
| 2.88  | Proprietary  | <Prtry>   | Or} | [1..1] |                  | 108  |

Used in element(s)

["Purpose" on page 40](#)

## 4.46.1 Code

*XML Tag:* Cd

*Presence:* [1..1]

*Definition:* Underlying reason for the payment transaction, as published in an external purpose code list.

*Datatype:* ["ExternalPurpose1Code" on page 164](#)

## 4.46.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Purpose, in a proprietary form.

*Datatype:* ["Max35Text" on page 171](#)

## 4.47 ReferredDocumentInformation3

*Definition:* Set of elements used to identify the documents referred to in the remittance information.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|----|--------|------------------|------|
| 2.102 | Type         | <Tp>      |    | [0..1] |                  | 108  |
| 2.107 | Number       | <Nb>      |    | [0..1] | 💡                | 108  |
| 2.108 | RelatedDate  | <RltdDt>  |    | [0..1] | 💡                | 109  |

**Used in element(s)**

["ReferredDocumentInformation" on page 121](#)

### 4.47.1 Type

*XML Tag:* Tp

*Presence:* [0..1]

*Definition:* Specifies the type of referred document.

The **Tp** block contains the following elements (see datatype ["ReferredDocumentType2" on page 110](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item      | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|-------|-------------------|-------------|----|--------|------------------|------|
| 2.103 | CodeOrProprietary | <CdOrPrtry> |    | [1..1] |                  | 110  |
| 2.106 | Issuer            | <Issr>      |    | [0..1] | 💡                | 110  |

### 4.47.2 Number

*XML Tag:* Nb

*Presence:* [0..1]

*Definition:* Unique and unambiguous identification of the referred document.

*Datatype:* ["Max35Text" on page 171](#)

#### Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/ReferredDocumentInformation/Number](#)) will be ignored by the Receiver.

## 4.47.3 RelatedDate

*XML Tag:* RltdDt

*Presence:* [0..1]

*Definition:* Date associated with the referred document.

*Datatype:* ["ISODate" on page 166](#)

#### Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/ReferredDocumentInformation/RelatedDate](#)) will be ignored by the Receiver.

## 4.48 ReferredDocumentType1Choice

*Definition:* Specifies the type of the document referred in the remittance information.

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines                                                                      | Page |
|-------|--------------|-----------|-----|--------|---------------------------------------------------------------------------------------|------|
| 2.104 | Code         | <Cd>      | {Or | [1..1] |                                                                                       | 109  |
| 2.105 | Proprietary  | <Prtry>   | Or} | [1..1] |  | 110  |

#### Used in element(s)

["CodeOrProprietary" on page 110](#)

### 4.48.1 Code

*XML Tag:* Cd

*Presence:* [1..1]

*Definition:* Document type in a coded form.

*Datatype:* ["DocumentType5Code" on page 156](#)

## 4.48.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Proprietary identification of the type of the remittance document.

*Datatype:* "Max35Text" on page 171

### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/ReferredDocumentInformation/Type/CodeOrProprietary/Proprietary) will be ignored by the Receiver.

## 4.49 ReferredDocumentType2

*Definition:* Specifies the type of the document referred in the remittance information.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item      | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|-------|-------------------|-------------|----|--------|------------------|------|
| 2.103 | CodeOrProprietary | <CdOrPrtry> |    | [1..1] |                  | 110  |
| 2.106 | Issuer            | <Issr>      |    | [0..1] | 💡                | 110  |

### Used in element(s)

"Type" on page 108

### 4.49.1 CodeOrProprietary

*XML Tag:* CdOrPrtry

*Presence:* [1..1]

*Definition:* Provides the type details of the referred document.

The **CdOrPrtry** block contains the following elements (see datatype "ReferredDocumentType1Choice" on page 109 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
| 2.104 | Code         | <Cd>      | {Or | [1..1] |                  | 109  |
| 2.105 | Proprietary  | <Prtry>   | Or} | [1..1] | 💡                | 110  |

### 4.49.2 Issuer

*XML Tag:* Issr

*Presence:* [0..1]

*Definition:* Identification of the issuer of the reference document type.

*Datatype:* "Max35Text" on page 171

#### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/ReferredDocumentInformation/Type/Issuer) will be ignored by the Receiver.

## 4.50 RegulatoryAuthority2

*Definition:* Entity requiring the regulatory reporting information.

🚫 Removed - 💡 Ignored - ⚠ Details below - 📘 Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|--------------|-----------|----|--------|------------------|------|
| 11.1.2 | Name         | <Nm>      |    | [0..1] |                  | 111  |
| 11.1.3 | Country      | <Ctry>    |    | [0..1] |                  | 111  |

#### Used in element(s)

"Authority" on page 112

### 4.50.1 Name

*XML Tag:* Nm

*Presence:* [0..1]

*Definition:* Name of the entity requiring the regulatory reporting information.

*Datatype:* "Max140Text" on page 169

### 4.50.2 Country

*XML Tag:* Ctry

*Presence:* [0..1]

*Definition:* Country of the entity that requires the regulatory reporting information.

*Datatype:* "CountryCode" on page 154

## 4.51 RegulatoryReporting3

*Definition:* Information needed due to regulatory and/or statutory requirements.

🚫 Removed - ✦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item                  | <XML Tag>       | Or | Mult.  | Usage Guidelines | Page |
|--------|-------------------------------|-----------------|----|--------|------------------|------|
| 11.1.0 | DebitCreditReportingIndicator | <DbtCdtRptgInd> |    | [0..1] | ✦                | 112  |
| 11.1.1 | Authority                     | <Authrty>       |    | [0..1] | ✦                | 112  |
| 11.1.4 | Details                       | <Dtls>          |    | [0..*] |                  | 112  |

Used in element(s)

"RegulatoryReporting" on page 40

## 4.51.1 DebitCreditReportingIndicator

XML Tag: DbtCdtRptgInd

Presence: [0..1]

*Definition:* Identifies whether the regulatory reporting information applies to the debit side, to the credit side or to both debit and credit sides of the transaction.

*Datatype:* "RegulatoryReportingType1Code" on page 176

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RegulatoryReporting/DebitCreditReportingIndicator) will be ignored by the Receiver.

## 4.51.2 Authority

XML Tag: Authrty

Presence: [0..1]

*Definition:* Entity requiring the regulatory reporting information.

The **Authrty** block contains the following elements (see datatype "RegulatoryAuthority2" on page 111 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|--------------|-----------|----|--------|------------------|------|
| 11.1.2 | Name         | <Nm>      |    | [0..1] |                  | 111  |
| 11.1.3 | Country      | <Ctry>    |    | [0..1] |                  | 111  |

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RegulatoryReporting/Authority) will be ignored by the Receiver.

## 4.51.3 Details

*XML Tag:* Dtls

*Presence:* [0..\*]

*Definition:* Set of elements used to provide details on the regulatory reporting information.

The **Dtls** block contains the following elements (see datatype "[StructuredRegulatoryReporting3](#)" on [page 118](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index   | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|---------|--------------|-----------|----|--------|------------------|------|
| 11.1.5  | Type         | <Tp>      |    | [0..1] | 💡                | 119  |
| 11.1.6  | Date         | <Dt>      |    | [0..1] | 💡                | 119  |
| 11.1.7  | Country      | <Ctry>    |    | [0..1] | 💡                | 119  |
| 11.1.8  | Code         | <Cd>      |    | [0..1] | 💡                | 120  |
| 11.1.9  | Amount       | <Amt>     |    | [0..1] | 💡                | 120  |
| 11.1.10 | Information  | <Inf>     |    | [0..*] | ⚠️               | 120  |

## 4.52 RemittanceAmount1

*Definition:* Nature of the amount and currency on a document referred to in the remittance section, typically either the original amount due/payable or the amount actually remitted for the referenced document.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item              | <XML Tag>           | Or | Mult.  | Usage Guidelines | Page |
|-------|---------------------------|---------------------|----|--------|------------------|------|
| 2.110 | DuePayableAmount          | <DuePyblAmt>        |    | [0..1] |                  | 113  |
| 2.111 | DiscountAppliedAmount     | <DscntApldAmt>      |    | [0..1] |                  | 114  |
| 2.112 | CreditNoteAmount          | <CdtNoteAmt>        |    | [0..1] |                  | 114  |
| 2.113 | TaxAmount                 | <TaxAmt>            |    | [0..1] | 💡                | 114  |
| 2.114 | AdjustmentAmountAndReason | <AdjstmntAmtAndRsn> |    | [0..*] | 💡                | 114  |
| 2.119 | RemittedAmount            | <RmtdAmt>           |    | [0..1] |                  | 115  |

**Used in element(s)**

"[ReferredDocumentAmount](#)" on [page 121](#)

### 4.52.1 DuePayableAmount

*XML Tag:* DuePyblAmt

*Presence:* [0..1]

*Definition:* Amount specified is the exact amount due and payable to the creditor.

*Datatype:* "[ActiveOrHistoricCurrencyAndAmount](#)" on [page 138](#)

## 4.52.2 DiscountAppliedAmount

XML Tag: DscntApldAmt

Presence: [0..1]

Definition: Amount of money that results from the application of an agreed discount to the amount due and payable to the creditor.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 138

## 4.52.3 CreditNoteAmount

XML Tag: CdtNoteAmt

Presence: [0..1]

Definition: Amount specified for the referred document is the amount of a credit note.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 138

## 4.52.4 TaxAmount

XML Tag: TaxAmt

Presence: [0..1]

Definition: Quantity of cash resulting from the calculation of the tax.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 138

### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/ReferredDocumentAmount/TaxAmount) will be ignored by the Receiver.

## 4.52.5 AdjustmentAmountAndReason

XML Tag: AdjstmntAmtAndRsn

Presence: [0..\*]

Definition: Set of elements used to provide information on the amount and reason of the document adjustment.

The **AdjstmntAmtAndRsn** block contains the following elements (see datatype "[DocumentAdjustment1](#)" on page 46 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item          | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|-------|-----------------------|-------------|----|--------|------------------|------|
| 2.115 | Amount                | <Amt>       |    | [1..1] |                  | 47   |
| 2.116 | CreditDebitIndicator  | <CdtDbtInd> |    | [0..1] |                  | 47   |
| 2.117 | Reason                | <Rsn>       |    | [0..1] |                  | 47   |
| 2.118 | AdditionalInformation | <AddtlInf>  |    | [0..1] |                  | 47   |

## Usage Guideline details

- This element(**pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/ReferredDocumentAmount/AdjustmentAmountAndReason**) will be ignored by the Receiver.

## 4.52.6 RemittedAmount

*XML Tag:* RmtdAmt

*Presence:* [0..1]

*Definition:* Amount of money remitted for the referred document.

*Datatype:* ["ActiveOrHistoricCurrencyAndAmount" on page 138](#)

## 4.53 RemittanceInformation5

*Definition:* Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system.

🚫 Removed - 💡 Ignored - ⚠️ Details below - 📌 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|----|--------|------------------|------|
| 2.99  | Unstructured | <Ustrd>   |    | [0..*] | ⚠️               | 115  |
| 2.100 | Structured   | <Strd>    |    | [0..*] |                  | 116  |

## Used in element(s)

["RemittanceInformation" on page 42](#)

### 4.53.1 Unstructured

*XML Tag:* Ustrd

*Presence:* [0..\*]

*Definition:* Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form.

*Datatype:* ["Max140Text" on page 169](#)

## Usage Guideline details

- on **pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Unstructured**
  - **HSBC\_Unstructured:**

Up to 4 lines of 35 characters can be transmitted to the beneficiary. The first line will be used for the EndToEnd-ID, leaving 3 lines of 35 chars available for additional information. Lines will be wrapped to 35 chars if longer. Information that cannot be passed on will be truncated

- on pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Unstructured

**Comment:**

This is depending on payment instrument.

## 4.53.2 Structured

*XML Tag:* Strd

*Presence:* [0..\*]

*Definition:* Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

The **Strd** block contains the following elements (see datatype "[StructuredRemittanceInformation7](#)" on page 121 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                    | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|-------|---------------------------------|---------------|----|--------|------------------|------|
| 2.101 | ReferredDocumentInformation     | <RfrdDocInf>  |    | [0..*] |                  | 121  |
| 2.109 | ReferredDocumentAmount          | <RfrdDocAmt>  |    | [0..1] |                  | 121  |
| 2.120 | CreditorReferenceInformation    | <CdtrRefInf>  |    | [0..1] |                  | 122  |
| 2.127 | Invoicer                        | <Invcr>       |    | [0..1] | 💡                | 122  |
| 2.128 | Invoicee                        | <Invcee>      |    | [0..1] | 💡                | 123  |
| 2.129 | AdditionalRemittanceInformation | <AddtlRmtInf> |    | [0..3] | 💡                | 123  |

## 4.54 RemittanceLocation2

*Definition:* Set of elements used to provide information on the remittance advice.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                        | <XML Tag>          | Or | Mult.  | Usage Guidelines | Page |
|-------|-------------------------------------|--------------------|----|--------|------------------|------|
| 2.92  | RemittanceIdentification            | <RmtId>            |    | [0..1] | ⚠                | 116  |
| 2.93  | RemittanceLocationMethod            | <RmtLctnMtd>       |    | [0..1] |                  | 117  |
| 2.94  | RemittanceLocationElectronicAddress | <RmtLctnElctrcAdr> |    | [0..1] |                  | 117  |
| 2.95  | RemittanceLocationPostalAddress     | <RmtLctnPstlAdr>   |    | [0..1] |                  | 117  |

**Used in element(s)**

"[RelatedRemittanceInformation](#)" on page 41

### 4.54.1 RemittanceIdentification

*XML Tag:* RmtId

*Presence:* [0..1]

*Definition:* Unique identification, as assigned by the initiating party, to unambiguously identify the remittance information sent separately from the payment instruction, such as a remittance advice.

*Datatype:* ["Max35Text" on page 171](#)

#### Usage Guideline details

- on **pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RelatedRemittanceInformation/RemittanceIdentification**

**Comment:**

Refer to Advising Appendix

## 4.54.2 RemittanceLocationMethod

*XML Tag:* RmtLctnMtd

*Presence:* [0..1]

*Definition:* Method used to deliver the remittance advice information.

*Datatype:* ["RemittanceLocationMethod2Code" on page 177](#)

## 4.54.3 RemittanceLocationElectronicAddress

*XML Tag:* RmtLctnElctrncAdr

*Presence:* [0..1]

*Definition:* Electronic address to which an agent is to send the remittance information.

*Datatype:* ["Max2048Text" on page 170](#)

## 4.54.4 RemittanceLocationPostalAddress

*XML Tag:* RmtLctnPstlAdr

*Presence:* [0..1]

*Definition:* Postal address to which an agent is to send the remittance information.

The **RmtLctnPstlAdr** block contains the following elements (see datatype ["NameAndAddress10" on page 64](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index                    | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------------------------|--------------|-----------|----|--------|------------------|------|
| 2.56 ,<br>2.62 ,<br>2.96 | Name         | <Nm>      |    | [1..1] |                  | 65   |
| 2.57 ,<br>2.63 ,<br>2.97 | Address      | <Adr>     |    | [1..1] |                  | 65   |

## 4.55 ServiceLevel8Choice\_\_1

*Definition:* Specifies the service level of the transaction.

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

| Index          | Message Item | <XML Tag> | Or  | Mult.  | Usage Guidelines | Page |
|----------------|--------------|-----------|-----|--------|------------------|------|
| 2.9 ,<br>2.34  | Code         | <Cd>      | {Or | [1..1] |                  | 118  |
| 2.10 ,<br>2.35 | Proprietary  | <Prtry>   | Or} | [1..1] | ♦ 🚫              | 118  |

**Used in element(s)**

"ServiceLevel" on page 92

## 4.55.1 Code

*XML Tag:* Cd

*Presence:* [1..1]

*Definition:* Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list.

*Datatype:* "HSBC\_UK\_ServiceLevel" on page 165

## 4.55.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Specifies a pre-agreed service or level of service between the parties, as a proprietary code.

*Datatype:* "Max35Text" on page 171

**Usage Guideline details**

- This element(pain.001.001.03/PaymentInformation/PaymentTypeInformation/ServiceLevel/Proprietary) is removed.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/PaymentTypeInformation/ServiceLevel/Proprietary) is removed.
- This element(pain.001.001.03/PaymentInformation/PaymentTypeInformation/ServiceLevel/Proprietary) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/PaymentTypeInformation/ServiceLevel/Proprietary) will be ignored by the Receiver.

## 4.56 StructuredRegulatoryReporting3

*Definition:* Information needed due to regulatory and statutory requirements.

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

| Index   | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|---------|--------------|-----------|----|--------|------------------|------|
| 11.1.5  | Type         | <Tp>      |    | [0..1] | ♦                | 119  |
| 11.1.6  | Date         | <Dt>      |    | [0..1] | ♦                | 119  |
| 11.1.7  | Country      | <Ctry>    |    | [0..1] | ♦                | 119  |
| 11.1.8  | Code         | <Cd>      |    | [0..1] | ♦                | 120  |
| 11.1.9  | Amount       | <Amt>     |    | [0..1] | ♦                | 120  |
| 11.1.10 | Information  | <Inf>     |    | [0..*] | ⚠                | 120  |

Used in element(s)

"Details" on page 112

## 4.56.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of the information supplied in the regulatory reporting details.

Datatype: "Max35Text" on page 171

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RegulatoryReporting/Details/Type) will be ignored by the Receiver.

## 4.56.2 Date

XML Tag: Dt

Presence: [0..1]

Definition: Date related to the specified type of regulatory reporting details.

Datatype: "ISODate" on page 166

Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RegulatoryReporting/Details/Date) will be ignored by the Receiver.

## 4.56.3 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Country related to the specified type of regulatory reporting details.

Datatype: ["CountryCode" on page 154](#)

#### Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RegulatoryReporting/Details/Country](#)) will be ignored by the Receiver.

## 4.56.4 Code

XML Tag: Cd

Presence: [0..1]

Definition: Specifies the nature, purpose, and reason for the transaction to be reported for regulatory and statutory requirements in a coded form.

Datatype: ["Max10Text" on page 168](#)

#### Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RegulatoryReporting/Details/Code](#)) will be ignored by the Receiver.

## 4.56.5 Amount

XML Tag: Amt

Presence: [0..1]

Definition: Amount of money to be reported for regulatory and statutory requirements.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 138](#)

#### Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RegulatoryReporting/Details/Amount](#)) will be ignored by the Receiver.

## 4.56.6 Information

XML Tag: Inf

Presence: [0..\*]

Definition: Additional details that cater for specific domestic regulatory requirements.

Datatype: ["Max35Text" on page 171](#)

#### Usage Guideline details

- on [pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RegulatoryReporting/Details/Information](#)
  - **HSBC\_RegulatoryDetails\_Information:**

For crossborder payment in transaction currency of CNY, purpose of payment is mandatory as a regulatory and clearing requirement.

Purpose must be one of below:

- 1) /BUSINESS/CAPITAL TRF
- 2) /BUSINESS/CHARITY DONATION
- 3) /BUSINESS/CURRENT ACC TXN
- 4) /BUSINESS/GOODS TRADE
- 5) /BUSINESS/SERVICE TRADE

## 4.57 StructuredRemittanceInformation7

*Definition:* Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item                    | <XML Tag>     | Or | Mult.  | Usage Guidelines | Page |
|-------|---------------------------------|---------------|----|--------|------------------|------|
| 2.101 | ReferredDocumentInformation     | <RfrdDocInf>  |    | [0..*] |                  | 121  |
| 2.109 | ReferredDocumentAmount          | <RfrdDocAmt>  |    | [0..1] |                  | 121  |
| 2.120 | CreditorReferenceInformation    | <CdtrRefInf>  |    | [0..1] |                  | 122  |
| 2.127 | Invoicer                        | <Invcr>       |    | [0..1] | 💡                | 122  |
| 2.128 | Invoicee                        | <Invcee>      |    | [0..1] | 💡                | 123  |
| 2.129 | AdditionalRemittanceInformation | <AddtlRmtInf> |    | [0..3] | 💡                | 123  |

Used in element(s)

"Structured" on page 116

### 4.57.1 ReferredDocumentInformation

XML Tag: RfrdDocInf

Presence: [0..\*]

*Definition:* Set of elements used to identify the documents referred to in the remittance information.

The **RfrdDocInf** block contains the following elements (see datatype "[ReferredDocumentInformation3](#)" on page 108 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|----|--------|------------------|------|
| 2.102 | Type         | <Tp>      |    | [0..1] |                  | 108  |
| 2.107 | Number       | <Nb>      |    | [0..1] | 💡                | 108  |
| 2.108 | RelatedDate  | <RltdDt>  |    | [0..1] | 💡                | 109  |

### 4.57.2 ReferredDocumentAmount

*XML Tag:* RfrdDocAmt

*Presence:* [0..1]

*Definition:* Set of elements used to provide details on the amounts of the referred document.

The **RfrdDocAmt** block contains the following elements (see datatype "[RemittanceAmount1](#)" on [page 113](#) for details)

🚫 Removed - ⬜ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item              | <XML Tag>           | Or | Mult.  | Usage Guidelines | Page |
|-------|---------------------------|---------------------|----|--------|------------------|------|
| 2.110 | DuePayableAmount          | <DuePyblAmt>        |    | [0..1] |                  | 113  |
| 2.111 | DiscountAppliedAmount     | <DscntApldAmt>      |    | [0..1] |                  | 114  |
| 2.112 | CreditNoteAmount          | <CdtNoteAmt>        |    | [0..1] |                  | 114  |
| 2.113 | TaxAmount                 | <TaxAmt>            |    | [0..1] | ⬜                | 114  |
| 2.114 | AdjustmentAmountAndReason | <AdjstmntAmtAndRsn> |    | [0..*] | ⬜                | 114  |
| 2.119 | RemittedAmount            | <RmtdAmt>           |    | [0..1] |                  | 115  |

## 4.57.3 CreditorReferenceInformation

*XML Tag:* CdtrRefInf

*Presence:* [0..1]

*Definition:* Reference information provided by the creditor to allow the identification of the underlying documents.

The **CdtrRefInf** block contains the following elements (see datatype "[CreditorReferenceInformation2](#)" on [page 42](#) for details)

🚫 Removed - ⬜ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|-------|--------------|-----------|----|--------|------------------|------|
| 2.121 | Type         | <Tp>      |    | [0..1] |                  | 42   |
| 2.126 | Reference    | <Ref>     |    | [0..1] | ⬜                | 42   |

## 4.57.4 Invoicer

*XML Tag:* Invcr

*Presence:* [0..1]

*Definition:* Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor.

The **Invcr** block contains the following elements (see datatype "[PartyIdentification32](#)" on page 70 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item       | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|--------|--------------------|-------------|----|--------|------------------|------|
| 9.1.0  | Name               | <Nm>        |    | [0..1] |                  | 70   |
| 9.1.1  | PostalAddress      | <PstlAdr>   |    | [0..1] |                  | 70   |
| 9.1.12 | Identification     | <Id>        |    | [0..1] |                  | 71   |
| 9.1.33 | CountryOfResidence | <CtryOfRes> |    | [0..1] |                  | 72   |
| 9.1.34 | ContactDetails     | <CtctDtls>  |    | [0..1] |                  | 72   |

#### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/Invoicer) will be ignored by the Receiver.

## 4.57.5 Invoicee

*XML Tag:* Invcee

*Presence:* [0..1]

*Definition:* Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor.

The **Invcee** block contains the following elements (see datatype "[PartyIdentification32](#)" on page 70 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item       | <XML Tag>   | Or | Mult.  | Usage Guidelines | Page |
|--------|--------------------|-------------|----|--------|------------------|------|
| 9.1.0  | Name               | <Nm>        |    | [0..1] |                  | 70   |
| 9.1.1  | PostalAddress      | <PstlAdr>   |    | [0..1] |                  | 70   |
| 9.1.12 | Identification     | <Id>        |    | [0..1] |                  | 71   |
| 9.1.33 | CountryOfResidence | <CtryOfRes> |    | [0..1] |                  | 72   |
| 9.1.34 | ContactDetails     | <CtctDtls>  |    | [0..1] |                  | 72   |

#### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/Invoicee) will be ignored by the Receiver.

## 4.57.6 AdditionalRemittanceInformation

*XML Tag:* AddtlRmtInf

*Presence:* [0..3]

*Definition:* Additional information, in free text form, to complement the structured remittance information.

*Datatype:* "Max140Text" on page 169

#### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/AdditionalRemittanceInformation) will be ignored by the Receiver.

## 4.58 TaxAmount1

*Definition:* Set of elements used to provide information on the tax amount(s) of tax record.

🚫 Removed - 💠 Ignored - ⚠️ Details below - M Mandatory - R[x..x] Repeatability[details]

| Index   | Message Item      | <XML Tag>      | Or | Mult.  | Usage Guidelines | Page |
|---------|-------------------|----------------|----|--------|------------------|------|
| 13.1.32 | Rate              | <Rate>         |    | [0..1] |                  | 124  |
| 13.1.33 | TaxableBaseAmount | <TaxblBaseAmt> |    | [0..1] |                  | 124  |
| 13.1.34 | TotalAmount       | <TtlAmt>       |    | [0..1] | 💠                | 124  |
| 13.1.35 | Details           | <Dtls>         |    | [0..*] |                  | 125  |

**Used in element(s)**

"TaxAmount" on page 135

### 4.58.1 Rate

*XML Tag:* Rate

*Presence:* [0..1]

*Definition:* Rate used to calculate the tax.

*Datatype:* "PercentageRate" on page 175

### 4.58.2 TaxableBaseAmount

*XML Tag:* TaxblBaseAmt

*Presence:* [0..1]

*Definition:* Amount of money on which the tax is based.

*Datatype:* "ActiveOrHistoricCurrencyAndAmount" on page 138

### 4.58.3 TotalAmount

*XML Tag:* TtlAmt

*Presence:* [0..1]

*Definition:* Total amount that is the result of the calculation of the tax for the record.

Datatype: ["ActiveOrHistoricCurrencyAndAmount"](#) on page 138

#### Usage Guideline details

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Record/TaxAmount/TotalAmount](#)) will be ignored by the Receiver.

## 4.58.4 Details

XML Tag: Dtls

Presence: [0..\*]

Definition: Set of elements used to provide details on the tax period and amount.

The **Dtls** block contains the following elements (see datatype ["TaxRecordDetails1"](#) on page 136 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index   | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|---------|--------------|-----------|----|--------|------------------|------|
| 13.1.36 | Period       | <Prd>     |    | [0..1] |                  | 136  |
| 13.1.42 | Amount       | <Amt>     |    | [1..1] | 💡                | 136  |

## 4.59 TaxAuthorisation1

Definition: Details of the authorised tax paying party.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index   | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|---------|--------------|-----------|----|--------|------------------|------|
| 13.1.9  | Title        | <Titl>    |    | [0..1] |                  | 125  |
| 13.1.10 | Name         | <Nm>      |    | [0..1] |                  | 125  |

#### Used in element(s)

["Authorisation"](#) on page 131

### 4.59.1 Title

XML Tag: Titl

Presence: [0..1]

Definition: Title or position of debtor or the debtor's authorised representative.

Datatype: ["Max35Text"](#) on page 171

### 4.59.2 Name

XML Tag: Nm

Presence: [0..1]

*Definition:* Name of the debtor or the debtor's authorised representative.

*Datatype:* "Max140Text" on page 169

## 4.60 TaxInformation3

*Definition:* Details about tax paid, or to be paid, to the government in accordance with the law, including pre-defined parameters such as thresholds and type of account.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index   | Message Item           | <XML Tag>         | Or | Mult.  | Usage Guidelines | Page |
|---------|------------------------|-------------------|----|--------|------------------|------|
| 13.1.0  | Creditor               | <Cdtr>            |    | [0..1] |                  | 126  |
| 13.1.4  | Debtor                 | <Dbtr>            |    | [0..1] |                  | 126  |
| 13.1.11 | AdministrationZone     | <AdmstnZn>        |    | [0..1] | 💡                | 127  |
| 13.1.12 | ReferenceNumber        | <RefNb>           |    | [0..1] |                  | 127  |
| 13.1.13 | Method                 | <Mtd>             |    | [0..1] |                  | 127  |
| 13.1.14 | TotalTaxableBaseAmount | <TtlTaxblBaseAmt> |    | [0..1] | 💡                | 127  |
| 13.1.15 | TotalTaxAmount         | <TtlTaxAmt>       |    | [0..1] | 💡                | 128  |
| 13.1.16 | Date                   | <Dt>              |    | [0..1] | 💡                | 128  |
| 13.1.17 | SequenceNumber         | <SeqNb>           |    | [0..1] |                  | 128  |
| 13.1.18 | Record                 | <Rcrd>            |    | [0..*] | R[0..10]         | 128  |

Used in element(s)

"Tax" on page 40

### 4.60.1 Creditor

*XML Tag:* Cdtr

*Presence:* [0..1]

*Definition:* Party on the credit side of the transaction to which the tax applies.

The **Cdtr** block contains the following elements (see datatype "TaxParty1" on page 129 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item               | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|----------------------------|-----------|----|--------|------------------|------|
| 13.1.1 | TaxIdentification          | <TaxId>   |    | [0..1] |                  | 129  |
| 13.1.2 | RegistrationIdentification | <RegnId>  |    | [0..1] | 💡                | 130  |
| 13.1.3 | TaxType                    | <TaxTp>   |    | [0..1] | 💡                | 130  |

### 4.60.2 Debtor

*XML Tag:* Dbtr

*Presence:* [0..1]

*Definition:* Set of elements used to identify the party on the debit side of the transaction to which the tax applies.

The **Dbtr** block contains the following elements (see datatype "[TaxParty2](#)" on page 130 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item               | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|----------------------------|-----------|----|--------|------------------|------|
| 13.1.5 | TaxIdentification          | <TaxId>   |    | [0..1] |                  | 130  |
| 13.1.6 | RegistrationIdentification | <RegnId>  |    | [0..1] | ✦                | 131  |
| 13.1.7 | TaxType                    | <TaxTp>   |    | [0..1] | ✦                | 131  |
| 13.1.8 | Authorisation              | <Authstn> |    | [0..1] | ✦                | 131  |

## 4.60.3 AdministrationZone

*XML Tag:* AdmstnZn

*Presence:* [0..1]

*Definition:* Territorial part of a country to which the tax payment is related.

*Datatype:* "[Max35Text](#)" on page 171

### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/AdministrationZone) will be ignored by the Receiver.

## 4.60.4 ReferenceNumber

*XML Tag:* RefNb

*Presence:* [0..1]

*Definition:* Tax reference information that is specific to a taxing agency.

*Datatype:* "[Max140Text](#)" on page 169

## 4.60.5 Method

*XML Tag:* Mtd

*Presence:* [0..1]

*Definition:* Method used to indicate the underlying business or how the tax is paid.

*Datatype:* "[Max35Text](#)" on page 171

## 4.60.6 TotalTaxableBaseAmount

*XML Tag:* TtlTaxblBaseAmt

*Presence:* [0..1]

*Definition:* Total amount of money on which the tax is based.

*Datatype:* ["ActiveOrHistoricCurrencyAndAmount" on page 138](#)

**Usage Guideline details**

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/TotalTaxableBaseAmount](#)) will be ignored by the Receiver.

## 4.60.7 TotalTaxAmount

*XML Tag:* TtlTaxAmt

*Presence:* [0..1]

*Definition:* Total amount of money as result of the calculation of the tax.

*Datatype:* ["ActiveOrHistoricCurrencyAndAmount" on page 138](#)

**Usage Guideline details**

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/TotalTaxAmount](#)) will be ignored by the Receiver.

## 4.60.8 Date

*XML Tag:* Dt

*Presence:* [0..1]

*Definition:* Date by which tax is due.

*Datatype:* ["ISODate" on page 166](#)

**Usage Guideline details**

- This element([pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Date](#)) will be ignored by the Receiver.

## 4.60.9 SequenceNumber

*XML Tag:* SeqNb

*Presence:* [0..1]

*Definition:* Sequential number of the tax report.

*Datatype:* ["Number" on page 173](#)

## 4.60.10 Record

*XML Tag:* Rcrd

*Presence:* [0..\*]

*Definition:* Record of tax details.

The **Rcrd** block contains the following elements (see datatype "[TaxRecord1](#)" on page 133 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index   | Message Item              | <XML Tag>  | Or | Mult.  | Usage Guidelines | Page |
|---------|---------------------------|------------|----|--------|------------------|------|
| 13.1.19 | Type                      | <Tp>       |    | [0..1] |                  | 133  |
| 13.1.20 | Category                  | <Ctgy>     |    | [0..1] | 💡                | 134  |
| 13.1.21 | CategoryDetails           | <CtgyDtls> |    | [0..1] | 💡                | 134  |
| 13.1.22 | DebtorStatus              | <DbtrSts>  |    | [0..1] | 💡                | 134  |
| 13.1.23 | CertificateIdentification | <CertId>   |    | [0..1] |                  | 134  |
| 13.1.24 | FormsCode                 | <FrmsCd>   |    | [0..1] |                  | 135  |
| 13.1.25 | Period                    | <Prd>      |    | [0..1] |                  | 135  |
| 13.1.31 | TaxAmount                 | <TaxAmt>   |    | [0..1] |                  | 135  |
| 13.1.43 | AdditionalInformation     | <AddtlInf> |    | [0..1] |                  | 135  |

#### Usage Guideline details

- on [pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Record](#)  
This element has change repeatability, the maximum occurrence has been changed to : 10

## 4.61 TaxParty1

*Definition:* Details about the entity involved in the tax paid or to be paid.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item               | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|----------------------------|-----------|----|--------|------------------|------|
| 13.1.1 | TaxIdentification          | <TaxId>   |    | [0..1] |                  | 129  |
| 13.1.2 | RegistrationIdentification | <RegnId>  |    | [0..1] | 💡                | 130  |
| 13.1.3 | TaxType                    | <TaxTp>   |    | [0..1] | 💡                | 130  |

#### Used in element(s)

["Creditor"](#) on page 126

### 4.61.1 TaxIdentification

*XML Tag:* TaxId

*Presence:* [0..1]

*Definition:* Tax identification number of the creditor.

*Datatype:* ["Max35Text"](#) on page 171

## 4.61.2 RegistrationIdentification

*XML Tag:* RegnId

*Presence:* [0..1]

*Definition:* Unique identification, as assigned by an organisation, to unambiguously identify a party.

*Datatype:* "Max35Text" on page 171

### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Creditor/RegistrationIdentification) will be ignored by the Receiver.

## 4.61.3 TaxType

*XML Tag:* TaxTp

*Presence:* [0..1]

*Definition:* Type of tax payer.

*Datatype:* "Max35Text" on page 171

### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Creditor/TaxType) will be ignored by the Receiver.

## 4.62 TaxParty2

*Definition:* Details about the entity involved in the tax paid or to be paid.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index  | Message Item               | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|--------|----------------------------|-----------|----|--------|------------------|------|
| 13.1.5 | TaxIdentification          | <TaxId>   |    | [0..1] |                  | 130  |
| 13.1.6 | RegistrationIdentification | <RegnId>  |    | [0..1] | 💡                | 131  |
| 13.1.7 | TaxType                    | <TaxTp>   |    | [0..1] | 💡                | 131  |
| 13.1.8 | Authorisation              | <Authstn> |    | [0..1] | 💡                | 131  |

### Used in element(s)

"Debtor" on page 126

## 4.62.1 TaxIdentification

*XML Tag:* TaxId

*Presence:* [0..1]

*Definition:* Tax identification number of the debtor.

*Datatype:* "Max35Text" on page 171

## 4.62.2 RegistrationIdentification

*XML Tag:* RegnId

*Presence:* [0..1]

*Definition:* Unique identification, as assigned by an organisation, to unambiguously identify a party.

*Datatype:* "Max35Text" on page 171

### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Debtor/RegistrationIdentification) will be ignored by the Receiver.

## 4.62.3 TaxType

*XML Tag:* TaxTp

*Presence:* [0..1]

*Definition:* Type of tax payer.

*Datatype:* "Max35Text" on page 171

### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Debtor/TaxType) will be ignored by the Receiver.

## 4.62.4 Authorisation

*XML Tag:* Authstn

*Presence:* [0..1]

*Definition:* Details of the authorised tax paying party.

The **Authstn** block contains the following elements (see datatype "TaxAuthorisation1" on page 125 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index   | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|---------|--------------|-----------|----|--------|------------------|------|
| 13.1.9  | Title        | <Tit/>    |    | [0..1] |                  | 125  |
| 13.1.10 | Name         | <Nm>      |    | [0..1] |                  | 125  |

## Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Debtor/Authorisation) will be ignored by the Receiver.

## 4.63 TaxPeriod1

*Definition:* Period of time details related to the tax payment.

Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

| Index                | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines                                                                    | Page |
|----------------------|--------------|-----------|----|--------|-------------------------------------------------------------------------------------|------|
| 13.1.26 ,<br>13.1.37 | Year         | <Yr>      |    | [0..1] |                                                                                     | 132  |
| 13.1.27 ,<br>13.1.38 | Type         | <Tp>      |    | [0..1] |  | 132  |
| 13.1.28 ,<br>13.1.39 | FromDate     | <FrToDt>  |    | [0..1] |  | 132  |

### Used in element(s)

"Period" on page 136, "Period" on page 135

### 4.63.1 Year

*XML Tag:* Yr

*Presence:* [0..1]

*Definition:* Year related to the tax payment.

*Datatype:* "ISODate" on page 166

### 4.63.2 Type

*XML Tag:* Tp

*Presence:* [0..1]

*Definition:* Identification of the period related to the tax payment.

*Datatype:* "TaxRecordPeriod1Code" on page 179

## Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Record/Period/Type) will be ignored by the Receiver.
- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Record/TaxAmount/Details/Period/Type) will be ignored by the Receiver.

### 4.63.3 FromToDate

*XML Tag:* FrToDt

*Presence:* [0..1]

*Definition:* Range of time between a start date and an end date for which the tax report is provided.

The **FrToDt** block contains the following elements (see datatype "[DatePeriodDetails](#)" on page 46 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index                | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|----------------------|--------------|-----------|----|--------|------------------|------|
| 13.1.29 ,<br>13.1.40 | FromDate     | <FrDt>    |    | [1..1] |                  | 46   |
| 13.1.30 ,<br>13.1.41 | ToDate       | <ToDt>    |    | [1..1] |                  | 46   |

#### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Record/TaxAmount/Details/Period/FromToDate) will be ignored by the Receiver.

## 4.64 TaxRecord1

*Definition:* Set of elements used to define the tax record.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index   | Message Item              | <XML Tag>  | Or | Mult.  | Usage Guidelines | Page |
|---------|---------------------------|------------|----|--------|------------------|------|
| 13.1.19 | Type                      | <Tp>       |    | [0..1] |                  | 133  |
| 13.1.20 | Category                  | <Ctgy>     |    | [0..1] | 💡                | 134  |
| 13.1.21 | CategoryDetails           | <CtgyDtls> |    | [0..1] | 💡                | 134  |
| 13.1.22 | DebtorStatus              | <DbtrSts>  |    | [0..1] | 💡                | 134  |
| 13.1.23 | CertificateIdentification | <CertId>   |    | [0..1] |                  | 134  |
| 13.1.24 | FormsCode                 | <FrmsCd>   |    | [0..1] |                  | 135  |
| 13.1.25 | Period                    | <Prd>      |    | [0..1] |                  | 135  |
| 13.1.31 | TaxAmount                 | <TaxAmt>   |    | [0..1] |                  | 135  |
| 13.1.43 | AdditionalInformation     | <AddtlInf> |    | [0..1] |                  | 135  |

**Used in element(s)**

"Record" on page 128

### 4.64.1 Type

*XML Tag:* Tp

*Presence:* [0..1]

*Definition:* High level code to identify the type of tax details.

*Datatype:* "Max35Text" on page 171

## 4.64.2 Category

*XML Tag:* CtgY

*Presence:* [0..1]

*Definition:* Specifies the tax code as published by the tax authority.

*Datatype:* "Max35Text" on page 171

### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Record/Category) will be ignored by the Receiver.

## 4.64.3 CategoryDetails

*XML Tag:* CtgYDtls

*Presence:* [0..1]

*Definition:* Provides further details of the category tax code.

*Datatype:* "Max35Text" on page 171

### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Record/CategoryDetails) will be ignored by the Receiver.

## 4.64.4 DebtorStatus

*XML Tag:* DbtrSts

*Presence:* [0..1]

*Definition:* Code provided by local authority to identify the status of the party that has drawn up the settlement document.

*Datatype:* "Max35Text" on page 171

### Usage Guideline details

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Record/DebtorStatus) will be ignored by the Receiver.

## 4.64.5 CertificateIdentification

*XML Tag:* CertId

*Presence:* [0..1]

*Definition:* Identification number of the tax report as assigned by the taxing authority.

*Datatype:* "Max35Text" on page 171

## 4.64.6 FormsCode

*XML Tag:* FrmsCd

*Presence:* [0..1]

*Definition:* Identifies, in a coded form, on which template the tax report is to be provided.

*Datatype:* "Max35Text" on page 171

## 4.64.7 Period

*XML Tag:* Prd

*Presence:* [0..1]

*Definition:* Set of elements used to provide details on the period of time related to the tax payment.

The **Prd** block contains the following elements (see datatype "TaxPeriod1" on page 132 for details)

❌ Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index                | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|----------------------|--------------|-----------|----|--------|------------------|------|
| 13.1.26 ,<br>13.1.37 | Year         | <Yr>      |    | [0..1] |                  | 132  |
| 13.1.27 ,<br>13.1.38 | Type         | <Tp>      |    | [0..1] | ✦                | 132  |
| 13.1.28 ,<br>13.1.39 | FromDate     | <FrToDt>  |    | [0..1] |                  | 132  |

## 4.64.8 TaxAmount

*XML Tag:* TaxAmt

*Presence:* [0..1]

*Definition:* Set of elements used to provide information on the amount of the tax record.

The **TaxAmt** block contains the following elements (see datatype "TaxAmount1" on page 124 for details)

❌ Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index   | Message Item      | <XML Tag>      | Or | Mult.  | Usage Guidelines | Page |
|---------|-------------------|----------------|----|--------|------------------|------|
| 13.1.32 | Rate              | <Rate>         |    | [0..1] |                  | 124  |
| 13.1.33 | TaxableBaseAmount | <TaxblBaseAmt> |    | [0..1] |                  | 124  |
| 13.1.34 | TotalAmount       | <TtlAmt>       |    | [0..1] | ✦                | 124  |
| 13.1.35 | Details           | <Dtls>         |    | [0..*] |                  | 125  |

## 4.64.9 AdditionalInformation

*XML Tag:* AddtlInf

*Presence:* [0..1]

*Definition:* Further details of the tax record.

*Datatype:* "Max140Text" on page 169

## 4.65 TaxRecordDetails1

*Definition:* Provides information on the individual tax amount(s) per period of the tax record.

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index   | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|---------|--------------|-----------|----|--------|------------------|------|
| 13.1.36 | Period       | <Prd>     |    | [0..1] |                  | 136  |
| 13.1.42 | Amount       | <Amt>     |    | [1..1] | ✦                | 136  |

**Used in element(s)**

"Details" on page 125

### 4.65.1 Period

*XML Tag:* Prd

*Presence:* [0..1]

*Definition:* Set of elements used to provide details on the period of time related to the tax payment.

The **Prd** block contains the following elements (see datatype "TaxPeriod1" on page 132 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index                | Message Item | <XML Tag> | Or | Mult.  | Usage Guidelines | Page |
|----------------------|--------------|-----------|----|--------|------------------|------|
| 13.1.26 ,<br>13.1.37 | Year         | <Yr>      |    | [0..1] |                  | 132  |
| 13.1.27 ,<br>13.1.38 | Type         | <Tp>      |    | [0..1] | ✦                | 132  |
| 13.1.28 ,<br>13.1.39 | FromDate     | <FrToDt>  |    | [0..1] | ✦                | 132  |

### 4.65.2 Amount

*XML Tag:* Amt

*Presence:* [1..1]

*Definition:* Underlying tax amount related to the specified period.

*Datatype:* "ActiveOrHistoricCurrencyAndAmount" on page 138

**Usage Guideline details**

- This element(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/Tax/Record/TaxAmount/Details/Amount) will be ignored by the Receiver.

## 5 Message Datatypes

**Note** The following chapter identifies the datatypes that are used in the message.

### 5.1 ActiveOrHistoricCurrencyAndAmount

*Definition:* A number of monetary units specified in an active or a historic currency where the unit of currency is explicit and compliant with ISO 4217.

*Type:* Amount

This data type must be used with the following XML Attributes:

| Attribute | Tag | Datatype                                   |
|-----------|-----|--------------------------------------------|
| Currency  | Ccy | "ActiveOrHistoricCurrencyCode" on page 138 |

#### Format

|                |    |
|----------------|----|
| minInclusive   | 0  |
| totalDigits    | 18 |
| fractionDigits | 5  |

#### Rules

##### R23 CurrencyAmount ✓

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

#### Used in element(s)

"Amount" on page 47, "Amount" on page 136, "Amount" on page 48, "Amount" on page 120, "Credit-NoteAmount" on page 114, "DiscountAppliedAmount" on page 114, "DuePayableAmount" on page 113, "InstructedAmount" on page 10, "RemittedAmount" on page 115, "TaxAmount" on page 114, "Taxable-BaseAmount" on page 124, "TotalAmount" on page 124, "TotalTaxAmount" on page 128, "TotalTaxableBaseAmount" on page 127

### 5.2 ActiveOrHistoricCurrencyCode

*Definition:* A code allocated to a currency by a Maintenance Agency under an international identification scheme, as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

*Type:* Code

**Format**

pattern [A-Z]{3,3}

**Rules****R21 ActiveOrHistoricCurrency ✓**

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

**Used in element(s)**

"Currency" on page 16, "CurrencyOfTransfer" on page 48

**Used in attribute(s)**

"ActiveOrHistoricCurrencyAndAmount" on page 138

**Restricts**

"ParentCurrencyCode" on page 173

## 5.3 AddressType2Code

*Definition:* Specifies the type of address.

*Type:* Code

| Code | Name        | Definition                                                 |
|------|-------------|------------------------------------------------------------|
| ADDR | Postal      | Address is the complete postal address.                    |
| BIZZ | Business    | Address is the business address.                           |
| DLVY | DeliveryTo  | Address is the address to which delivery is to take place. |
| HOME | Residential | Address is the home address.                               |
| MLTO | MailTo      | Address is the address to which mail is sent.              |
| PBOX | POBox       | Address is a postal office (PO) box.                       |

**Used in element(s)**

"AddressType" on page 100, "AddressType" on page 96

**Restricts**

"AddressTypeCode" on page 140

## 5.4 AddressTypeCode

*Definition:* Specifies the type of address.

*Type:* Code

| Code | Name        | Definition                                                 |
|------|-------------|------------------------------------------------------------|
| ADDR | Postal      | Address is the complete postal address.                    |
| BIZZ | Business    | Address is the business address.                           |
| DLVY | DeliveryTo  | Address is the address to which delivery is to take place. |
| HOME | Residential | Address is the home address.                               |
| MLTO | MailTo      | Address is the address to which mail is sent.              |
| PBOX | POBox       | Address is a postal office (PO) box.                       |

**Is restricted by**

"AddressType2Code" on page 139

## 5.5 AmountDirectionCode

*Definition:* Specifies if an operation is an increase or a decrease or the result of a reversal operation.

*Type:* Code

| Code | Name           | Definition                                                    |
|------|----------------|---------------------------------------------------------------|
| CRDT | Credit         | Operation is an increase.                                     |
| DBIT | Debit          | Operation is a decrease.                                      |
| RVCD | ReversalCredit | Debit entry used to reverse a previously booked credit entry. |
| RVDB | ReversalDebit  | Credit entry used to reverse a previously booked debit entry. |

**Is restricted by**

"CreditDebitCode" on page 155

## 5.6 AnyBICIdentifier

*Definition:* Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

*Type:* IdentifierSet

**Format**

pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}

**Rules****R20 AnyBIC ✓**

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consists of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC.

**Used in element(s)**

"BICOrBEI" on page 67

## 5.7 Authorisation1Code

*Definition:* Specifies the level of approval depending on a number of factors, including payment type, threshold amount or local country or operations practice.

*Type:* Code

| Code | Name                          | Definition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|------|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AUTH | PreAuthorisedFile             | Indicates a file has been pre authorised or approved within the originating customer environment and no further approval is required.                                                                                                                                                                                                                                                                                                                                                                       |
| FDET | FileLevelAuthorisationDetails | Indicates that a file requires additional file level approval, with the ability to view both the payment information block and supporting customer credit transaction detail.                                                                                                                                                                                                                                                                                                                               |
| FSUM | FileLevelAuthorisationSummary | <p>Indicates that a file requires additional file level approval, with the ability to view only the payment information block level information.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• on pain.001.001.03/GroupHeader/Authorisation/Code/FileLevelAuthorisationSummary</li> </ul> <p><b>Comment:</b><br/>PaymentInformationId is mandatory at this authorisation level and should be unique within a file if multiple batches are used.</p> |

| Code | Name                          | Definition                                                                                                                                                                                                                                                                                                      |
|------|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ILEV | InstructionLevelAuthorisation | <p>Indicates that a file requires all customer transactions to be authorised or approved.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(pain.001.001.03/Group-Header/Authorisation/Code/InstructionLevelAuthorisation) is removed.</li> </ul> |

**Used in element(s)**

"Code" on page 10

**Restricts**

"AuthorisationCode" on page 142

## 5.8 AuthorisationCode

*Definition:* Specifies the level of approval depending on a number of factors, including payment type, threshold amount or local country or operations practice.

*Type:* Code

| Code | Name                          | Definition                                                                                                                                                                    |
|------|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AUTH | PreAuthorisedFile             | Indicates a file has been pre authorised or approved within the originating customer environment and no further approval is required.                                         |
| FDET | FileLevelAuthorisationDetails | Indicates that a file requires additional file level approval, with the ability to view both the payment information block and supporting customer credit transaction detail. |
| FSUM | FileLevelAuthorisationSummary | Indicates that a file requires additional file level approval, with the ability to view only the payment information block level information.                                 |
| ILEV | InstructionLevelAuthorisation | Indicates that a file requires all customer transactions to be authorised or approved.                                                                                        |

**Is restricted by**

"Authorisation1Code" on page 141

## 5.9 BICIdentifier

*Definition:* Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

*Type:* IdentifierSet

#### Format

pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}

#### Rules

##### R22 BIC ✓

Valid BICs for financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consist of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid BIC Code

#### Used in element(s)

["BIC" on page 50](#)

## 5.10 BatchBookingIndicator

*Definition:* Identifies whether the sending party requests a single debit or credit entry per individual transaction or a batch entry for the sum of the amounts of all transactions.

*Type:* Indicator

*Meaning When True:* Identifies that a batch entry for the sum of the amounts of all transactions in the batch or message is requested.

*Meaning When False:* Identifies that a single entry for each of the transactions in the batch or message is requested.

#### Used in element(s)

["BatchBooking" on page 84](#)

## 5.11 CashAccountType4Code

*Definition:* Specifies the nature, or use, of the cash account.

*Type:* Code

| Code | Name        | Definition                                                                           |
|------|-------------|--------------------------------------------------------------------------------------|
| CACC | Current     | Account used to post debits and credits when no specific account has been nominated. |
| CASH | CashPayment | Account used for the payment of cash.                                                |

| Code | Name       | Definition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|------|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|      |            | <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Code/CashPayment) will be ignored by the Receiver.</li> <li>• This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/CashPayment) will be ignored by the Receiver.</li> </ul>                                                                                     |
| CHAR | Charges    | <p>Account used for charges if different from the account for payment.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Code/Charges) will be ignored by the Receiver.</li> <li>• This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/Charges) will be ignored by the Receiver.</li> </ul>                  |
| CISH | CashIncome | <p>Account used for payment of income if different from the current cash account.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Code/CashIncome) will be ignored by the Receiver.</li> <li>• This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/CashIncome) will be ignored by the Receiver.</li> </ul> |
| COMM | Commission | <p>Account used for commission if different from the account for payment.</p>                                                                                                                                                                                                                                                                                                                                                                                                                    |

| Code | Name            | Definition                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|------|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|      |                 | <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Code/Commission) will be ignored by the Receiver.</li> <li>• This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/Commission) will be ignored by the Receiver.</li> </ul>                                                                             |
| LOAN | Loan            | Account used for loans.                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| MGLD | MarginalLending | <p>Account used for a marginal lending facility.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Code/MarginalLending) will be ignored by the Receiver.</li> <li>• This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/MarginalLending) will be ignored by the Receiver.</li> </ul>              |
| MOMA | MoneyMarket     | <p>Account used for money markets if different from the cash account.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Code/MoneyMarket) will be ignored by the Receiver.</li> <li>• This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/MoneyMarket) will be ignored by the Receiver.</li> </ul> |

| Code | Name                | Definition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|------|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NREX | NonResidentExternal | <p>Account used for non-resident external.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Code/NonResidentExternal) will be ignored by the Receiver.</li> <li>• This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/NonResidentExternal) will be ignored by the Receiver.</li> </ul>                                    |
| ODFT | Overdraft           | <p>Account is used for overdrafts.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Code/Overdraft) will be ignored by the Receiver.</li> <li>• This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/Overdraft) will be ignored by the Receiver.</li> </ul>                                                                |
| ONDP | OverNightDeposit    | Account used for overnight deposits.                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| SACC | Settlement          | <p>Account used to post debit and credit entries, as a result of transactions cleared and settled through a specific clearing and settlement system.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Code/Settlement) will be ignored by the Receiver.</li> <li>• This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/</li> </ul> |

| Code | Name    | Definition                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|      |         | xor/Code/Settlement) will be ignored by the Receiver.                                                                                                                                                                                                                                                                                                                                                                                                                 |
| SLRY | Salary  | <p>Accounts used for salary payments.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Code/Salary) will be ignored by the Receiver.</li> <li>• This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/Salary) will be ignored by the Receiver.</li> </ul>                          |
| SVGS | Savings | Account used for savings.                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| TAXE | Tax     | <p>Account used for taxes if different from the account for payment.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Code/Tax) will be ignored by the Receiver.</li> <li>• This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/Tax) will be ignored by the Receiver.</li> </ul> |

| Code | Name        | Definition                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|------|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TRAS | CashTrading | <p>Account used for trading if different from the current cash account.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Type/xor/Code/CashTrading) will be ignored by the Receiver.</li> <li>• This code(pain.001.001.03/PaymentInformation/DebtorAccount/Type/xor/Code/CashTrading) will be ignored by the Receiver.</li> </ul> |

Used in element(s)

"Code" on page 17

Restricts

"CashAccountTypeCode" on page 148

## 5.12 CashAccountTypeCode

*Definition:* Specifies the nature, or use, of the cash account.

*Type:* Code

| Code | Name            | Definition                                                                           |
|------|-----------------|--------------------------------------------------------------------------------------|
| CACC | Current         | Account used to post debits and credits when no specific account has been nominated. |
| CASH | CashPayment     | Account used for the payment of cash.                                                |
| CHAR | Charges         | Account used for charges if different from the account for payment.                  |
| CISH | CashIncome      | Account used for payment of income if different from the current cash account.       |
| COLL | Collateral      | Account is for collateral.                                                           |
| COMM | Commission      | Account used for commission if different from the account for payment.               |
| LEND | Lending         | Account is for the coverage of lending.                                              |
| LOAN | Loan            | Account used for loans.                                                              |
| MARR | MarginReturn    | Account is for margin returns.                                                       |
| MGLD | MarginalLending | Account used for a marginal lending facility.                                        |

| Code | Name                | Definition                                                                                                                                        |
|------|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| MOMA | MoneyMarket         | Account used for money markets if different from the cash account.                                                                                |
| NREX | NonResidentExternal | Account used for non-resident external.                                                                                                           |
| ODFT | Overdraft           | Account is used for overdrafts.                                                                                                                   |
| ONDP | OverNightDeposit    | Account used for overnight deposits.                                                                                                              |
| SACC | Settlement          | Account used to post debit and credit entries, as a result of transactions cleared and settled through a specific clearing and settlement system. |
| SEGT | Segregated          | Account is an segregated account.                                                                                                                 |
| SETT | FinancialSettlement | Account is for financial settlements.                                                                                                             |
| SLRY | Salary              | Accounts used for salary payments.                                                                                                                |
| SVGS | Savings             | Account used for savings.                                                                                                                         |
| TAXE | Tax                 | Account used for taxes if different from the account for payment.                                                                                 |
| TRAS | CashTrading         | Account used for trading if different from the current cash account.                                                                              |

Is restricted by

"CashAccountType4Code" on page 143

## 5.13 ChargeBearerType1Code

*Definition:* Specifies which party(ies) will pay charges due for processing of the instruction.

*Type:* Code

| Code | Name            | Definition                                                                                                                                                                                                                                                                                                                                                                     |
|------|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CRED | BorneByCreditor | All transaction charges are to be borne by the creditor.                                                                                                                                                                                                                                                                                                                       |
| DEBT | BorneByDebtor   | All transaction charges are to be borne by the debtor.                                                                                                                                                                                                                                                                                                                         |
| SHAR | Shared          | In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor, transaction charges on the receiver side are to be borne by the debtor. |

| Code | Name                  | Definition                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|------|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SLEV | FollowingServiceLevel | <p>Charges are to be applied following the rules agreed in the service level and/or scheme.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(pain.001.001.03/PaymentInformation/ChargeBearer/FollowingServiceLevel) is removed.</li> <li>• This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/ChargeBearer/FollowingServiceLevel) will be ignored by the Receiver.</li> </ul> |

**Used in element(s)**

["ChargeBearer" on page 89](#), ["ChargeBearer" on page 30](#)

**Restricts**

["ChargeBearerTypeCode" on page 150](#)

## 5.14 ChargeBearerTypeCode

*Definition:* Specifies which party(ies) will pay charges due for processing of the instruction.

*Type:* Code

| Code | Name                  | Definition                                                                                                                                                                                                                                                                                                                                                                     |
|------|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CRED | BorneByCreditor       | All transaction charges are to be borne by the creditor.                                                                                                                                                                                                                                                                                                                       |
| DEBT | BorneByDebtor         | All transaction charges are to be borne by the debtor.                                                                                                                                                                                                                                                                                                                         |
| SHAR | Shared                | In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor, transaction charges on the receiver side are to be borne by the debtor. |
| SLEV | FollowingServiceLevel | Charges are to be applied following the rules agreed in the service level and/or scheme.                                                                                                                                                                                                                                                                                       |

**Is restricted by**

["ChargeBearerType1Code" on page 149](#)

## 5.15 ChequeDelivery1Code

*Definition:* Specifies the method to be used in delivering a cheque to a party.

*Type:* Code

| Code | Name                       | Definition                                                               |
|------|----------------------------|--------------------------------------------------------------------------|
| CRCD | CourierToCreditor          | Cheque is to be sent through courier services to creditor.               |
| CRDB | CourierToDebtor            | Cheque is to be sent through courier services to debtor.                 |
| CRFA | CourierToFinalAgent        | Cheque is to be sent through courier services to creditor agent.         |
| MLCD | MailToCreditor             | Cheque is to be sent through mail services to creditor.                  |
| MLDB | MailToDebtor               | Cheque is to be sent through mail services to debtor.                    |
| MLFA | MailToFinalAgent           | Cheque is to be sent through mail services to creditor agent.            |
| PUCD | PickUpByCreditor           | Cheque will be picked up by the creditor.                                |
| PUDB | PickUpByDebtor             | Cheque will be picked up by the debtor.                                  |
| PUFA | PickUpByFinalAgent         | Cheque will be picked up by the creditor agent.                          |
| RGCD | RegisteredMailToCreditor   | Cheque is to be sent through registered mail services to creditor.       |
| RGDB | RegisteredMailToDebtor     | Cheque is to be sent through registered mail services to debtor.         |
| RGFA | RegisteredMailToFinalAgent | Cheque is to be sent through registered mail services to creditor agent. |

**Used in element(s)**

"Code" on page 22

**Restricts**

"ChequeDeliveryCode" on page 151

## 5.16 ChequeDeliveryCode

*Definition:* Specifies the method to be used in delivering a cheque to a party.

*Type:* Code

| Code | Name              | Definition                                                 |
|------|-------------------|------------------------------------------------------------|
| CRCD | CourierToCreditor | Cheque is to be sent through courier services to creditor. |
| CRDB | CourierToDebtor   | Cheque is to be sent through courier services to debtor.   |

| Code | Name                       | Definition                                                               |
|------|----------------------------|--------------------------------------------------------------------------|
| CRFA | CourierToFinalAgent        | Cheque is to be sent through courier services to creditor agent.         |
| MLCD | MailToCreditor             | Cheque is to be sent through mail services to creditor.                  |
| MLDB | MailToDebtor               | Cheque is to be sent through mail services to debtor.                    |
| MLFA | MailToFinalAgent           | Cheque is to be sent through mail services to creditor agent.            |
| PUCD | PickUpByCreditor           | Cheque will be picked up by the creditor.                                |
| PUDB | PickUpByDebtor             | Cheque will be picked up by the debtor.                                  |
| PUFA | PickUpByFinalAgent         | Cheque will be picked up by the creditor agent.                          |
| RGCD | RegisteredMailToCreditor   | Cheque is to be sent through registered mail services to creditor.       |
| RGDB | RegisteredMailToDebtor     | Cheque is to be sent through registered mail services to debtor.         |
| RGFA | RegisteredMailToFinalAgent | Cheque is to be sent through registered mail services to creditor agent. |

Is restricted by

"ChequeDelivery1Code" on page 151

## 5.17 ChequeType2Code

*Definition:* Specifies the type of cheque.

*Type:* Code

| Code | Name                    | Definition                                                                                                                                                                                                                                                                                    |
|------|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BCHQ | BankCheque              | Cheque drawn on the account of the debtor's financial institution, which is debited on the debtor's account when the cheque is issued. These cheques are printed by the debtor's financial institution and payment is guaranteed by the financial institution. Synonym is 'cashier's cheque'. |
| CCCH | CertifiedCustomerCheque | Cheque drawn on the account of the debtor, and debited on the debtor's account when the cheque is cashed. The financial institution prints and certifies the cheque, guaranteeing the payment.                                                                                                |
| CCHQ | CustomerCheque          | Cheque drawn on the account of the debtor, and debited on the debtor's account when the cheque is cashed. Synonym is 'corporate cheque'.                                                                                                                                                      |
| DRFT | Draft                   | A guaranteed bank cheque with a future value date (do not pay before), which in commercial terms is a 'negotiable instrument': the beneficiary can receive                                                                                                                                    |

| Code | Name            | Definition                                                                                                                                                                                                                                                             |
|------|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|      |                 | early payment from any bank under subtraction of a discount. The ordering customer's account is debited on value date.                                                                                                                                                 |
| ELDR | ElectronicDraft | An instrument with a future value date (do not pay before), which in commercial terms is a 'negotiable instrument': the beneficiary can receive early payment from any bank under subtraction of a discount. The ordering customer's account is debited on value date. |

**Used in element(s)**

"ChequeType" on page 19

**Restricts**

"ChequeTypeCode" on page 153

## 5.18 ChequeTypeCode

*Definition:* Specifies the type of cheque.

*Type:* Code

| Code | Name                    | Definition                                                                                                                                                                                                                                                                                              |
|------|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BCHQ | BankCheque              | Cheque drawn on the account of the debtor's financial institution, which is debited on the debtor's account when the cheque is issued. These cheques are printed by the debtor's financial institution and payment is guaranteed by the financial institution. Synonym is 'cashier's cheque'.           |
| BKDF | BankDraft               | Cheque drawn by a bank on itself or its agent. A person who owes money to another buys the draft from a bank for cash and hands it to the creditor who need have no fear that it might be dishonoured. A bank draft is also called a banker's cheque, banker's draft, bank check, or treasurer's check. |
| CCCH | CertifiedCustomerCheque | Cheque drawn on the account of the debtor, and debited on the debtor's account when the cheque is cashed. The financial institution prints and certifies the cheque, guaranteeing the payment.                                                                                                          |
| CCHQ | CustomerCheque          | Cheque drawn on the account of the debtor, and debited on the debtor's account when the cheque is cashed. Synonym is 'corporate cheque'.                                                                                                                                                                |
| CLCQ | CircularCheque          | An instruction from a bank to its correspondent bank to pay the creditor a stated sum upon the presentation of a means of identification.                                                                                                                                                               |

| Code | Name            | Definition                                                                                                                                                                                                                                                                        |
|------|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CRCQ | CrossedCheque   | Cheque that must be paid into an account and not cashed over the counter. There are two parallel lines across the face of a crossed cheque.                                                                                                                                       |
| DRFT | Draft           | A guaranteed bank cheque with a future value date (do not pay before), which in commercial terms is a 'negotiable instrument': the beneficiary can receive early payment from any bank under subtraction of a discount. The ordering customer's account is debited on value date. |
| ELDR | ElectronicDraft | An instrument with a future value date (do not pay before), which in commercial terms is a 'negotiable instrument': the beneficiary can receive early payment from any bank under subtraction of a discount. The ordering customer's account is debited on value date.            |
| OCHQ | OnlineCheque    | Cheque initiated or completed through an online service.                                                                                                                                                                                                                          |
| OPCQ | OpenCheque      | Cheque that may only be cashed at the bank of origin.                                                                                                                                                                                                                             |
| ORCQ | OrderCheque     | Cheque made payable to a named recipient 'or order'. The payee can either deposit the cheque in an account or endorse it to a third party.                                                                                                                                        |

Is restricted by

"ChequeType2Code" on page 152

## 5.19 CountryCode

*Definition:* Code to identify a country, a dependency, or another area of particular geopolitical interest, on the basis of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

*Type:* Code

### Format

pattern [A-Z]{2,2}

### Rules

#### R12 Country ✓

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

**Used in element(s)**

["Country" on page 106](#), ["Country" on page 98](#), ["Country" on page 111](#), ["Country" on page 119](#), ["CountryOfBirth" on page 45](#), ["CountryOfResidence" on page 77](#), ["CountryOfResidence" on page 72](#)

## 5.20 CreditDebitCode

*Definition:* Specifies if an operation is an increase or a decrease.

*Type:* Code

| Code | Name   | Definition                |
|------|--------|---------------------------|
| CRDT | Credit | Operation is an increase. |
| DBIT | Debit  | Operation is a decrease.  |

**Used in element(s)**

["CreditDebitIndicator" on page 47](#)

**Restricts**

["AmountDirectionCode" on page 140](#)

## 5.21 DecimalNumber

*Definition:* Number of objects represented as a decimal number, for example 0.75 or 45.6.

*Type:* Quantity

**Format**

|                |    |
|----------------|----|
| totalDigits    | 18 |
| fractionDigits | 17 |

**Used in element(s)**

["ControlSum" on page 84](#), ["ControlSum" on page 61](#)

## 5.22 DocumentType3Code

*Definition:* Specifies a type of financial or commercial document.

*Type:* Code

| Code | Name                         | Definition                                                                                                     |
|------|------------------------------|----------------------------------------------------------------------------------------------------------------|
| DISP | DispatchAdvice               | Document is a dispatch advice.                                                                                 |
| FXDR | ForeignExchangeDealReference | Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers. |
| PUOR | PurchaseOrder                | Document is a purchase order.                                                                                  |
| RADM | RemittanceAdviceMessage      | Document is a remittance advice sent separately from the current transaction.                                  |

| Code | Name                             | Definition                                                                                                             |
|------|----------------------------------|------------------------------------------------------------------------------------------------------------------------|
| RPIN | RelatedPaymentInstruction        | Document is a linked payment instruction to which the current payment instruction is related, eg, in a cover scenario. |
| SCOR | StructuredCommunicationReference | Document is a structured communication reference provided by the creditor to identify the referred transaction.        |

**Used in element(s)**

"Code" on page 43

**Restricts**

"DocumentTypeCode" on page 157

## 5.23 DocumentType5Code

*Definition:* Specifies a type of financial or commercial document.

*Type:* Code

| Code | Name                                   | Definition                                                                                                                            |
|------|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| AROI | AccountReceivableOpenItem              | Document is a payment that applies to a specific source document.                                                                     |
| BOLD | BillOfLading                           | Document is a shipping notice.                                                                                                        |
| CINV | CommercialInvoice                      | Document is an invoice.                                                                                                               |
| CMCN | CommercialContract                     | Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.              |
| CNFA | CreditNoteRelatedToFinancialAdjustment | Document is a credit note for the final amount settled for a commercial transaction.                                                  |
| CREN | CreditNote                             | Document is a credit note.                                                                                                            |
| DEBN | DebitNote                              | Document is a debit note.                                                                                                             |
| DISP | DispatchAdvice                         | Document is a dispatch advice.                                                                                                        |
| DNFA | DebitNoteRelatedToFinancialAdjustment  | Document is a debit note for the final amount settled for a commercial transaction.                                                   |
| HIRI | HireInvoice                            | Document is an invoice for the hiring of human resources or renting goods or equipment.                                               |
| MSIN | MeteredServiceInvoice                  | Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter. |
| SBIN | SelfBilledInvoice                      | Document is an invoice issued by the debtor.                                                                                          |

| Code | Name                            | Definition                                                                                  |
|------|---------------------------------|---------------------------------------------------------------------------------------------|
| SOAC | StatementOfAccount              | Document is a statement of the transactions posted to the debtor's account at the supplier. |
| TSUT | TradeServicesUtilityTransaction | Document is a transaction identifier as assigned by the Trade Services Utility.             |
| VCHR | Voucher                         | Document is an electronic payment document.                                                 |

**Used in element(s)**

"Code" on page 109

**Restricts**

"DocumentTypeCode" on page 157

## 5.24 DocumentTypeCode

*Definition:* Specifies a type of financial or commercial document.

*Type:* Code

| Code | Name                                   | Definition                                                                                                                            |
|------|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| AROI | AccountReceivableOpenItem              | Document is a payment that applies to a specific source document.                                                                     |
| BOLD | BillOfLading                           | Document is a shipping notice.                                                                                                        |
| CINV | CommercialInvoice                      | Document is an invoice.                                                                                                               |
| CMCN | CommercialContract                     | Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.              |
| CNFA | CreditNoteRelatedToFinancialAdjustment | Document is a credit note for the final amount settled for a commercial transaction.                                                  |
| CREN | CreditNote                             | Document is a credit note.                                                                                                            |
| DEBN | DebitNote                              | Document is a debit note.                                                                                                             |
| DISP | DispatchAdvice                         | Document is a dispatch advice.                                                                                                        |
| DNFA | DebitNoteRelatedToFinancialAdjustment  | Document is a debit note for the final amount settled for a commercial transaction.                                                   |
| FXDR | ForeignExchangeDealReference           | Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.                        |
| HIRI | HireInvoice                            | Document is an invoice for the hiring of human resources or renting goods or equipment.                                               |
| MSIN | MeteredServiceInvoice                  | Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter. |

| Code | Name                             | Definition                                                                                                             |
|------|----------------------------------|------------------------------------------------------------------------------------------------------------------------|
| PUOR | PurchaseOrder                    | Document is a purchase order.                                                                                          |
| RADM | RemittanceAdviceMessage          | Document is a remittance advice sent separately from the current transaction.                                          |
| RPIN | RelatedPaymentInstruction        | Document is a linked payment instruction to which the current payment instruction is related, eg, in a cover scenario. |
| SBIN | SelfBilledInvoice                | Document is an invoice issued by the debtor.                                                                           |
| SCOR | StructuredCommunicationReference | Document is a structured communication reference provided by the creditor to identify the referred transaction.        |
| SOAC | StatementOfAccount               | Document is a statement of the transactions posted to the debtor's account at the supplier.                            |
| TSUT | TradeServicesUtilityTransaction  | Document is a transaction identifier as assigned by the Trade Services Utility.                                        |
| VCHR | Voucher                          | Document is an electronic payment document.                                                                            |

Is restricted by

["DocumentType3Code" on page 155](#), ["DocumentType5Code" on page 156](#)

## 5.25 ExchangeRateType1Code

*Definition:* Specifies a type of financial or commercial document.

*Type:* Code

| Code | Name   | Definition                                                        |
|------|--------|-------------------------------------------------------------------|
| AGRD | Agreed | Exchange rate applied is the rate agreed between the parties.     |
| SALE | Sale   | Exchange rate applied is the market rate at the time of the sale. |
| SPOT | Spot   | Exchange rate applied is the spot rate.                           |

Used in element(s)

["RateType" on page 49](#)

Restricts

["ExchangeRateTypeCode" on page 158](#)

## 5.26 ExchangeRateTypeCode

*Definition:* Code used to define the type of the currency exchange.

*Type:* Code

| Code | Name   | Definition                                                        |
|------|--------|-------------------------------------------------------------------|
| AGRD | Agreed | Exchange rate applied is the rate agreed between the parties.     |
| SALE | Sale   | Exchange rate applied is the market rate at the time of the sale. |
| SPOT | Spot   | Exchange rate applied is the spot rate.                           |

Is restricted by

"ExchangeRateType1Code" on page 158

## 5.27 ExternalAccountIdentification1Code

*Definition:* Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* Code

### Format

|           |   |
|-----------|---|
| minLength | 1 |
| maxLength | 4 |

### Used in element(s)

"Code" on page 9

### Restricts

"ExternalAccountIdentificationCode" on page 159

## 5.28 ExternalAccountIdentificationCode

*Definition:* Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* Code

### Format

|           |   |
|-----------|---|
| minLength | 1 |
| maxLength | 4 |

**Is restricted by**

"ExternalAccountIdentification1Code" on page 159

## 5.29 ExternalCategoryPurpose1Code

*Definition:* Specifies the category purpose, as published in an external category purpose code list.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* Code

### **Format**

|           |   |
|-----------|---|
| minLength | 1 |
| maxLength | 4 |

**Used in element(s)**

"Code" on page 18

### **Restricts**

"ExternalCategoryPurposeCode" on page 160

## 5.30 ExternalCategoryPurposeCode

*Definition:* Specifies the category purpose, as published in an external category purpose code list.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* Code

### **Format**

|           |   |
|-----------|---|
| minLength | 1 |
| maxLength | 4 |

**Is restricted by**

"ExternalCategoryPurpose1Code" on page 160

## 5.31 ExternalClearingSystemIdentification1Code

*Definition:* Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* Code

### **Format**

|           |   |
|-----------|---|
| minLength | 1 |
|-----------|---|

|           |   |
|-----------|---|
| maxLength | 5 |
|-----------|---|

**Used in element(s)**

"Code" on page 23

**Restricts**

"ExternalClearingSystemIdentificationCode" on page 161

## 5.32 ExternalClearingSystemIdentificationCode

*Definition:* Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* Code

**Format**

|           |   |
|-----------|---|
| minLength | 1 |
| maxLength | 5 |

**Is restricted by**

"ExternalClearingSystemIdentification1Code" on page 160

## 5.33 ExternalFinancialInstitutionIdentification1Code

*Definition:* Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* Code

**Format**

|           |   |
|-----------|---|
| minLength | 1 |
| maxLength | 4 |

**Used in element(s)**

"Code" on page 50

**Restricts**

"ExternalFinancialInstitutionIdentificationCode" on page 161

## 5.34 ExternalFinancialInstitutionIdentificationCode

*Definition:* Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* Code

**Format**

|           |   |
|-----------|---|
| minLength | 1 |
| maxLength | 4 |

**Is restricted by**

"ExternalFinancialInstitutionIdentification1Code" on page 161

## 5.35 ExternalLocalInstrument1Code

*Definition:* Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* Code

**Format**

|           |    |
|-----------|----|
| minLength | 1  |
| maxLength | 35 |

**Used in element(s)**

"Code" on page 64

**Restricts**

"ExternalLocalInstrumentCode" on page 162

## 5.36 ExternalLocalInstrumentCode

*Definition:* Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* Code

**Format**

|           |    |
|-----------|----|
| minLength | 1  |
| maxLength | 35 |

**Is restricted by**

"ExternalLocalInstrument1Code" on page 162

## 5.37 ExternalOrganisationIdentification1Code

*Definition:* Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* Code

**Format**

|           |   |
|-----------|---|
| minLength | 1 |
| maxLength | 4 |

**Used in element(s)**

"Code" on page 68

**Restricts**

"ExternalOrganisationIdentificationCode" on page 163

## 5.38 ExternalOrganisationIdentificationCode

*Definition:* Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* Code

**Format**

|           |   |
|-----------|---|
| minLength | 1 |
| maxLength | 4 |

**Is restricted by**

"ExternalOrganisationIdentification1Code" on page 163

## 5.39 ExternalPersonIdentification1Code

*Definition:* Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* Code

### Format

|           |   |
|-----------|---|
| minLength | 1 |
| maxLength | 4 |

### Used in element(s)

["Code" on page 95](#)

### Restricts

["ExternalPersonIdentificationCode" on page 164](#)

## 5.40 ExternalPersonIdentificationCode

*Definition:* Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* Code

### Format

|           |   |
|-----------|---|
| minLength | 1 |
| maxLength | 4 |

### Is restricted by

["ExternalPersonIdentification1Code" on page 164](#)

## 5.41 ExternalPurpose1Code

*Definition:* Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* Code

**Format**

|           |   |
|-----------|---|
| minLength | 1 |
| maxLength | 4 |

**Used in element(s)**

"Code" on page 108

**Restricts**

"ExternalPurposeCode" on page 165

## 5.42 ExternalPurposeCode

*Definition:* Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* Code

**Format**

|           |   |
|-----------|---|
| minLength | 1 |
| maxLength | 4 |

**Is restricted by**

"ExternalPurpose1Code" on page 164

## 5.43 HSBC\_UK\_ServiceLevel

*Definition:*

This datatype has been created by the Publisher of this Usage Guideline.

*Type:* Code

**Format**

|           |   |
|-----------|---|
| minLength | 1 |
| maxLength | 4 |

| Code | Name                 | Definition           |
|------|----------------------|----------------------|
| PRPT | EBA Priority Service | EBA Priority Service |
| SDVA | Same Day Value       | Same Day Value       |
| URGP | Urgent Payment       | Urgent Payment       |

**Used in element(s)**

["Code" on page 118](#)

## 5.44 IBAN2007Identifier

*Definition:* An identifier used internationally by financial institutions to uniquely identify the account of a customer at a financial institution, as described in the latest edition of the international standard ISO 13616: 2007 - "Banking and related financial services - International Bank Account Number (IBAN)".

*Type:* IdentifierSet

**Format**

pattern [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}

**Rules****R19 IBAN ✓**

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00003
- *Error Text:* Invalid IBAN format or invalid check digits.

**Used in element(s)**

["IBAN" on page 8](#)

## 5.45 ISODate

*Definition:* A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

*Type:* Date

**Used in element(s)**

["BirthDate" on page 45](#), ["ChequeMaturityDate" on page 21](#), ["Date" on page 128](#), ["Date" on page 119](#), ["FromDate" on page 46](#), ["PoolingAdjustmentDate" on page 85](#), ["RelatedDate" on page 109](#), ["RequestedExecutionDate" on page 85](#), ["ToDate" on page 46](#), ["Year" on page 132](#)

## 5.46 ISODatetime

*Definition:* A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in either UTC time format (YYYY-MM-DDThh:mm:ss.sssZ), local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm), or local time format (YYYY-MM-DDThh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: DateTime

Used in element(s)

"CreationDateTime" on page 60

## 5.47 Instruction3Code

*Definition:* Specifies further instructions concerning the processing of a payment instruction, provided by the sending clearing agent to the next agent(s).

Type: Code

| Code | Name                | Definition                                                                                           |
|------|---------------------|------------------------------------------------------------------------------------------------------|
| CHQB | PayCreditorByCheque | (Ultimate) creditor must be paid by cheque.                                                          |
| HOLD | HoldCashForCreditor | Amount of money must be held for the (ultimate) creditor, who will call. Pay on identification.      |
| PHOB | PhoneBeneficiary    | Please advise/contact (ultimate) creditor/claimant by phone.                                         |
| TELB | Telecom             | Please advise/contact (ultimate) creditor/claimant by the most efficient means of telecommunication. |

Used in element(s)

"Code" on page 62

Restricts

"InstructionCode" on page 167

## 5.48 InstructionCode

*Definition:* Specifies further instructions concerning the processing of a payment instruction.

Type: Code

| Code | Name                | Definition                                  |
|------|---------------------|---------------------------------------------|
| CHQB | PayCreditorByCheque | (Ultimate) creditor must be paid by cheque. |

| Code | Name                | Definition                                                                                                                                       |
|------|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| HOLD | HoldCashForCreditor | Amount of money must be held for the (ultimate) creditor, who will call. Pay on identification.                                                  |
| PBEN | PayTheBeneficiary   | (Ultimate) creditor to be paid only after verification of identity.                                                                              |
| PHOA | PhoneNextAgent      | Please advise/contact next agent by phone.                                                                                                       |
| PHOB | PhoneBeneficiary    | Please advise/contact (ultimate) creditor/claimant by phone.                                                                                     |
| TELA | TelecomNextAgent    | Please advise/contact next agent by the most efficient means of telecommunication.                                                               |
| TELB | Telecom             | Please advise/contact (ultimate) creditor/claimant by the most efficient means of telecommunication.                                             |
| TFRO | TimeFrom            | Payment instruction will be valid and eligible for execution from the date and time stipulated.                                                  |
| TTIL | TimeTill            | Payment instruction is valid and eligible for execution until the date and time stipulated. Otherwise, the payment instruction will be rejected. |

Is restricted by

"Instruction3Code" on page 167

## 5.49 Max10Text

*Definition:* Specifies a character string with a maximum length of 10 characters.

*Type:* Text

### Format

|           |    |
|-----------|----|
| minLength | 1  |
| maxLength | 10 |

### Used in element(s)

"Code" on page 120

## 5.50 Max128Text

*Definition:* Specifies a character string with a maximum length of 128 characters.

*Type:* Text

### Format

|           |   |
|-----------|---|
| minLength | 1 |
|-----------|---|

|           |     |
|-----------|-----|
| maxLength | 128 |
|-----------|-----|

**Used in element(s)**

"Proprietary" on page 11

## 5.51 Max12Text

*Definition:* Specifies a character string with a maximum length of 12 characters.

*Type:* Text

**Format**

|           |    |
|-----------|----|
| minLength | 1  |
| maxLength | 12 |

**Used in element(s)**

"ExchangeRate" on page 48

## 5.52 Max140Text

*Definition:* Specifies a character string with a maximum length of 140 characters.

*Type:* Text

**Format**

|           |     |
|-----------|-----|
| minLength | 1   |
| maxLength | 140 |

**Used in element(s)**

"AdditionalInformation" on page 47, "AdditionalInformation" on page 135, "AdditionalRemittanceInformation" on page 123, "InstructionForDebtorAgent" on page 39, "InstructionInformation" on page 62, "Name" on page 13, "Name" on page 25, "Name" on page 70, "Name" on page 51, "Name" on page 65, "Name" on page 125, "Name" on page 111, "ReferenceNumber" on page 127, "Unstructured" on page 115

## 5.53 Max15NumericText

*Definition:* Specifies a numeric string with a maximum length of 15 digits.

*Type:* Text

**Format**

|         |             |
|---------|-------------|
| pattern | [0-9]{1,15} |
|---------|-------------|

**Used in element(s)**

"NumberOfTransactions" on page 84, "NumberOfTransactions" on page 60

## 5.54 Max16Text

*Definition:* Specifies a character string with a maximum length of 16 characters.

*Type:* Text

### Format

|           |    |
|-----------|----|
| minLength | 1  |
| maxLength | 16 |

### Used in element(s)

"BuildingNumber" on page 103, "BuildingNumber" on page 97, "EndToEndIdentification" on page 79, "PostCode" on page 104, "PostCode" on page 98

## 5.55 Max2048Text

*Definition:* Specifies a character string with a maximum length of 2048 characters.

*Type:* Text

### Format

|           |      |
|-----------|------|
| minLength | 1    |
| maxLength | 2048 |

### Used in element(s)

"EmailAddress" on page 25, "RemittanceLocationElectronicAddress" on page 117

## 5.56 Max28Text

*Definition:* Specifies a character string with a maximum length of 28 characters.

This datatype has been created by the Publisher of this Usage Guideline.

*Type:* Text

### Format

|           |    |
|-----------|----|
| minLength | 1  |
| maxLength | 28 |

### Used in element(s)

"ContractIdentification" on page 49

## 5.57 Max34Text

*Definition:* Specifies a character string with a maximum length of 34 characters.

*Type:* Text

**Format**

|           |    |
|-----------|----|
| minLength | 1  |
| maxLength | 34 |

**Used in element(s)**

["Identification" on page 54](#)

## 5.58 Max35Text

*Definition:* Specifies a character string with a maximum length of 35 characters.

*Type:* Text

**Format**

|           |    |
|-----------|----|
| minLength | 1  |
| maxLength | 35 |

**Used in element(s)**

["AddressLine" on page 106](#), ["AdministrationZone" on page 127](#), ["Category" on page 134](#), ["CategoryDetails" on page 134](#), ["CertificateIdentification" on page 134](#), ["ChequeNumber" on page 19](#), ["CityOfBirth" on page 45](#), ["CountrySubDivision" on page 105](#), ["CountrySubDivision" on page 98](#), ["DebtorStatus" on page 134](#), ["FormsCode" on page 135](#), ["FormsCode" on page 21](#), ["Identification" on page 55](#), ["Identification" on page 13](#), ["Identification" on page 56](#), ["Identification" on page 58](#), ["Information" on page 120](#), ["InstructionIdentification" on page 78](#), ["Issuer" on page 56](#), ["Issuer" on page 54](#), ["Issuer" on page 57](#), ["Issuer" on page 59](#), ["Issuer" on page 110](#), ["Issuer" on page 44](#), ["MemberIdentification" on page 24](#), ["MemoField" on page 21](#), ["MessageIdentification" on page 59](#), ["Method" on page 127](#), ["Number" on page 108](#), ["Other" on page 26](#), ["PaymentInformationIdentification" on page 83](#), ["PrintLocation" on page 22](#), ["Proprietary" on page 118](#), ["Proprietary" on page 23](#), ["Proprietary" on page 50](#), ["Proprietary" on page 9](#), ["Proprietary" on page 17](#), ["Proprietary" on page 68](#), ["Proprietary" on page 95](#), ["Proprietary" on page 108](#), ["Proprietary" on page 110](#), ["Proprietary" on page 43](#), ["Proprietary" on page 22](#), ["Proprietary" on page 64](#), ["Proprietary" on page 18](#), ["ProvinceOfBirth" on page 45](#), ["Reference" on page 42](#), ["RegionalClearingZone" on page 21](#), ["RegistrationIdentification" on page 130](#), ["RegistrationIdentification" on page 131](#), ["RemittanceIdentification" on page 116](#), ["StreetName" on page 102](#), ["TaxIdentification" on page 129](#), ["TaxIdentification" on page 130](#), ["TaxType" on page 130](#), ["TaxType" on page 131](#), ["Title" on page 125](#), ["TownName" on page 104](#), ["TownName" on page 98](#), ["Type" on page 133](#), ["Type" on page 119](#)

## 5.59 Max4Text

*Definition:* Specifies a character string with a maximum length of 4 characters.

*Type:* Text

**Format**

|           |   |
|-----------|---|
| minLength | 1 |
| maxLength | 4 |

**Used in element(s)**

["Reason" on page 47](#)

## 5.60 Max70Text

*Definition:* Specifies a character string with a maximum length of 70characters.

*Type:* Text

**Format**

|           |    |
|-----------|----|
| minLength | 1  |
| maxLength | 70 |

**Used in element(s)**

["AddressLine" on page 99](#), ["Department" on page 101](#), ["Department" on page 97](#), ["Name" on page 73](#), ["Name" on page 16](#), ["StreetName" on page 97](#), ["SubDepartment" on page 101](#), ["SubDepartment" on page 97](#)

## 5.61 NamePrefix1Code

*Definition:* Specifies the terms used to formally address a person.

*Type:* Code

| Code | Name   | Definition                           |
|------|--------|--------------------------------------|
| DOCT | Doctor | Title of the person is Doctor or Dr. |
| MADM | Madam  | Title of the person is Madam.        |
| MISS | Miss   | Title of the person is Miss.         |
| MIST | Mister | Title of the person is Mister or Mr. |

**Used in element(s)**

["NamePrefix" on page 25](#)

**Restricts**

["NamePrefixCode" on page 172](#)

## 5.62 NamePrefixCode

*Definition:* Specifies the terms used to formally address a person.

*Type:* Code

| Code | Name          | Definition                                  |
|------|---------------|---------------------------------------------|
| DOCT | Doctor        | Title of the person is Doctor or Dr.        |
| MADM | Madam         | Title of the person is Madam.               |
| MIKS | GenderNeutral | Title of the person is gender neutral (Mx). |

| Code | Name   | Definition                           |
|------|--------|--------------------------------------|
| MISS | Miss   | Title of the person is Miss.         |
| MIST | Mister | Title of the person is Mister or Mr. |

Is restricted by

["NamePrefix1Code" on page 172](#)

## 5.63 Number

*Definition:* Number of objects represented as an integer.

*Type:* Quantity

### Format

|                |    |
|----------------|----|
| totalDigits    | 18 |
| fractionDigits | 0  |

### Used in element(s)

["SequenceNumber" on page 128](#)

## 5.64 ParentCurrencyCode

*Definition:* Code allocated to a currency, by a maintenance agency, under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds". Valid currency codes are registered with the ISO 4217 Maintenance Agency, and consist of three contiguous letters.

*Type:* Code

### Format

|         |            |
|---------|------------|
| pattern | [A-Z]{3,3} |
|---------|------------|

Is restricted by

["ActiveOrHistoricCurrencyCode" on page 138](#)

## 5.65 PaymentMethod3Code

*Definition:* Specifies the transfer method that will be used to transfer an amount of money.

*Type:* Code

| Code | Name   | Definition                                                                                  |
|------|--------|---------------------------------------------------------------------------------------------|
| CHK  | Cheque | Written order to a bank to pay a certain amount of money from one person to another person. |

| Code | Name           | Definition                                                                                                                                                                                                                                                               |
|------|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|      |                | <b>Usage Guideline restrictions for this code</b> <ul style="list-style-type: none"> <li>• This code(pain.001.001.03/PaymentInformation/PaymentMethod/Cheque) is removed.</li> </ul>                                                                                     |
| TRA  | TransferAdvice | Transfer of an amount of money in the books of the account servicer. An advice should be sent back to the account owner.                                                                                                                                                 |
| TRF  | CreditTransfer | Transfer of an amount of money in the books of the account servicer.<br><br><b>Usage Guideline restrictions for this code</b> <ul style="list-style-type: none"> <li>• This code(pain.001.001.03/PaymentInformation/PaymentMethod/CreditTransfer) is removed.</li> </ul> |

**Used in element(s)**

"PaymentMethod" on page 83

**Restricts**

"PaymentMethodCode" on page 174

## 5.66 PaymentMethodCode

*Definition:* Specifies the transfer method that will be used to transfer the cash.

*Type:* Code

| Code | Name           | Definition                                                                                                                              |
|------|----------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| CHK  | Cheque         | Written order to a bank to pay a certain amount of money from one person to another person.                                             |
| CLAS | Classical      | Classical method.                                                                                                                       |
| DD   | DirectDebit    | Collection of an amount of money from the debtor's bank account by the creditor. The amount of money and dates of collections may vary. |
| DIRE | Direct         | Direct method.                                                                                                                          |
| TRA  | TransferAdvice | Transfer of an amount of money in the books of the account servicer. An advice should be sent back to the account owner.                |

| Code | Name           | Definition                                                           |
|------|----------------|----------------------------------------------------------------------|
| TRF  | CreditTransfer | Transfer of an amount of money in the books of the account servicer. |

Is restricted by

"PaymentMethod3Code" on page 173

## 5.67 PercentageRate

*Definition:* Rate expressed as a percentage, ie, in hundredths, for example, 0.7 is 7/10 of a percent, and 7.0 is 7%.

*Type:* Rate

### Format

|                |    |
|----------------|----|
| totalDigits    | 11 |
| fractionDigits | 10 |

### Used in element(s)

"Rate" on page 124

## 5.68 PhoneNumber

*Definition:* The collection of information which identifies a specific phone or FAX number as defined by telecom services.

It consists of a "+" followed by the country code (from 1 to 3 characters) then a "-" and finally, any combination of numbers, "(", ")", "+ and "-" (up to 30 characters).

*Type:* Text

### Format

|         |                               |
|---------|-------------------------------|
| pattern | \+[0-9]{1,3}-[0-9()+\-]{1,30} |
|---------|-------------------------------|

### Used in element(s)

"FaxNumber" on page 25, "MobileNumber" on page 25, "PhoneNumber" on page 25

## 5.69 Priority2Code

*Definition:* Specifies the priority level of an event.

*Type:* Code

| Code | Name   | Definition                |
|------|--------|---------------------------|
| HIGH | High   | Priority level is high.   |
| NORM | Normal | Priority level is normal. |

**Used in element(s)**

["InstructionPriority" on page 92](#), ["InstructionPriority" on page 21](#)

**Restricts**

["PriorityCode" on page 176](#)

## 5.70 PriorityCode

*Definition:* Specifies the priority level of an event.

*Type:* Code

| Code | Name   | Definition                                            |
|------|--------|-------------------------------------------------------|
| HIGH | High   | Priority level is high.                               |
| LOWW | Low    | Priority level is low.                                |
| NORM | Normal | Priority level is normal.                             |
| URGT | Urgent | Priority level is urgent (highest priority possible). |

**Is restricted by**

["Priority2Code" on page 175](#)

## 5.71 RegulatoryReportingType1Code

*Definition:* Identifies whether the regulatory reporting information applies to the debit side, to the credit side or to both debit and credit sides of the transaction.

*Type:* Code

| Code | Name   | Definition                                                     |
|------|--------|----------------------------------------------------------------|
| BOTH | Both   | Regulatory information applies to both credit and debit sides. |
| CRED | Credit | Regulatory information applies to the credit side.             |
| DEBT | Debit  | Regulatory information applies to the debit side.              |

**Used in element(s)**

["DebitCreditReportingIndicator" on page 112](#)

**Restricts**

["RegulatoryReportingTypeCode" on page 176](#)

## 5.72 RegulatoryReportingTypeCode

*Definition:* Identifies whether the regulatory reporting information applies to the debit side, to the credit side or to both debit and credit sides of the transaction.

*Type:* Code

| Code | Name   | Definition                                                     |
|------|--------|----------------------------------------------------------------|
| BOTH | Both   | Regulatory information applies to both credit and debit sides. |
| CRED | Credit | Regulatory information applies to the credit side.             |
| DEBT | Debit  | Regulatory information applies to the debit side.              |

Is restricted by

"RegulatoryReportingType1Code" on page 176

## 5.73 RemittanceLocationMethod2Code

*Definition:* Specifies the method used to deliver the remittance advice information.

*Type:* Code

| Code | Name                      | Definition                                                                                                                                                                                                                                                                                                                                                                                                    |
|------|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EDIC | ElectronicDataInterchange | <p>Remittance advice information must be sent through Electronic Data Interchange (EDI).</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RelatedRemittanceInformation/RemittanceLocationMethod/ElectronicDataInterchange) will be ignored by the Receiver.</li> </ul> |
| EMAL | EMail                     | Remittance advice information must be sent through e-mail.                                                                                                                                                                                                                                                                                                                                                    |
| FAXI | Fax                       | Remittance advice information must be faxed.                                                                                                                                                                                                                                                                                                                                                                  |
| POST | Post                      | Remittance advice information must be sent through postal services.                                                                                                                                                                                                                                                                                                                                           |
| SMSM | SMS                       | Remittance advice information must be sent through by phone as a short message service (SMS).                                                                                                                                                                                                                                                                                                                 |

| Code | Name                      | Definition                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| URID | UniformResourceIdentifier | <p>Remittance advice information needs to be sent to a Uniform Resource Identifier (URI). URI is a compact string of characters that uniquely identify an abstract or physical resource. URI's are the super-set of identifiers, such as URLs, email addresses, ftp sites, etc, and as such, provide the syntax for all of the identification schemes.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(pain.001.001.03/PaymentInformation/CreditTransferTransactionInformation/RelatedRemittanceLocationMethod/UniformResourceIdentifier) will be ignored by the Receiver.</li> </ul> |

**Used in element(s)**

"RemittanceLocationMethod" on page 117

**Restricts**

"RemittanceLocationMethodCode" on page 178

## 5.74 RemittanceLocationMethodCode

*Definition:* Specifies the method used to deliver the remittance advice information.

*Type:* Code

| Code | Name                      | Definition                                                                                    |
|------|---------------------------|-----------------------------------------------------------------------------------------------|
| EDIC | ElectronicDataInterchange | Remittance advice information must be sent through Electronic Data Interchange (EDI).         |
| EMAL | EMail                     | Remittance advice information must be sent through e-mail.                                    |
| FAXI | Fax                       | Remittance advice information must be faxed.                                                  |
| POST | Post                      | Remittance advice information must be sent through postal services.                           |
| SMSM | SMS                       | Remittance advice information must be sent through by phone as a short message service (SMS). |

| Code | Name                      | Definition                                                                                                                                                                                                                                                                                                                                          |
|------|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| URID | UniformResourceIdentifier | Remittance advice information needs to be sent to a Uniform Resource Identifier (URI). URI is a compact string of characters that uniquely identify an abstract or physical resource. URI's are the super-set of identifiers, such as URLs, email addresses, ftp sites, etc, and as such, provide the syntax for all of the identification schemes. |

Is restricted by

"RemittanceLocationMethod2Code" on page 177

## 5.75 TaxRecordPeriod1Code

*Definition:* Specifies the period related to the tax payment.

*Type:* Code

| Code | Name          | Definition                                          |
|------|---------------|-----------------------------------------------------|
| HLF1 | FirstHalf     | Tax is related to the first half of the period.     |
| HLF2 | SecondHalf    | Tax is related to the second half of the period.    |
| MM01 | FirstMonth    | Tax is related to the second month of the period.   |
| MM02 | SecondMonth   | Tax is related to the first month of the period.    |
| MM03 | ThirdMonth    | Tax is related to the third month of the period.    |
| MM04 | FourthMonth   | Tax is related to the fourth month of the period.   |
| MM05 | FifthMonth    | Tax is related to the fifth month of the period.    |
| MM06 | SixthMonth    | Tax is related to the sixth month of the period.    |
| MM07 | SeventhMonth  | Tax is related to the seventh month of the period.  |
| MM08 | EighthMonth   | Tax is related to the eighth month of the period.   |
| MM09 | NinthMonth    | Tax is related to the ninth month of the period.    |
| MM10 | TenthMonth    | Tax is related to the tenth month of the period.    |
| MM11 | EleventhMonth | Tax is related to the eleventh month of the period. |
| MM12 | TwelfthMonth  | Tax is related to the twelfth month of the period.  |

| Code | Name          | Definition                                          |
|------|---------------|-----------------------------------------------------|
| QTR1 | FirstQuarter  | Tax is related to the first quarter of the period.  |
| QTR2 | SecondQuarter | Tax is related to the second quarter of the period. |
| QTR3 | ThirdQuarter  | Tax is related to the third quarter of the period.  |
| QTR4 | FourthQuarter | Tax is related to the forth quarter of the period.  |

**Used in element(s)**

"Type" on page 132

**Restricts**

"TaxRecordPeriodCode" on page 180

## 5.76 TaxRecordPeriodCode

*Definition:* Specifies the period related to the tax payment.

*Type:* Code

| Code | Name         | Definition                                         |
|------|--------------|----------------------------------------------------|
| HLF1 | FirstHalf    | Tax is related to the first half of the period.    |
| HLF2 | SecondHalf   | Tax is related to the second half of the period.   |
| MM01 | FirstMonth   | Tax is related to the second month of the period.  |
| MM02 | SecondMonth  | Tax is related to the first month of the period.   |
| MM03 | ThirdMonth   | Tax is related to the third month of the period.   |
| MM04 | FourthMonth  | Tax is related to the fourth month of the period.  |
| MM05 | FifthMonth   | Tax is related to the fifth month of the period.   |
| MM06 | SixthMonth   | Tax is related to the sixth month of the period.   |
| MM07 | SeventhMonth | Tax is related to the seventh month of the period. |
| MM08 | EighthMonth  | Tax is related to the eighth month of the period.  |
| MM09 | NinthMonth   | Tax is related to the ninth month of the period.   |
| MM10 | TenthMonth   | Tax is related to the tenth month of the period.   |

| Code | Name          | Definition                                          |
|------|---------------|-----------------------------------------------------|
| MM11 | EleventhMonth | Tax is related to the eleventh month of the period. |
| MM12 | TwelfthMonth  | Tax is related to the twelfth month of the period.  |
| QTR1 | FirstQuarter  | Tax is related to the first quarter of the period.  |
| QTR2 | SecondQuarter | Tax is related to the second quarter of the period. |
| QTR3 | ThirdQuarter  | Tax is related to the third quarter of the period.  |
| QTR4 | FourthQuarter | Tax is related to the forth quarter of the period.  |

**Is restricted by**

"TaxRecordPeriod1Code" on page 179

# Legal Notices

## Copyright

SWIFT © 2018. All rights reserved.

This material is a component of MyStandards, the SWIFT collaborative Web application used to manage standards definitions and industry usage. It can only be used and distributed in accordance with MyStandards Terms of Use.

Unless otherwise agreed in writing with SWIFT SCRL, you have no right to:

- authorise external end users to use this component for other purposes than their internal use.
- remove, alter, cover, obfuscate or cancel from view any copyright or other proprietary rights notices appearing in this physical medium.
- re-sell or authorise another party e.g. software and service providers, to re-sell this component.

## Confidentiality

This publication may contain SWIFT or third-party confidential information. Only disclose it outside your organisation in accordance with MyStandards Terms of Use and your related license rights.

This component is provided 'AS IS'. SWIFT does not give and excludes any express or implied warranties with respect to this component such as but not limited to any guarantee as to its quality, supply or availability.

Any and all rights, including title, ownership rights, copyright, trademark, patents, and any other intellectual property rights of whatever nature in this component will remain the exclusive property of SWIFT or its licensors.

## Trademarks and Patents

SWIFT is the trade name of S.W.I.F.T. SCRL. The following are registered trademarks of SWIFT: SWIFT, the SWIFT logo, 3SKey, Innotribe, Sibos, SWIFTNet, MyStandards, SWIFTReady, and Accord. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.