



Usage Guideline

HSBC_pain.001.001.02_LowValuePayment_UK BACS

HSBC_pain.001.001.02_LowValuePayment_Europe

This document describes a usage guideline restricting the base message **MX pain.001.001.02**. You can also consult [this information online](#).

Published by HSBC Direct Channels and generated by [MyStandards](#).

29 January 2016

Table of Contents

Message Functionality	3
1 Restriction summary	4
2 Structure	5
3 Rules	6
4 Message Building Blocks	7
5 Message Components	9
6 Message Datatypes	125
Legal Notices	161

Message Functionality

Overview

BACS payments are domestic, non-urgent payments (ACH payments) in the United Kingdom of Great Britain and Northern Ireland. Processable amounts are limited by the credit limit set by the BACS clearing system only. If a client has more than one agreement with the BACS clearing system (and consequently multiple ID numbers), the BACS ID needs to be provided in the payment instruction.

The beneficiary account is addressed via the sort code of the beneficiary's bank and the (domestic) account number. The sort code is exactly 6 digits long with a prefix of "GBDSC" or "XXXXX".

If the beneficiary holds an account with a Building Society that is not part of the BACS clearing, both the account number of the building society with its supporting bank and the "roll number" of the beneficiary account are required.

The reference information that can be passed on to the beneficiary is limited to 18 characters. The EndToEndIdentification is used to transport the reference. No further payment details can be supported with this payment type.

Payment files need to respect the 3-day clearing cycle of the BACS payments. Payment files should be with HSBC at least two working days before the requested execution date.

Outline

The HSBC_pain.001.001.02_LowValuePayment_Europe / HSBC_pain.001.001.02_LowValuePayment_UK BACS message is composed of 2 building blocks

a. GroupHeader

Set of characteristics shared by all individual transactions included in the message.

b. PaymentInformation

Set of characteristics that applies to the debit side of the payment transactions included in the credit transfer initiation.

1 Restriction summary

This Usage Guideline restricts the pain.001.001.02 message.

Restriction Type	See page
Removed elements	9, 10, 10, 10, 10, 11, 11, 11, 12, 12, 13, 26, 26, 28, 28, 28, 28, 31, 32, 34, 34, 35, 35, 36, 51, 51, 52, 52, 52, 52, 53, 53, 54, 61, 61, 66, 67, 67, 68, 68, 68, 73, 77, 87, 91, 96, 96, 103, 103, 103, 103, 104, 104, 104, 105, 105, 114, 114, 130, 135, 135, 135, 135, 136, 136, 144, 144, 155, 159, 159
Make mandatory	36, 37, 38, 48, 48, 50, 50, 77, 78, 80, 81, 84, 96, 96
Reduce Multiplicity	58
Ignore	18, 18, 18, 18, 19, 19, 20, 20, 21, 33, 39, 39, 40, 40, 60, 75, 77, 77, 78, 81, 90, 92, 92, 93, 93, 95, 95, 118, 119, 121, 121, 121, 122, 122, 123, 123
Text rules	31, 33, 55, 57, 58, 58, 58, 59, 72, 85, 88, 115, 122
Conditional rules	n.a.
Fixed values	145
Truncates	n.a.
Comments	14, 14, 29, 32, 33, 42, 53, 54, 57, 58, 72, 78, 80, 80, 81, 84, 86, 89, 92
Annotations	n.a.
Changed datatypes	n.a.
Extensions	n.a.
Synonyms	n.a.

2 Structure

⊘ Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	<i>CustomerCreditTransferInitiationV02</i>	<pain.001.001.02>		[1..1]		
1.0	GroupHeader	<GrpHdr>		[1..1]		7
1.1	MessageIdentification	<MsgId>		[1..1]	⚠	57
1.2	CreationDateTime	<CreDtTm>		[1..1]	⚠	57
1.3	Authorisation	<Authstn>		[0..2]	⚠ R[0..1]	57
1.4	BatchBooking	<BtchBookg>		[0..1]	⚠	58
1.5	NumberOfTransactions	<NbOfTx>		[1..1]	⚠	58
1.6	ControlSum	<CtrlSum>		[0..1]	⚠	59
1.7	Grouping	<Grpg>		[1..1]		59
1.8	InitiatingParty	<InitgPty>		[1..1]		59
1.9	ForwardingAgent	<FwdgAgt>		[0..1]	♦	60
2.0	PaymentInformation	<PmtInf>		[1..*]		7
2.1	PaymentInformationIdentification	<PmtInfId>		[0..1]	⚠	88
2.2	PaymentMethod	<PmtMtd>		[1..1]		88
2.3	PaymentTypeInformation	<PmtTpInf>		[0..1]		89
2.13	RequestedExecutionDate	<ReqdExctnDt>		[1..1]	⚠	89
2.14	PoolingAdjustmentDate	<PoolgAdjstmntDt>		[0..1]	♦	89
2.15	Debtor	<Dbtr>		[1..1]		90
2.16	DebtorAccount	<DbtrAcct>		[1..1]		90
2.17	DebtorAgent	<DbtrAgt>		[1..1]		91
2.18	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]	⊘	91
2.19	UltimateDebtor	<UltmtDbtr>		[0..1]	♦ ⚠	91
2.20	ChargeBearer	<ChrgBr>		[0..1]	♦	92
2.21	ChargesAccount	<ChrgsAcct>		[0..1]	♦	92
2.22	ChargesAccountAgent	<ChrgsAcctAgt>		[0..1]	♦	93
2.23	CreditTransferTransactionInformation	<CdtTrfTxInf>		[1..*]		93

3 Rules

R1 Grouping1Rule

If GroupHeader/Grouping is present and equals GRPD, then one and only one occurrence of PaymentInformation must be present.

Error handling: Undefined

R2 Grouping2Rule

If GroupHeader/Grouping is present and equals SNGL, then each occurrence of PaymentInformation must contain one and only one occurrence of PaymentInformation/CreditTransferTransactionInformation.

Error handling: Undefined

4 Message Building Blocks

Note The following chapter identifies the building blocks of the HSBC_pain.001.001.02_LowValuePayment_Europe / HSBC_pain.001.001.02_LowValuePayment_UK BACS message definition.

4.1 GroupHeader

XML Tag: GrpHdr

Presence: [1..1]

Definition: Set of characteristics shared by all individual transactions included in the message.

The **GrpHdr** block contains the following elements (see datatype "GroupHeader1__1" on page 56 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - 📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1	MessageIdentification	<MsgId>		[1..1]	⚠	57
1.2	CreationDateTime	<CreDtTm>		[1..1]	⚠	57
1.3	Authorisation	<Authstn>		[0..2]	⚠ R[0..1]	57
1.4	BatchBooking	<BtchBookg>		[0..1]	⚠	58
1.5	NumberOfTransactions	<NbOfTx>		[1..1]	⚠	58
1.6	ControlSum	<CtrlSum>		[0..1]	⚠	59
1.7	Grouping	<Grpg>		[1..1]		59
1.8	InitiatingParty	<InitgPty>		[1..1]		59
1.9	ForwardingAgent	<FwdgAgt>		[0..1]	💡	60

4.2 PaymentInformation

XML Tag: PmtInf

Presence: [1..*]

Definition: Set of characteristics that applies to the debit side of the payment transactions included in the credit transfer initiation.

The **PmtInf** block contains the following elements (see datatype "PaymentInstructionInformation1__1" on page 86 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.1	PaymentInformationIdentification	<PmtInfId>		[0..1]	⚠	88
2.2	PaymentMethod	<PmtMtd>		[1..1]		88
2.3	PaymentTypeInformation	<PmtTpInf>		[0..1]		89
2.13	RequestedExecutionDate	<ReqdExctnDt>		[1..1]	⚠	89
2.14	PoolingAdjustmentDate	<PoolgAdjstmntDt>		[0..1]	✦	89
2.15	Debtor	<Dbtr>		[1..1]		90
2.16	DebtorAccount	<DbtrAcct>		[1..1]		90
2.17	DebtorAgent	<DbtrAgt>		[1..1]		91
2.18	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]	🚫	91
2.19	UltimateDebtor	<UltmtDbtr>		[0..1]	✦ ⚠	91
2.20	ChargeBearer	<ChrgBr>		[0..1]	✦	92
2.21	ChargesAccount	<ChrgsAcct>		[0..1]	✦	92
2.22	ChargesAccountAgent	<ChrgsAcctAgt>		[0..1]	✦	93
2.23	CreditTransferTransactionInformation	<CdtTrfTxInf>		[1..*]		93

5 Message Components

Note The following chapter identifies the message components.

5.1 AccountIdentification3Choice

Definition: Unique identifier of an account as assigned by the account servicer.

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.1	IBAN	<IBAN>	{Or	[1..1]	🚫	9
1.1.2	BBAN	<BBAN>	Or	[1..1]	🚫	9
1.1.3	UPIC	<UPIC>	Or	[1..1]	🚫	10
1.1.4	ProprietaryAccount	<PrtryAcct>	Or}	[1..1]		10

Used in element(s)

"Identification" on page 17

5.1.1 IBAN

XML Tag: IBAN

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Datatype: "IBANIdentifier" on page 146

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/CreditorAgentAccount/Identification/IBAN) is removed.

5.1.2 BBAN

XML Tag: BBAN

Presence: [1..1]

Definition: Basic Bank Account Number (BBAN) - identifier used nationally by financial institutions, ie, in individual countries, generally as part of a National Account Numbering Scheme(s), to uniquely identify the account of a customer.

Datatype: "BBANIdentifier" on page 126

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/CreditorAgentAccount/Identification/BBAN](#)) is removed.
- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent1Account/Identification/BBAN](#)) is removed.

5.1.3 UPIC

XML Tag: UPIC

Presence: [1..1]

Definition: Universal Payment Identification Code (UPIC) - identifier used by the New York Clearing House to mask confidential data, such as bank accounts and bank routing numbers. UPIC numbers remain with business customers, regardless of banking relationship changes.

Datatype: ["UPICIdentifier"](#) on page 160

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/CreditorAgentAccount/Identification/UPIC](#)) is removed.
- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent1Account/Identification/UPIC](#)) is removed.

5.1.4 ProprietaryAccount

XML Tag: PrtryAcct

Presence: [1..1]

Definition: Account number used by financial institutions in individual countries to identify an account of a customer, but not necessarily the bank and branch of the financial institution in which the account is held.

The **PrtryAcct** block contains the following elements (see datatype ["SimpleIdentificationInformation2"](#) on page 114 for details)

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.5	Identification	<Id>		[1..1]		114

5.2 AccountIdentification3Choice__1

Definition: Unique identifier of an account as assigned by the account servicer.

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.1	IBAN	<IBAN>	{Or	[1..1]	🚫	11
1.1.2	BBAN	<BBAN>	Or	[1..1]	🚫	11
1.1.3	UPIC	<UPIC>	Or	[1..1]	🚫	11
1.1.4	ProprietaryAccount	<PrtryAcct>	Or}	[1..1]		12

Used in element(s)

["Identification" on page 19](#)

5.2.1 IBAN

XML Tag: IBAN

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Datatype: ["IBANIdentifier" on page 146](#)

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Identification/IBAN](#)) is removed.

5.2.2 BBAN

XML Tag: BBAN

Presence: [1..1]

Definition: Basic Bank Account Number (BBAN) - identifier used nationally by financial institutions, ie, in individual countries, generally as part of a National Account Numbering Scheme(s), to uniquely identify the account of a customer.

Datatype: ["BBANIdentifier" on page 126](#)

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/DebtorAccount/Identification/BBAN](#)) is removed.
- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Identification/BBAN](#)) is removed.

5.2.3 UPIC

XML Tag: UPIC

Presence: [1..1]

Definition: Universal Payment Identification Code (UPIC) - identifier used by the New York Clearing House to mask confidential data, such as bank accounts and bank routing numbers. UPIC numbers remain with business customers, regardless of banking relationship changes.

Datatype: "UPICIdentifier" on page 160

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/DebtorAccount/Identification/UPIC) is removed.
- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount/Identification/UPIC) is removed.

5.2.4 ProprietaryAccount

XML Tag: PrtryAcct

Presence: [1..1]

Definition: Account number used by financial institutions in individual countries to identify an account of a customer, but not necessarily the bank and branch of the financial institution in which the account is held.

The **PrtryAcct** block contains the following elements (see datatype "[SimpleIdentificationInformation2__1](#)" on page 114 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - 📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.5	Identification	<Id>		[1..1]	⚠️	115

5.3 AmountType2Choice__1

Definition: Amount of money to be moved between the debtor and creditor, expressed in debtor's account currency or converted in another currency.

🚫 Removed - 💡 Ignored - ⚠️ Details below - 📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.38	InstructedAmount	<InstdAmt>	{Or	[1..1]		12
2.39	EquivalentAmount	<EqvtAmt>	Or}	[1..1]	🚫	13

Used in element(s)

"Amount" on page 30

5.3.1 InstructedAmount

XML Tag: InstdAmt

Presence: [1..1]

Definition: Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

Datatype: "HSBC_AmountAndGBPCurrency" on page 145

5.3.2 EquivalentAmount

XML Tag: EqvtAmt

Presence: [1..1]

Definition: Amount of money to be transferred between the debtor and creditor, before deduction of charges, expressed in the currency of the debtor's account, and to be transferred into a different currency.

Usage : Currency of the amount is expressed in the currency of the debtor's account, but the amount to be transferred is in another currency. The debtor agent will convert the amount and currency to the to be transferred amount and currency, eg, 'pay equivalent of 100000 EUR in JPY'(and account is in EUR).

The **EqvtAmt** block contains the following elements (see datatype "[EquivalentAmount](#)" on page 45 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.40	Amount	<Amt>		[1..1]		45
2.41	CurrencyOfTransfer	<CcyOfTrf>		[1..1]		46

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/Amount/EquivalentAmount](#)) is removed.

5.4 BranchAndFinancialInstitutionIdentification3

Definition: Unique and unambiguous identifier of a financial institution or a branch of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
4.1.0	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	14
4.1.37	BranchIdentification	<BrnchId>		[0..1]		14

Used in element(s)

"ChargesAccountAgent" on page 93, "CreditorAgent" on page 36, "DebtorAgent" on page 91, "ForwardingAgent" on page 60, "IntermediaryAgent1" on page 33, "IntermediaryAgent2" on page 34, "IntermediaryAgent3" on page 35

5.4.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identifier of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "FinancialInstitutionIdentification5Choice" on page 50 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
4.1.1	BIC	<BIC>	{Or	[1..1]	🚫	51
4.1.2	ClearingSystemMemberIdentification	<ClrSysMmbld>	Or	[1..1]	🚫	51
4.1.5	NameAndAddress	<NmAndAdr>	Or	[1..1]	🚫	52
4.1.16	ProprietaryIdentification	<PrtryId>	Or	[1..1]	🚫	52
4.1.19	CombinedIdentification	<CmbndId>	Or}	[1..1]	⚠️	53

Usage Guideline details

- on pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification**
Comment:
 In line with the SWIFT XML rulebook, HSBC only supports the CombinedIdentification option.
- on pain.001.001.02/PaymentInformation/DebtorAgent/FinancialInstitutionIdentification**
Comment:
 In line with the SWIFT XML rulebook, HSBC only supports the CombinedIdentification option.

5.4.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Information identifying a specific branch of a financial institution.

Usage : this component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData](#)" on page 15 for details)

❌ Removed - ✦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
4.1.38	Identification	<Id>		[0..1]		15
4.1.39	Name	<Nm>		[0..1]		15
4.1.40	PostalAddress	<PstlAdr>		[0..1]		15

5.5 BranchData

Definition: Information that locates and identifies a specific branch of a financial institution.

❌ Removed - ✦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
4.1.38	Identification	<Id>		[0..1]		15
4.1.39	Name	<Nm>		[0..1]		15
4.1.40	PostalAddress	<PstlAdr>		[0..1]		15

Used in element(s)

"[BranchIdentification](#)" on page 14

5.5.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a branch of a financial institution.

Datatype: "[Max35Text](#)" on page 151

5.5.2 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "[Max35Text](#)" on page 151

5.5.3 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress1" on page 101 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.2 , 4.1.8 , 4.1.26 , 4.1.41 , 3.1.5 , 3.1.19 , 6.1.0	AddressType	<AdrTp>		[0..1]		103
5.1.3 , 4.1.9 , 4.1.27 , 4.1.42 , 3.1.6 , 3.1.20 , 6.1.1	AddressLine	<AdrLine>		[0..5]		103
5.1.4 , 4.1.10 , 4.1.28 , 4.1.43 , 3.1.7 , 3.1.21 , 6.1.2	StreetName	<StrtNm>		[0..1]		104
5.1.5 , 4.1.11 , 4.1.29 , 4.1.44 , 3.1.8 , 3.1.22 , 6.1.3	BuildingNumber	<BldgNb>		[0..1]		104
5.1.6 , 4.1.12 , 4.1.30 , 4.1.45 , 3.1.9 , 3.1.23 , 6.1.4	PostCode	<PstCd>		[0..1]		104
5.1.7 , 4.1.13 , 4.1.31 , 4.1.46 , 3.1.10 , 3.1.24 , 6.1.5	TownName	<TwnNm>		[0..1]		104
5.1.8 , 4.1.14 , 4.1.32 , 4.1.47 , 3.1.11 , 3.1.25 , 6.1.6	CountrySubDivision	<CtrySubDvsn>		[0..1]		105

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.9 , 4.1.15 , 4.1.33 , 4.1.48 , 3.1.12 , 3.1.26 , 6.1.7	Country	<Ctry>		[1..1]		105

5.6 CashAccount7

Definition: Information used for identifying an account.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.0	Identification	<Id>		[1..1]		17
1.1.6	Type	<Tp>		[0..1]	💡	17
1.1.9	Currency	<Ccy>		[0..1]	💡	18
1.1.10	Name	<Nm>		[0..1]	💡	18

Used in element(s)

"ChargesAccount" on page 92, "CreditorAgentAccount" on page 36, "DebtorAgentAccount" on page 91, "IntermediaryAgent1Account" on page 34, "IntermediaryAgent2Account" on page 35, "IntermediaryAgent3Account" on page 36

5.6.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of the account between the account owner and the account servicer.

The **Id** block contains the following elements (see datatype "[AccountIdentification3Choice](#)" on page 9 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.1	IBAN	<IBAN>	{Or	[1..1]	🚫	9
1.1.2	BBAN	<BBAN>	Or	[1..1]	🚫	9
1.1.3	UPIC	<UPIC>	Or	[1..1]	🚫	10
1.1.4	ProprietaryAccount	<PrtryAcct>	Or}	[1..1]		10

5.6.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Nature, or use, of the account.

The **Tp** block contains the following elements (see datatype "[CashAccountType2](#)" on page 21 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.7	Code	<Cd>	{Or	[1..1]		21
1.1.8	Proprietary	<Prtry>	Or}	[1..1]		21

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent1Account/Type) will be ignored by the Receiver.
- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/CreditorAgentAccount/Type) will be ignored by the Receiver.

5.6.3 Currency

XML Tag: Ccy

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies and the initiating party needs to identify which currency needs to be used for settlement on the account.

Datatype: "[CurrencyCode](#)" on page 137

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/CreditorAgentAccount/Currency) will be ignored by the Receiver.
- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent1Account/Currency) will be ignored by the Receiver.

5.6.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the account, assigned by the account servicing institution in agreement with the account owner in order to provide an additional means of identification of the account.

Usage : the account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: "Max70Text" on page 152

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/CreditorAgentAccount/Name) will be ignored by the Receiver.
- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent1Account/Name) will be ignored by the Receiver.

5.7 CashAccount7__1

Definition: Information used for identifying an account.

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.0	Identification	<Id>		[1..1]		19
1.1.6	Type	<Tp>		[0..1]	♦	20
1.1.9	Currency	<Ccy>		[0..1]	♦	20
1.1.10	Name	<Nm>		[0..1]	♦	20

Used in element(s)

"CreditorAccount" on page 37, "DebtorAccount" on page 90

5.7.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of the account between the account owner and the account servicer.

The **Id** block contains the following elements (see datatype "AccountIdentification3Choice__1" on page 10 for details)

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.1	IBAN	<IBAN>	{Or	[1..1]	🚫	11
1.1.2	BBAN	<BBAN>	Or	[1..1]	🚫	11
1.1.3	UPIC	<UPIC>	Or	[1..1]	🚫	11
1.1.4	ProprietaryAccount	<PrtryAcct>	Or}	[1..1]		12

5.7.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Nature, or use, of the account.

The **Tp** block contains the following elements (see datatype "[CashAccountType2](#)" on page 21 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.7	Code	<Cd>	{Or	[1..1]		21
1.1.8	Proprietary	<Prtry>	Or}	[1..1]		21

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/DebtorAccount/Type) will be ignored by the Receiver.

5.7.3 Currency

XML Tag: Ccy

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies and the initiating party needs to identify which currency needs to be used for settlement on the account.

Datatype: "[CurrencyCode](#)" on page 137

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/DebtorAccount/Currency) will be ignored by the Receiver.

5.7.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the account, assigned by the account servicing institution in agreement with the account owner in order to provide an additional means of identification of the account.

Usage : the account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: "[Max70Text](#)" on page 152

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/DebtorAccount/Name](#)) will be ignored by the Receiver.

5.8 CashAccountType2

Definition: Nature or use of the account.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.7	Code	<Cd>	{Or	[1..1]		21
1.1.8	Proprietary	<Prtry>	Or}	[1..1]		21

Used in element(s)

["Type" on page 20](#), ["Type" on page 17](#)

5.8.1 Code

XML Tag: Cd

Presence: [1..1]

Warning Either Code or Proprietary must be present, but not both.

Definition: Account type, in a coded form.

Datatype: ["CashAccountType4Code" on page 128](#)

5.8.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Warning Either Code or Proprietary must be present, but not both.

Definition: Nature or use of the account in a proprietary form.

Datatype: ["Max35Text" on page 151](#)

5.9 Cheque5

Definition: Set of characteristics related to a cheque instruction, such as cheque type or cheque number.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
3.1.0	ChequeType	<ChqTp>		[0..1]		22
3.1.1	ChequeNumber	<ChqNb>		[0..1]		22
3.1.2	ChequeFrom	<ChqFr>		[0..1]		23
3.1.13	DeliveryMethod	<DlvryMtd>		[0..1]		23
3.1.16	DeliverTo	<DlvrTo>		[0..1]		23
3.1.27	InstructionPriority	<InstrPrty>		[0..1]		24
3.1.28	ChequeMaturityDate	<ChqMtrtyDt>		[0..1]		24
3.1.29	FormsCode	<FrmsCd>		[0..1]		24
3.1.30	MemoField	<MemoFld>		[0..1]		24
3.1.31	RegionalClearingZone	<RgnlClrZone>		[0..1]		24
3.1.32	PrintLocation	<PrtLctn>		[0..1]		25

Rules

R22 ChequeMaturityDateRule

If ChequeType is present and is DRFT or ELDR, then ChequeMaturityDate is optional. If ChequeType is not present or is different from DRFT or ELDR, then ChequeMaturityDate is not allowed.

Rule rationale: ChequeMaturityDate may be present only when ChequeType is DRFT or ELDR.

Error handling: Undefined

Used in element(s)

"ChequeInstruction" on page 31

5.9.1 ChequeType

XML Tag: ChqTp

Presence: [0..1]

Definition: Specifies the type of cheque to be issued by the first agent.

Datatype: "ChequeType2Code" on page 132

5.9.2 ChequeNumber

XML Tag: ChqNb

Presence: [0..1]

Definition: Identifies the cheque number.

Datatype: "Max35Text" on page 151

5.9.3 ChequeFrom

XML Tag: ChqFr

Presence: [0..1]

Definition: Identifies the party that ordered the issuance of the cheque.

The **ChqFr** block contains the following elements (see datatype "[NameAndAddress3](#)" on page 61 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
3.1.3 , 3.1.17 , 2.82	Name	<Nm>		[1..1]		62
3.1.4 , 3.1.18 , 2.83	Address	<Adr>		[1..1]		62

5.9.4 DeliveryMethod

XML Tag: DlvryMtd

Presence: [0..1]

Definition: Specifies the delivery method of the cheque by the debtor's agent.

The **DlvryMtd** block contains the following elements (see datatype "[ChequeDeliveryMethod1Choice](#)" on page 25 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
3.1.14	Code	<Cd>	{Or	[1..1]		25
3.1.15	Proprietary	<Prtry>	Or}	[1..1]		25

5.9.5 DeliverTo

XML Tag: DlvTo

Presence: [0..1]

Definition: Identifies the party to whom the debtor's agent should send the cheque.

The **DlvrTo** block contains the following elements (see datatype "[NameAndAddress3](#)" on page 61 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
3.1.3 , 3.1.17 , 2.82	Name	<Nm>		[1..1]		62
3.1.4 , 3.1.18 , 2.83	Address	<Adr>		[1..1]		62

5.9.6 InstructionPriority

XML Tag: InstrPrty

Presence: [0..1]

Definition: Urgency or order of importance that the originator would like the recipient of the payment instruction to apply to the processing of the payment instruction.

Datatype: "[Priority2Code](#)" on page 156

5.9.7 ChequeMaturityDate

XML Tag: ChqMtrtyDt

Presence: [0..1]

Definition: Date when the draft becomes payable and the debtor's account is debited.

Datatype: "[ISODate](#)" on page 147

5.9.8 FormsCode

XML Tag: FrmsCd

Presence: [0..1]

Definition: Code agreed between the initiating party and the debtor's agent, that specifies the cheque layout, company logo and digitised signature to be used to print the cheque.

Datatype: "[Max35Text](#)" on page 151

5.9.9 MemoField

XML Tag: MemoFld

Presence: [0..1]

Definition: Information that needs to be printed on a cheque, used by the payer to add miscellaneous information.

Datatype: "[Max35Text](#)" on page 151

5.9.10 RegionalClearingZone

XML Tag: RgnlClrZone

Presence: [0..1]

Definition: Regional area in which the cheque can be cleared, when a country has no nation-wide cheque clearing organisation.

Datatype: ["Max35Text" on page 151](#)

5.9.11 PrintLocation

XML Tag: PrtLctn

Presence: [0..1]

Definition: Specifies the print location of the cheque.

Datatype: ["Max35Text" on page 151](#)

5.10 ChequeDeliveryMethod1Choice

Definition: Set of characteristics related to a cheque instruction, such as cheque type or cheque number.

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
3.1.14	Code	<Cd>	{Or	[1..1]		25
3.1.15	Proprietary	<Prtry>	Or}	[1..1]		25

Used in element(s)

["DeliveryMethod" on page 23](#)

5.10.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the delivery method of the cheque by the debtor's agent.

Datatype: ["ChequeDelivery1Code" on page 131](#)

5.10.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies a proprietary delivery method of the cheque by the debtor's agent.

Datatype: ["Max35Text" on page 151](#)

5.11 ClearingSystemMemberIdentification3Choice

Definition: Choice of identifiers for a clearing system member, as assigned by the clearing system. In some clearing systems, the accounts of the clearing system members are also assigned an identifier.

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
4.1.3 , 4.1.22	Identification	<Id>	{Or	[1..1]		26
4.1.4 , 4.1.23	Proprietary	<Prtry>	Or}	[1..1]	🚫	26

Used in element(s)

"ClearingSystemMemberIdentification" on page 47, "ClearingSystemMemberIdentification" on page 51

5.11.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification for a clearing system member, identified in the list of clearing system member identifications published externally.

Datatype: "ExternalClearingSystemMemberCode" on page 142

5.11.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Identification Code for a clearing system, that has not yet been identified in the list of clearing systems.

Datatype: "Max35Text" on page 151

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/CombinedIdentification/ClearingSystemMemberIdentification/Proprietary) is removed.
- This element(pain.001.001.02/PaymentInformation/DebtorAgent/FinancialInstitutionIdentification/CombinedIdentification/ClearingSystemMemberIdentification/Proprietary) is removed.

5.12 CreditTransferTransactionInformation1__1

Definition: Set of elements providing information specific to the individual transaction(s) included in the message.

Removed -
 Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.24	PaymentIdentification	<PmtId>		[1..1]		29
2.27	PaymentTypeInfo	<PmtTplnf>		[0..1]		29
2.37	Amount	<Amt>		[1..1]		30
2.42	ExchangeRateInformation	<XchgRateInf>		[0..1]		30
2.46	ChargeBearer	<ChrgBr>		[0..1]		31
2.47	ChequeInstruction	<ChqInstr>		[0..1]		31
2.48	UltimateDebtor	<UltmtDbtr>		[0..1]		32
2.49	IntermediaryAgent1	<IntrmyAgt1>		[0..1]		33
2.50	IntermediaryAgent1Account	<IntrmyAgt1Acct>		[0..1]		34
2.51	IntermediaryAgent2	<IntrmyAgt2>		[0..1]		34
2.52	IntermediaryAgent2Account	<IntrmyAgt2Acct>		[0..1]		35
2.53	IntermediaryAgent3	<IntrmyAgt3>		[0..1]		35
2.54	IntermediaryAgent3Account	<IntrmyAgt3Acct>		[0..1]		36
2.55	CreditorAgent	<CdtrAgt>		[0..1]		36
2.56	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		36
2.57	Creditor	<Cdtr>		[0..1]		37
2.58	CreditorAccount	<CdtrAcct>		[0..1]		37
2.59	UltimateCreditor	<UltmtCdtr>		[0..1]		38
2.60	InstructionForCreditorAgent	<InstrForCdtrAgt>		[0..*]		38
2.63	InstructionForDebtorAgent	<InstrForDbtrAgt>		[0..1]		39
2.64	Purpose	<Purp>		[0..1]		39
2.67	RegulatoryReporting	<RgltryRptg>		[0..10]		40
2.76	Tax	<Tax>		[0..1]		40
2.77	RelatedRemittanceInformation	<RltdRmtInf>		[0..10]		41
2.84	RemittanceInformation	<RmtInf>		[0..1]		41

Rules

R15 IntermediaryAgent2Rule

If IntermediaryAgent2 is present, then IntermediaryAgent1 must be present.

Error handling: Undefined

Usage Guideline restrictions for this element

- This rule(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent2Rule) is removed.

R16 IntermediaryAgent3Rule

If IntermediaryAgent3 is present, then IntermediaryAgent2 must be present.

Error handling: Undefined

Usage Guideline restrictions for this element

- This rule(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent3Rule) is removed.

R17 InstructionForCreditorAgentRule

If InstructionForCreditorAgent/Code contains CHQB, then CreditorAccount is not allowed.

Error handling: Undefined

R18 IntermediaryAgent1AccountRule

If IntermediaryAgent1 is not present, then IntermediaryAgent1Account is not allowed.

Error handling: Undefined

R19 IntermediaryAgent2AccountRule

If IntermediaryAgent2 is not present, then IntermediaryAgent2Account is not allowed.

Error handling: Undefined

Usage Guideline restrictions for this element

- This rule(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent2AccountRule) is removed.

R20 IntermediaryAgent3AccountRule

If IntermediaryAgent3 is not present, then IntermediaryAgent3Account is not allowed.

Error handling: Undefined

Usage Guideline restrictions for this element

- This rule(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent3AccountRule) is removed.

Guidelines**1. UltimateCreditorGuideline**

UltimateCreditor may only be present if different from Creditor.

2. UltimateDebtorGuideline

UltimateDebtor may only be present if different from Debtor.

Used in element(s)

["CreditTransferTransactionInformation" on page 93](#)

5.12.1 PaymentIdentification

XML Tag: PmtId

Presence: [1..1]

Definition: Set of elements to reference a payment instruction.

The **PmtId** block contains the following elements (see datatype ["PaymentIdentification1__1"](#) on page 85 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.25	InstructionIdentification	<InstrId>		[0..1]	⚠️	85
2.26	EndToEndIdentification	<EndToEndId>		[1..1]	⚠️	85

Usage Guideline details

- on [pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/PaymentIdentification](#)

Comment:

The Payment Identification tag allows the originator to specify two reference numbers for the transaction. Where used, the Instruction ID is viewed as the customer to bank reference. In line with industry agreement, the EndToEndID is used to reference the payment for all parties (including the beneficiary).

5.12.2 PaymentTypeInformation

XML Tag: PmtTpInf

Presence: [0..1]

Definition: Set of elements used to further specify the type of transaction.

The **PmtTpInf** block contains the following elements (see datatype "PaymentTypeInformation1" on page 94 for details)

🚫 Removed - ⚡ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.4 , 2.28	InstructionPriority	<InstrPrty>		[0..1]	⚡	95
2.5 , 2.29	ServiceLevel	<SvcLv>	{Or	[0..1]	🚫	95
2.8 , 2.32	ClearingChannel	<ClrChan>	Or}	[0..1]	M	96
2.9 , 2.33	LocalInstrument	<LclInstrm>		[0..1]		96
2.12 , 2.36	CategoryPurpose	<CtgyPurp>		[0..1]		97

5.12.3 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

The **Amt** block contains the following elements (see datatype "AmountType2Choice__1" on page 12 for details)

🚫 Removed - ⚡ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.38	InstructedAmount	<InstdAmt>	{Or	[1..1]		12
2.39	EquivalentAmount	<EqvtAmt>	Or}	[1..1]	🚫	13

5.12.4 ExchangeRateInformation

XML Tag: XchgRateInf

Presence: [0..1]

Definition: Further detailed information on the exchange rate specified in the payment transaction.

The **XchgRateInf** block contains the following elements (see datatype "[ExchangeRateInformation1](#)" on [page 46](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.43	ExchangeRate	<XchgRate>		[0..1]		46
2.44	RateType	<RateTp>		[0..1]		46
2.45	ContractIdentification	<CtrctId>		[0..1]		46

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/ExchangeRateInformation](#)) is removed.

5.12.5 ChargeBearer

XML Tag: ChrgBr

Presence: [0..1]

Definition: Specifies which party/parties will bear the charges associated with the processing of the payment transaction.

Datatype: "[ChargeBearerType1Code](#)" on [page 130](#)

Usage Guideline details

- on [pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/ChargeBearer](#)
 - **HSBC_ChargeBearer:**

Depending on type of payment, some options may be invalid. If not used, HSBC will default to SHAR

5.12.6 ChequeInstruction

XML Tag: ChqInstr

Presence: [0..1]

Definition: Information related to the issuance of a cheque.

The **ChqInstr** block contains the following elements (see datatype "Cheque5" on page 21 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
3.1.0	ChequeType	<ChqTp>		[0..1]		22
3.1.1	ChequeNumber	<ChqNb>		[0..1]		22
3.1.2	ChequeFrom	<ChqFr>		[0..1]		23
3.1.13	DeliveryMethod	<DlvryMtd>		[0..1]		23
3.1.16	DeliverTo	<DlvrTo>		[0..1]		23
3.1.27	InstructionPriority	<InstrPrty>		[0..1]		24
3.1.28	ChequeMaturityDate	<ChqMtrtyDt>		[0..1]		24
3.1.29	FormsCode	<FrmsCd>		[0..1]		24
3.1.30	MemoField	<MemoFld>		[0..1]		24
3.1.31	RegionalClearingZone	<RgnlClrZone>		[0..1]		24
3.1.32	PrintLocation	<PrtLctn>		[0..1]		25

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/ChequeInstruction) is removed.
- on pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/ChequeInstruction

Comment:

Refer to COS Product Appendix

5.12.7 UltimateDebtor

XML Tag: UltmtDbtr

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor.

The **UltmtDbtr** block contains the following elements (see datatype "[PartyIdentification8](#)" on page 75 for details)

🚫 Removed - ⬜ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.0	Name	<Nm>		[0..1]		75
5.1.1	PostalAddress	<PstlAdr>		[0..1]		75
5.1.10	Identification	<Id>		[0..1]	⬜	77
5.1.41	CountryOfResidence	<CtryOfRes>		[0..1]	⬜	77

Usage Guideline details

- on [pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor](#)

Comment:

Name of the party owing the money may be provided if different from debtor.

5.12.8 IntermediaryAgent1

XML Tag: IntrmyAgt1

Presence: [0..1]

Definition: Agent between the debtor agent and creditor agent.

Usage: If more than one intermediary agent is present, then IntermediaryAgent1 identifies the agent between the debtor agent and the intermediary agent 2.

The **IntrmyAgt1** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification3](#)" on page 13 for details)

🚫 Removed - ⬜ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
4.1.0	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		14
4.1.37	BranchIdentification	<BrnchId>		[0..1]		14

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent1](#)) will be ignored by the Receiver.
- on [pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent1](#)

– **HSBC_IntermediaryAgent1:**

Intermediary agent if required for the payment. This information should only be provided if specifically requested by the payee

5.12.9 IntermediaryAgent1Account

XML Tag: IntrmyAgt1Acct

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 1 at its servicing agent in the payment chain.

The **IntrmyAgt1Acct** block contains the following elements (see datatype "[CashAccount7](#)" on [page 17](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.0	Identification	<Id>		[1..1]		17
1.1.6	Type	<Tp>		[0..1]	💡	17
1.1.9	Currency	<Ccy>		[0..1]	💡	18
1.1.10	Name	<Nm>		[0..1]	💡	18

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent1Account](#)) is removed.

5.12.10 IntermediaryAgent2

XML Tag: IntrmyAgt2

Presence: [0..1]

Definition: Agent between the debtor agent and creditor agent.

Usage: If more than two intermediary agents are present, then IntermediaryAgent2 identifies the agent between the intermediary agent 1 and the intermediary agent 3.

The **IntrmyAgt2** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification3](#)" on [page 13](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
4.1.0	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		14
4.1.37	BranchIdentification	<BrnchId>		[0..1]		14

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent2](#)) is removed.

5.12.11 IntermediaryAgent2Account

XML Tag: IntrmyAgt2Acct

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 2 at its servicing agent in the payment chain.

The **IntrmyAgt2Acct** block contains the following elements (see datatype "[CashAccount7](#)" on [page 17](#) for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.0	Identification	<Id>		[1..1]		17
1.1.6	Type	<Tp>		[0..1]		17
1.1.9	Currency	<Ccy>		[0..1]		18
1.1.10	Name	<Nm>		[0..1]		18

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent2Account](#)) is removed.

5.12.12 IntermediaryAgent3

XML Tag: IntrmyAgt3

Presence: [0..1]

Definition: Agent between the debtor agent and creditor agent.

Usage: If IntermediaryAgent3 is present, then it identifies the agent between the intermediary agent 2 and the creditor agent.

The **IntrmyAgt3** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification3](#)" on [page 13](#) for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
4.1.0	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		14
4.1.37	BranchIdentification	<BrnchId>		[0..1]		14

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent3](#)) is removed.

5.12.13 IntermediaryAgent3Account

XML Tag: IntrmyAgt3Acct

Presence: [0..1]

Definition: Unambiguous identification of the account of the intermediary agent 3 at its servicing agent in the payment chain.

The **IntrmyAgt3Acct** block contains the following elements (see datatype "[CashAccount7](#)" on [page 17](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.0	Identification	<Id>		[1..1]		17
1.1.6	Type	<Tp>		[0..1]		17
1.1.9	Currency	<Ccy>		[0..1]		18
1.1.10	Name	<Nm>		[0..1]		18

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/IntermediaryAgent3Account](#)) is removed.

5.12.14 CreditorAgent

XML Tag: CdtrAgt

Presence: [0..1]

Definition: Financial institution servicing an account for the creditor.

The **CdtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification3](#)" on [page 13](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
4.1.0	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠️	14
4.1.37	BranchIdentification	<BrnchId>		[0..1]		14

Usage Guideline details

- on [pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent](#)
This element is now mandatory, the minimum occurrence has been changed to : 1

5.12.15 CreditorAgentAccount

XML Tag: CdtrAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction.

The **CdtrAgtAcct** block contains the following elements (see datatype "[CashAccount7](#)" on page 17 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.0	Identification	<Id>		[1..1]		17
1.1.6	Type	<Tp>		[0..1]	💡	17
1.1.9	Currency	<Ccy>		[0..1]	💡	18
1.1.10	Name	<Nm>		[0..1]	💡	18

5.12.16 Creditor

XML Tag: Cdtr

Presence: [0..1]

Definition: Party to which an amount of money is due.

The **Cdtr** block contains the following elements (see datatype "[PartyIdentification8__2](#)" on page 81 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.0	Name	<Nm>		[0..1]	M ⚠	81
5.1.1	PostalAddress	<PstlAdr>		[0..1]	M ⚠	81
5.1.10	Identification	<Id>		[0..1]		84
5.1.41	CountryOfResidence	<CtryOfRes>		[0..1]		84

Usage Guideline details

- on [pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/Creditor](#)
This element is now mandatory, the minimum occurrence has been changed to : 1

5.12.17 CreditorAccount

XML Tag: CdtrAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.

The **CdtrAcct** block contains the following elements (see datatype "CashAccount7__1" on page 19 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.0	Identification	<Id>		[1..1]		19
1.1.6	Type	<Tp>		[0..1]		20
1.1.9	Currency	<Ccy>		[0..1]		20
1.1.10	Name	<Nm>		[0..1]		20

Usage Guideline details

- on pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/CreditorAccount

This element is now mandatory, the minimum occurrence has been changed to : 1

5.12.18 UltimateCreditor

XML Tag: UltmtCdtr

Presence: [0..1]

Definition: Ultimate party to which an amount of money is due.

The **UltmtCdtr** block contains the following elements (see datatype "PartyIdentification8" on page 75 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.0	Name	<Nm>		[0..1]		75
5.1.1	PostalAddress	<PstlAdr>		[0..1]		75
5.1.10	Identification	<Id>		[0..1]		77
5.1.41	CountryOfResidence	<CtryOfRes>		[0..1]		77

5.12.19 InstructionForCreditorAgent

XML Tag: InstrForCdtrAgt

Presence: [0..*]

Definition: Further information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor agent.

The **InstrForCdtrAgt** block contains the following elements (see datatype "[InstructionForCreditorAgent1](#)" on page 60 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.61	Code	<Cd>		[0..1]		60
2.62	InstructionInformation	<InstrInf>		[0..1]		60

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/InstructionForCreditorAgent](#)) will be ignored by the Receiver.

5.12.20 InstructionForDebtorAgent

XML Tag: InstrForDbtrAgt

Presence: [0..1]

Definition: Further information related to the processing of the payment instruction that may need to be acted upon by the debtor agent, depending on agreement between debtor and the debtor agent.

Usage: The instruction can relate to a level of service, can be an instruction to be executed by the debtor's agent, or can be information required by the debtor's agent to process the instruction.

Datatype: "[Max140Text](#)" on page 149

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/InstructionForDebtorAgent](#)) will be ignored by the Receiver.

5.12.21 Purpose

XML Tag: Purp

Presence: [0..1]

Definition: Underlying reason for the payment transaction, eg, a charity payment, or a commercial agreement between the creditor and the debtor.

Usage: purpose is used by the end-customers, ie originating party, initiating party, debtor, creditor, final party, to provide information concerning the nature of the payment transaction. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

The **Purp** block contains the following elements (see datatype "Purpose1Choice" on page 105 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.65	Code	<Cd>	{Or	[1..1]		106
2.66	Proprietary	<Prtry>	Or}	[1..1]		106

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/Purpose) will be ignored by the Receiver.

5.12.22 RegulatoryReporting

XML Tag: RgltryRptg

Presence: [0..10]

Definition: Information needed due to regulatory and statutory requirements.

The **RgltryRptg** block contains the following elements (see datatype "RegulatoryReporting2" on page 109 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.68	DebitCreditReportingIndicator	<DbtCdtRptgInd>		[0..1]		110
2.69	Authority	<Authrty>		[0..1]		110
2.72	RegulatoryDetails	<RgltryDtls>		[0..1]		110

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/RegulatoryReporting) will be ignored by the Receiver.

5.12.23 Tax

XML Tag: Tax

Presence: [0..1]

Definition: Amount of money due to the government or tax authority, according to various pre-defined parameters such as thresholds or income.

The **Tax** block contains the following elements (see datatype "[TaxInformation2__1](#)" on [page 120](#) for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
7.1.0	CreditorTaxIdentification	<CdtrTaxId>		[0..1]	💡	121
7.1.1	CreditorTaxType	<CdtrTaxTp>		[0..1]	💡	121
7.1.2	DebtorTaxIdentification	<DbtrTaxId>		[0..1]	💡	121
7.1.3	TaxReferenceNumber	<TaxRefNb>		[0..1]	⚠	121
7.1.4	TotalTaxableBaseAmount	<TtlTaxblBaseAmt>		[0..1]	💡	122
7.1.5	TotalTaxAmount	<TtlTaxAmt>		[0..1]	💡	122
7.1.6	TaxDate	<TaxDt>		[0..1]	💡	122
7.1.7	TaxTypeInformation	<TaxTplnf>		[0..*]	💡	123

5.12.24 RelatedRemittanceInformation

XML Tag: RltdRmtInf

Presence: [0..10]

Definition: Information related to the handling of the remittance information by any of the agents in the transaction processing chain.

The **RltdRmtInf** block contains the following elements (see datatype "[RemittanceLocation1](#)" on [page 112](#) for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.78	RemittanceIdentification	<RmtId>		[0..1]		112
2.79	RemittanceLocationMethod	<RmtLctnMtd>		[0..1]		112
2.80	RemittanceLocationElectronicAddress	<RmtLctnElctrcAdr>		[0..1]		113
2.81	RemittanceLocationPostalAddress	<RmtLctnPstlAdr>		[0..1]		113

5.12.25 RemittanceInformation

XML Tag: RmtInf

Presence: [0..1]

Definition: Information that enables the matching, ie, reconciliation, of a payment with the items that the payment is intended to settle, eg, commercial invoices in an account receivable system.

The **RmtInf** block contains the following elements (see datatype "[RemittanceInformation1](#)" on [page 111](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.85	Unstructured	<Ustrd>		[0..*]		111
2.86	Structured	<Strd>		[0..*]		111

Usage Guideline details

- on [pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation](#)

Comment:

The Remittance Information section contains information about the purpose of the payment. Typically, only limited information can be sent with the payment (payment details) due to restrictions in the clearing systems.

5.13 CreditorReferenceInformation1

Definition: Structured information supplied to enable the matching, i.e. reconciliation, of a payment with the items that the payment is intended to settle, eg, commercial invoices in an accounts receivable system.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.101	CreditorReferenceType	<CdtrRefTp>		[0..1]		42
2.105	CreditorReference	<CdtrRef>		[0..1]		43

Used in element(s)

"[CreditorReferenceInformation](#)" on [page 117](#)

5.13.1 CreditorReferenceType

XML Tag: CdtrRefTp

Presence: [0..1]

Definition: Provides the type of the creditor reference.

The **CdtrRefTp** block contains the following elements (see datatype "[CreditorReferenceType1](#)" on page 43 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.102	Code	<Cd>	{Or	[1..1]		43
2.103	Proprietary	<Prtry>	Or}	[1..1]		44
2.104	Issuer	<Issr>		[0..1]		44

5.13.2 CreditorReference

XML Tag: CdtrRef

Presence: [0..1]

Definition: Unique and unambiguous reference assigned by the creditor to refer to the payment transaction.

Usage: if available, the initiating party should provide this reference in the structured remittance information, to enable reconciliation by the creditor upon receipt of the cash.

If the business context requires the use of a creditor reference or a payment remit identification, and only one identifier can be passed through the end-to-end chain, the creditor's reference or payment remittance identification should be quoted in the end-to-end transaction identification.

Datatype: "[Max35Text](#)" on page 151

5.14 CreditorReferenceType1

Definition: Specifies the type of the documents referred by the creditor.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.102	Code	<Cd>	{Or	[1..1]		43
2.103	Proprietary	<Prtry>	Or}	[1..1]		44
2.104	Issuer	<Issr>		[0..1]		44

Used in element(s)

"[CreditorReferenceType](#)" on page 42

5.14.1 Code

XML Tag: Cd

Presence: [1..1]

Warning If Code is present then Proprietary must not be present.

If Proprietary is present then Code must not be present.

Definition: Coded creditor reference type.

Datatype: "DocumentType3Code" on page 139

5.14.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Warning If Code is present then Proprietary must not be present.

If Proprietary is present then Code must not be present.

Definition: Creditor reference type not available in a coded format.

Datatype: "Max35Text" on page 151

5.14.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Identification of the issuer of the credit reference type.

Datatype: "Max35Text" on page 151

5.15 DateAndPlaceOfBirth

Definition: Date and place of birth of a person.

🚫 Removed - 💡 Ignored - ⚠️ Details below - 📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.33	BirthDate	<BirthDt>		[1..1]		44
5.1.34	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		45
5.1.35	CityOfBirth	<CityOfBirth>		[1..1]		45
5.1.36	CountryOfBirth	<CtryOfBirth>		[1..1]		45

Used in element(s)

"DateAndPlaceOfBirth" on page 100

5.15.1 BirthDate

XML Tag: BirthDt

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: "ISODate" on page 147

5.15.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: ["Max35Text" on page 151](#)

5.15.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: ["Max35Text" on page 151](#)

5.15.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: ["CountryCode" on page 136](#)

5.16 EquivalentAmount

Definition: Amount of money to be transferred between the debtor and creditor, before deduction of charges, expressed in the currency of the debtor's account, and to be transferred into a different currency.

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.40	Amount	<Amt>		[1..1]		45
2.41	CurrencyOfTransfer	<CcyOfTrf>		[1..1]		46

Used in element(s)

["EquivalentAmount" on page 13](#)

5.16.1 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money to be transferred between debtor and creditor, before deduction of charges, expressed in the currency of the debtor's account, and to be transferred in a different currency.

Usage : Currency of the amount is expressed in the currency of the debtor's account, but the amount to be transferred is in another currency. The first agent will convert the amount and currency to the to be transferred amount and currency, eg, 'pay equivalent of 100000 EUR in JPY'(and account is in EUR).

Datatype: ["CurrencyAndAmount" on page 137](#)

5.16.2 CurrencyOfTransfer

XML Tag: CcyOfTrf

Presence: [1..1]

Definition: Specifies the currency of the to be transferred amount, which is different from the currency of the debtor's account.

Datatype: ["CurrencyCode" on page 137](#)

5.17 ExchangeRateInformation1

Definition: Further detailed information on the exchange rate that has been used in the payment transaction.

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.43	ExchangeRate	<XchgRate>		[0..1]		46
2.44	RateType	<RateTp>		[0..1]		46
2.45	ContractIdentification	<CtrctId>		[0..1]		46

Used in element(s)

["ExchangeRateInformation" on page 30](#)

5.17.1 ExchangeRate

XML Tag: XchgRate

Presence: [0..1]

Definition: The factor used for conversion of an amount from one currency to another. This reflects the price at which one currency was bought with another currency.

Datatype: ["BaseOneRate" on page 127](#)

5.17.2 RateType

XML Tag: RateTp

Presence: [0..1]

Definition: Specifies the type used to complete the currency exchange.

Datatype: ["ExchangeRateType1Code" on page 142](#)

5.17.3 ContractIdentification

XML Tag: CtrctId

Presence: [0..1]

Definition: Unique and unambiguous reference to the foreign exchange contract agreed between the initiating party/creditor and the debtor agent.

Datatype: "Max35Text" on page 151

5.18 FinancialInstitutionIdentification3

Definition: Unique and unambiguous identifier of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
4.1.20	BIC	<BIC>		[0..1]		47
4.1.21	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]	M	47
4.1.24	Name	<Nm>		[0..1]		48
4.1.25	PostalAddress	<PstlAdr>		[0..1]	M	48
4.1.34	ProprietaryIdentification	<PrtryId>		[0..1]		50

Used in element(s)

"CombinedIdentification" on page 53

5.18.1 BIC

XML Tag: BIC

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICIdentifier" on page 126

5.18.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Unique and unambiguous identifier of a clearing system member, as assigned by the system or system administrator.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification3Choice" on page 25 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
4.1.3 , 4.1.22	Identification	<Id>	{Or	[1..1]		26
4.1.4 , 4.1.23	Proprietary	<Prtry>	Or}	[1..1]	🚫	26

Usage Guideline details

- on **pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/CombinedIdentification/ClearingSystemMemberIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **pain.001.001.02/PaymentInformation/DebtorAgent/FinancialInstitutionIdentification/CombinedIdentification/ClearingSystemMemberIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.18.3 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max70Text" on page 152

5.18.4 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "[PostalAddress1](#)" on [page 101](#) for details)

🚫 Removed - ⬜ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.2 , 4.1.8 , 4.1.26 , 4.1.41 , 3.1.5 , 3.1.19 , 6.1.0	AddressType	<AdrTp>		[0..1]		103
5.1.3 , 4.1.9 , 4.1.27 , 4.1.42 , 3.1.6 , 3.1.20 , 6.1.1	AddressLine	<AdrLine>		[0..5]		103
5.1.4 , 4.1.10 , 4.1.28 , 4.1.43 , 3.1.7 , 3.1.21 , 6.1.2	StreetName	<StrtNm>		[0..1]		104
5.1.5 , 4.1.11 , 4.1.29 , 4.1.44 , 3.1.8 , 3.1.22 , 6.1.3	BuildingNumber	<BldgNb>		[0..1]		104
5.1.6 , 4.1.12 , 4.1.30 , 4.1.45 , 3.1.9 , 3.1.23 , 6.1.4	PostCode	<PstCd>		[0..1]		104
5.1.7 , 4.1.13 , 4.1.31 , 4.1.46 , 3.1.10 , 3.1.24 , 6.1.5	TownName	<TwnNm>		[0..1]		104
5.1.8 , 4.1.14 , 4.1.32 , 4.1.47 , 3.1.11 , 3.1.25 , 6.1.6	CountrySubDivision	<CtrySubDvsn>		[0..1]		105

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.9 , 4.1.15 , 4.1.33 , 4.1.48 , 3.1.12 , 3.1.26 , 6.1.7	Country	<Ctry>		[1..1]		105

Usage Guideline details

- on **pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/CombinedIdentification/PostalAddress**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **pain.001.001.02/PaymentInformation/DebtorAgent/FinancialInstitutionIdentification/CombinedIdentification/PostalAddress**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.18.5 ProprietaryIdentification

XML Tag: PrtryId

Presence: [0..1]

Definition: Unique and unambiguous identifier, as assigned to a financial institution using a proprietary identification scheme.

The **PrtryId** block contains the following elements (see datatype "GenericIdentification3" on page 54 for details)

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.21 , 4.1.17 , 4.1.35	Identification	<Id>		[1..1]		54
5.1.22 , 4.1.18 , 4.1.36	Issuer	<Issr>		[0..1]		54

5.19 FinancialInstitutionIdentification5Choice

Definition: Unique and unambiguous identifier of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
4.1.1	BIC	<BIC>	{Or	[1..1]	🚫	51
4.1.2	ClearingSystemMemberIdentification	<ClrSysMmbld>	Or	[1..1]	🚫	51
4.1.5	NameAndAddress	<NmAndAdr>	Or	[1..1]	🚫	52
4.1.16	ProprietaryIdentification	<PrtryId>	Or	[1..1]	🚫	52
4.1.19	CombinedIdentification	<CmbndId>	Or}	[1..1]	⚠	53

Used in element(s)

"FinancialInstitutionIdentification" on page 14

5.19.1 BIC

XML Tag: BIC

Presence: [1..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICIdentifier" on page 126

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/DebtorAgent/FinancialInstitutionIdentification/BIC) is removed.
- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/BIC) is removed.

5.19.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [1..1]

Definition: Unique and unambiguous identifier of a clearing system member, as assigned by the system or system administrator.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification3Choice" on page 25 for details)

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
4.1.3 , 4.1.22	Identification	<Id>	{Or	[1..1]		26
4.1.4 , 4.1.23	Proprietary	<Prtry>	Or}	[1..1]		26

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/DebtorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification](#)) is removed.
- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification](#)) is removed.

5.19.3 NameAndAddress

XML Tag: NmAndAdr

Presence: [1..1]

Definition: Identifies the name and address of a financial institution.

The **NmAndAdr** block contains the following elements (see datatype "[NameAndAddress7](#)" on [page 64](#) for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
4.1.6	Name	<Nm>		[1..1]		64
4.1.7	PostalAddress	<PstlAdr>		[1..1]		64

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/DebtorAgent/FinancialInstitutionIdentification/NameAndAddress](#)) is removed.
- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/NameAndAddress](#)) is removed.

5.19.4 ProprietaryIdentification

XML Tag: PrtryId

Presence: [1..1]

Definition: Unique and unambiguous identifier, as assigned to a financial institution using a proprietary identification scheme.

The **PrtryId** block contains the following elements (see datatype "[GenericIdentification3](#)" on page 54 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.21 , 4.1.17 , 4.1.35	Identification	<Id>		[1..1]		54
5.1.22 , 4.1.18 , 4.1.36	Issuer	<Issr>		[0..1]		54

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/DebtorAgent/FinancialInstitutionIdentification/ProprietaryIdentification](#)) is removed.
- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/ProprietaryIdentification](#)) is removed.

5.19.5 CombinedIdentification

XML Tag: CmbndId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, through a combination of globally recognised or proprietary identification scheme.

The **CmbndId** block contains the following elements (see datatype "[FinancialInstitutionIdentification3](#)" on page 47 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
4.1.20	BIC	<BIC>		[0..1]		47
4.1.21	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]	M	47
4.1.24	Name	<Nm>		[0..1]		48
4.1.25	PostalAddress	<PstlAdr>		[0..1]	M	48
4.1.34	ProprietaryIdentification	<PrtryId>		[0..1]		50

Usage Guideline details

- on [pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/CreditorAgent/FinancialInstitutionIdentification/CombinedIdentification](#)

Comment:

Sort code (6 digits) should be provided in [ClearingSystemMemberIdentification/Identification](#) under [CombinedIdentification](#).

- on pain.001.001.02/PaymentInformation/DebtorAgent/FinancialInstitutionIdentification/CombinedIdentification

Comment:

Sort code is required, but the Swift BIC can additionally be provided. For sort code use ClearingSystemMemberIdentification/Identification under CombinedIdentification.

5.20 GenericIdentification3

Definition: Information related to an identification, eg, party identification or account identification.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.21 , 4.1.17 , 4.1.35	Identification	<Id>		[1..1]		54
5.1.22 , 4.1.18 , 4.1.36	Issuer	<Issr>		[0..1]	🚫	54

Used in element(s)

"ProprietaryIdentification" on page 68, "ProprietaryIdentification" on page 50, "ProprietaryIdentification" on page 52

5.20.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Name or number assigned by an entity to enable recognition of that entity, eg, account identifier.

Datatype: "Max35Text" on page 151

5.20.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 151

Usage Guideline details

- This element(pain.001.001.02/GroupHeader/InitiatingParty/Identification/OrganisationIdentification/ProprietaryIdentification/Issuer) is removed.

5.21 GenericIdentification3__1

Definition: Information related to an identification, eg, party identification or account identification.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.21 , 4.1.17 , 4.1.35	Identification	<Id>		[1..1]	⚠️	55
5.1.22 , 4.1.18 , 4.1.36	Issuer	<Issr>		[0..1]		55

Used in element(s)

"ProprietaryIdentification" on page 71

5.21.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Name or number assigned by an entity to enable recognition of that entity, eg, account identifier.

Datatype: "Max6Text" on page 151

Usage Guideline details

- on pain.001.001.02/PaymentInformation/Debtor/Identification/OrganisationIdentification/ProprietaryIdentification/Identification
 - **HSBC_Identification:**

Identification should be BACS ID. If not provided, BACS ID will be enriched from static data

5.21.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 151

5.22 GenericIdentification4

Definition: Information related to an identification, eg, party identification or account identification.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.38	Identification	<Id>		[1..1]		56
5.1.39	IdentificationType	<IdTp>		[1..1]		56

Used in element(s)

"OtherIdentification" on page 100

5.22.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identifier issued to a person for which no specific identifier has been defined.

Datatype: "Max35Text" on page 151

5.22.2 IdentificationType

XML Tag: IdTp

Presence: [1..1]

Definition: Specifies the nature of the identifier.

Usage: IdentificationType is used to specify what kind of identifier is used. It should be used in case the identifier is different from the identifiers listed in the pre-defined identifier list.

Datatype: "Max35Text" on page 151

5.23 GroupHeader1__1

Definition: Set of characteristics shared by all individual transactions included in the message.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1	MessageIdentification	<MsgId>		[1..1]	⚠️	57
1.2	CreationDateTime	<CreDtTm>		[1..1]	⚠️	57
1.3	Authorisation	<Authstn>		[0..2]	⚠️ R[0..1]	57
1.4	BatchBooking	<BtchBookg>		[0..1]	⚠️	58
1.5	NumberOfTransactions	<NbOfTx>		[1..1]	⚠️	58
1.6	ControlSum	<CtrlSum>		[0..1]	⚠️	59
1.7	Grouping	<Grpg>		[1..1]		59
1.8	InitiatingParty	<InitgPty>		[1..1]		59
1.9	ForwardingAgent	<FwdgAgt>		[0..1]	💡	60

Used in element(s)

["GroupHeader" on page 7](#)

5.23.1 MessageIdentification

XML Tag: MsgId

Presence: [1..1]

Definition: Point to point reference assigned by the instructing party and sent to the next party in the chain to unambiguously identify the message.

Usage: The instructing party has to make sure that 'MessageIdentification' is unique per instructed party for a pre-agreed period.

Datatype: ["Max35Text" on page 151](#)

Usage Guideline details

- on [pain.001.001.02/GroupHeader/MessageIdentification](#)

- **HSBC_MessageIdentification:**

Message Identification is a unique message reference used with status messages returned for the processing of the file.

5.23.2 CreationDateTime

XML Tag: CreDtTm

Presence: [1..1]

Definition: Date and time at which a (group of) payment instruction(s) was created by the instructing party.

Datatype: ["ISODateTime" on page 147](#)

Usage Guideline details

- on [pain.001.001.02/GroupHeader/CreationDateTime](#)

- Comment:**

Creation date must not be older than 5 days.

5.23.3 Authorisation

XML Tag: Authstn

Presence: [0..2]

Definition: User identification or any user key that allows to check if the initiating party is allowed to initiate transactions from the account specified in the initiation.

Usage: the content is not of a technical nature, but reflects the organisational structure at the initiating side. The authorisation element can typically be used in relay scenarios, payment initiations, payment returns or payment reversals that are initiated on behalf of a different party than the initiating party.

Datatype: ["HSBC_Authorisation" on page 145](#)

Usage Guideline details

- on **pain.001.001.02/GroupHeader/Authorisation**

This element has change repeatability, the maximum occurrence has been changed to : 1

- on **pain.001.001.02/GroupHeader/Authorisation**

- **HSBC_Authorisation:**

Code 'AUTH' is defaulted if not used.

- on **pain.001.001.02/GroupHeader/Authorisation**

Comment:

HSBC supports interoperability with HSBCnet.

5.23.4 BatchBooking

XML Tag: BtchBookg

Presence: [0..1]

Definition: Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions in the message is requested.

Datatype: ["BatchBookingIndicator" on page 127](#)

Usage Guideline details

- on **pain.001.001.02/GroupHeader/BatchBooking**

- **HSBC_BatchBooking:**

Only two values are allowed:

1. TRUE = Single entry on the Bank Statement for total value of Batch.
2. False= All transactions will be reported individually on Bank Statement.

Default value is True

Country conditions apply, please check with your Integration Manager.

5.23.5 NumberOfTransactions

XML Tag: NbOfTxS

Presence: [1..1]

Definition: Number of individual transactions contained in the message.

Datatype: ["Max15NumericText" on page 149](#)

Usage Guideline details

- on **pain.001.001.02/GroupHeader/NumberOfTransactions**

- **HSBC_NumberofTransactions:**

Number of Transactions will be verified against the number of occurrences of 'Credit Transfer Transaction Information <CdtTrfTxInf>' in the message

5.23.6 ControlSum

XML Tag: CtrlSum

Presence: [0..1]

Definition: Total of all individual amounts included in the message, irrespective of currencies.

Datatype: "DecimalNumber" on page 138

Usage Guideline details

- on pain.001.001.02/GroupHeader/ControlSum

- HSBC_ControlSum:

Hash total of all payment amounts regardless of currency.
If provided, this will be verified.

5.23.7 Grouping

XML Tag: Grpg

Presence: [1..1]

Definition: Indicates whether common accounting information in the transaction is included once for all transactions or repeated for each single transaction.

Datatype: "Grouping1Code" on page 143

5.23.8 InitiatingParty

XML Tag: InitgPty

Presence: [1..1]

Definition: Party initiating the payment. In the payment context, this can either be the debtor (in a credit transfer), the creditor (in a direct debit), or the party that initiates the payment on behalf of the debtor or creditor.

The **InitgPty** block contains the following elements (see datatype "PartyIdentification8" on page 75 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.0	Name	<Nm>		[0..1]	💡	75
5.1.1	PostalAddress	<PstlAdr>		[0..1]	💡	75
5.1.10	Identification	<Id>		[0..1]	M	77
5.1.41	CountryOfResidence	<CtryOfRes>		[0..1]	🚫	77

5.23.9 ForwardingAgent

XML Tag: FwdgAgt

Presence: [0..1]

Definition: Financial institution that receives the instruction from the initiating party and forwards it to the next agent in the payment chain for execution.

The **FwdgAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification3](#)" on page 13 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
4.1.0	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		14
4.1.37	BranchIdentification	<BrnchId>		[0..1]		14

Usage Guideline details

- This element(pain.001.001.02/GroupHeader/ForwardingAgent) will be ignored by the Receiver.

5.24 InstructionForCreditorAgent1

Definition: Further information related to the processing of the payment instruction that may need to be acted upon by the creditor's agent. The instruction may relate to a level of service, or may be an instruction that has to be executed by the creditor's agent, or may be information required by the creditor's agent.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.61	Code	<Cd>		[0..1]		60
2.62	InstructionInformation	<InstrInf>		[0..1]		60

Used in element(s)

"[InstructionForCreditorAgent](#)" on page 38

5.24.1 Code

XML Tag: Cd

Presence: [0..1]

Definition: Coded information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor's agent.

Datatype: "[Instruction3Code](#)" on page 148

5.24.2 InstructionInformation

XML Tag: InstrInf

Presence: [0..1]

Definition: Further information complementing the coded instruction or instruction to the creditor's agent that is bilaterally agreed or specific to a user community.

Datatype: "Max140Text" on page 149

5.25 LocalInstrument1Choice

Definition: Set of elements that further identifies the type of local instruments being requested by the initiating party.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.10 , 2.34	Code	<Cd>	{Or	[1..1]	🚫	61
2.11 , 2.35	Proprietary	<Prtry>	Or}	[1..1]		61

Used in element(s)

"LocalInstrument" on page 96

5.25.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the local instrument published in an external local instrument code list.

Datatype: "ExternalLocalInstrumentCode" on page 143

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/PaymentTypeInformation/LocalInstrument/Code) is removed.
- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/PaymentTypeInformation/LocalInstrument/Code) is removed.

5.25.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the local instrument as a proprietary code.

Datatype: "Max35Text" on page 151

5.26 NameAndAddress3

Definition: Information that locates and identifies a party.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
3.1.3 , 3.1.17 , 2.82	Name	<Nm>		[1..1]		62
3.1.4 , 3.1.18 , 2.83	Address	<Adr>		[1..1]		62

Used in element(s)

"ChequeFrom" on page 23, "DeliverTo" on page 23, "RemittanceLocationPostalAddress" on page 113

5.26.1 Name

XML Tag: Nm

Presence: [1..1]

Definition: Name by which a party is known and is usually used to identify that identity.

Datatype: "Max70Text" on page 152

5.26.2 Address

XML Tag: Adr

Presence: [1..1]

Definition: Postal address of a party.

The **Adr** block contains the following elements (see datatype "[PostalAddress1](#)" on page 101 for details)

🚫 Removed - ⬜ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.2 , 4.1.8 , 4.1.26 , 4.1.41 , 3.1.5 , 3.1.19 , 6.1.0	AddressType	<AdrTp>		[0..1]	🚫	103
5.1.3 , 4.1.9 , 4.1.27 , 4.1.42 , 3.1.6 , 3.1.20 , 6.1.1	AddressLine	<AdrLine>		[0..5]	🚫	103
5.1.4 , 4.1.10 , 4.1.28 , 4.1.43 , 3.1.7 , 3.1.21 , 6.1.2	StreetName	<StrtNm>		[0..1]	🚫	104
5.1.5 , 4.1.11 , 4.1.29 , 4.1.44 , 3.1.8 , 3.1.22 , 6.1.3	BuildingNumber	<BldgNb>		[0..1]	🚫	104
5.1.6 , 4.1.12 , 4.1.30 , 4.1.45 , 3.1.9 , 3.1.23 , 6.1.4	PostCode	<PstCd>		[0..1]	🚫	104
5.1.7 , 4.1.13 , 4.1.31 , 4.1.46 , 3.1.10 , 3.1.24 , 6.1.5	TownName	<TwnNm>		[0..1]	🚫	104
5.1.8 , 4.1.14 , 4.1.32 , 4.1.47 , 3.1.11 , 3.1.25 , 6.1.6	CountrySubDivision	<CtrySubDvsn>		[0..1]	🚫	105

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.9 , 4.1.15 , 4.1.33 , 4.1.48 , 3.1.12 , 3.1.26 , 6.1.7	Country	<Ctry>		[1..1]		105

5.27 NameAndAddress7

Definition: Name and address of an institution.

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
4.1.6	Name	<Nm>		[1..1]		64
4.1.7	PostalAddress	<PstlAdr>		[1..1]		64

Used in element(s)

"NameAndAddress" on page 52

5.27.1 Name

XML Tag: Nm

Presence: [1..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max70Text" on page 152

5.27.2 PostalAddress

XML Tag: PstlAdr

Presence: [1..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "[PostalAddress1](#)" on [page 101](#) for details)

🚫 Removed - ⬜ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.2 , 4.1.8 , 4.1.26 , 4.1.41 , 3.1.5 , 3.1.19 , 6.1.0	AddressType	<AdrTp>		[0..1]		103
5.1.3 , 4.1.9 , 4.1.27 , 4.1.42 , 3.1.6 , 3.1.20 , 6.1.1	AddressLine	<AdrLine>		[0..5]		103
5.1.4 , 4.1.10 , 4.1.28 , 4.1.43 , 3.1.7 , 3.1.21 , 6.1.2	StreetName	<StrtNm>		[0..1]		104
5.1.5 , 4.1.11 , 4.1.29 , 4.1.44 , 3.1.8 , 3.1.22 , 6.1.3	BuildingNumber	<BldgNb>		[0..1]		104
5.1.6 , 4.1.12 , 4.1.30 , 4.1.45 , 3.1.9 , 3.1.23 , 6.1.4	PostCode	<PstCd>		[0..1]		104
5.1.7 , 4.1.13 , 4.1.31 , 4.1.46 , 3.1.10 , 3.1.24 , 6.1.5	TownName	<TwnNm>		[0..1]		104
5.1.8 , 4.1.14 , 4.1.32 , 4.1.47 , 3.1.11 , 3.1.25 , 6.1.6	CountrySubDivision	<CtrySubDvsn>		[0..1]		105

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.9 , 4.1.15 , 4.1.33 , 4.1.48 , 3.1.12 , 3.1.26 , 6.1.7	Country	<Ctry>		[1..1]		105

5.28 OrganisationIdentification2

Definition: Unique and unambiguous way to identify an organisation.

🚫 Removed - 💡 Ignored - ⚠️ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.12	BIC	<BIC>		[0..1]	🚫	66
5.1.13	IBEI	<IBEI>		[0..1]	🚫	66
5.1.14	BEI	<BEI>		[0..1]		67
5.1.15	EANGLN	<EANGLN>		[0..1]	🚫	67
5.1.16	CHIPSUniversalIdentification	<USCHU>		[0..1]	🚫	67
5.1.17	DUNS	<DUNS>		[0..1]	🚫	68
5.1.18	BankPartyIdentification	<BkPtyId>		[0..1]		68
5.1.19	TaxIdentificationNumber	<TaxIdNb>		[0..1]	🚫	68
5.1.20	ProprietaryIdentification	<PrtryId>		[0..1]		68

Used in element(s)

"OrganisationIdentification" on page 71

5.28.1 BIC

XML Tag: BIC

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICIdentifier" on page 126

Usage Guideline details

- This element(pain.001.001.02/GroupHeader/InitiatingParty/Identification/OrganisationIdentification/BIC) is removed.

5.28.2 IBEI

XML Tag: IBEI

Presence: [0..1]

Definition: International Business Entity Identifier to uniquely identify business entities playing a role in the lifecycle of and events related to a financial instrument. (tentative - to be confirmed)

Datatype: "IBEIIdentifier" on page 147

Usage Guideline details

- This element([pain.001.001.02/GroupHeader/InitiatingParty/Identification/OrganisationIdentification/IBEI](#)) is removed.

5.28.3 BEI

XML Tag: BEI

Presence: [0..1]

Definition: Code allocated to a non-financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BEIIdentifier" on page 126

5.28.4 EANGLN

XML Tag: EANGLN

Presence: [0..1]

Definition: Global Location Number. A non-significant reference number used to identify legal entities, functional entities, or physical entities according to the European Association for Numbering (EAN) numbering scheme rules. The number is used to retrieve detailed information that is linked to it.

Datatype: "EANGLNIdentifier" on page 141

Usage Guideline details

- This element([pain.001.001.02/GroupHeader/InitiatingParty/Identification/OrganisationIdentification/EANGLN](#)) is removed.

5.28.5 CHIPSUniversalIdentification

XML Tag: USCHU

Presence: [0..1]

Definition: (United States) Clearing House Interbank Payments System (CHIPS) Universal Identification (UID) - identifies entities that own accounts at CHIPS participating financial institutions, through which CHIPS payments are effected. The CHIPS UID is assigned by the New York Clearing House.

Datatype: "CHIPSUniversalIdentifier" on page 127

Usage Guideline details

- This element([pain.001.001.02/GroupHeader/InitiatingParty/Identification/OrganisationIdentification/CHIPSUniversalIdentification](#)) is removed.

5.28.6 DUNS

XML Tag: DUNS

Presence: [0..1]

Definition: Data Universal Numbering System. A unique identification number provided by Dun & Bradstreet to identify an organization.

Datatype: ["DunsIdentifier" on page 141](#)

Usage Guideline details

- This element([pain.001.001.02/GroupHeader/InitiatingParty/Identification/OrganisationIdentification/DUNS](#)) is removed.

5.28.7 BankPartyIdentification

XML Tag: BkPtyId

Presence: [0..1]

Definition: Unique and unambiguous assignment made by a specific bank to identify a relationship as defined between the bank and its client.

Datatype: ["Max35Text" on page 151](#)

5.28.8 TaxIdentificationNumber

XML Tag: TaxIdNb

Presence: [0..1]

Definition: Number assigned by a tax authority to an entity.

Datatype: ["Max35Text" on page 151](#)

Usage Guideline details

- This element([pain.001.001.02/GroupHeader/InitiatingParty/Identification/OrganisationIdentification/TaxIdentificationNumber](#)) is removed.

5.28.9 ProprietaryIdentification

XML Tag: PrtryId

Presence: [0..1]

Definition: Unique and unambiguous identifier for an organisation that is allocated by an institution.

The **PrtryId** block contains the following elements (see datatype "[GenericIdentification3](#)" on page 54 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.21 , 4.1.17 , 4.1.35	Identification	<Id>		[1..1]		54
5.1.22 , 4.1.18 , 4.1.36	Issuer	<Issr>		[0..1]	🚫	54

5.29 OrganisationIdentification2__1

Definition: Unique and unambiguous way to identify an organisation.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.12	BIC	<BIC>		[0..1]		69
5.1.13	IBEI	<IBEI>		[0..1]		69
5.1.14	BEI	<BEI>		[0..1]		70
5.1.15	EANGLN	<EANGLN>		[0..1]		70
5.1.16	CHIPSUniversalIdentification	<USCHU>		[0..1]		70
5.1.17	DUNS	<DUNS>		[0..1]		70
5.1.18	BankPartyIdentification	<BkPtyId>		[0..1]		70
5.1.19	TaxIdentificationNumber	<TaxIdNb>		[0..1]		71
5.1.20	ProprietaryIdentification	<PrtryId>		[0..1]		71

Used in element(s)

"[OrganisationIdentification](#)" on page 73

5.29.1 BIC

XML Tag: BIC

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "[BICIdentifier](#)" on page 126

5.29.2 IBEI

XML Tag: IBEI

Presence: [0..1]

Definition: International Business Entity Identifier to uniquely identify business entities playing a role in the lifecycle of and events related to a financial instrument. (tentative - to be confirmed)

Datatype: "IBEIIdentifier" on page 147

5.29.3 BEI

XML Tag: BEI

Presence: [0..1]

Definition: Code allocated to a non-financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BEIIdentifier" on page 126

5.29.4 EANGLN

XML Tag: EANGLN

Presence: [0..1]

Definition: Global Location Number. A non-significant reference number used to identify legal entities, functional entities, or physical entities according to the European Association for Numbering (EAN) numbering scheme rules. The number is used to retrieve detailed information that is linked to it.

Datatype: "EANGLNIdentifier" on page 141

5.29.5 CHIPSUniversalIdentification

XML Tag: USCHU

Presence: [0..1]

Definition: (United States) Clearing House Interbank Payments System (CHIPS) Universal Identification (UID) - identifies entities that own accounts at CHIPS participating financial institutions, through which CHIPS payments are effected. The CHIPS UID is assigned by the New York Clearing House.

Datatype: "CHIPSUniversalIdentifier" on page 127

5.29.6 DUNS

XML Tag: DUNS

Presence: [0..1]

Definition: Data Universal Numbering System. A unique identification number provided by Dun & Bradstreet to identify an organization.

Datatype: "DunsIdentifier" on page 141

5.29.7 BankPartyIdentification

XML Tag: BkPtyId

Presence: [0..1]

Definition: Unique and unambiguous assignment made by a specific bank to identify a relationship as defined between the bank and its client.

Datatype: "Max35Text" on page 151

5.29.8 TaxIdentificationNumber

XML Tag: TaxIdNb

Presence: [0..1]

Definition: Number assigned by a tax authority to an entity.

Datatype: ["Max35Text" on page 151](#)

5.29.9 ProprietaryIdentification

XML Tag: PrtryId

Presence: [0..1]

Definition: Unique and unambiguous identifier for an organisation that is allocated by an institution.

The **PrtryId** block contains the following elements (see datatype ["GenericIdentification3_1" on page 54](#) for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.21 , 4.1.17 , 4.1.35	Identification	<Id>		[1..1]	⚠	55
5.1.22 , 4.1.18 , 4.1.36	Issuer	<Issr>		[0..1]		55

5.30 Party2Choice

Definition: Choice between the identification of a person and the identification of a non-financial institution.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.11	OrganisationIdentification	<OrgId>	{Or	[1..1]	⚠	71
5.1.23	PrivateIdentification	<PrvtId>	Or}	[1..4]	🚫	72

Used in element(s)

["Identification" on page 84](#), ["Identification" on page 77](#)

5.30.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way of identifying an organisation.

The **OrgId** block contains the following elements (see datatype "[OrganisationIdentification2](#)" on [page 66](#) for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.12	BIC	<BIC>		[0..1]	🚫	66
5.1.13	IBEI	<IBEI>		[0..1]	🚫	66
5.1.14	BEI	<BEI>		[0..1]		67
5.1.15	EANGLN	<EANGLN>		[0..1]	🚫	67
5.1.16	CHIPSUniversalIdentification	<USCHU>		[0..1]	🚫	67
5.1.17	DUNS	<DUNS>		[0..1]	🚫	68
5.1.18	BankPartyIdentification	<BkPtyId>		[0..1]		68
5.1.19	TaxIdentificationNumber	<TaxIdNb>		[0..1]	🚫	68
5.1.20	ProprietaryIdentification	<PrtryId>		[0..1]		68

Usage Guideline details

- on **pain.001.001.02/GroupHeader/InitiatingParty/Identification/OrganisationIdentification**

- **HSBC_InitiatingPartyIdentification:**

At least one of the following items is mandatory, either BEI or Bank Party Identification or ProprietaryIdentification/Identification.

- on **pain.001.001.02/GroupHeader/InitiatingParty/Identification/OrganisationIdentification**

Comment:

Provide HSBC Connect Customer ID in OrganisationIdentification/BankPartyIdentification.

Alternatively, the following can be provided:

BEI under OrganisationIdentification/BEI or
SIRET ID under OrganisationIdentification/ProprietaryIdentification/Identification.

5.30.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..4]

Definition: Unique and unambiguous identification of a person, eg, passport.

The **PrvtId** block contains the following elements (see datatype "PersonIdentification3" on page 97 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.24	DriversLicenseNumber	<DrvrsLicNb>	{Or	[1..1]		97
5.1.25	CustomerNumber	<CstmrNb>	Or	[1..1]		98
5.1.26	SocialSecurityNumber	<SclSctyNb>	Or	[1..1]		98
5.1.27	AlienRegistrationNumber	<AlnRegnNb>	Or	[1..1]		98
5.1.28	PassportNumber	<PsptNb>	Or	[1..1]		98
5.1.29	TaxIdentificationNumber	<TaxIdNb>	Or	[1..1]		99
5.1.30	IdentityCardNumber	<IdntyCardNb>	Or	[1..1]		99
5.1.31	EmployerIdentificationNumber	<MplyrIdNb>	Or	[1..1]		99
5.1.32	DateAndPlaceOfBirth	<DtAndPlcOfBirth>	Or	[1..1]		100
5.1.37	OtherIdentification	<OthrId>	Or}	[1..1]		100
5.1.40	Issuer	<Issr>		[0..1]		100

Usage Guideline details

- This element(pain.001.001.02/GroupHeader/InitiatingParty/Identification/PrivateIdentification) is removed.

5.31 Party2Choice__1

Definition: Choice between the identification of a person and the identification of a non-financial institution.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.11	OrganisationIdentification	<OrgId>	{Or	[1..1]		73
5.1.23	PrivateIdentification	<PrvtId>	Or}	[1..4]		74

Used in element(s)

"Identification" on page 80

5.31.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way of identifying an organisation.

The **OrgId** block contains the following elements (see datatype "[OrganisationIdentification2__1](#)" on page 69 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.12	BIC	<BIC>		[0..1]		69
5.1.13	IBEI	<IBEI>		[0..1]		69
5.1.14	BEI	<BEI>		[0..1]		70
5.1.15	EANGLN	<EANGLN>		[0..1]		70
5.1.16	CHIPSUniversalIdentification	<USCHU>		[0..1]		70
5.1.17	DUNS	<DUNS>		[0..1]		70
5.1.18	BankPartyIdentification	<BkPtyId>		[0..1]		70
5.1.19	TaxIdentificationNumber	<TaxIdNb>		[0..1]		71
5.1.20	ProprietaryIdentification	<PrtryId>		[0..1]		71

5.31.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..4]

Definition: Unique and unambiguous identification of a person, eg, passport.

The **PrvtId** block contains the following elements (see datatype "[PersonIdentification3](#)" on page 97 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.24	DriversLicenseNumber	<DrvrLicNb>	{Or	[1..1]		97
5.1.25	CustomerNumber	<CstmrNb>	Or	[1..1]		98
5.1.26	SocialSecurityNumber	<ScISctyNb>	Or	[1..1]		98
5.1.27	AlienRegistrationNumber	<AlnRegnNb>	Or	[1..1]		98
5.1.28	PassportNumber	<PsptNb>	Or	[1..1]		98
5.1.29	TaxIdentificationNumber	<TaxIdNb>	Or	[1..1]		99
5.1.30	IdentityCardNumber	<IdntyCardNb>	Or	[1..1]		99
5.1.31	EmployerIdentificationNumber	<MplyrIdNb>	Or	[1..1]		99
5.1.32	DateAndPlaceOfBirth	<DtAndPlcOfBirth>	Or	[1..1]		100
5.1.37	OtherIdentification	<OthrId>	Or}	[1..1]		100
5.1.40	Issuer	<Issr>		[0..1]		100

5.32 PartyIdentification8

Definition: Identification of a person, a financial institution or a non-financial institution.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.0	Name	<Nm>		[0..1]	💡	75
5.1.1	PostalAddress	<PstlAdr>		[0..1]	💡	75
5.1.10	Identification	<Id>		[0..1]	M 💡	77
5.1.41	CountryOfResidence	<CtryOfRes>		[0..1]	💡 🚫	77

Used in element(s)

"InitiatingParty" on page 59, "Invoicee" on page 118, "Invoicer" on page 118, "UltimateCreditor" on page 38, "UltimateDebtor" on page 91, "UltimateDebtor" on page 32

5.32.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max70Text" on page 152

Usage Guideline details

- This element(pain.001.001.02/GroupHeader/InitiatingParty/Name) will be ignored by the Receiver.

5.32.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress1" on page 101 for details)

🚫 Removed - ⬜ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.2 , 4.1.8 , 4.1.26 , 4.1.41 , 3.1.5 , 3.1.19 , 6.1.0	AddressType	<AdrTp>		[0..1]	🚫	103
5.1.3 , 4.1.9 , 4.1.27 , 4.1.42 , 3.1.6 , 3.1.20 , 6.1.1	AddressLine	<AdrLine>		[0..5]		103
5.1.4 , 4.1.10 , 4.1.28 , 4.1.43 , 3.1.7 , 3.1.21 , 6.1.2	StreetName	<StrtNm>		[0..1]		104
5.1.5 , 4.1.11 , 4.1.29 , 4.1.44 , 3.1.8 , 3.1.22 , 6.1.3	BuildingNumber	<BldgNb>		[0..1]		104
5.1.6 , 4.1.12 , 4.1.30 , 4.1.45 , 3.1.9 , 3.1.23 , 6.1.4	PostCode	<PstCd>		[0..1]		104
5.1.7 , 4.1.13 , 4.1.31 , 4.1.46 , 3.1.10 , 3.1.24 , 6.1.5	TownName	<TwnNm>		[0..1]		104
5.1.8 , 4.1.14 , 4.1.32 , 4.1.47 , 3.1.11 , 3.1.25 , 6.1.6	CountrySubDivision	<CtrySubDvsn>		[0..1]		105

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.9 , 4.1.15 , 4.1.33 , 4.1.48 , 3.1.12 , 3.1.26 , 6.1.7	Country	<Ctry>		[1..1]		105

Usage Guideline details

- This element(pain.001.001.02/GroupHeader/InitiatingParty/PostalAddress) will be ignored by the Receiver.

5.32.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous way of identifying an organisation or an individual person.

The **Id** block contains the following elements (see datatype "[Party2Choice](#)" on page 71 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.11	OrganisationIdentification	<OrgId>	{Or	[1..1]	⚠	71
5.1.23	PrivateIdentification	<PrvtId>	Or}	[1..4]	🚫	72

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/Identification) will be ignored by the Receiver.
- on pain.001.001.02/GroupHeader/InitiatingParty/Identification
This element is now mandatory, the minimum occurrence has been changed to : 1

5.32.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "[CountryCode](#)" on page 136

Usage Guideline details

- This element(pain.001.001.02/GroupHeader/InitiatingParty/CountryOfResidence) is removed.

- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/CountryOfResidence) will be ignored by the Receiver.

5.33 PartyIdentification8__1

Definition: Identification of a person, a financial institution or a non-financial institution.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.0	Name	<Nm>		[0..1]	M ⚠	78
5.1.1	PostalAddress	<PstlAdr>		[0..1]	M ⚠	78
5.1.10	Identification	<Id>		[0..1]	⚠	80
5.1.41	CountryOfResidence	<CtryOfRes>		[0..1]	💡	80

Used in element(s)

"Debtor" on page 90

5.33.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max18Text" on page 150

Usage Guideline details

- on pain.001.001.02/PaymentInformation/Debtor/Name
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pain.001.001.02/PaymentInformation/Debtor/Name
Comment:
Name of ordering party.

5.33.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "[PostalAddress1](#)" on [page 101](#) for details)

🚫 Removed - ⬜ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.2 , 4.1.8 , 4.1.26 , 4.1.41 , 3.1.5 , 3.1.19 , 6.1.0	AddressType	<AdrTp>		[0..1]		103
5.1.3 , 4.1.9 , 4.1.27 , 4.1.42 , 3.1.6 , 3.1.20 , 6.1.1	AddressLine	<AdrLine>		[0..5]		103
5.1.4 , 4.1.10 , 4.1.28 , 4.1.43 , 3.1.7 , 3.1.21 , 6.1.2	StreetName	<StrtNm>		[0..1]		104
5.1.5 , 4.1.11 , 4.1.29 , 4.1.44 , 3.1.8 , 3.1.22 , 6.1.3	BuildingNumber	<BldgNb>		[0..1]		104
5.1.6 , 4.1.12 , 4.1.30 , 4.1.45 , 3.1.9 , 3.1.23 , 6.1.4	PostCode	<PstCd>		[0..1]		104
5.1.7 , 4.1.13 , 4.1.31 , 4.1.46 , 3.1.10 , 3.1.24 , 6.1.5	TownName	<TwnNm>		[0..1]		104
5.1.8 , 4.1.14 , 4.1.32 , 4.1.47 , 3.1.11 , 3.1.25 , 6.1.6	CountrySubDivision	<CtrySubDvsn>		[0..1]		105

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.9 , 4.1.15 , 4.1.33 , 4.1.48 , 3.1.12 , 3.1.26 , 6.1.7	Country	<Ctry>		[1..1]		105

Usage Guideline details

- on pain.001.001.02/PaymentInformation/Debtor/PostalAddress

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pain.001.001.02/PaymentInformation/Debtor/PostalAddress

Comment:

The address is limited to 4 lines of 35 chars.

5.33.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous way of identifying an organisation or an individual person.

The **Id** block contains the following elements (see datatype "Party2Choice__1" on page 73 for details)

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.11	OrganisationIdentification	<OrgId>	{Or	[1..1]		73
5.1.23	PrivateIdentification	<PrvtId>	Or}	[1..4]		74

Usage Guideline details

- on pain.001.001.02/PaymentInformation/Debtor/Identification

Comment:

Identification numbers can be stated for the party; organisations and private persons are differentiated. For organisation IDs, one instance of OrgId with a set of optional identifications can be included. For private identifications, the PrivateIdentification tag may repeat up to 4 times with exactly one ID each. It is acceptable to use the same ID multiple times (e.g. a passport number) if distinct values are provided (i.e. the person has more than one passport).

5.33.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "CountryCode" on page 136

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/Debtor/CountryOfResidence) will be ignored by the Receiver.

5.34 PartyIdentification8__2

Definition: Identification of a person, a financial institution or a non-financial institution.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.0	Name	<Nm>		[0..1]	M ⚠	81
5.1.1	PostalAddress	<PstlAdr>		[0..1]	M ⚠	81
5.1.10	Identification	<Id>		[0..1]		84
5.1.41	CountryOfResidence	<CtryOfRes>		[0..1]		84

Used in element(s)

"Creditor" on page 37

5.34.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "Max18Text" on page 150

Usage Guideline details

- on pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/Creditor/Name
This element is now mandatory, the minimum occurrence has been changed to : 1
- on pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/Creditor/Name
Comment:
Creditor (beneficiary) name is mandatory and max. 18 characters in length. Longer names will be truncated.

5.34.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "[PostalAddress1](#)" on [page 101](#) for details)

🚫 Removed - ⬜ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.2 , 4.1.8 , 4.1.26 , 4.1.41 , 3.1.5 , 3.1.19 , 6.1.0	AddressType	<AdrTp>		[0..1]		103
5.1.3 , 4.1.9 , 4.1.27 , 4.1.42 , 3.1.6 , 3.1.20 , 6.1.1	AddressLine	<AdrLine>		[0..5]		103
5.1.4 , 4.1.10 , 4.1.28 , 4.1.43 , 3.1.7 , 3.1.21 , 6.1.2	StreetName	<StrtNm>		[0..1]		104
5.1.5 , 4.1.11 , 4.1.29 , 4.1.44 , 3.1.8 , 3.1.22 , 6.1.3	BuildingNumber	<BldgNb>		[0..1]		104
5.1.6 , 4.1.12 , 4.1.30 , 4.1.45 , 3.1.9 , 3.1.23 , 6.1.4	PostCode	<PstCd>		[0..1]		104
5.1.7 , 4.1.13 , 4.1.31 , 4.1.46 , 3.1.10 , 3.1.24 , 6.1.5	TownName	<TwnNm>		[0..1]		104
5.1.8 , 4.1.14 , 4.1.32 , 4.1.47 , 3.1.11 , 3.1.25 , 6.1.6	CountrySubDivision	<CtrySubDvsn>		[0..1]		105

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.9 , 4.1.15 , 4.1.33 , 4.1.48 , 3.1.12 , 3.1.26 , 6.1.7	Country	<Ctry>		[1..1]		105

Usage Guideline details

- on pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/Creditor/PostalAddress

This element is now mandatory, the minimum occurrence has been changed to : 1

- on pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/Creditor/PostalAddress

Comment:

Up to 5 occurrences of AddressLine can provide a formatted or "unstructured" address. Alternatively, a structured address can be provided using the street name, building number, post code, town name, and "country sub-division" (e.g. a county or state) tags. If structured addresses are provided, AddressLine can be used to provide additional name lines or a building name etc.; it may not repeat any information already contained in the structured part of the address. That is to say, either a structured or an unstructured address may be provided, but not both at the same time.

Since printing and forwarding of address data is limited, often to 4 lines of 35 chars, HSBC recommend you limit the address information to the essential components to avoid truncation

5.34.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous way of identifying an organisation or an individual person.

The **Id** block contains the following elements (see datatype "Party2Choice" on page 71 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.11	OrganisationIdentification	<OrgId>	{Or	[1..1]		71
5.1.23	PrivateIdentification	<PrvtId>	Or}	[1..4]		72

5.34.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "CountryCode" on page 136

5.35 PaymentIdentification1__1

Definition: Set of elements used to provide further means of referencing a payment transaction.

🚫 Removed - 💡 Ignored - ⚠️ Details below - 📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.25	InstructionIdentification	<InstrId>		[0..1]	⚠️	85
2.26	EndToEndIdentification	<EndToEndId>		[1..1]	⚠️	85

Used in element(s)

"PaymentIdentification" on page 29

5.35.1 InstructionIdentification

XML Tag: InstrId

Presence: [0..1]

Definition: Unique identification as assigned by an instructing party for an instructed party to unambiguously identify the instruction.

Usage: the instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction.

Datatype: "Max35Text" on page 151

Usage Guideline details

- on pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/PaymentIdentification/InstructionIdentification

– HSBC_InstructionIdentification:

InstructionIdentification is a transaction identification between ordering party and the bank. This field can be used for duplicate instruction checking. This option is available as part of the customer set-up process.
Please note: Where the HSBC Advising service is used, the InstructionIdentification must be unique across the first 12 digits and is mandatory.

5.35.2 EndToEndIdentification

XML Tag: EndToEndId

Presence: [1..1]

Definition: Unique identification assigned by the initiating party to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.

Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction.

Datatype: "Max18Text" on page 150

Usage Guideline details

- on pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/PaymentIdentification/EndToEndIdentification

Comment:

A maximum length of 18 chars is supported by BACS; if a longer ID is provided it will be truncated. Please note that for building society payments the roll number will be populated therefore no ID can be transmitted to the beneficiary.

5.36 PaymentInstructionInformation1__1

Definition: Set of characteristics that apply to the debit side of the payment transactions included in the credit transfer transaction initiation.

🚫 Removed - 💡 Ignored - ⚠️ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.1	PaymentInformationIdentification	<PmtInflId>		[0..1]	⚠️	88
2.2	PaymentMethod	<PmtMtd>		[1..1]		88
2.3	PaymentTypeInformation	<PmtTplInf>		[0..1]		89
2.13	RequestedExecutionDate	<ReqdExctnDt>		[1..1]	⚠️	89
2.14	PoolingAdjustmentDate	<PoolgAdjstmntDt>		[0..1]	💡	89
2.15	Debtor	<Dbtr>		[1..1]		90
2.16	DebtorAccount	<DbtrAcct>		[1..1]		90
2.17	DebtorAgent	<DbtrAgt>		[1..1]		91
2.18	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]	🚫	91
2.19	UltimateDebtor	<UltmtDbtr>		[0..1]	💡 ⚠️	91
2.20	ChargeBearer	<ChrgBr>		[0..1]	💡	92
2.21	ChargesAccount	<ChrgsAcct>		[0..1]	💡	92
2.22	ChargesAccountAgent	<ChrgsAcctAgt>		[0..1]	💡	93
2.23	CreditTransferTransactionInformation	<CdtTrfTxInf>		[1..*]		93

Rules

R3 PaymentTypeInformationRule

If PaymentTypeInformation is present, then CreditTransferTransactionInformation/PaymentTypeInformation is not allowed.

Error handling: Undefined

R4 ChequeInstructionRule

If PaymentMethod is CHK, then CreditTransferTransactionInformation/ChequeInstruction is optional. If PaymentMethod is different from CHK, then CreditTransferTransactionInformation/ChequeInstruction is not allowed.

Rule rationale: ChequeInstructionDetails may be present if the payment method is Cheque. It must not be present if the payment method is 'Transfer'.

Error handling: Undefined

Usage Guideline restrictions for this element

- This rule(pain.001.001.02/PaymentInformation/ChequeInstructionRule) is removed.

R5 ChargesAccountRule

If ChargesAccountAgent is present, then ChargesAccount must be present.

Error handling: Undefined

R6 ChargesAccountAgentRule

If ChargesAccountAgent is present, it must contain a branch of the DebtorAgent. It must not contain a completely different financial institution.

Error handling: Undefined

R7 CreditorAndOrCreditorAccountRule

If PaymentMethod is CHK, then CreditTransferTransactionInformation/CreditorAccount is not allowed.

If PaymentMethod is different from CHK and if CreditTransferTransactionInformation/Creditor is not present, then CreditTransferTransactionInformation/CreditorAccount is mandatory.

If PaymentMethod is different from CHK and if CreditTransferTransactionInformation/Creditor is present, then CreditTransferTransactionInformation/CreditorAccount is optional.

Error handling: Undefined

R8 CreditorAgentRule

If PaymentMethod is CHK and if CreditTransferTransactionInformation/ ChequeInstruction/DeliveryMethod is present and is equal to MLFA, CRFA, RGFA or PUFA, then CreditTransferTransactionInformation/CreditorAgent is mandatory.

If PaymentMethod is CHK and if CreditTransferTransactionInformation/ ChequeInstruction/DeliveryMethod is not present or is not equal to MLFA, CRFA, RGFA or PUFA, then CreditTransferTransactionInformation/CreditorAgent is not allowed.

Error handling: Undefined

R9 ChargeBearerRule

If ChargeBearer is present, then CreditTransferTransactionInformation/ChargeBearer is not allowed.

If CreditTransferTransactionInformation/ChargeBearer is present, then ChargeBearer is not allowed.

CreditTransferTransactionInformation/ChargeBearer and ChargeBearer may both be absent.

Error handling: Undefined

Guidelines

1. UltimateDebtorGuideline

UltimateDebtor may only be present if different from Debtor.

2. ChequeInstructionDeliverToDebtorGuideline

If CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and if CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod/Code is CRDB or MLDB or PUIDB or RGDB, then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different than Debtor.

3. ChequeInstructionDeliverToCreditorGuideline

If PaymentInformation/CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and is CRCD or MLCD or PUCD or RGCD, then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different from CreditTransferTransactionInformation/Creditor.

4. ChequeInstructionDeliverToCreditorAgentGuideline

If CreditTransferTransactionInformation/ChequeInstruction/DeliveryMethod is present and is CRFA or MLFA or PUFA or RGFA, then CreditTransferTransactionInformation/ChequeInstruction/DeliverTo may only be present if different than CreditTransferTransactionInformation/Creditor.

5. ChequeFromGuideline

CreditTransferTransactionInformation/ChequeInstruction/ChequeFrom may only be present if different from CreditTransferTransactionInformation/UltimateDebtor or Debtor.

Used in element(s)

"PaymentInformation" on page 7

5.36.1 PaymentInformationIdentification

XML Tag: PmtInfId

Presence: [0..1]

Definition: Reference assigned by a sending party to unambiguously identify the payment information block within the message.

Datatype: "Max18Text" on page 150

Usage Guideline details

- on pain.001.001.02/PaymentInformation/PaymentInformationIdentification

- HSBC_PaymentInformationIdentification:

Batch reference number. This reference will be the debit reference reported on the account statement.

5.36.2 PaymentMethod

XML Tag: PmtMtd

Presence: [1..1]

Definition: Specifies the means of payment that will be used to move the amount of money.

Datatype: "PaymentMethod3Code" on page 154

5.36.3 PaymentTypeInformation

XML Tag: PmtTpInf

Presence: [0..1]

Definition: Set of elements used to further specify the type of transaction.

The **PmtTpInf** block contains the following elements (see datatype "PaymentTypeInformation1" on page 94 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.4 , 2.28	InstructionPriority	<InstrPrty>		[0..1]	💡	95
2.5 , 2.29	ServiceLevel	<SvcLvl>	{Or	[0..1]	🚫	95
2.8 , 2.32	ClearingChannel	<ClrChanl>	Or}	[0..1]	M	96
2.9 , 2.33	LocalInstrument	<LclInstrm>		[0..1]		96
2.12 , 2.36	CategoryPurpose	<CtgyPurp>		[0..1]		97

5.36.4 RequestedExecutionDate

XML Tag: ReqdExctnDt

Presence: [1..1]

Definition: Date at which the initiating party requests the clearing agent to process the payment. If payment by cheque, the date when the cheque must be generated by the bank.

Usage: This is the date on which the debtor's account(s) is (are) to be debited.

Datatype: "ISODate" on page 147

Usage Guideline details

- on pain.001.001.02/PaymentInformation/RequestedExecutionDate

Comment:

Work day on which the payment should be initiated.

5.36.5 PoolingAdjustmentDate

XML Tag: PoolgAdjstmntDt

Presence: [0..1]

Definition: Date used for the correction of the value date of a cash pool movement that has been posted with a different value date.

Datatype: "ISODate" on page 147

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/PoolingAdjustmentDate) will be ignored by the Receiver.

5.36.6 Debtor

XML Tag: Dbtr

Presence: [1..1]

Definition: Party that owes an amount of money to the (ultimate) creditor.

The **Dbtr** block contains the following elements (see datatype "PartyIdentification8__1" on page 78 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.0	Name	<Nm>		[0..1]	M ⚠	78
5.1.1	PostalAddress	<PstlAdr>		[0..1]	M ⚠	78
5.1.10	Identification	<Id>		[0..1]	⚠	80
5.1.41	CountryOfResidence	<CtryOfRes>		[0..1]	💡	80

5.36.7 DebtorAccount

XML Tag: DbtrAcct

Presence: [1..1]

Definition: Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.

The **DbtrAcct** block contains the following elements (see datatype "CashAccount7__1" on page 19 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.0	Identification	<Id>		[1..1]		19
1.1.6	Type	<Tp>		[0..1]	💡	20
1.1.9	Currency	<Ccy>		[0..1]	💡	20
1.1.10	Name	<Nm>		[0..1]	💡	20

5.36.8 DebtorAgent

XML Tag: DbtrAgt

Presence: [1..1]

Definition: Financial institution servicing an account for the debtor.

The **DbtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification3](#)" on page 13 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
4.1.0	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠️	14
4.1.37	BranchIdentification	<BrnchId>		[0..1]		14

5.36.9 DebtorAgentAccount

XML Tag: DbtrAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain.

The **DbtrAgtAcct** block contains the following elements (see datatype "[CashAccount7](#)" on page 17 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.0	Identification	<Id>		[1..1]		17
1.1.6	Type	<Tp>		[0..1]		17
1.1.9	Currency	<Ccy>		[0..1]		18
1.1.10	Name	<Nm>		[0..1]		18

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/DebtorAgentAccount](#)) is removed.

5.36.10 UltimateDebtor

XML Tag: UltmtDbtr

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor.

The **UltmtDbtr** block contains the following elements (see datatype "PartyIdentification8" on page 75 for details)

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.0	Name	<Nm>		[0..1]		75
5.1.1	PostalAddress	<PstlAdr>		[0..1]		75
5.1.10	Identification	<Id>		[0..1]		77
5.1.41	CountryOfResidence	<CtryOfRes>		[0..1]		77

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/UltimateDebtor) will be ignored by the Receiver.
- on pain.001.001.02/PaymentInformation/UltimateDebtor

Comment:

Name of the party owing the money may be provided if different from debtor.

5.36.11 ChargeBearer

XML Tag: ChrgBr

Presence: [0..1]

Definition: Specifies which party/parties will bear the charges associated with the processing of the payment transaction.

Datatype: "ChargeBearerType1Code" on page 130

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/ChargeBearer) will be ignored by the Receiver.

5.36.12 ChargesAccount

XML Tag: ChrgsAcct

Presence: [0..1]

Definition: Account used to process charges associated with a transaction.

Usage : charges account should be used when charges have to be booked to an account different from the account identified in debtor's account.

The **ChrgsAcct** block contains the following elements (see datatype "[CashAccount7](#)" on page 17 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.0	Identification	<Id>		[1..1]		17
1.1.6	Type	<Tp>		[0..1]		17
1.1.9	Currency	<Ccy>		[0..1]		18
1.1.10	Name	<Nm>		[0..1]		18

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/ChargesAccount) will be ignored by the Receiver.

5.36.13 ChargesAccountAgent

XML Tag: ChrgsAcctAgt

Presence: [0..1]

Definition: Agent that services a charges account.

Usage : charges account agent should only be used when the charges account agent is different from the debtor agent.

The **ChrgsAcctAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification3](#)" on page 13 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
4.1.0	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		14
4.1.37	BranchIdentification	<BrnchId>		[0..1]		14

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/ChargesAccountAgent) will be ignored by the Receiver.

5.36.14 CreditTransferTransactionInformation

XML Tag: CdtTrfTxInf

Presence: [1..*]

Definition: Set of elements providing information specific to the individual transaction(s) included in the message.

The **CdtTrfTxInf** block contains the following elements (see datatype "CreditTransferTransactionInformation1__1" on page 26 for details)

🚫 Removed - ✦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.24	PaymentIdentification	<PmtId>		[1..1]	⚠	29
2.27	PaymentTypeInformation	<PmtTplnf>		[0..1]		29
2.37	Amount	<Amt>		[1..1]		30
2.42	ExchangeRateInformation	<XchgRateInf>		[0..1]	🚫	30
2.46	ChargeBearer	<ChrgBr>		[0..1]	⚠	31
2.47	ChequeInstruction	<ChqInstr>		[0..1]	🚫 ⚠	31
2.48	UltimateDebtor	<UltmtDbtr>		[0..1]	⚠	32
2.49	IntermediaryAgent1	<IntrmyAgt1>		[0..1]	✦ ⚠	33
2.50	IntermediaryAgent1Account	<IntrmyAgt1Acct>		[0..1]	🚫	34
2.51	IntermediaryAgent2	<IntrmyAgt2>		[0..1]	🚫	34
2.52	IntermediaryAgent2Account	<IntrmyAgt2Acct>		[0..1]	🚫	35
2.53	IntermediaryAgent3	<IntrmyAgt3>		[0..1]	🚫	35
2.54	IntermediaryAgent3Account	<IntrmyAgt3Acct>		[0..1]	🚫	36
2.55	CreditorAgent	<CdtrAgt>		[0..1]	M	36
2.56	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		36
2.57	Creditor	<Cdtr>		[0..1]	M	37
2.58	CreditorAccount	<CdtrAcct>		[0..1]	M	37
2.59	UltimateCreditor	<UltmtCdtr>		[0..1]		38
2.60	InstructionForCreditorAgent	<InstrForCdtrAgt>		[0..*]	✦	38
2.63	InstructionForDebtorAgent	<InstrForDbtrAgt>		[0..1]	✦	39
2.64	Purpose	<Purp>		[0..1]	✦	39
2.67	RegulatoryReporting	<RgltryRptg>		[0..10]	✦	40
2.76	Tax	<Tax>		[0..1]		40
2.77	RelatedRemittanceInformation	<RltdRmtInf>		[0..10]		41
2.84	RemittanceInformation	<RmtInf>		[0..1]	⚠	41

5.37 PaymentTypeInformation1

Definition: Set of elements that further details the information related to the type of payment.

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.4 , 2.28	InstructionPriority	<InstrPrty>		[0..1]	♦	95
2.5 , 2.29	ServiceLevel	<SvcLvl>	{Or	[0..1]	🚫	95
2.8 , 2.32	ClearingChannel	<ClrChanl>	Or}	[0..1]	M	96
2.9 , 2.33	LocalInstrument	<LclInstrm>		[0..1]		96
2.12 , 2.36	CategoryPurpose	<CtgyPurp>		[0..1]		97

Used in element(s)

"PaymentTypeInformation" on page 89, "PaymentTypeInformation" on page 29

5.37.1 InstructionPriority

XML Tag: InstrPrty

Presence: [0..1]

Definition: Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction.

Datatype: "Priority2Code" on page 156

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/PaymentTypeInformation/InstructionPriority) will be ignored by the Receiver.
- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/PaymentTypeInformation/InstructionPriority) will be ignored by the Receiver.

5.37.2 ServiceLevel

XML Tag: SvcLvl

Presence: [0..1]

Warning If ServiceLevel is present then ClearingChannel must is not allowed.

If ClearingChannel is present then ServiceLevel must is not allowed.

Definition: Agreement under which or rules under which the transaction should be processed.

The **SvcLvl** block contains the following elements (see datatype "[ServiceLevel2Choice](#)" on page 113 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.6 , 2.30	Code	<Cd>	{Or	[1..1]		113
2.7 , 2.31	Proprietary	<Prtry>	Or}	[1..1]	🚫	114

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/PaymentTypeInformation/xor/ServiceLevel](#)) is removed.
- This element([pain.001.001.02/PaymentInformation/PaymentTypeInformation/xor/ServiceLevel](#)) is removed.

5.37.3 ClearingChannel

XML Tag: ClrChanl

Presence: [0..1]

Warning If ServiceLevel is present then ClearingChannel must is not allowed.
If ClearingChannel is present then ServiceLevel must is not allowed.

Definition: Specifies the clearing channel to be used for the instruction.

Datatype: "[ClearingChannel2Code](#)" on page 134

Usage Guideline details

- on [pain.001.001.02/PaymentInformation/PaymentTypeInformation/xor/ClearingChannel](#)
This element is now mandatory, the minimum occurrence has been changed to : 1
- on [pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/PaymentTypeInformation/xor/ClearingChannel](#)
This element is now mandatory, the minimum occurrence has been changed to : 1

5.37.4 LocalInstrument

XML Tag: LclInstrm

Presence: [0..1]

Definition: User community specific instrument.

Usage : When available, codes provided by local authorities should be used.

The **LclInstrm** block contains the following elements (see datatype "[LocalInstrument1Choice](#)" on page 61 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.10 , 2.34	Code	<Cd>	{Or	[1..1]	🚫	61
2.11 , 2.35	Proprietary	<Prtry>	Or}	[1..1]		61

5.37.5 CategoryPurpose

XML Tag: Ctgypurp

Presence: [0..1]

Definition: Specifies the high level purpose of the instruction based on a set of pre-defined categories.

Datatype: "[PaymentCategoryPurpose1Code](#)" on page 152

5.38 PersonIdentification3

Definition: Unique and unambiguous way to identify a person.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.24	DriversLicenseNumber	<DrvrLicNb>	{Or	[1..1]		97
5.1.25	CustomerNumber	<CstmrNb>	Or	[1..1]		98
5.1.26	SocialSecurityNumber	<ScISctyNb>	Or	[1..1]		98
5.1.27	AlienRegistrationNumber	<AlnRegnNb>	Or	[1..1]		98
5.1.28	PassportNumber	<PsptNb>	Or	[1..1]		98
5.1.29	TaxIdentificationNumber	<TaxIdNb>	Or	[1..1]		99
5.1.30	IdentityCardNumber	<IdntyCardNb>	Or	[1..1]		99
5.1.31	EmployerIdentificationNumber	<MplyrIdNb>	Or	[1..1]		99
5.1.32	DateAndPlaceOfBirth	<DtAndPlcOfBirth>	Or	[1..1]		100
5.1.37	OtherIdentification	<OthrId>	Or}	[1..1]		100
5.1.40	Issuer	<Issr>		[0..1]		100

Used in element(s)

"[PrivateIdentification](#)" on page 74, "[PrivateIdentification](#)" on page 72

5.38.1 DriversLicenseNumber

XML Tag: DrvrLicNb

Presence: [1..1]

Warning One and only one Message Element in the list (DateAndPlaceOfBirth, CustomerNumber, DriversLicenseNumber, SocialSecurityNumber, AlienRegistrationNumber, PassportNumber, TaxIdentificationNumber, IdentityCardNumber, EmployerIdentificationNumber, OtherIdentification, DateAndPlaceOfBirth) must be present.

Definition: Number assigned by a license authority to a driver's license.

Datatype: ["Max35Text" on page 151](#)

5.38.2 CustomerNumber

XML Tag: CstmrNb

Presence: [1..1]

Warning One and only one Message Element in the list (DateAndPlaceOfBirth, CustomerNumber, DriversLicenseNumber, SocialSecurityNumber, AlienRegistrationNumber, PassportNumber, TaxIdentificationNumber, IdentityCardNumber, EmployerIdentificationNumber, OtherIdentification, DateAndPlaceOfBirth) must be present.

Definition: Number assigned by an agent to identify its customer.

Datatype: ["Max35Text" on page 151](#)

5.38.3 SocialSecurityNumber

XML Tag: SclSctyNb

Presence: [1..1]

Warning One and only one Message Element in the list (DateAndPlaceOfBirth, CustomerNumber, DriversLicenseNumber, SocialSecurityNumber, AlienRegistrationNumber, PassportNumber, TaxIdentificationNumber, IdentityCardNumber, EmployerIdentificationNumber, OtherIdentification, DateAndPlaceOfBirth) must be present.

Definition: Number assigned by a social security agency.

Datatype: ["Max35Text" on page 151](#)

5.38.4 AlienRegistrationNumber

XML Tag: AlnRegnNb

Presence: [1..1]

Warning One and only one Message Element in the list (DateAndPlaceOfBirth, CustomerNumber, DriversLicenseNumber, SocialSecurityNumber, AlienRegistrationNumber, PassportNumber, TaxIdentificationNumber, IdentityCardNumber, EmployerIdentificationNumber, OtherIdentification, DateAndPlaceOfBirth) must be present.

Definition: Number assigned by a government agency to identify foreign nationals.

Datatype: ["Max35Text" on page 151](#)

5.38.5 PassportNumber

XML Tag: PsptNb

Presence: [1..1]

Warning One and only one Message Element in the list (DateAndPlaceOfBirth, CustomerNumber, DriversLicenseNumber, SocialSecurityNumber, AlienRegistrationNumber, PassportNumber, TaxIdentificationNumber, IdentityCardNumber, EmployerIdentificationNumber, OtherIdentification, DateAndPlaceOfBirth) must be present.

Definition: Number assigned by a passport authority to a passport.

Datatype: ["Max35Text" on page 151](#)

5.38.6 TaxIdentificationNumber

XML Tag: TaxIdNb

Presence: [1..1]

Warning One and only one Message Element in the list (DateAndPlaceOfBirth, CustomerNumber, DriversLicenseNumber, SocialSecurityNumber, AlienRegistrationNumber, PassportNumber, TaxIdentificationNumber, IdentityCardNumber, EmployerIdentificationNumber, OtherIdentification, DateAndPlaceOfBirth) must be present.

Definition: Number assigned by a tax authority to an entity.

Datatype: ["Max35Text" on page 151](#)

5.38.7 IdentityCardNumber

XML Tag: IdntyCardNb

Presence: [1..1]

Warning One and only one Message Element in the list (DateAndPlaceOfBirth, CustomerNumber, DriversLicenseNumber, SocialSecurityNumber, AlienRegistrationNumber, PassportNumber, TaxIdentificationNumber, IdentityCardNumber, EmployerIdentificationNumber, OtherIdentification, DateAndPlaceOfBirth) must be present.

Definition: Number assigned by a national authority to an identity card.

Datatype: ["Max35Text" on page 151](#)

5.38.8 EmployerIdentificationNumber

XML Tag: MplyrIdNb

Presence: [1..1]

Warning One and only one Message Element in the list (DateAndPlaceOfBirth, CustomerNumber, DriversLicenseNumber, SocialSecurityNumber, AlienRegistrationNumber, PassportNumber, TaxIdentificationNumber, IdentityCardNumber, EmployerIdentificationNumber, OtherIdentification, DateAndPlaceOfBirth) must be present.

Definition: Number assigned to an employer by a registration authority.

Datatype: ["Max35Text" on page 151](#)

5.38.9 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [1..1]

Warning One and only one Message Element in the list (DateAndPlaceOfBirth, CustomerNumber, DriversLicenseNumber, SocialSecurityNumber, AlienRegistrationNumber, PassportNumber, TaxIdentificationNumber, IdentityCardNumber, EmployerIdentificationNumber, OtherIdentification, DateAndPlaceOfBirth) must be present.

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "[DateAndPlaceOfBirth](#)" on page 44 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.33	BirthDate	<BirthDt>		[1..1]		44
5.1.34	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		45
5.1.35	CityOfBirth	<CityOfBirth>		[1..1]		45
5.1.36	CountryOfBirth	<CtryOfBirth>		[1..1]		45

5.38.10 OtherIdentification

XML Tag: OthrId

Presence: [1..1]

Warning One and only one Message Element in the list (DateAndPlaceOfBirth, CustomerNumber, DriversLicenseNumber, SocialSecurityNumber, AlienRegistrationNumber, PassportNumber, TaxIdentificationNumber, IdentityCardNumber, EmployerIdentificationNumber, OtherIdentification, DateAndPlaceOfBirth) must be present.

Definition: Identifier issued to a person for which no specific identifier has been defined.

The **OthrId** block contains the following elements (see datatype "[GenericIdentification4](#)" on page 55 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.38	Identification	<Id>		[1..1]		56
5.1.39	IdentificationType	<IdTp>		[1..1]		56

5.38.11 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identifier.

Datatype: "Max35Text" on page 151

5.39 PostalAddress1

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.2 , 4.1.8 , 4.1.26 , 4.1.41 , 3.1.5 , 3.1.19 , 6.1.0	AddressType	<AdrTp>		[0..1]		103
5.1.3 , 4.1.9 , 4.1.27 , 4.1.42 , 3.1.6 , 3.1.20 , 6.1.1	AddressLine	<AdrLine>		[0..5]		103
5.1.4 , 4.1.10 , 4.1.28 , 4.1.43 , 3.1.7 , 3.1.21 , 6.1.2	StreetName	<StrtNm>		[0..1]		104
5.1.5 , 4.1.11 , 4.1.29 , 4.1.44 , 3.1.8 , 3.1.22 , 6.1.3	BuildingNumber	<BldgNb>		[0..1]		104
5.1.6 , 4.1.12 , 4.1.30 , 4.1.45 , 3.1.9 , 3.1.23 , 6.1.4	PostCode	<PstCd>		[0..1]		104
5.1.7 , 4.1.13 , 4.1.31 , 4.1.46 , 3.1.10 , 3.1.24 , 6.1.5	TownName	<TwnNm>		[0..1]		104
5.1.8 , 4.1.14 , 4.1.32 , 4.1.47 , 3.1.11 , 3.1.25 , 6.1.6	CountrySubDivision	<CtrySubDvsn>		[0..1]		105

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.9 , 4.1.15 , 4.1.33 , 4.1.48 , 3.1.12 , 3.1.26 , 6.1.7	Country	<Ctry>		[1..1]		105

Used in element(s)

"Address" on page 62, "PostalAddress" on page 78, "PostalAddress" on page 81, "PostalAddress" on page 15, "PostalAddress" on page 75, "PostalAddress" on page 64, "PostalAddress" on page 48

5.39.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

Datatype: "AddressType2Code" on page 125

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/UltimateDebtor/PostalAddress/AddressType) is removed.
- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/RelatedRemittanceInformation/RemittanceLocationPostalAddress/Address/AddressType) is removed.
- This element(pain.001.001.02/PaymentInformation/UltimateDebtor/PostalAddress/AddressType) is removed.

5.39.2 AddressLine

XML Tag: AdrLine

Presence: [0..5]

Definition: Information that locates and identifies a specific address, as defined by postal services, that is presented in free format text.

Datatype: "Max70Text" on page 152

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/RelatedRemittanceInformation/RemittanceLocationPostalAddress/Address/AddressLine) is removed.

5.39.3 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: "Max70Text" on page 152

Usage Guideline details

- This element(**pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/RelatedRemittanceInformation/RemittanceLocationPostalAddress/Address/StreetName**) is removed.

5.39.4 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: "Max16Text" on page 149

Usage Guideline details

- This element(**pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/RelatedRemittanceInformation/RemittanceLocationPostalAddress/Address/BuildingNumber**) is removed.

5.39.5 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: "Max16Text" on page 149

Usage Guideline details

- This element(**pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/RelatedRemittanceInformation/RemittanceLocationPostalAddress/Address/PostCode**) is removed.

5.39.6 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "Max35Text" on page 151

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/RelatedRemittanceInformation/RemittanceLocationPostalAddress/Address/TownName) is removed.

5.39.7 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country for example, state, region, county.

Datatype: "Max35Text" on page 151

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/RelatedRemittanceInformation/RemittanceLocationPostalAddress/Address/CountrySubDivision) is removed.

5.39.8 Country

XML Tag: Ctry

Presence: [1..1]

Definition: Nation with its own government.

Datatype: "CountryCode" on page 136

5.40 Purpose1Choice

Definition: Underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, i.e. initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.65	Code	<Cd>	{Or	[1..1]		106
2.66	Proprietary	<Prtry>	Or}	[1..1]		106

Used in element(s)

"Purpose" on page 39

5.40.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the underlying reason for the payment transaction, as published in an external purpose code list.

Datatype: ["ExternalPurposeCode" on page 143](#)

5.40.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: User community specific purpose.

Usage: When available, codes provided by local communities should be used.

Datatype: ["Max35Text" on page 151](#)

5.41 ReferredDocumentAmount1Choice

Definition: Nature of the amount and currency on a document referred to in the remittance section, typically either the original amount due/payable or the amount actually remitted for the referenced document.

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.95	DuePayableAmount	<DuePyblAmt>	{Or	[1..1]		106
2.96	DiscountAppliedAmount	<DscntApldAmt>	Or	[1..1]		106
2.97	RemittedAmount	<RmtdAmt>	Or	[1..1]		107
2.98	CreditNoteAmount	<CdtNoteAmt>	Or	[1..1]		107
2.99	TaxAmount	<TaxAmt>	Or}	[1..1]		107

Used in element(s)

["ReferredDocumentAmount" on page 117](#)

5.41.1 DuePayableAmount

XML Tag: DuePyblAmt

Presence: [1..1]

Definition: Amount specified is the exact amount due and payable to the creditor.

Datatype: ["CurrencyAndAmount" on page 137](#)

5.41.2 DiscountAppliedAmount

XML Tag: DscntApldAmt

Presence: [1..1]

Definition: Amount of money that results from the application of an agreed discount to the amount due and payable to the creditor.

Datatype: ["CurrencyAndAmount" on page 137](#)

5.41.3 RemittedAmount

XML Tag: RmtdAmt

Presence: [1..1]

Definition: Amount of money remitted for the referred document.

Datatype: ["CurrencyAndAmount" on page 137](#)

5.41.4 CreditNoteAmount

XML Tag: CdtNoteAmt

Presence: [1..1]

Definition: Amount specified for the referred document is the amount of a credit note.

Datatype: ["CurrencyAndAmount" on page 137](#)

5.41.5 TaxAmount

XML Tag: TaxAmt

Presence: [1..1]

Definition: Quantity of cash resulting from the calculation of the tax.

Datatype: ["CurrencyAndAmount" on page 137](#)

5.42 ReferredDocumentInformation1

Definition: Structured information supplied to fully identify the documents referred to in the remittance information.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.88	ReferredDocumentType	<RfrdDocTp>		[0..1]		107
2.92	ReferredDocumentNumber	<RfrdDocNb>		[0..1]		108

Used in element(s)

["ReferredDocumentInformation" on page 116](#)

5.42.1 ReferredDocumentType

XML Tag: RfrdDocTp

Presence: [0..1]

Definition: Provides the type of the referred document.

The **RfrdDocTp** block contains the following elements (see datatype "[ReferredDocumentType1](#)" on page 108 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.89	Code	<Cd>	{Or	[1..1]		108
2.90	Proprietary	<Prtry>	Or}	[1..1]		108
2.91	Issuer	<Issr>		[0..1]		109

5.42.2 ReferredDocumentNumber

XML Tag: RfrdDocNb

Presence: [0..1]

Definition: Unique and unambiguous identification number of the referred document.

Datatype: "[Max35Text](#)" on page 151

5.43 ReferredDocumentType1

Definition: Specifies the type of the document referred in the remittance information.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.89	Code	<Cd>	{Or	[1..1]		108
2.90	Proprietary	<Prtry>	Or}	[1..1]		108
2.91	Issuer	<Issr>		[0..1]		109

Used in element(s)

"[ReferredDocumentType](#)" on page 107

5.43.1 Code

XML Tag: Cd

Presence: [1..1]

Warning If Code is present then Proprietary must not be present.

If Proprietary is present then Code must not be present.

Definition: Document type in a coded form.

Datatype: "[DocumentType2Code](#)" on page 138

5.43.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Warning If Code is present then Proprietary must not be present.
If Proprietary is present then Code must not be present.

Definition: Proprietary identification of the type of the remittance document.

Datatype: "Max35Text" on page 151

5.43.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Identification of the issuer of the reference document type.

Datatype: "Max35Text" on page 151

5.44 RegulatoryAuthority

Definition: Entity requiring the regulatory reporting information.

🚫 Removed - 💡 Ignored - ⚠️ Details below - 📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.70	AuthorityName	<AuthrtyNm>		[0..1]		109
2.71	AuthorityCountry	<AuthrtyCtry>		[0..1]		109

Used in element(s)

"Authority" on page 110

5.44.1 AuthorityName

XML Tag: AuthrtyNm

Presence: [0..1]

Definition: Name of the entity requiring the regulatory reporting information.

Datatype: "Max70Text" on page 152

5.44.2 AuthorityCountry

XML Tag: AuthrtyCtry

Presence: [0..1]

Definition: Country of the entity requiring the regulatory reporting information.

Datatype: "CountryCode" on page 136

5.45 RegulatoryReporting2

Definition: Information needed due to regulatory and/or statutory requirements.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.68	DebitCreditReportingIndicator	<DbtCdtRptgInd>		[0..1]		110
2.69	Authority	<Authrty>		[0..1]		110
2.72	RegulatoryDetails	<RgltryDtls>		[0..1]		110

Used in element(s)

"RegulatoryReporting" on page 40

5.45.1 DebitCreditReportingIndicator

XML Tag: DbtCdtRptgInd

Presence: [0..1]

Definition: Identifies whether the regulatory reporting information applies to the debit side, to the credit side or to both debit and credit sides of the transaction.

Datatype: "RegulatoryReportingType1Code" on page 156

5.45.2 Authority

XML Tag: Authrty

Presence: [0..1]

Definition: Entity requiring the regulatory reporting information.

The **Authrty** block contains the following elements (see datatype "RegulatoryAuthority" on page 109 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.70	AuthorityName	<AuthrtyNm>		[0..1]		109
2.71	AuthorityCountry	<AuthrtyCtry>		[0..1]		109

5.45.3 RegulatoryDetails

XML Tag: RgltryDtls

Presence: [0..1]

Definition: Details related to the regulatory reporting information.

The **RgltryDtIs** block contains the following elements (see datatype "[StructuredRegulatoryReporting2](#)" on page 115 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.73	Code	<Cd>		[0..1]		115
2.74	Amount	<Amt>		[0..1]		115
2.75	Information	<Inf>		[0..1]		116

5.46 RemittanceInformation1

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, eg, commercial invoices in an accounts' receivable system.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.85	Unstructured	<Ustrd>		[0..*]		111
2.86	Structured	<Strd>		[0..*]		111

Used in element(s)

"[RemittanceInformation](#)" on page 41

5.46.1 Unstructured

XML Tag: Ustrd

Presence: [0..*]

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, eg, commercial invoices in an accounts' receivable system in an unstructured form.

Datatype: "[Max140Text](#)" on page 149

5.46.2 Structured

XML Tag: Strd

Presence: [0..*]

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, eg, commercial invoices in an accounts' receivable system in a structured form.

The **Strd** block contains the following elements (see datatype "[StructuredRemittanceInformation6](#)" on [page 116](#) for details)

🚫 Removed - ⚠ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.87	ReferredDocumentInformation	<RfrdDocInf>		[0..1]		116
2.93	ReferredDocumentRelatedDate	<RfrdDocRltdDt>		[0..1]		117
2.94	ReferredDocumentAmount	<RfrdDocAmt>		[0..*]		117
2.100	CreditorReferenceInformation	<CdtrRefInf>		[0..1]		117
2.106	Invoicer	<Invcr>		[0..1]	⚠	118
2.107	Invoicee	<Invcee>		[0..1]	⚠	118
2.108	AdditionalRemittanceInformation	<AddtlRmtInf>		[0..1]		119

5.47 RemittanceLocation1

Definition: Remittance information that provides all remittance address elements, that enables the matching, i.e. reconciliation, of a payment with the items that the transaction is intended to settle.

🚫 Removed - ⚠ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.78	RemittanceIdentification	<RmtId>		[0..1]		112
2.79	RemittanceLocationMethod	<RmtLctnMtd>		[0..1]		112
2.80	RemittanceLocationElectronicAddress	<RmtLctnElctrcAdr>		[0..1]		113
2.81	RemittanceLocationPostalAddress	<RmtLctnPstlAdr>		[0..1]		113

Used in element(s)

"[RelatedRemittanceInformation](#)" on [page 41](#)

5.47.1 RemittanceIdentification

XML Tag: RmtId

Presence: [0..1]

Definition: Unique and unambiguous identification of the remittance information, e.g. a remittance advice, which is sent separately from the payment instruction.

Datatype: "[Max35Text](#)" on [page 151](#)

5.47.2 RemittanceLocationMethod

XML Tag: RmtLctnMtd

Presence: [0..1]

Definition: Specifies the method used to deliver the remittance advice information.

Datatype: ["RemittanceLocationMethod1Code" on page 157](#)

5.47.3 RemittanceLocationElectronicAddress

XML Tag: RmtLctnElctrncAdr

Presence: [0..1]

Definition: Electronic address to which an agent is to send the remittance information.

Datatype: ["Max256Text" on page 150](#)

5.47.4 RemittanceLocationPostalAddress

XML Tag: RmtLctnPstlAdr

Presence: [0..1]

Definition: Postal address to which an agent is to send the remittance information.

The **RmtLctnPstlAdr** block contains the following elements (see datatype ["NameAndAddress3" on page 61](#) for details)

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
3.1.3 , 3.1.17 , 2.82	Name	<Nm>		[1..1]		62
3.1.4 , 3.1.18 , 2.83	Address	<Adr>		[1..1]		62

5.48 ServiceLevel2Choice

Definition: Specifies the service level of the transaction.

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.6 , 2.30	Code	<Cd>	{Or	[1..1]		113
2.7 , 2.31	Proprietary	<Prtry>	Or}	[1..1]		114

Used in element(s)

["ServiceLevel" on page 95](#)

5.48.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Identification of a pre-agreed level of service between the parties in a coded form.

Datatype: ["ServiceLevel1Code" on page 159](#)

5.48.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Proprietary identification of a pre-agreed level of service between the parties.

Datatype: ["Max35Text" on page 151](#)

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/PaymentTypeInformation/xor/ServiceLevel/Proprietary](#)) is removed.
- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/PaymentTypeInformation/xor/ServiceLevel/Proprietary](#)) is removed.

5.49 SimpleIdentificationInformation2

Definition: Information related to a party identification or account identification.

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.5	Identification	<Id>		[1..1]		114

Used in element(s)

["ProprietaryAccount" on page 10](#)

5.49.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Name or number assigned by an entity to enable recognition of that entity, eg, account identifier.

Datatype: ["Max34Text" on page 150](#)

5.50 SimpleIdentificationInformation2__1

Definition: Information related to a party identification or account identification.

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
1.1.5	Identification	<Id>		[1..1]		115

Used in element(s)

["ProprietaryAccount" on page 12](#)

5.50.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Name or number assigned by an entity to enable recognition of that entity, eg, account identifier.

Datatype: ["Max8Text" on page 152](#)

Usage Guideline details

- on [pain.001.001.02/PaymentInformation/DebtorAccount/Identification/ProprietaryAccount/Identification](#)

- **HSBC_Identification:**

Debit account should be provided as domestic account number.

5.51 StructuredRegulatoryReporting2

Definition: Information needed due to regulatory and statutory requirements.

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.73	Code	<Cd>		[0..1]		115
2.74	Amount	<Amt>		[0..1]		115
2.75	Information	<Inf>		[0..1]		116

Used in element(s)

["RegulatoryDetails" on page 110](#)

5.51.1 Code

XML Tag: Cd

Presence: [0..1]

Definition: Specifies the nature, purpose, and reason for the transaction to be reported for regulatory and statutory requirements in a coded form.

Datatype: ["Max3Text" on page 151](#)

5.51.2 Amount

XML Tag: Amt

Presence: [0..1]

Definition: Amount of money to be reported for regulatory and statutory requirements.

Datatype: ["CurrencyAndAmount" on page 137](#)

5.51.3 Information

XML Tag: Inf

Presence: [0..1]

Definition: Additional details that cater for specific domestic regulatory requirements.

Usage: Information is used to provide details that are not catered for in the Code or/and Amount elements.

Datatype: ["Max35Text" on page 151](#)

5.52 StructuredRemittanceInformation6

Definition: Structured information supplied to enable the matching, i.e. reconciliation, of a payment with the items that the payment is intended to settle, eg, commercial invoices in an accounts receivable system.

🚫 Removed - 💡 Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.87	ReferredDocumentInformation	<RfrdDocInf>		[0..1]		116
2.93	ReferredDocumentRelatedDate	<RfrdDocRltdDt>		[0..1]		117
2.94	ReferredDocumentAmount	<RfrdDocAmt>		[0..*]		117
2.100	CreditorReferenceInformation	<CdtrRefInf>		[0..1]		117
2.106	Invoicer	<Invcr>		[0..1]	💡	118
2.107	Invoicee	<Invcee>		[0..1]	💡	118
2.108	AdditionalRemittanceInformation	<AddtlRmtInf>		[0..1]		119

Used in element(s)

["Structured" on page 111](#)

5.52.1 ReferredDocumentInformation

XML Tag: RfrdDocInf

Presence: [0..1]

Definition: Reference information to allow the identification of the underlying reference documents.

The **RfrdDocInf** block contains the following elements (see datatype "[ReferredDocumentInformation1](#)" on page 107 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.88	ReferredDocumentType	<RfrdDocTp>		[0..1]		107
2.92	ReferredDocumentNumber	<RfrdDocNb>		[0..1]		108

5.52.2 ReferredDocumentRelatedDate

XML Tag: RfrdDocRltdDt

Presence: [0..1]

Definition: Date associated with the referred document, eg, date of issue.

Datatype: "[ISODate](#)" on page 147

5.52.3 ReferredDocumentAmount

XML Tag: RfrdDocAmt

Presence: [0..*]

Definition: Amount of money and currency of a document referred to in the remittance section. The amount is typically either the original amount due and payable, or the amount actually remitted for the referred document.

The **RfrdDocAmt** block contains the following elements (see datatype "[ReferredDocumentAmount1Choice](#)" on page 106 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.95	DuePayableAmount	<DuePyblAmt>	{Or	[1..1]		106
2.96	DiscountAppliedAmount	<DscntApldAmt>	Or	[1..1]		106
2.97	RemittedAmount	<RmtdAmt>	Or	[1..1]		107
2.98	CreditNoteAmount	<CdtNoteAmt>	Or	[1..1]		107
2.99	TaxAmount	<TaxAmt>	Or}	[1..1]		107

5.52.4 CreditorReferenceInformation

XML Tag: CdtrRefInf

Presence: [0..1]

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

The **CdtrRefInf** block contains the following elements (see datatype "[CreditorReferenceInformation1](#)" on page 42 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
2.101	CreditorReferenceType	<CdtrRefTp>		[0..1]		42
2.105	CreditorReference	<CdtrRef>		[0..1]		43

5.52.5 Invoicer

XML Tag: Invcr

Presence: [0..1]

Definition: Identification of the organization issuing the invoice when different than the creditor or final party.

The **Invcr** block contains the following elements (see datatype "[PartyIdentification8](#)" on page 75 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.0	Name	<Nm>		[0..1]		75
5.1.1	PostalAddress	<PstlAdr>		[0..1]		75
5.1.10	Identification	<Id>		[0..1]		77
5.1.41	CountryOfResidence	<CtryOfRes>		[0..1]		77

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/Invoicer) will be ignored by the Receiver.

5.52.6 Invoicee

XML Tag: Invicee

Presence: [0..1]

Definition: Identification of the party to whom an invoice is issued, when different than the originator or debtor.

The **Invoicee** block contains the following elements (see datatype "[PartyIdentification8](#)" on page 75 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
5.1.0	Name	<Nm>		[0..1]		75
5.1.1	PostalAddress	<PstlAdr>		[0..1]		75
5.1.10	Identification	<Id>		[0..1]		77
5.1.41	CountryOfResidence	<CtryOfRes>		[0..1]		77

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/RemittanceInformation/Structured/Invoicee](#)) will be ignored by the Receiver.

5.52.7 AdditionalRemittanceInformation

XML Tag: AddtlRmtInf

Presence: [0..1]

Definition: Additional information, in free text form, to complement the structured remittance information.

Datatype: "[Max140Text](#)" on page 149

5.53 TaxDetails

Definition: Set of characteristics defining the type of tax.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
7.1.8	CertificateIdentification	<CertId>		[0..1]		120
7.1.9	TaxType	<TaxTp>		[0..1]		120

Rules

R21 CertificateIdentificationAndOrTaxTypeRule

If CertificateIdentification is not present, then TaxType is mandatory.

If CertificateIdentification is present, then TaxType is optional.

Error handling: Undefined

Used in element(s)

"[TaxTypeInformation](#)" on page 123

5.53.1 CertificateIdentification

XML Tag: CertId

Presence: [0..1]

Definition: Document issued by first agent on behalf of debtor to report withholding tax to taxing authority.

Datatype: "Max35Text" on page 151

5.53.2 TaxType

XML Tag: TaxTp

Presence: [0..1]

Definition: Information on the type of tax.

The **TaxTp** block contains the following elements (see datatype "TaxType" on page 123 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - 📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
7.1.10	CategoryDescription	<CtgyDesc>		[0..1]		123
7.1.11	Rate	<Rate>		[0..1]		124
7.1.12	TaxableBaseAmount	<TaxblBaseAmt>		[0..1]		124
7.1.13	Amount	<Amt>		[0..1]		124

5.54 TaxInformation2__1

Definition: Details about tax paid, or to be paid, to the government in accordance with the law, including pre-defined parameters such as thresholds and type of account.

🚫 Removed - 💡 Ignored - ⚠️ Details below - 📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
7.1.0	CreditorTaxIdentification	<CdtrTaxId>		[0..1]	💡	121
7.1.1	CreditorTaxType	<CdtrTaxTp>		[0..1]	💡	121
7.1.2	DebtorTaxIdentification	<DbtrTaxId>		[0..1]	💡	121
7.1.3	TaxReferenceNumber	<TaxRefNb>		[0..1]	⚠️	121
7.1.4	TotalTaxableBaseAmount	<TtlTaxblBaseAmt>		[0..1]	💡	122
7.1.5	TotalTaxAmount	<TtlTaxAmt>		[0..1]	💡	122
7.1.6	TaxDate	<TaxDt>		[0..1]	💡	122
7.1.7	TaxTypeInformation	<TaxTpInf>		[0..*]	💡	123

Used in element(s)

"Tax" on page 40

5.54.1 CreditorTaxIdentification

XML Tag: CdtrTaxId

Presence: [0..1]

Definition: Tax Identification Number of the creditor.

Datatype: "Max35Text" on page 151

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/Tax/CreditorTaxIdentification) will be ignored by the Receiver.

5.54.2 CreditorTaxType

XML Tag: CdtrTaxTp

Presence: [0..1]

Definition: Type of tax payer (creditor).

Datatype: "Max35Text" on page 151

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/Tax/CreditorTaxType) will be ignored by the Receiver.

5.54.3 DebtorTaxIdentification

XML Tag: DbtrTaxId

Presence: [0..1]

Definition: Tax Identification Number of the debtor.

Datatype: "Max35Text" on page 151

Usage Guideline details

- This element(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/Tax/DebtorTaxIdentification) will be ignored by the Receiver.

5.54.4 TaxReferenceNumber

XML Tag: TaxRefNb

Presence: [0..1]

Definition: Tax reference information that is specific to a taxing agency.

Datatype: "Max3Text" on page 151

Usage Guideline details

- on `pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/Tax/TaxReferenceNumber`

– **HSBC_TaxReferenceNumber:**

RTI - Real Time Information

Where the Originator of the Payroll BACS file is an employer making payments to which Income Tax (PAYE - Pay As You Earn) regulations apply, then the 3 character code (used as part of the algorithm to calculate the Unique Reference Number that forms part of the employers' RTI submission direct to HMRC) must be quoted preceded by '/ '.

This request is only applicable to Bacs Direct submitters, therefore customers/employers using their own Service User Number.

5.54.5 TotalTaxableBaseAmount

XML Tag: TtlTaxblBaseAmt

Presence: [0..1]

Definition: Total amount of money on which the tax is based.

Datatype: ["CurrencyAndAmount" on page 137](#)

Usage Guideline details

- This element(`pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/Tax/TotalTaxableBaseAmount`) will be ignored by the Receiver.

5.54.6 TotalTaxAmount

XML Tag: TtlTaxAmt

Presence: [0..1]

Definition: Amount of money resulting from the calculation of the tax.

Datatype: ["CurrencyAndAmount" on page 137](#)

Usage Guideline details

- This element(`pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/Tax/TotalTaxAmount`) will be ignored by the Receiver.

5.54.7 TaxDate

XML Tag: TaxDt

Presence: [0..1]

Definition: Date by which tax is due.

Datatype: ["ISODate" on page 147](#)

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/Tax/TaxDate](#)) will be ignored by the Receiver.

5.54.8 TaxTypeInformation

XML Tag: TaxTpInf

Presence: [0..*]

Definition: Set of characteristics defining the type of tax.

The **TaxTpInf** block contains the following elements (see datatype "[TaxDetails](#)" on [page 119](#) for details)

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
7.1.8	CertificateIdentification	<CertId>		[0..1]		120
7.1.9	TaxType	<TaxTp>		[0..1]		120

Usage Guideline details

- This element([pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/Tax/TaxTypeInformation](#)) will be ignored by the Receiver.

5.55 TaxType

Definition: Information on the type of tax.

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
7.1.10	CategoryDescription	<CtgyDesc>		[0..1]		123
7.1.11	Rate	<Rate>		[0..1]		124
7.1.12	TaxableBaseAmount	<TaxblBaseAmt>		[0..1]		124
7.1.13	Amount	<Amt>		[0..1]		124

Used in element(s)

"[TaxType](#)" on [page 120](#)

5.55.1 CategoryDescription

XML Tag: CtgyDesc

Presence: [0..1]

Definition: Description of the tax that is being paid, including specific representation required by taxing authority.

Datatype: "Max35Text" on page 151

5.55.2 Rate

XML Tag: Rate

Presence: [0..1]

Definition: Rate used to calculate the tax.

Datatype: "PercentageRate" on page 155

5.55.3 TaxableBaseAmount

XML Tag: TaxblBaseAmt

Presence: [0..1]

Definition: Amount of money on which the tax is based.

Datatype: "CurrencyAndAmount" on page 137

5.55.4 Amount

XML Tag: Amt

Presence: [0..1]

Definition: Amount of money resulting from the calculation of the tax.

Datatype: "CurrencyAndAmount" on page 137

6 Message Datatypes

Note The following chapter identifies the datatypes that are used in the message.

6.1 AddressType2Code

Definition: Specifies the type of address.

Type: Code

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Used in element(s)

["AddressType" on page 103](#)

Restricts

["AddressTypeCode" on page 125](#)

6.2 AddressTypeCode

Definition: Specifies the type of address.

Type: Code

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Is restricted by

["AddressType2Code" on page 125](#)

6.3 BBANIdentifier

Definition: Basic Bank Account Number (BBAN). Identifier used nationally by financial institutions, ie, in individual countries, generally as part of a National Account Numbering Scheme(s), which uniquely identifies the account of a customer.

Type: IdentifierSet

Format

pattern [a-zA-Z0-9]{1,30}

Used in element(s)

"BBAN" on page 11, "BBAN" on page 9

6.4 BEIIdentifier

Definition: Code allocated to a non-financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}

Rules

R12 BEI ✓

Valid BICs for non-financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consist of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00002
- *Error Text:* Invalid BEI Code

Used in element(s)

"BEI" on page 70, "BEI" on page 67

6.5 BICIdentifier

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}

Rules

R11 BIC ✓

Valid BICs for financial institutions are registered by the ISO 9362 Registration Authority in the BIC directory, and consist of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid BIC Code

Used in element(s)

["BIC" on page 69](#), ["BIC" on page 66](#), ["BIC" on page 47](#), ["BIC" on page 51](#)

6.6 BaseOneRate

Definition: Rate expressed as a decimal, eg, 0.7 is 7/10 and 70%.

Type: Rate

Format

totalDigits	11
fractionDigits	10

Used in element(s)

["ExchangeRate" on page 46](#)

6.7 BatchBookingIndicator

Definition: Identifies whether the sending party requests a single debit or credit entry per individual transaction or a batch entry for the sum of the amounts of all transactions.

Type: Indicator

Meaning When True: Identifies that a batch entry for the sum of the amounts of all transactions in the batch or message is requested.

Meaning When False: Identifies that a single entry for each of the transactions in the batch or message is requested.

Used in element(s)

["BatchBooking" on page 58](#)

6.8 CHIPSUniversalIdentifier

Definition: (United States) Clearing House Interbank Payments System (CHIPS) Universal Identification (UID). Identifies entities that own accounts at CHIPS participating financial institutions, through which CHIPS payments are effected. The CHIPS UID is assigned by the New York Clearing House.

Type: IdentifierSet

Format

pattern CH[0-9]{6,6}

Used in element(s)

"CHIPSUniversalIdentification" on page 70, "CHIPSUniversalIdentification" on page 67

6.9 CashAccountType4Code

Definition: Specifies the nature, or use, of the cash account.

Type: Code

Code	Name	Definition
CACC	Current	Account used to post debits and credits when no specific account has been nominated.
CASH	CashPayment	Account used for the payment of cash.
CHAR	Charges	Account used for charges if different from the account for payment.
CISH	CashIncome	Account used for payment of income if different from the current cash account.
COMM	Commission	Account used for commission if different from the account for payment.
LOAN	Loan	Account used for loans.
MGLD	MarginalLending	Account used for a marginal lending facility.
MOMA	MoneyMarket	Account used for money markets if different from the cash account.
NREX	NonResidentExternal	Account used for non-resident external.
ODFT	Overdraft	Account is used for overdrafts.
ONDP	OverNightDeposit	Account used for overnight deposits.
SACC	Settlement	Account used to post debit and credit entries, as a result of transactions cleared and settled through a specific clearing and settlement system.
SLRY	Salary	Accounts used for salary payments.
SVGS	Savings	Account used for savings.
TAXE	Tax	Account used for taxes if different from the account for payment.
TRAS	CashTrading	Account used for trading if different from the current cash account.

Used in element(s)

"Code" on page 21

Restricts

"CashAccountTypeCode" on page 129

6.10 CashAccountTypeCode

Definition: Specifies the nature, or use, of the cash account.

Type: Code

Code	Name	Definition
CACC	Current	Account used to post debits and credits when no specific account has been nominated.
CASH	CashPayment	Account used for the payment of cash.
CHAR	Charges	Account used for charges if different from the account for payment.
CISH	CashIncome	Account used for payment of income if different from the current cash account.
COLL	Collateral	Account is for collateral.
COMM	Commission	Account used for commission if different from the account for payment.
LEND	Lending	Account is for the coverage of lending.
LOAN	Loan	Account used for loans.
MARR	MarginReturn	Account is for margin returns.
MGLD	MarginalLending	Account used for a marginal lending facility.
MOMA	MoneyMarket	Account used for money markets if different from the cash account.
NREX	NonResidentExternal	Account used for non-resident external.
ODFT	Overdraft	Account is used for overdrafts.
ONDP	OverNightDeposit	Account used for overnight deposits.
SACC	Settlement	Account used to post debit and credit entries, as a result of transactions cleared and settled through a specific clearing and settlement system.
SEGT	Segregated	Account is an segregated account.
SETT	FinancialSettlement	Account is for financial settlements.
SLRY	Salary	Accounts used for salary payments.
SVGS	Savings	Account used for savings.
TAXE	Tax	Account used for taxes if different from the account for payment.
TRAS	CashTrading	Account used for trading if different from the current cash account.

Is restricted by

["CashAccountType4Code" on page 128](#)

6.11 ChargeBearerType1Code

Definition: Specifies which party(ies) will pay charges due for processing of the instruction.

Type: Code

Code	Name	Definition
CRED	BorneByCreditor	All transaction charges are to be borne by the creditor.
DEBT	BorneByDebtor	All transaction charges are to be borne by the debtor.
SHAR	Shared	In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor, transaction charges on the receiver side are to be borne by the debtor.
SLEV	FollowingServiceLevel	Charges are to be applied following the rules agreed in the service level and/or scheme. Usage Guideline restrictions for this code • This code(pain.001.001.02/PaymentInformation/CreditTransfer-TransactionInformation/ChargeBearer/FollowingServiceLevel) is removed.

Used in element(s)

["ChargeBearer" on page 92](#), ["ChargeBearer" on page 31](#)

Restricts

["ChargeBearerTypeCode" on page 130](#)

6.12 ChargeBearerTypeCode

Definition: Specifies which party(ies) will pay charges due for processing of the instruction.

Type: Code

Code	Name	Definition
CRED	BorneByCreditor	All transaction charges are to be borne by the creditor.

Code	Name	Definition
DEBT	BorneByDebtor	All transaction charges are to be borne by the debtor.
SHAR	Shared	In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor, transaction charges on the receiver side are to be borne by the debtor.
SLEV	FollowingServiceLevel	Charges are to be applied following the rules agreed in the service level and/or scheme.

Is restricted by

"ChargeBearerType1Code" on page 130

6.13 ChequeDelivery1Code

Definition: Specifies the method to be used in delivering a cheque to a party.

Type: Code

Code	Name	Definition
CRCD	CourierToCreditor	Cheque is to be sent through courier services to creditor.
CRDB	CourierToDebtor	Cheque is to be sent through courier services to debtor.
CRFA	CourierToFinalAgent	Cheque is to be sent through courier services to creditor agent.
MLCD	MailToCreditor	Cheque is to be sent through mail services to creditor.
MLDB	MailToDebtor	Cheque is to be sent through mail services to debtor.
MLFA	MailToFinalAgent	Cheque is to be sent through mail services to creditor agent.
PUCD	PickUpByCreditor	Cheque will be picked up by the creditor
PUDB	PickUpByDebtor	Cheque will be picked up by the debtor.
PUFA	PickUpByFinalAgent	Cheque will be picked up by the creditor agent.
RGCD	RegisteredMailToCreditor	Cheque is to be sent through registered mail services to creditor.
RGDB	RegisteredMailToDebtor	Cheque is to be sent through registered mail services to debtor
RGFA	RegisteredMailToFinalAgent	Cheque is to be sent through registered mail services to creditor agent.

Used in element(s)"Code" on page 25**Restricts**"ChequeDeliveryCode" on page 132

6.14 ChequeDeliveryCode

Definition: Specifies the method to be used in delivering a cheque to a party.*Type:* Code

Code	Name	Definition
CRCD	CourierToCreditor	Cheque is to be sent through courier services to creditor.
CRDB	CourierToDebtor	Cheque is to be sent through courier services to debtor.
CRFA	CourierToFinalAgent	Cheque is to be sent through courier services to creditor agent.
MLCD	MailToCreditor	Cheque is to be sent through mail services to creditor.
MLDB	MailToDebtor	Cheque is to be sent through mail services to debtor.
MLFA	MailToFinalAgent	Cheque is to be sent through mail services to creditor agent.
PUCD	PickUpByCreditor	Cheque will be picked up by the creditor
PUDB	PickUpByDebtor	Cheque will be picked up by the debtor.
PUFA	PickUpByFinalAgent	Cheque will be picked up by the creditor agent.
RGCD	RegisteredMailToCreditor	Cheque is to be sent through registered mail services to creditor.
RGDB	RegisteredMailToDebtor	Cheque is to be sent through registered mail services to debtor
RGFA	RegisteredMailToFinalAgent	Cheque is to be sent through registered mail services to creditor agent.

Is restricted by"ChequeDelivery1Code" on page 131

6.15 ChequeType2Code

Definition: Specifies the type of cheque.*Type:* Code

Code	Name	Definition
BCHQ	BankCheque	Cheque drawn on the account of the debtor's financial institution, which is debited on the debtor's account when

Code	Name	Definition
		the cheque is issued. These cheques are printed by the debtor's financial institution and payment is guaranteed by the financial institution. Synonym is 'cashier's cheque'.
CCCH	CertifiedCustomerCheque	Cheque drawn on the account of the debtor, and debited on the debtor's account when the cheque is cashed. The financial institution prints and certifies the cheque, guaranteeing the payment.
CCHQ	CustomerCheque	Cheque drawn on the account of the debtor, and debited on the debtor's account when the cheque is cashed. Synonym is 'corporate cheque'.
DRFT	Draft	A guaranteed bank cheque with a future value date (do not pay before), which in commercial terms is a 'negotiable instrument': the beneficiary can receive early payment from any bank under subtraction of a discount. The ordering customer's account is debited on value date.
ELDR	ElectronicDraft	An instrument with a future value date (do not pay before), which in commercial terms is a 'negotiable instrument': the beneficiary can receive early payment from any bank under subtraction of a discount. The ordering customer's account is debited on value date.

Used in element(s)

["ChequeType" on page 22](#)

Restricts

["ChequeTypeCode" on page 133](#)

6.16 ChequeTypeCode

Definition: Specifies the type of cheque.

Type: Code

Code	Name	Definition
BCHQ	BankCheque	Cheque drawn on the account of the debtor's financial institution, which is debited on the debtor's account when the cheque is issued. These cheques are printed by the debtor's financial institution and payment is guaranteed by the financial institution. Synonym is 'cashier's cheque'.
BKDF	BankDraft	Cheque drawn by a bank on itself or its agent. A person who owes money to another buys the draft from a bank for cash and hands it to the creditor who need have no fear that it might be dis-

Code	Name	Definition
		honoured. A bank draft is also called a banker's cheque, banker's draft, bank check, or treasurer's check.
CCCH	CertifiedCustomerCheque	Cheque drawn on the account of the debtor, and debited on the debtor's account when the cheque is cashed. The financial institution prints and certifies the cheque, guaranteeing the payment.
CCHQ	CustomerCheque	Cheque drawn on the account of the debtor, and debited on the debtor's account when the cheque is cashed. Synonym is 'corporate cheque'.
CLCQ	CircularCheque	An instruction from a bank to its correspondent bank to pay the creditor a stated sum upon the presentation of a means of identification.
CRCQ	CrossedCheque	Cheque that must be paid into an account and not cashed over the counter. There are two parallel lines across the face of a crossed cheque.
DRFT	Draft	A guaranteed bank cheque with a future value date (do not pay before), which in commercial terms is a 'negotiable instrument': the beneficiary can receive early payment from any bank under subtraction of a discount. The ordering customer's account is debited on value date.
ELDR	ElectronicDraft	An instrument with a future value date (do not pay before), which in commercial terms is a 'negotiable instrument': the beneficiary can receive early payment from any bank under subtraction of a discount. The ordering customer's account is debited on value date.
OCHQ	OnlineCheque	Cheque initiated or completed through an online service.
OPCQ	OpenCheque	Cheque that may only be cashed at the bank of origin.
ORCQ	OrderCheque	Cheque made payable to a named recipient 'or order'. The payee can either deposit the cheque in an account or endorse it to a third party.

Is restricted by

"ChequeType2Code" on page 132

6.17 ClearingChannel2Code

Definition: Specifies the clearing channel for the routing of the transaction, as part of the payment type identification.

Type: Code

Code	Name	Definition
BOOK	BookTransfer	Payment through internal book transfer. Usage Guideline restrictions for this code • This code(pain.001.001.02/PaymentInformation/PaymentTypeInformation/xor/ClearingChannel/BookTransfer) is removed. • This code(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/PaymentTypeInformation/xor/ClearingChannel/BookTransfer) is removed.
MPNS	MassPaymentNetSystem	Clearing channel is a mass payment net settlement system.
RTGS	RealTimeGrossSettlementSystem	Clearing channel is a real-time gross settlement system. Usage Guideline restrictions for this code • This code(pain.001.001.02/PaymentInformation/PaymentTypeInformation/xor/ClearingChannel/RealTimeGrossSettlementSystem) is removed. • This code(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/PaymentTypeInformation/xor/ClearingChannel/RealTimeGrossSettlementSystem) is removed.

Code	Name	Definition
RTNS	RealTimeNetSettlementSystem	Clearing channel is a real-time net settlement system. Usage Guideline restrictions for this code • This code(pain.001.001.02/PaymentInformation/PaymentTypeInformation/xor/ClearingChannel/RealTimeNetSettlementSystem) is removed. • This code(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/PaymentTypeInformation/xor/ClearingChannel/RealTimeNetSettlementSystem) is removed.

Used in element(s)

"ClearingChannel" on page 96

Restricts

"ClearingChannelCode" on page 136

6.18 ClearingChannelCode

Definition: Specifies the clearing channel for the routing of the transaction, as part of the payment type identification.

Type: Code

Code	Name	Definition
BOOK	BookTransfer	Payment through internal book transfer.
MPNS	MassPaymentNetSystem	Clearing channel is a mass payment net settlement system.
RTGS	RealTimeGrossSettlementSystem	Clearing channel is a real-time gross settlement system.
RTNS	RealTimeNetSettlementSystem	Clearing channel is a real-time net settlement system.

Is restricted by

"ClearingChannel2Code" on page 134

6.19 CountryCode

Definition: Code to identify a country, a dependency, or another area of particular geopolitical interest, on the basis of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Type: Code

Format

pattern [A-Z]{2,2}

Rules

R10 Country ✓

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Error handling:

- Error severity: Fatal
- Error Code: D00004
- Error Text: Invalid Country Code.

Used in element(s)

["AuthorityCountry" on page 109](#), ["Country" on page 105](#), ["CountryOfBirth" on page 45](#), ["CountryOfResidence" on page 80](#), ["CountryOfResidence" on page 84](#), ["CountryOfResidence" on page 77](#)

6.20 CurrencyAndAmount

Definition: Number of monetary units specified in a currency, where the unit of currency is explicit and compliant with ISO 4217. The decimal separator is a dot.

Note: A zero amount is considered a positive amount.

Type: Amount

This data type must be used with the following XML Attributes:

Attribute	Tag	Datatype
Currency	Ccy	"CurrencyCode" on page 137

Format

minInclusive	0
totalDigits	18
fractionDigits	5

Used in element(s)

["Amount" on page 124](#), ["Amount" on page 45](#), ["Amount" on page 115](#), ["CreditNoteAmount" on page 107](#), ["DiscountAppliedAmount" on page 106](#), ["DuePayableAmount" on page 106](#), ["RemittedAmount" on page 107](#), ["TaxAmount" on page 107](#), ["TaxableBaseAmount" on page 124](#), ["TotalTaxAmount" on page 122](#), ["TotalTaxableBaseAmount" on page 122](#)

6.21 CurrencyCode

Definition: Code allocated to a currency, by a maintenance agency, under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds". Valid currency codes are registered with the ISO 4217 Maintenance Agency, and consist of three contiguous letters.

Type: Code

Format

pattern [A-Z]{3,3}

Rules**R13 ValidationByTable**

Must be a valid currency code which is registered with the ISO 4217 Maintenance Agency, and consist of three contiguous letters.

Error handling: Undefined

Used in element(s)

"Currency" on page 20, "Currency" on page 18, "CurrencyOfTransfer" on page 46

Used in attribute(s)

"HSBC_AmountAndGBPCurrency" on page 145, "CurrencyAndAmount" on page 137

6.22 DecimalNumber

Definition: Number of objects represented as a decimal number, eg, 0.75 or 45.6.

Type: Quantity

Format

totalDigits 18

fractionDigits 17

Used in element(s)

"ControlSum" on page 59

6.23 DocumentType2Code

Definition: Specifies a type of financial or commercial document.

Type: Code

Code	Name	Definition
CINV	CommercialInvoice	Document is an invoice.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.

Code	Name	Definition
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
DISP	DispatchAdvice	Document is a dispatch advice.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.

Used in element(s)

"Code" on page 108

Restricts

"DocumentTypeCode" on page 140

6.24 DocumentType3Code

Definition: Specifies a type of financial or commercial document.

Type: Code

Code	Name	Definition
DISP	DispatchAdvice	Document is a dispatch advice.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
PUOR	PurchaseOrder	Document is a purchase order.
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, eg, in a cover scenario.

Code	Name	Definition
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.

Used in element(s)

"Code" on page 43

Restricts

"DocumentTypeCode" on page 140

6.25 DocumentTypeCode

Definition: Specifies a type of financial or commercial document.

Type: Code

Code	Name	Definition
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
BOLD	BillOfLading	Document is a shipping notice.
CINV	CommercialInvoice	Document is an invoice.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
DISP	DispatchAdvice	Document is a dispatch advice.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
PUOR	PurchaseOrder	Document is a purchase order.
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.

Code	Name	Definition
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, eg, in a cover scenario.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.
VCHR	Voucher	Document is an electronic payment document.

Is restricted by

"DocumentType2Code" on page 138, "DocumentType3Code" on page 139

6.26 DunsIdentifier

Definition: Data Universal Numbering System. A unique identification number provided by Dun & Bradstreet to identify an organization.

Type: IdentifierSet

Format

pattern [0-9]{9,9}

Used in element(s)

"DUNS" on page 70, "DUNS" on page 68

6.27 EANGLNIdentifier

Definition: Global Location Number. A non-significant reference number used to identify legal entities, functional entities or physical entities according to the European Association for Numbering (EAN) numbering scheme rules. The number is used to retrieve the detailed information linked to it.

Type: IdentifierSet

Format

pattern [0-9]{13,13}

Used in element(s)

"EANGLN" on page 70, "EANGLN" on page 67

6.28 ExchangeRateType1Code

Definition: Specifies a type of financial or commercial document.

Type: Code

Code	Name	Definition
AGRD	Agreed	Exchange rate applied is the rate agreed between the parties.
SALE	Sale	Exchange rate applied is the market rate at the time of the sale.
SPOT	Spot	Exchange rate applied is the spot rate.

Used in element(s)

"RateType" on page 46

Restricts

"ExchangeRateTypeCode" on page 142

6.29 ExchangeRateTypeCode

Definition: Code used to define the type of the currency exchange.

Type: Code

Code	Name	Definition
AGRD	Agreed	Exchange rate applied is the rate agreed between the parties.
SALE	Sale	Exchange rate applied is the market rate at the time of the sale.
SPOT	Spot	Exchange rate applied is the spot rate.

Is restricted by

"ExchangeRateType1Code" on page 142

6.30 ExternalClearingSystemMemberCode

Definition: Specifies the external clearing system member code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: Code

Format

minLength	1
maxLength	35

Used in element(s)

["Identification" on page 26](#)

6.31 ExternalLocalInstrumentCode

Definition: Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

Type: Text

Format

minLength	1
maxLength	35

Used in element(s)

["Code" on page 61](#)

6.32 ExternalPurposeCode

Definition: Specifies the external purpose code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: Code

Format

minLength	1
maxLength	35

Used in element(s)

["Code" on page 106](#)

6.33 Grouping1Code

Definition: Specifies the grouping options of the payment transaction.

Type: Code

Code	Name	Definition
GRPD	Grouped	Indicates that there is only one occurrence of the payment information block and several occurrences of the payment transaction block.

Code	Name	Definition
		Usage Guideline restrictions for this code • This code(pain.001.001.02/Group-Header/Grouping/Grouped) is removed.
MIXD	Mixed	Indicates that there are one or several occurrences of the payment information block where each of the occurrences might contain one or several occurrences of the payment transaction block.
SNGL	Single	Indicates that for each occurrences of the payment information block, exactly one occurrence of the payment transaction block is present. Usage Guideline restrictions for this code • This code(pain.001.001.02/Group-Header/Grouping/Single) is removed.

Used in element(s)

"Grouping" on page 59

Restricts

"GroupingCode" on page 144

6.34 GroupingCode

Definition: Specifies the grouping options of the payment transaction.

Type: Code

Code	Name	Definition
GRPD	Grouped	Indicates that there is only one occurrence of the payment information block and several occurrences of the payment transaction block.
MIXD	Mixed	Indicates that there are one or several occurrences of the payment information block where each of the occurrences might contain one or several occurrences of the payment transaction block.

Code	Name	Definition
SNGL	Single	Indicates that for each occurrences of the payment information block, exactly one occurrence of the payment transaction block is present.

Is restricted by

"Grouping1Code" on page 143

6.35 HSBC_AmountAndGBPCurrency

Definition: Only currency GBP is allowed.

Amount must be between 0.01 GBP and 999999999.99 GBP.

Note that when the functionality will be available, the currency will be restricted to GBP in the datatype definition.

Type: Amount

This data type must be used with the following XML Attributes:

Attribute	Tag	Datatype
Currency	Ccy	"CurrencyCode" on page 137
Usage Guideline restrictions for this attribute on pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/Amount/InstructedAmount/Currency Single value: GBP		

Format

minInclusive	0.01
maxInclusive	999999999.99

Used in element(s)

"InstructedAmount" on page 12

6.36 HSBC_Authorisation

Definition:

This datatype has been created by the Publisher of this Usage Guideline.

Type: Code

Format

length 4

Code	Name	Definition
AUTH	PreAuthorisedFile	Indicates a file has been pre authorised or approved within the originating customer environment and no further approval is required
FDET	FileLevelAuthorisationDetails	Indicates that a file requires additional file level approval in HSBCnet, with the ability to view only the payment information block level information. PaymentInformationId is mandatory at this authorisation level and should be unique within a file if multiple batches are used
FSUM	FileLevelAuthorisationSummary	Indicates that a file requires additional file level approval in HSBCnet, with the ability to view both the payment information block and supporting customer credit transaction detail
ILEV	InstructionLevelAuthorisation	Indicates that a file requires all customer transactions to be authorised or approved independently in HSBCnet

Used in element(s)

"Authorisation" on page 57

6.37 IBANIdentifier

Definition: An identifier used internationally by financial institutions to uniquely identify the account of a customer at a financial institution, as described in the latest edition of the international standard ISO 13616. "Banking and related financial services - International Bank Account Number (IBAN)".

Type: IdentifierSet

Format

pattern [a-zA-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}

Rules

R14 IBAN ✓

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

Error handling:

- Error severity: Fatal
- Error Code: D00003
- Error Text: Invalid IBAN format or invalid check digits

Used in element(s)

["IBAN" on page 11](#), ["IBAN" on page 9](#)

6.38 IBElIdentifier

Definition: International Business Entity Identifier to uniquely identify business entities playing a role in the lifecycle of and events related to a financial instrument. (tentative - to be confirmed).

Type: IdentifierSet

Format

pattern [A-Z]{2,2}[B-DF-HJ-NP-TV-XZ0-9]{7,7}[0-9]{1,1}

Used in element(s)

["IBEI" on page 69](#), ["IBEI" on page 66](#)

6.39 ISODate

Definition: A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Type: Date

Used in element(s)

["BirthDate" on page 44](#), ["ChequeMaturityDate" on page 24](#), ["PoolingAdjustmentDate" on page 89](#), ["ReferredDocumentRelatedDate" on page 117](#), ["RequestedExecutionDate" on page 89](#), ["TaxDate" on page 122](#)

6.40 ISODateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in either UTC time format (YYYY-MM-DDThh:mm:ss.sssZ), local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm), or local time format (YYYY-MM-DDThh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: DateTime

Used in element(s)

["CreationDateTime" on page 57](#)

6.41 Instruction3Code

Definition: Specifies further instructions concerning the processing of a payment instruction, provided by the sending clearing agent to the next agent(s).

Type: Code

Code	Name	Definition
CHQB	PayCreditorByCheque	(Ultimate) creditor must be paid by cheque.
HOLD	HoldCashForCreditor	Amount of money must be held for the (ultimate) creditor, who will call. Pay on identification.
PHOB	PhoneBeneficiary	Please advise/contact (ultimate) creditor/claimant by phone
TELB	Telecom	Please advise/contact (ultimate) creditor/claimant by the most efficient means of telecommunication.

Used in element(s)

["Code" on page 60](#)

Restricts

["InstructionCode" on page 148](#)

6.42 InstructionCode

Definition: Specifies further instructions concerning the processing of a payment instruction.

Type: Code

Code	Name	Definition
CHQB	PayCreditorByCheque	(Ultimate) creditor must be paid by cheque.
HOLD	HoldCashForCreditor	Amount of money must be held for the (ultimate) creditor, who will call. Pay on identification.
PBEN	PayTheBeneficiary	(Ultimate) creditor to be paid only after verification of identity.
PHOA	PhoneNextAgent	Please advise/contact next agent by phone.
PHOB	PhoneBeneficiary	Please advise/contact (ultimate) creditor/claimant by phone
TELA	TelecomNextAgent	Please advise/contact next agent by the most efficient means of telecommunication.

Code	Name	Definition
TELB	Telecom	Please advise/contact (ultimate) creditor/claimant by the most efficient means of telecommunication.
TFRO	TimeFrom	Payment instruction will be valid and eligible for execution from the date and time stipulated.
TTIL	TimeTill	Payment instruction is valid and eligible for execution until the date and time stipulated. Otherwise, the payment instruction will be rejected.

Is restricted by

"Instruction3Code" on page 148

6.43 Max140Text

Definition: Specifies a character string with a maximum length of 140 characters.

Type: Text

Format

minLength	1
maxLength	140

Used in element(s)

"AdditionalRemittanceInformation" on page 119, "InstructionForDebtorAgent" on page 39, "InstructionInformation" on page 60, "Unstructured" on page 111

6.44 Max15NumericText

Definition: Specifies a numeric string with a maximum length of 15 digits.

Type: Text

Format

pattern	[0-9]{1,15}
---------	-------------

Used in element(s)

"NumberOfTransactions" on page 58

6.45 Max16Text

Definition: Specifies a character string with a maximum length of 16 characters.

Type: Text

Format

minLength	1
maxLength	16

Used in element(s)

"BuildingNumber" on page 104, "PostCode" on page 104

6.46 Max18Text

Definition: Specifies a character string with a maximum length of 18 characters.

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

minLength	1
maxLength	18

Used in element(s)

"EndToEndIdentification" on page 85, "Name" on page 78, "Name" on page 81, "PaymentInformationIdentification" on page 88

6.47 Max256Text

Definition: Specifies a character string with a maximum length of 256 characters.

Type: Text

Format

minLength	1
maxLength	256

Used in element(s)

"RemittanceLocationElectronicAddress" on page 113

6.48 Max34Text

Definition: Specifies a character string with a maximum length of 34 characters.

Type: Text

Format

minLength	1
maxLength	34

Used in element(s)

["Identification" on page 114](#)

6.49 Max35Text

Definition: Specifies a character string with a maximum length of 35 characters.

Type: Text

Format

minLength	1
maxLength	35

Used in element(s)

["AlienRegistrationNumber" on page 98](#), ["BankPartyIdentification" on page 70](#), ["BankPartyIdentification" on page 68](#), ["CategoryDescription" on page 123](#), ["CertificateIdentification" on page 120](#), ["ChequeNumber" on page 22](#), ["CityOfBirth" on page 45](#), ["ContractIdentification" on page 46](#), ["CountrySubDivision" on page 105](#), ["CreditorReference" on page 43](#), ["CreditorTaxIdentification" on page 121](#), ["CreditorTax-Type" on page 121](#), ["CustomerNumber" on page 98](#), ["DebtorTaxIdentification" on page 121](#), ["Driver-sLicenseNumber" on page 97](#), ["EmployerIdentificationNumber" on page 99](#), ["FormsCode" on page 24](#), ["Identification" on page 15](#), ["Identification" on page 54](#), ["Identification" on page 56](#), ["IdentificationType" on page 56](#), ["IdentityCardNumber" on page 99](#), ["Information" on page 116](#), ["InstructionIdentification" on page 85](#), ["Issuer" on page 55](#), ["Issuer" on page 54](#), ["Issuer" on page 100](#), ["Issuer" on page 109](#), ["Issuer" on page 44](#), ["MemoField" on page 24](#), ["MessageIdentification" on page 57](#), ["Name" on page 15](#), ["PassportNumber" on page 98](#), ["PrintLocation" on page 25](#), ["Proprietary" on page 26](#), ["Proprietary" on page 21](#), ["Proprietary" on page 106](#), ["Proprietary" on page 108](#), ["Proprietary" on page 44](#), ["Proprietary" on page 114](#), ["Proprietary" on page 61](#), ["Proprietary" on page 25](#), ["ProvinceOfBirth" on page 45](#), ["ReferredDocumentNumber" on page 108](#), ["RegionalClearingZone" on page 24](#), ["RemittanceIdentification" on page 112](#), ["SocialSecurityNumber" on page 98](#), ["TaxIdentificationNumber" on page 71](#), ["TaxIdentificationNumber" on page 68](#), ["TaxIdentificationNumber" on page 99](#), ["TownName" on page 104](#)

6.50 Max3Text

Definition: Specifies a character string with a maximum length of 3 characters.

Type: Text

Format

minLength	1
maxLength	3

Used in element(s)

["Code" on page 115](#), ["TaxReferenceNumber" on page 121](#)

6.51 Max6Text

Definition: Specifies a character string with a maximum length of 6 characters.

Type: Text

Format

minLength	1
maxLength	6

Used in element(s)

"Identification" on page 55

6.52 Max70Text

Definition: Specifies a character string with a maximum length of 70characters.

Type: Text

Format

minLength	1
maxLength	70

Used in element(s)

"AddressLine" on page 103, "AuthorityName" on page 109, "Name" on page 20, "Name" on page 75, "Name" on page 18, "Name" on page 64, "Name" on page 48, "Name" on page 62, "StreetName" on page 104

6.53 Max8Text

Definition: Specifies a character string with a maximum length of 8 characters.

Type: Text

Format

minLength	1
maxLength	8

Used in element(s)

"Identification" on page 115

6.54 PaymentCategoryPurpose1Code

Definition: Specifies the type of transaction that resulted in the payment.

Type: Code

Code	Name	Definition
CASH	CashManagementTransfer	Transaction is a general cash management instruction.
CORT	TradeSettlementPayment	Transaction is related to settlement of a trade, eg a foreign exchange deal or a securities transaction.

Code	Name	Definition
DIVI	Dividend	Transaction is the payment of dividends.
GOVT	GovernmentPayment	Transaction is a payment to or from a government department.
HEDG	Hedging	Transaction is related to the payment of a hedging operation.
INTC	IntraCompanyPayment	Transaction is an intra-company payment, ie, a payment between two companies belonging to the same group.
INTE	Interest	Transaction is the payment of interest.
LOAN	Loan	Transaction is related to the transfer of a loan to a borrower.
PENS	PensionPayment	Transaction is the payment of pension.
SALA	SalaryPayment	Transaction is the payment of salaries.
SECU	Securities	Transaction is the payment of securities.
SSBE	SocialSecurityBenefit	Transaction is a social security benefit, ie payment made by a government to support individuals.
SUPP	SupplierPayment	Transaction is related to a payment to a supplier.
TAXS	TaxPayment	Transaction is the payment of taxes.
TRAD	Trade	Transaction is related to the payment of a trade transaction.
TREA	TreasuryPayment	Transaction is related to treasury operations.
VATX	ValueAddedTaxPayment	Transaction is the payment of value added tax.
WHLD	WithHolding	Transaction is the payment of withholding tax.

Used in element(s)

["CategoryPurpose" on page 97](#)

Restricts

["PaymentCategoryPurposeCode" on page 153](#)

6.55 PaymentCategoryPurposeCode

Definition: Specifies the type of transaction that resulted in the payment.

Type: Code

Code	Name	Definition
CASH	CashManagementTransfer	Transaction is a general cash management instruction.

Code	Name	Definition
CORT	TradeSettlementPayment	Transaction is related to settlement of a trade, eg a foreign exchange deal or a securities transaction.
DIVI	Dividend	Transaction is the payment of dividends.
GOVT	GovernmentPayment	Transaction is a payment to or from a government department.
HEDG	Hedging	Transaction is related to the payment of a hedging operation.
INTC	IntraCompanyPayment	Transaction is an intra-company payment, ie, a payment between two companies belonging to the same group.
INTE	Interest	Transaction is the payment of interest.
LOAN	Loan	Transaction is related to the transfer of a loan to a borrower.
PENS	PensionPayment	Transaction is the payment of pension.
SALA	SalaryPayment	Transaction is the payment of salaries.
SECU	Securities	Transaction is the payment of securities.
SSBE	SocialSecurityBenefit	Transaction is a social security benefit, ie payment made by a government to support individuals.
SUPP	SupplierPayment	Transaction is related to a payment to a supplier.
TAXS	TaxPayment	Transaction is the payment of taxes.
TRAD	Trade	Transaction is related to the payment of a trade transaction.
TREA	TreasuryPayment	Transaction is related to treasury operations.
VATX	ValueAddedTaxPayment	Transaction is the payment of value added tax.
WHLD	WithHolding	Transaction is the payment of withholding tax.

Is restricted by

"PaymentCategoryPurpose1Code" on page 152

6.56 PaymentMethod3Code

Definition: Specifies the transfer method that will be used to transfer an amount of money.

Type: Code

Code	Name	Definition
CHK	Cheque	Written order to a bank to pay a certain amount of money from one person to another person.

Code	Name	Definition
		Usage Guideline restrictions for this code • This code(pain.001.001.02/PaymentInformation/PaymentMethod/Cheque) is removed.
TRA	TransferAdvice	Transfer of an amount of money in the books of the account servicer. An advice should be sent back to the account owner.
TRF	CreditTransfer	Transfer of an amount of money in the books of the account servicer.

Used in element(s)

["PaymentMethod" on page 88](#)

Restricts

["PaymentMethodCode" on page 155](#)

6.57 PaymentMethodCode

Definition: Specifies the transfer method that will be used to transfer the cash.

Type: Code

Code	Name	Definition
CHK	Cheque	Written order to a bank to pay a certain amount of money from one person to another person.
CLAS	Classical	Classical method.
DD	DirectDebit	Collection of an amount of money from the debtor's bank account by the creditor. The amount of money and dates of collections may vary.
DIRE	Direct	Direct method.
TRA	TransferAdvice	Transfer of an amount of money in the books of the account servicer. An advice should be sent back to the account owner.
TRF	CreditTransfer	Transfer of an amount of money in the books of the account servicer.

Is restricted by

["PaymentMethod3Code" on page 154](#)

6.58 PercentageRate

Definition: Rate expressed as a percentage, ie, in hundredths, eg, 0.7 is 7/10 of a percent, and 7.0 is 7%.

Type: Rate

Format

totalDigits	11
fractionDigits	10

Used in element(s)

"Rate" on page 124

6.59 Priority2Code

Definition: Specifies the priority level of an event.

Type: Code

Code	Name	Definition
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

Used in element(s)

"InstructionPriority" on page 95, "InstructionPriority" on page 24

Restricts

"PriorityCode" on page 156

6.60 PriorityCode

Definition: Specifies the priority level of an event.

Type: Code

Code	Name	Definition
HIGH	High	Priority level is high.
LOWW	Low	Priority level is low.
NORM	Normal	Priority level is normal.
URGT	Urgent	Priority level is urgent (highest priority possible)

Is restricted by

"Priority2Code" on page 156

6.61 RegulatoryReportingType1Code

Definition: Identifies whether the regulatory reporting information applies to the debit side, to the credit side or to both debit and credit sides of the transaction.

Type: Code

Code	Name	Definition
BOTH	Both	Regulatory information applies to both credit and debit sides.
CRED	Credit	Regulatory information applies to the credit side.
DEBT	Debit	Regulatory information applies to the debit side.

Used in element(s)

["DebitCreditReportingIndicator" on page 110](#)

Restricts

["RegulatoryReportingTypeCode" on page 157](#)

6.62 RegulatoryReportingTypeCode

Definition: Identifies whether the regulatory reporting information applies to the debit side, to the credit side or to both debit and credit sides of the transaction.

Type: Code

Code	Name	Definition
BOTH	Both	Regulatory information applies to both credit and debit sides.
CRED	Credit	Regulatory information applies to the credit side.
DEBT	Debit	Regulatory information applies to the debit side.

Is restricted by

["RegulatoryReportingType1Code" on page 156](#)

6.63 RemittanceLocationMethod1Code

Definition: Specifies the method used to deliver the remittance advice information.

Type: Code

Code	Name	Definition
EDIC	ElectronicDataInterchange	Remittance advice information must be sent through Electronic Data Interchange (EDI).
EMAL	Email	Remittance advice information must be sent through e-mail.

Code	Name	Definition
FAXI	Fax	Remittance advice information must be faxed.
POST	Post	Remittance advice information must be sent through postal services.
URID	UniformResourceIdentifier	Remittance advice information needs to be sent to a Uniform Resource Identifier (URI). URI is a compact string of characters that uniquely identify an abstract or physical resource. URI's are the super-set of identifiers, such as URLs, email addresses, ftp sites, etc, and as such, provide the syntax for all of the identification schemes.

Used in element(s)

["RemittanceLocationMethod" on page 112](#)

Restricts

["RemittanceLocationMethodCode" on page 158](#)

6.64 RemittanceLocationMethodCode

Definition: Specifies the method used to deliver the remittance advice information.

Type: Code

Code	Name	Definition
EDIC	ElectronicDataInterchange	Remittance advice information must be sent through Electronic Data Interchange (EDI).
EMAL	EMail	Remittance advice information must be sent through e-mail.
FAXI	Fax	Remittance advice information must be faxed.
POST	Post	Remittance advice information must be sent through postal services.
SMSM	SMS	Remittance advice information must be sent through by phone as a short message service (SMS).
URID	UniformResourceIdentifier	Remittance advice information needs to be sent to a Uniform Resource Identifier (URI). URI is a compact string of characters that uniquely identify an abstract or physical resource. URI's are the super-set of identifiers, such as URLs, email addresses, ftp sites, etc, and as such, provide the syntax for all of the identification schemes.

Is restricted by

["RemittanceLocationMethod1Code" on page 157](#)

6.65 ServiceLevel1Code

Definition: Specifies the pre-agreed level of service between the parties.

Type: Code

Code	Name	Definition
PRPT	EBAPriorityService	Transaction must be processed according to the EBA Priority Service.
SDVA	SameDayValue	Payment must be executed with same day value to the creditor.
SEPA	SingleEuroPaymentsArea	Payment must be executed following the Single Euro Payments Area scheme. Usage Guideline restrictions for this code • This code(pain.001.001.02/PaymentInformation/CreditTransferTransactionInformation/PaymentTypeInformation/xor/ServiceLevel/Code/SingleEuroPaymentsArea) is removed. • This code(pain.001.001.02/PaymentInformation/PaymentTypeInformation/xor/ServiceLevel/Code/SingleEuroPaymentsArea) is removed.

Used in element(s)

"Code" on page 113

Restricts

"ServiceLevelCode" on page 159

6.66 ServiceLevelCode

Definition: Specifies the pre-agreed level of service between the parties.

Type: Code

Code	Name	Definition
PRPT	EBAPriorityService	Transaction must be processed according to the EBA Priority Service.
SDVA	SameDayValue	Payment must be executed with same day value to the creditor.

Code	Name	Definition
SEPA	SingleEuroPaymentsArea	Payment must be executed following the Single Euro Payments Area scheme.

Is restricted by

"ServiceLevel1Code" on page 159

6.67 UPIIdentifier

Definition: Universal Payment Identification Code (UPIC). Identifier used by the New York Clearing House to mask confidential data, such as bank accounts and bank routing numbers. UPIC numbers remain with business customers, regardless of banking relationship changes.

Type: IdentifierSet

Format

pattern [0-9]{8,17}

Used in element(s)

"UPIC" on page 11, "UPIC" on page 10

Legal Notices

Copyright

SWIFT © 2016. All rights reserved.

This material is a component of MyStandards, the SWIFT collaborative Web application used to manage standards definitions and industry usage. It can only be used and distributed in accordance with MyStandards Terms of Use.

Unless otherwise agreed in writing with SWIFT SCRL, you have no right to:

- authorise external end users to use this component for other purposes than their internal use.
- remove, alter, cover, obfuscate or cancel from view any copyright or other proprietary rights notices appearing in this physical medium.
- re-sell or authorise another party e.g. software and service providers, to re-sell this component.

Confidentiality

This publication may contain SWIFT or third-party confidential information. Only disclose it outside your organisation in accordance with MyStandards Terms of Use and your related license rights.

This component is provided 'AS IS'. SWIFT does not give and excludes any express or implied warranties with respect to this component such as but not limited to any guarantee as to its quality, supply or availability.

Any and all rights, including title, ownership rights, copyright, trademark, patents, and any other intellectual property rights of whatever nature in this component will remain the exclusive property of SWIFT or its licensors.

Trademarks and Patents

SWIFT is the trade name of S.W.I.F.T. SCRL. The following are registered trademarks of SWIFT: SWIFT, the SWIFT logo, 3SKey, Innotribe, Sibos, SWIFTNet, MyStandards, SWIFTReady, and Accord. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.