FFR Roadster Torque Specs (all in lb-ft)

Front Suspension & Steering
Lower control arm → frame: 100–110
Upper ball joint threaded into UCA: 125
Upper A-arm → frame: 80–85
Upper A-arm pivot bolts: 54
Shock upper mount: 40
Shock lower mount: 40
Sway-bar lower bolts: 40
Lower ball joint → spindle: 80–90
Upper ball joint → spindle: 70–80
Steering arm → spindle: 60
Spindle hub nut: 225–250
Tie-rod end with castle nut: 25
Tie-rod end with locknut: 59

Front Brakes
Caliper slider-pin bolts: 23–26
Caliper mounting bolts → spindle: 95
Brake hose banjo bolt → caliper: 29

Brake Hose / Banjo Bolts
Front brake hose → caliper: 29
Rear brake hose → caliper: 32

Driveshaft & Differential
IRS CV axle nut: 98 + additional 45°
Driveshaft adapter → IRS pinion flange: 41
Solid-axle driveshaft bolts: 70
IRS driveshaft → driveshaft adapter: 70

Wheels
Lug nuts: 90

Oil Filter Relocator
Relocator fittings: Max 28

Solid-Axle / 3-Link Rear Suspension
Traction-lock bracket short bolts: 55–70
Upper link → axle: 75–82
Upper link → frame: 75–82
Lower control arm → axle: 75–82
Lower control arm → frame: 75–82
Upper shock → frame: 40–50
Lower shock → axle bracket: 40–50
Panhard bar: 75–82

Independent Rear Suspension (IRS)
Center section → frame, front: 100
Center section → frame, rear: 100
Brake caliper → caliper bracket: 24
Brake caliper bracket → spindle: 129
Brake hose banjo bolt → caliper: 29
Lower control arm → frame: 100
Lower control arm → spindle: 100
Toe link → frame: 100
Toe link → spindle: 100
Upper control arm → frame: 100
Upper control arm → spindle: 100
Hub → spindle: 98
CV axle nut: 98 + 45°
Driveshaft adapter → pinion flange: 41
Driveshaft → driveshaft adapter: 70

Additional IRS installation values
Replacement rear wheel studs: 100
Sway-bar ctrl arm / toe-link mounting: 100
Sway-bar frame mount bolts: 30
Sway-bar lower/end-link bolts: 40
Upper shock bolt: 40
Lower shock bolt: 40

General Bolt Torque Specs (all in lb-ft)

SAE zinc-plated		Metric zinc-plated	Stainless
1/4"-20: 8	7/16"-24: 54	M8: 18	3/16": 11 lb-ft / 132 in-lb
1/4"-28: 10	1/2"-13: 75	M10: 33	3/8": 16 lb-ft / 192 in-lb
5/16"-18: 17	1/2"-20: 83	M12: 61	
5/16"-24: 19	9/16"-12: 100	M14: 98	
3/8"-16: 30	9/16"-18: 100	M16: 120	
3/8"-24: 34	5/8"-11: 100		
7/16"-14: 48	5/8"-14: 100		