

Sesión 7



Selecting

Selecting columns

Using the *select()* verb, we can answer interesting questions about our dataset by focusing in on related groups of verbs. The colon (:) is useful for getting many columns at a time.

Select the columns for *state*, *county*, *population*, and (using a colon) all five of those industry-related variables; there are five consecutive variables in the table related to the industry of people's work: professional, service, office, construction, and production.



Break
15 minutes

Select helpers

These helpers select variables based on their names:

- `starts_with()`: Starts with a prefix.
- `ends_with()`: Ends with a suffix.
- `contains()`: Contains a literal string.

Select the columns `state`, `county`, `population`, and all those that end with `work`.

The rename verb

rename() changes the names of individual variables using `new_name = old_name` syntax.

In this exercise, you'll rename the `n` column from `count()` to something more descriptive.

Renaming a column as part of a select

rename() isn't the only way you can choose a new name for a column; you can also choose a name as part of a `select()`.

Select the columns *state*, *county*, and *poverty* from the *counties* dataset; in the same step, rename the *poverty* column to *poverty_rate*.

Using transmute

The *transmute* verb allows you to control which variables you keep, which variables you calculate, and which variables you drop.

- Keep only the *state*, *county*, and *population* columns, and add a new column, *density*, that contains the population per land_area.
- Filter for only *counties* with a population greater than one million.
- Sort the table in ascending order of *density*.

Choosing among the four verbs

You've learned about the four verbs: *select*, *mutate*, *transmute*, and *rename*. Here, you'll choose the appropriate verb for each situation.

- Choose the right verb for changing the name of the *unemployment* column to *unemployment_rate*
- Choose the right verb for keeping only the columns *state*, *county*, and the ones containing *poverty*.
- Calculate a new column called *fraction_women* with the fraction of the *population* made up of *women*, without dropping any columns.
- Keep only three columns: the *state*, *county*, and *employed / population*, which you'll call *employment_rate*.

Joining Data with dplyr



Joining parts and part categories

The *inner_join* is the key to bring tables together. To use it, you need to provide the two tables that must be joined and the columns on which they should be joined.

In this exercise, you'll join a list of LEGO parts, available as `parts`, with these parts' corresponding categories, available as `part_categories`.