

Package ‘Rsero’

June 3, 2019

Type Package

Title Estimate the annual force of infection using serological data

Version 1.0

Author Nathanael Hoze

Maintainer Nathanael Hoze <nathanael.hoze@gmail.com>

Description Fit models of the force of infection to serological data using Bayesian MCMC methods. The package provides a standardized format for handling serological data, contains various serocatalytic models of force of infection, fits the models to the data, and provides tools to analyse and plot the results of the fits.

License What license is it under?

Depends R (>= 3.0.2),
Rcpp (>= 0.12.13),
corrplot,
ggplot2,
binom,
methods,
bayesplot,
rstan,
rstantools,
shinystan,
shiny,
httpuv

LinkingTo StanHeaders (>= 2.16.0.1),
rstan (>= 2.16.2),
BH (>= 1.65.0.1),
Rcpp (>= 0.12.13),
RcppEigen (>= 0.3.3.3.0)

RoxygenNote 6.1.1

Suggests knitr,
rmarkdown,
testthat

VignetteBuilder knitr

URL <https://github.com/nathoze/Rsero>

R topics documented:

Rsero-package	2
combine_surveys	2
compute_information_criteria	3
correlation_posterior	4
fit	5
FOImodel	7
parameters_credible_intervals	9
plot.FOIfit	10
plot_posterior	11
SeroData	12
seroprevalence	13
seroprevalence.fit	14
seroprevalence.plot	15
simulate_SeroData	15
subset.SeroData	17
Index	19

Rsero-package	<i>Rsero: Estimate the annual force of infection using serological data</i>
---------------	---

Description

Fit models of the force of infection to serological data using Bayesian MCMC methods. The package provides a standardized format for handling serological data, contains various serocatalytic models of force of infection, fits the models to the data, and provides tools to analyse and plot the results of the fits.

See Also

- Useful links:
- <https://github.com/nathoze/Rsero>

combine_surveys	<i>Combine serological surveys</i>
-----------------	------------------------------------

Description

The function combine_surveys creates a new object of the class SeroData from two SeroData objects. In particular, it allows combining serological surveys sampled at different dates.

Usage

```
combine_surveys(SeroData1, SeroData2)
```

Arguments

- | | |
|-----------|---------------------------|
| SeroData1 | A first SeroData object. |
| SeroData2 | A second SeroData object. |

Value

A SeroData object.

Author(s)

Nathanael Hoze <nathanael.hoze@gmail.com>

See Also

[SeroData](#) Define the format of the serological data.

[subset](#) Extract a smaller subset of a SeroData object.

Examples

```
# Combine two simulated surveys, one sampled in 2015, with one-year age categories,  
# and another one sampled in 1995 with 10-year age categories.  
Years <- c(1976,1992)  
FOI <- c(0.2,0.3)  
data1 <- simulate_SeroData(sampling_year = 2015, epidemic_years = Years, foi = FOI)  
data2 <- simulate_SeroData(sampling_year = 1995, age_cats=10, epidemic_years = Years, foi = FOI)  
data <- combine_surveys(data1,data2)
```

compute_information_criteria

Compute the AIC, DIC and WAIC

Description

This function returns the Aikake Information Criterion (AIC), the Deviance Information Criterion (DIC) and the Watanabe Aikake Information Criterion (WAIC) from a fit of the class [FOIfit](#).

Usage

```
compute_information_criteria(FOIfit, ...)
```

Arguments

FOIfit A FOIfit object

Value

A list with the class `information_criteria`, which contains the following items:

- AIC: The Aikake Information Criterion.
- DIC: The Deviance Information Criterion.
- WAIC: The Wakanabe-Aikake Information Criterion.
- MLE: The Maximum-likelihood, estimated as the maximal value of the likelihood in the drawn samples, used in the AIC.
- k: Number of parameters, used in the AIC.
- Dbar: Mean deviance, used in the DIC.

- pD: Effective number of parameters of the model, used in the DIC.
- pwaic: Estimated effective number of parameters, used in the WAIC.
- lpd: log pointwise predictive density, used in the WAIC.

Author(s)

Nathanael Hoze <nathanael.hoze@gmail.com>

References

See Gelman et al. Stat Comput (2014) 24:997-1016 DOI 10.1007/s11222-013-9416-2

Examples

```
data('one_peak_simulation')
model <- FOImodel(type='outbreak', K=1, background=1)
F1 = fit(model = model, data = data )
compute_information_criteria(FOIfit = F1)
```

correlation_posterior *Plot the correlation matrix of the output*

Description

Compute and plot the correlation matrix of the parameters obtained from a MCMC fit. It returns a n-by-n matrix, where n is the number of parameters.

Usage

```
correlation_posterior(FOIfit, show_coefficients = TRUE)
```

Arguments

FOIfit	An object of the class FOIfit.
show_coefficients	Boolean. If TRUE, shows the value of the correlation coefficient on the plotted matrix. Default = TRUE.

Value

The correlation matrix.

Author(s)

Nathanael Hoze <nathanael.hoze@gmail.com>

Examples

```
data('two_peaks_simulation')
model <- FOImodel('outbreak',K=2, background = 1)
F <- fit(data=data, model=model)
M <- correlation_posterior(F)
```

fit

*Fit force of infection models to serological data***Description**

Runs a Bayesian MCMC using rstan to draw samples of a model of the class FOImodel, with data of the class SeroData. It is an adaptation of the function [sampling](#) in the rstan package.

Usage

```
fit(model, data = data, iter = 5000, chains = 4, warmup = floor(iter/2),
    thin = 1, seed = sample.int(.Machine$integer.max, 1), init = "random",
    check_data = TRUE, sample_file = NULL, diagnostic_file = NULL,
    verbose = FALSE, algorithm = c("NUTS", "HMC", "Fixed_param"),
    control = NULL, include = TRUE, cores = getOption("mc.cores", 1L),
    open_progress = interactive() && !isatty(stdout()) &&
    !identical(Sys.getenv("RSTUDIO"), "1"), show_messages = TRUE, ...)

## S3 method for class 'FOIfit'
print(x, ...)

summary.FOIfit(x, ...)
```

Arguments

model	A FOImodel object, generated by the function FOImodel .
data	A SeroData object, generated by the function SeroData .
iter	integer. Number of iterations for each chain, including warmup. Default = 5000.
chains	integer. Number of independent Markov chains. Default = 4.
warmup	A positive integer specifying the number of warmup (aka burnin) iterations per chain. If step-size adaptation is on (which it is by default), this also controls the number of iterations for which adaptation is run (and hence these warmup samples should not be used for inference). The number of warmup iterations should not be larger than iter and the default is iter/2.
thin	A positive integer specifying the period for saving samples. The default is 1, which is usually the recommended value.
seed	The seed for random number generation. The default is generated from 1 to the maximum integer supported by R on the machine. Even if multiple chains are used, only one seed is needed, with other chains having seeds derived from that of the first chain to avoid dependent samples. When a seed is specified by a number, as.integer will be applied to it. If as.integer produces NA, the seed is generated randomly. The seed can also be specified as a character string of digits, such as "12345", which is converted to integer.
init	Initial values specification. See the detailed documentation for the init argument in stan .
check_data	Logical, defaulting to TRUE. If TRUE the data will be preprocessed; otherwise not. See the Note section in stan .

sample_file	An optional character string providing the name of a file. If specified the draws for <i>all</i> parameters and other saved quantities will be written to the file. If not provided, files are not created. When the folder specified is not writable, <code>tempdir()</code> is used. When there are multiple chains, an underscore and chain number are appended to the file name prior to the <code>.csv</code> extension.
diagnostic_file	An optional character string providing the name of a file. If specified the diagnostics data for <i>all</i> parameters will be written to the file. If not provided, files are not created. When the folder specified is not writable, <code>tempdir()</code> is used. When there are multiple chains, an underscore and chain number are appended to the file name prior to the <code>.csv</code> extension.
verbose	TRUE or FALSE: flag indicating whether to print intermediate output from Stan on the console, which might be helpful for model debugging.
algorithm	One of sampling algorithms that are implemented in Stan. Current options are "NUTS" (No-U-Turn sampler, Hoffman and Gelman 2011, Betancourt 2017), "HMC" (static HMC), or "Fixed_param". The default and preferred algorithm is "NUTS".
control	A named list of parameters to control the sampler's behavior. See the details in the documentation for the <code>control</code> argument in stan .
include	Logical scalar defaulting to TRUE indicating whether to include or exclude the parameters given by the <code>pars</code> argument. If FALSE, only entire multidimensional parameters can be excluded, rather than particular elements of them.
cores	Number of cores to use when executing the chains in parallel, which defaults to 1 but we recommend setting the <code>mc.cores</code> option to be as many processors as the hardware and RAM allow (up to the number of chains).
open_progress	Logical scalar that only takes effect if <code>cores > 1</code> but is recommended to be TRUE in interactive use so that the progress of the chains will be redirected to a file that is automatically opened for inspection. For very short runs, the user might prefer FALSE.
show_messages	Either a logical scalar (defaulting to TRUE) indicating whether to print the summary of Informational Messages to the screen after a chain is finished or a character string naming a path where the summary is stored. Setting to FALSE is not recommended unless you are very sure that the model is correct up to numerical error.

Value

A list with the class `FOIfit`, which contains the following items:

- `fit`: The results of the fit, of class `stanfit`.
- `data`: The input data.
- `model`: The input model.

Author(s)

Nathanael Hoze <nathanael.hoze@gmail.com>

See Also

[SeroData](#) Define the format of the serological data.
[FOImodel](#) Define a model.

Examples

```
data <- simulate_SeroData(number_samples = 1000,
  age_cats = 1,
  epidemic_years = c(1976,1992),
  foi = c(0.2,0.3))
model <- FOIModel('outbreak', K = 2)
F1 <- fit(model = model, data = data)
seroprevalence.fit(F1)
plot(F1)
```

FOIModel

Model of the force of infection

Description

This function creates an object of the class FOIModel. Inputs are the type of the model (required), additional parameters if required by the model, and parameters for the prior distributions. The models to be given as an input are predefined. More details are given in the vignette models.

Usage

```
FOIModel(type = "constant", K = 1, seroreversion = 0, background = 0,
  prioralpha1 = 0, prioralpha2 = 5, priorbeta1 = 0, priorbeta2 = 5,
  priorT1 = 0, priorT2 = 70, priorC1 = 0, priorC2 = 10, priorY1 = 0,
  priorY2 = 100, priorbg1 = 0, priorbg2 = 1, priorRho1 = 0,
  priorRho2 = 10, cat_bg = 0, cat_lambda = 0, ...)

## S3 method for class 'FOIModel'
print(x, ...)
```

Arguments

type	<p>A character with the name of model. The options are:</p> <ul style="list-style-type: none"> • 'constant': Constant force of infection • 'outbreak': Series of outbreak modeled with gaussians • 'independent': Yearly independent values of the force of infection • 'intervention': Piecewise constant force of infection. The number of phases with a constant level is given by the variable K • 'constantoutbreak': A combination of K outbreaks with a constant yearly force of infection
K	integer. An additional parameter used in the outbreak, constantoutbreak and intervention stan models. This parameter is the number of Gaussians used in the model. Default = NULL.
seroreversion	integer, equal to 0 or 1. If seroreversion=0 the model includes a rate of seroreversion (waning immunity). See the vignette models for details. Default = 0.
background	integer, equal to 0 or 1. If background=1 the model includes a background infection probability. See the vignette models for details. Default = 0.

prioralpha1	First parameter of the uniform prior distribution of the parameter alpha, used as the intensity of the force of infection in the outbreak and intervention models. Default = 0.
prioralpha2	Second parameter of the uniform prior distribution of the parameter alpha, used as the intensity of the force of infection in the outbreak and intervention models. Default = 5.
priorbeta1	First parameter of the uniform prior distribution of the parameter beta, used as the spread of the force of infection in the outbreak and intervention models. Default = 0.
priorbeta2	Second parameter of the uniform prior distribution of the parameter beta, used as the spread of the force of infection in the outbreak and intervention models. Default = 1.
priorT1	First parameter for the uniform distribution for the T parameter, used as the time of infection in the outbreak and intervention models. T is defined as the number of years between the survey and the outbreak. Default = 0.
priorT2	Second parameter for the uniform distribution for the T parameter, used as the time of infection in the outbreak and intervention models. Default = 70.
priorC1	First parameter of the uniform prior distribution for the constant force of infection, used in the constant and intervention models. Default = 0.
priorC2	Second parameter of the uniform prior distribution for the constant force of infection, used in the constant and intervention models. Default = 10.
priorY1	Mean of the normal distribution for the logit of the annual hazard of infection, used in the independent models. Default = 0.
priorY2	Standard-deviation of the normal distribution for the logit of the annual hazard of infection, used in the independent models. Default = 100.
priorbg1	First parameter of the uniform prior distribution for the pB parameter (background probability of infection) when background = 1. Default = 0.
priorbg2	Second shape parameter of the beta distribution for the pB parameter (background probability of infection) when background = 1. Default = 1.
priorRho1	First parameter of the uniform prior distribution for rho, the seroreversion rate used when seroreversion=1. Default = 0.
priorRho2	Second parameter of the uniform prior distribution for rho, the seroreversion rate used when seroreversion=1. Default = 10.
cat_bg	integer, equal to 0 or 1. If cat_bg=1 a specific value of the background infection probability pB is attributed to each category (see SeroData). See the vignette models for details. Default = 0.
cat_lambda	integer, equal to 0 or 1. If cat_lambda=1 the force of infection varies accross the different categories defined in an objet SeroData. See the vignette models for details. Default = 0.
...	Additional arguments (not used).
x	A object of the class FOImodel.
cat_lambda	integer, equal to 0 or 1. If cat_lambda=1 the force of infection varies accross the different categories defined in an objet SeroData. See the vignette models for details. Default = 0.

Value

A list with the class `FOImodel`, which contains the following items:

- `type`: The type of the model.
- `stanname`: The name of the stan file used.
- `estimated_parameters`: The number of estimated parameters.
- `priors`: a list with the priors.
- `K`: the input parameter used in the outbreak and intervention models, if given.

Author(s)

Nathanael Hoze <nathanael.hoze@gmail.com>

Examples

```
## A gaussian model, with one gaussian, and background infection
model <- FOImodel(type='outbreak', background = 1, K = 1)
```

```
## A gaussian model, with two gaussians, background infection, and user-defined hyperparameters
model <- FOImodel('outbreak', background=1, K = 2, prioralpha1 = 0, prioralpha2 = 1)
```

```
## An intervention model, consisting in two constant phases, with seroreversion and user-defined hyperparameter
model <- FOImodel('intervention', K=2, seroreversion=1, priorRho1=0.1)
```

parameters_credible_intervals

Analyse a FOIfit

Description

Determines the mean and quantiles of the parameters estimated in the fit. By default, it returns the mean, the median and 95 % credible interval of the parameters.

Usage

```
parameters_credible_intervals(FOIfit, quant = c(0.025, 0.5, 0.975))
```

Arguments

<code>FOIfit</code>	An object of the class <code>FOIfit</code> .
<code>quant</code>	Numeric. Contains the list of the estimated quantiles given between 0 and 1. Default parameters are the 2.5%, 50 % and 97.5 % quantiles given by <code>quant = c(0.025, 0.5, 0.975)</code> .

Value

A dataframe containing the input quantiles and the mean of the posterior distributions.

Author(s)

Nathanael Hoze <nathanael.hoze@gmail.com>

Examples

```
data("1peakSimulation")
model <- FOImodel(type='outbreak', seroreversion=TRUE, K=1)
options(mc.cores = parallel::detectCores())
Fit <- fit(data = data, model = model)
parameters_credible_intervals(Fit)

# an example where other quantiles are specified
data("1peakSimulation")
model <- FOImodel(type='outbreak', seroreversion=TRUE, K=1)
options(mc.cores = parallel::detectCores())
Fit <- fit(data = data, model = model)
parameters_credible_intervals(Fit, quant=c(0.25,0.5,0.75))
```

plot.FOIfit

Plot the force of infection

Description

Plot the mean and credible interval of the yearly force of infection, given an object of the class FOIfit. The function plot uses the package ggplot2. It returns a graphical object that can be further modified.

Usage

```
plot.FOIfit(x, mean_only = FALSE, individual_samples = 0, YLIM = 1,
  maxYears = NULL, ...)
```

Arguments

x	The FOIfit object to be plotted.
mean_only	Boolean. If FALSE, plot the mean force of infection as well as an envelope of the 95% credible interval. Default = FALSE.
individual_samples	Integer. Number of individual samples to be plotted additionally to the mean and the credible interval of the force of infection. The individual_samples samples are randomly chosen in the chains. Default = 0.
YLIM	Upper limit of the y-axis. Default = 1. The lower limit is set to 0.

Value

A list of ggplot2 objects.

Author(s)

Nathanael Hoze <nathanael.hoze@gmail.com>

Examples

```
data <- simulate_SeroData( max_age = 50, epidemic_years = c(1976,1992), foi = c(0.2,0.3))
model <- FOImodel(type='outbreak', background=1, K = 2)
Fit <- fit(model = model, data = data)
p <- plot(Fit)
p+ylim(0,1)
```

plot_posterior	<i>Plot posterior distribution</i>
----------------	------------------------------------

Description

Plot the posterior distribution of the parameters estimated in a FOIfit.

Usage

```
plot_posterior(FOIfit)
```

Arguments

FOIfit An object of the class FOIfit.

Value

A list with the posterior plots. These plots are generated with the ggplot2 package and can be modified.

Author(s)

Nathanael Hoze <nathanael.hoze@gmail.com>

Examples

```
# Here describe how to access the plots
P <- plot_posterior(FOIfit)
P[[1]]+ylim(0,200)
```

SeroData*Create a dataset containing the serological data and other information*

Description

This function contains the definition of the class `SeroData`. It requires the age and seropositivity of individuals, and accepts more input parameters.

Usage

```
SeroData(age_at_sampling, age = NULL, Y, age_cats = 1, max_age = NULL,
         sampling_year = NULL, location = NULL, sex = NULL, category = 1, ...)

compute.age.groups(age, sampling_year)
```

Arguments

<code>age_at_sampling</code>	A vector of integers containing the age of the sampled individuals at the time of sampling.
<code>Y</code>	A vector containing the seropositivity status of the sampled individuals. It can be in a numeric form (1 or 0) or boolean (TRUE or FALSE). This vector must have the same size as <code>age</code> .
<code>age_cats</code>	Integer. The length in years of the age classes. Default = 1.
<code>max_age</code>	Integer. The maximal age considered for the individuals in the sample. Individuals older than <code>max_age</code> are set equal to <code>max_age</code> .
<code>sampling_year</code>	Integer. Defines the sampling year. It can be a single value or a vector of the same size as the number of sampled individuals. If it is a single value, all the sampled individuals have the same sampling year. Default = 2017.
<code>location</code>	An optional character factor defining the sampling location. It can be a single chain of characters or a vector of the same size as the number of sampled individuals. Default = NULL.
<code>sex</code>	An optional character factor defining the sex of the individuals. It can be a single chain of characters or a vector of the same size as the number of sampled individuals. Default = NULL.
<code>category</code>	An optional element defining the category of the individuals. This feature is used when fitting the models assuming different risks of infection for the different categories. It can be a single element or a vector of the size of the number of individuals. Default = 1.
<code>...</code>	Additional arguments (not used).

Value

A list with the class `SeroData`, which contains the following items:

- `age`: A vector of integers containing the age of the sampled individuals at the time of the latest sampling, of length `N`.
- `age_at_sampling`: A vector of integers containing the age of the sampled individuals at the time of sampling, of length `N`.

- Y: A vector of seropositivity status, of length N.
- N: The number of individuals considered.
- A: The maximal age.
- NGroups: The total number of age groups.
- sampling_year: A vector of sampling years, of length N.
- location: A vector of the sampling location, of length N.
- sex: A vector of the sex of each individual, of length N.

Author(s)

Nathanael Hoze <nathanael.hoze@gmail.com>

Examples

```
## A very simple example of a serological survey with three individuals:
data = SeroData(age_at_sampling = c(10,32,24), Y=c(0,1,1), max_age = 50, age_cats = 1, sampling_year = 2017)

seroprevalence(data = data)
data2 = subset(data,c(1,3))
seroprevalence(data = data2, age_cats = 5)
```

seroprevalence

Compute the seroprevalence

Description

Compute the seroprevalence using an object of the class SeroData. If multiple category are defined, it will also compute the seroprevalence for each category.

Usage

```
seroprevalence(data)
```

Arguments

data An object of the class SeroData.

Value

The mean and 95 % confidence interval of the seroprevalence

Author(s)

Nathanael Hoze <nathanael.hoze@gmail.com>

Examples

```
## A very simple example of a serological survey with three individuals:
data = SeroData(age_at_sampling = c(10,32,24), Y=c(0,1,1), max_age = 50, age_cats = 1, sampling_year = 2017)
seroprevalence(data = data)
```

`seroprevalence.fit` *Plot the fit of the seroprevalence vs. age*

Description

Plot the mean and credible interval of the posterior of the seroprevalence, given an object of the class `FOIfit`. See function [seroprevalence](#) for plotting the seroprevalence from the data. The function returns graphical objects that can be further modified.

Usage

```
seroprevalence.fit(FOIfit, individual_samples = 0, age_cats = 10,
  YLIM = 1, ...)
```

Arguments

<code>FOIfit</code>	The <code>FOIfit</code> object to be plotted.
<code>individual_samples</code>	Integer. Number of individual samples to be plotted additionally to the mean and the credible interval of the force of infection. The <code>individual_samples</code> samples are randomly chosen in the chains. Default = 0.
<code>age_cats</code>	Integer. Length of the age groups (in years). Used if <code>show_data</code> = <code>TRUE</code> . Default = 10.
<code>YLIM</code>	Upper limit of the y-axis. Default = 1. The lower limit is set to 0.
<code>show_data</code>	Boolean. If <code>TRUE</code> , shows the fraction of seropositive as well. By default, ages are associated in groups of <code>age_cats</code> years. Default = <code>TRUE</code> .

Value

A list of `ggplot2` objects.

Author(s)

Nathanael Hoze <nathanael.hoze@gmail.com>

Examples

```
data <- simulate_SeroData( max_age = 50, epidemic_years = c(1976,1992), foi = c(0.2,0.3))
model <- FOImodel(type='outbreak', background=TRUE, K = 2)

Fit <- fit(model = model, data = data)

# plot the fraction of seropositive, with 2 individual samples
p <- seroprevalence.fit(Fit, individual_samples = 2,YLIM=0.2)
```

seroprevalence.plot *Plot the seroprevalence by age*

Description

Plot the mean and 95 % confidence interval of the seroprevalence by age-class. Accepts as an input a SeroData object. If multiple category are defined, it will also compute the seroprevalence for each category.

Usage

```
seroprevalence.plot(data, age_cats = 10, YLIM = 1, ...)
```

Arguments

data	An object of the class SeroData.
age_cats	Integer. The length in years of the age classes. Default = 10.
YLIM	Upper limit of the y-axis. Default = 1. The lower limit is set to 0.

Value

a list with plots of the seroprevalence for each category, or one plot if only one category is defined.

Author(s)

Nathanael Hoze <nathanael.hoze@gmail.com>

Examples

```
dat = data("one_peak_simulation")
seroprevalence.plot(data = dat)
```

simulate_SeroData *Simulate a serological survey*

Description

Simulate a serological survey, based on years of epidemics and force of infection.

Usage

```
simulate_SeroData(number_samples = 500, equal_number = FALSE,
  age_cats = 1, max_age = 70, sampling_year = 2019,
  epidemic_years = c(2000, 1987, 1982), foi = c(0.3, 0.2, 0.4),
  location = NULL, sex = NULL, category = 1, pb = 0, rho = 0)
```

Arguments

number_samples	integer. The number of individuals in the simulated serological survey. Default = 500.
equal_number	boolean. If FALSE, draw random ages with a uniform distribution between 1 and max_age. if TRUE, generates a SeroData object with an equal distribution of the ages. Default = FALSE.
age_cats	integer. The length in years of the age classes. Default = 1.
max_age	integer. The maximal age. Default = 70.
sampling_year	integer. Default = 2019.
epidemic_years	numeric. A vector with the years where the force of infection is positive. The force of infection at the non specified years is equal to zero. Default = c(2000,1987,1982).
foi	numeric. The force of infection at the years defined in epidemic_years. It must be the same size as epidemic_years. Default = c(0.3,0.2,0.4).
location	An optional character factor defining the sampling location. It can be a single chain of characters or a vector of the same size as the number of sampled individuals. Default = NULL.
sex	An optional character factor defining the sex of the individuals. It can be a single chain of characters or a vector of the same size as the number of sampled individuals. Default = NULL.
pb	numeric, between 0 and 1. Probability for an individual to be seropositive independently of the force of infection (background probability of infection). Default = 0.
rho	numeric, 0 or positive. Seroreversion rate. Default = 0.

Value

An object of the class SeroData.

Author(s)

Nathanael Hoze <nathanael.hoze@gmail.com>

See Also

[SeroData](#) Define the format of the serological data.

Examples

```
## Simulates a serological survey taken in a population that experienced
## a series of three epidemics in 1972, 1988 and 1996.

data = simulate_SeroData(number_samples = 1000,
  age_cats = 1,
  sampling_year = 2015,
  max_age = 50,
  epidemic_years = c(1996,1988,1972),
  foi = c(0.2,0.1,0.3),
  pb = 0)

seroprevalence(data)
```



```
## 500 individuals sampled in 2019, in a population that experienced two epidemics, in 1962
## and 2012.
## Sampled individuals have additionally a probability of being seropositive equal to pb = 0.1.
years = seq(1962,2012)
alpha=c(0.25, 0.1)
T=c(1974, 2000)
beta=c(1,0.5)
FOI = alpha[1]*exp(-(years-T[1])^2/beta[1]^2) + alpha[2]*exp(-(years-T[2])^2/beta[2]^2)
data1 <- simulate_SeroData( epidemic_years = years,foi=FOI, pb=0.1)
seroprevalence(data1)

## Adding another survey, sampled in 2005, where ages are categorized in 5 year groups:
data2 <- simulate_SeroData(age_cats = 5,
  epidemic_years = years,
  foi=FOI,
  pb=0.1,
  sampling_year = 2005)
data <- combine_surveys(data1,data2)
seroprevalence(data)
```

subset.SeroData	<i>Creates a subset of a serological survey</i>
-----------------	---

Description

This function create a serological survey of the class SeroData.

Usage

```
## S3 method for class 'SeroData'
subset(data, sub = seq(1, data$N), loc = NULL,
  category = NULL)
```

Arguments

sub	Used in the subset function. A list of the indices of the individuals to be considered in the new SeroData object.
loc	Used in the subset function. A list of the location of the individuals to be considered in the new SeroData object.
sex	An optional character factor defining the sex of the individuals. It can be a single chain of characters or a vector of the same size as the number of sampled individuals. Default = NULL.
...	Additional arguments (not used).

Value

A list with the class SeroData, which contains the following items:

- age: A vector of integers containing the age of the sampled individuals at the time of the latest sampling, of length N.
- age_at_sampling: A vector of integers containing the age of the sampled individuals at the time of sampling, of length N.
- Y: A vector of seropositivity status, of length N.
- N: The number of individuals considered.
- A: The maximal age.
- NGroups: The total number of age groups.
- sampling_year: A vector of sampling years, of length N.
- location: A vector of the sampling location, of length N.
- sex: A vector of the sex of each individual, of length N.

Author(s)

Nathanael Hoze <nathanael.hoze@gmail.com>

Examples

```
## A very simple example of a serological survey with three individuals:
data = SeroData(age_at_sampling = c(10,32,24), Y=c(0,1,1), max_age = 50, age_cats = 1, sampling_year = 2017)

seroprevalence(data = data)
data2 = subset(data,c(1,3))

# add example with subset(data, location)
```

Index

`combine_surveys`, [2](#)
`compute.age.groups (SeroData)`, [12](#)
`compute_information_criteria`, [3](#)
`correlation_posterior`, [4](#)

`fit`, [5](#)
`FOIfit`, [3](#)
`FOImodel`, [5](#), [6](#), [7](#)

`parameters_credible_intervals`, [9](#)
`plot.FOIfit`, [10](#)
`plot_posterior`, [11](#)
`print.FOIfit (fit)`, [5](#)
`print.FOImodel (FOImodel)`, [7](#)

`Rsero (Rsero-package)`, [2](#)
`Rsero-package`, [2](#)

`sampling`, [5](#)
`SeroData`, [3](#), [5](#), [6](#), [12](#), [16](#)
`seroprevalence`, [13](#), [14](#)
`seroprevalence.fit`, [14](#)
`seroprevalence.plot`, [15](#)
`simulate_SeroData`, [15](#)
`stan`, [5](#), [6](#)
`subset.SeroData`, [17](#)
`summary.FOIfit (fit)`, [5](#)