

ZAPIER GUIDE

Deal Inspection (Slack /dealcheck) – Zapier Implementation Guide

Workflow ID: 31-deal-inspection • Backstory public rollout asset



This file is a plain-English implementation guide. It is not an importable JSON artifact.

Zapier does not accept a reusable “upload this workflow JSON” format for the kind of cross-workspace assets this catalog is describing. To replicate this workflow in Zapier, build it as one or more Zaps plus, when needed, a custom Zapier app. If you want a reusable public Zap Template, every integration in the template must be a public integration, and Zapier rejects templates that include Code, custom Webhook, or custom Formatter steps. If you are creating workflows through Zapier workflow-creation APIs, use Public Apps because private apps are not supported there.

Workflow Summary

- Workflow ID: `31-deal-inspection`
- Category: pipeline-forecasting
- Source trigger in this catalog: Slack slash command – /dealcheck |
- Recommended Zapier trigger surface: Zapier Interfaces form/button, native app trigger, or private custom app trigger
- Delivery targets: Slack channel or direct message

What To Build In Zapier

- Published Backstory custom Zapier app with explicit search and create actions
- Slack app actions for channel posts and direct messages
- Zapier Tables or Storage for state, routing maps, and dedupe keys

Recommended Implementation Shape

1. Publish the Backstory integration as a custom Zapier app before you try to templatzize the workflow. Use the Zapier Platform UI or CLI if you need custom triggers or actions.
2. Create the primary Zap with the trigger and the minimum deterministic steps needed to gather source data and reach structured synthesis.

3. Split delivery, approvals, or fan-out into additional Zaps when the workflow naturally decomposes or when public-template restrictions would block a single-Zap design.
4. Use Zapier Tables or Storage for routing maps, dedupe keys, approval state, or cross-Zap handoff instead of hiding state in code.
5. If you plan to publish a public Zap Template, test the template path separately from any internal/private workspace build.

Custom App Actions To Provide

- `backstory_list_source_records`
- `backstory_get_record_context`
- `backstory_publish_run_summary`
- `load_routing_map`

Zaps To Create

- `31_deal_inspection_primary_zap` – Trigger: Zapier Interfaces form/button, native app trigger, or private custom app trigger. Native steps: Backstory custom Zapier app action: `resolve_deal_context` -> Backstory custom Zapier app action: `pull_backstory_signals` -> AI step backed by a native LLM app returning strict JSON for Generate Inspection Summary -> Native delivery step: Slack app action for Post Slack Result. Notes: Keep the primary Zap focused on normalization, source access, and structured synthesis. Route secondary fan-out through additional native Zaps when template restrictions or retry requirements demand decomposition.
- `31_deal_inspection_delivery_or_followup_zap` – Trigger: Zapier Tables state change, Interfaces action, or an upstream custom app event. Native steps: Read `delivery_payload` and target metadata from structured fields -> Slack app action: Send Channel Message or Send Direct Message. Notes: Use this secondary Zap when you need reusable delivery fan-out, fallback paths, or approval boundaries without falling back to Webhooks or Code steps.

Contracts To Preserve

- `run_context` : workflow-level execution context such as trigger, mode, lookback, delivery mode, and dry-run state.
- `source_record` : normalized business record from the source adapter or source-system action layer.
- `enrichment_context` : MCP or native app enrichment results used only during synthesis.
- `delivery_payload` : deterministic delivery fields for the final native connector or app action.

Structured AI Requirements

- `generate_inspection_summary` : return JSON only with keys `title`, `summary`, `confidence`, `recommended_actions`, `source_refs`. Intent: Uses one agent pass to turn the merged signals into a

concise risk summary and next steps.

Validation Checklist

- Do not treat this guide as an importable JSON workflow; build the workflow as one or more Zaps and, if needed, a custom Zapier app.
- If you want a reusable public Zap Template, only public integrations can be used in the template.
- Do not include Code, custom Webhook, or custom Formatter steps in a public Zap Template.
- If you are creating workflows through Zapier workflow-creation APIs, use Public Apps only and avoid Paths because they are not currently supported there.
- Validate structured AI output before any Slack, Teams, email, calendar, Jira, or sink action runs.

Official References

- [Zap templates restrictions](#)
- [Known limitations for workflow creation](#)
- [Build with CLI](#)
- [Zapier action design](#)
- [Add a create action](#)
- [AI actions](#)
- [Custom actions and API requests actions](#)