

BACKSTORY AUTOMATION CATALOG

Zapier implementation guide for the 12-win-loss-debrief workflow

Implementation guide · Generated 2026-05-31

Win/Loss Debrief Generator — Zapier Implementation Guide

This file is a plain-English implementation guide. It is not an importable JSON artifact.

Zapier does not accept a reusable “upload this workflow JSON” format for the kind of cross-workspace assets this catalog is describing. To replicate this workflow in Zapier, build it as one or more Zaps plus, when needed, a custom Zapier app. If you want a reusable public Zap Template, every integration in the template must be a public integration, and Zapier rejects templates that include Code, custom Webhook, or custom Formatter steps. If you are creating workflows through Zapier workflow-creation APIs, use Public Apps because private apps are not supported there.

Workflow Summary

- Workflow ID: 12-win-loss-debrief
- Category: coaching-enablement
- Source trigger in this catalog: Webhook — CRM deal stage change to Closed Won/Lost |
- Recommended Zapier trigger surface: Native CRM app trigger or private custom Zapier app trigger
- Delivery targets: Slack channel or direct message, Microsoft Teams channel or chat, Email delivery

What To Build In Zapier

- Published Backstory custom Zapier app with explicit search and create actions
- Native Salesforce, HubSpot, or Dynamics app triggers and actions
- Slack app actions for channel posts and direct messages
- Microsoft Teams app actions or companion Microsoft 365 app steps
- Gmail, Microsoft Outlook, or Email by Zapier actions
- Meeting-system native app or published custom Zapier app for transcript retrieval

Recommended Implementation Shape

1. Publish the Backstory integration as a custom Zapier app before you try to templatzize the workflow. Use the Zapier Platform UI or CLI if you need custom triggers or actions.
2. Create the primary Zap with the trigger and the minimum deterministic steps needed to gather source data and reach structured synthesis.
3. Split delivery, approvals, or fan-out into additional Zaps when the workflow naturally decomposes or when public-template restrictions would block a single-Zap design.
4. Keep routing and field mapping explicit in native steps rather than burying them in ad hoc code.
5. If you plan to publish a public Zap Template, test the template path separately from any internal/private workspace build.

Custom App Actions To Provide

- `backstory_list_source_records`
- `backstory_get_record_context`
- `backstory_publish_run_summary`
- `meeting_source_fetch_artifact`

Zaps To Create

- `12_win_loss_debrief_primary_zap` — Trigger: Native CRM app trigger or private custom Zapier app trigger. Native steps: Backstory custom Zapier app action: `fetch_deal_timeline` -> AI step backed by a native LLM app returning strict JSON for AI Debrief Analysis -> Native delivery step: Slack app action for Deliver Debrief. Notes: Keep the primary Zap focused on normalization, source access, and structured synthesis. Route secondary fan-out through additional native Zaps when template restrictions or retry requirements demand decomposition.
- `12_win_loss_debrief_delivery_or_followup_zap` — Trigger: Zapier Tables state change, Interfaces action, or an upstream custom app event. Native steps: Read `delivery_payload` and target metadata from structured fields -> Slack app action: Send Channel Message or Send Direct Message -> Microsoft Teams app action or Microsoft 365 companion action -> Gmail, Outlook, or Email by Zapier action. Notes: Use this secondary Zap when you need reusable delivery fan-out, fallback paths, or approval boundaries without falling back to Webhooks or Code steps.

Contracts To Preserve

- `run_context` : workflow-level execution context such as trigger, mode, lookback, delivery mode, and dry-run state.
- `source_record` : normalized business record from the source adapter or source-system action layer.
- `enrichment_context` : MCP or native app enrichment results used only during synthesis.

- `delivery_payload`: deterministic delivery fields for the final native connector or app action.

Structured AI Requirements

- `ai_debrief_analysis`: return JSON only with keys `title`, `summary`, `confidence`, `recommended_actions`, `source_refs`. Intent: AI Agent analyzes the full timeline, identifies key moments (first exec meeting, proposal sent, competitor mention, engagement gaps), and generates a structured debrief.

Validation Checklist

- Do not treat this guide as an importable JSON workflow; build the workflow as one or more Zaps and, if needed, a custom Zapier app.
- If you want a reusable public Zap Template, only public integrations can be used in the template.
- Do not include Code, custom Webhook, or custom Formatter steps in a public Zap Template.
- If you are creating workflows through Zapier workflow-creation APIs, use Public Apps only and avoid Paths because they are not currently supported there.
- Validate structured AI output before any Slack, Teams, email, calendar, Jira, or sink action runs.

Official References

- [Zap templates restrictions](#)
- [Known limitations for workflow creation](#)
- [Build with CLI](#)
- [Zapier action design](#)
- [Add a create action](#)
- [AI actions](#)
- [Custom actions and API requests actions](#)