

BACKSTORY AUTOMATION CATALOG

Workato implementation guide for the 14-territory-heat-map workflow

Implementation guide · Generated 2026-05-31

Territory Heat Map — Workato Implementation Guide

This file is a plain-English implementation guide. It is not an importable JSON artifact.

Workato moves reusable automation between workspaces as recipe packages, and package import uses a `.zip` file in Recipe Lifecycle Management. Imported connections arrive as placeholders and must be authenticated in the destination workspace. Build this workflow in Workato as recipes, recipe functions, connectors, properties, and tables, then export/import the package when you need to promote it between environments.

Workflow Summary

- Workflow ID: `14-territory-heat-map`
- Category: strategic-intelligence
- Source trigger in this catalog: Schedule — Weekly Monday 6:30 AM |
- Recommended Workato trigger surface: Scheduler by Workato
- Delivery targets: Slack channel or direct message, Microsoft Teams channel or chat, Email delivery

What To Create In Workato

- Backstory custom connector built with the Connector SDK
- Slack connector or Workbot for Slack for channel and DM delivery
- Microsoft Teams connector or Workbot for Microsoft Teams
- Gmail, Microsoft Outlook, or approved email connector for message delivery
- Meeting-system connector or approved custom connector for transcript intake

Build Order

1. Create or choose the target project and folder where this workflow will live.
2. Build or install the Backstory custom connector in Connector SDK. If you have an OpenAPI 3.0 definition, Workato supports using that as a starting point in the Connector SDK.

3. Create the Recipe Function `normalize_run_context` so reusable logic is not trapped inside one large recipe.
4. Create the Recipe Function `load_source_records` so reusable logic is not trapped inside one large recipe.
5. Create the Recipe Function `assemble_business_context` so reusable logic is not trapped inside one large recipe.
6. Create the Recipe Function `render_delivery_payload` so reusable logic is not trapped inside one large recipe.
7. Build the primary recipe `14_territory_heat_map_primary_recipe` with the trigger surface Scheduler by Workato.
8. Store routing defaults, destination IDs, and mode switches in connections, environment properties, project properties, lookup tables, or data tables.
9. Test the recipe and each function with representative payloads, then export the project as a Workato package `.zip` if you need to move it to QA or production.

Recipe Functions To Create

- `normalize_run_context` : Normalize the Territory Heat Map trigger into the shared `run_context` contract. Inputs: `trigger_payload`, workflow defaults. Outputs: `run_context`. Native features: Recipe function by Workato, Formula mode, Variables.
- `load_source_records` : Load and normalize the primary Territory Heat Map business inputs into `source_record` objects. Inputs: `run_context`. Outputs: `source_record[]`. Native features: Recipe function by Workato, Backstory custom connector action, Meeting-system connector action.
- `assemble_business_context` : Join the intermediate context needed for Territory Heat Map, especially Fetch Territory Assignments, Calculate Account Momentum. Inputs: `source_record[]`, `run_context`. Outputs: `source_record[]`, `enrichment_context` candidates. Native features: Lists, Object actions, Recipe data pills.
- `render_delivery_payload` : Render normalized `delivery_payload` objects for Territory Heat Map. Inputs: `structured_ai_json`, `source_record`, `run_context`. Outputs: `delivery_payload`. Native features: Recipe function by Workato, Object construction, Formula mode.

Primary Recipe Outline

1. Call `normalize_run_context`
2. Use Backstory custom connector action for Fetch Territory Assignments
3. Use Backstory custom connector action for Calculate Account Momentum
4. Use an LLM connector or AI step to return strict JSON for AI Territory Summary
5. Use Slack connector for Deliver Heat Map Digest

6. Record deterministic run summary and retry state

Contracts To Preserve

- `run_context` : workflow-level execution context such as trigger, mode, lookback, delivery mode, and dry-run state.
- `source_record` : normalized business record from the source adapter or source-system action layer.
- `enrichment_context` : MCP or native app enrichment results used only during synthesis.
- `delivery_payload` : deterministic delivery fields for the final native connector or app action.

Structured AI Requirements

- `ai_territory_summary` : return JSON only with keys `title`, `summary`, `confidence`, `recommended_actions`, `source_refs`. Intent: AI Agent analyzes the momentum map, identifies the hottest opportunities and coldest risks, and recommends a prioritized focus list for the week.

Validation Checklist

- No repeated Universal HTTP or custom-action sprawl for Slack, calendar, CRM, or email delivery when a native connector exists.
- All secrets live in connections, environment properties, or project properties rather than formula literals.
- LLM or agent output is validated as structured JSON before any delivery or persistence step runs.
- Recipe Functions, lookup tables, and data tables own reuse, routing, and dedupe instead of large inline scripts.
- If this build is moved between workspaces, export and import it as a Workato package `.zip`, then reconnect placeholder connections in the target workspace.

Official References

- [Recipe lifecycle management](#)
- [Importing packages](#)
- [Recipe function by Workato](#)
- [Using the Workato Connector SDK](#)
- [Slack connector](#)
- [Google Calendar connector](#)