SHÜÜT — v1 Build Spec

1. What this is

SHÜÜT is a voice-note-first social feed for London-based startup founders. A founder records a short voice note (max 90 seconds to start), it's automatically transcribed into clean text, and it publishes to a public, chronological feed — transcript as the primary scannable content, with the original audio playable alongside it.

Initial purpose: give London founders the easiest possible way to jam out a raw idea, take, or update by voice — no typing, no editing, no friction — and have it show up as a real post other founders can read or listen to.

v1 goal: validate that founders will (a) record regularly and (b) that other founders will read/listen. Nothing else needs to be true yet.

---

2. Core user flow

1. **Sign up** — email only to start (no Google auth for v1). No onboarding wizard: just name and handle (can be the same) + one-line bio, then straight into the app.
2. **Record** — tap record, speak, hard cap at 90 seconds. No retake before posting — no re-record — but no auto-post either; after recording, the user clicks to post.
3. **Transcribe** — on stop, audio is sent for transcription (ElevenLabs). Clean the raw transcript automatically: strip filler words ("um," "uh," false starts, repeated words), fix obvious punctuation, but preserve the speaker's actual phrasing and voice — this is not a summary, it's a cleaned verbatim transcript.
4. **Publish** — post goes live immediately on submit. A post = transcript text (primary) + inline audio player (secondary) + timestamp + author.
5. **Share prompt (post-publish only)** — immediately after a post goes live, show a share sheet: "Share to X" and "Share to WhatsApp" buttons. Pre-fill the share text with a short excerpt of the transcript (first ~100–120 characters, truncated at a word boundary) + the direct link back to the post on shuut.me. Sharing is optional and happens *after* publish, never before — publishing itself has zero friction.
6. **Feed** — chronological only, all posts from people you follow (plus, since this is a small seed community, consider a single unfiltered "Everyone" tab for v1 so early users can find each other before follow graphs exist). No algorithmic ranking.

7. **Follow / unfollow** — from any profile or post. That's the entire social graph mechanic for v1.
8. **Reshüüt** — from any post, a user can reshüüt it: the original post appears in their own profile and in their followers' feeds, clearly attributed to the original author (original audio + transcript stay intact, not re-recordable or editable by the resharer). No added commentary on a reshüüt for v1 — that's a quote-tweet-equivalent and stays out of scope for now.

---

3. The one differentiator: per-founder "ask me" agent

- Every user has an agent scoped **only** to their own published transcripts — no separate knowledge base upload step in v1.
- On any profile, visitors can ask the agent a question about that founder (e.g. "what does James think about cold starts?").
- The agent answers **grounded only in that user's actual posts**, and every answer links back to the specific source post(s) it drew from. If the agent doesn't have enough posted content to answer, it says so plainly rather than guessing.
- This is the retention hook: more posts → smarter, more useful agent → real incentive to keep recording, independent of follower count or likes (there are none).

---

4. Explicitly out of scope for v1

Do not build any of the following yet — comment out or omit entirely:

- Direct messages
- Notifications beyond a basic "X followed you" alert
- Hashtags or search
- Replies / threading / comments
- Likes, or classic engagement counts — **exception:** the emoji reaction set defined in Section 7 is in scope; it replaces likes rather than adding to them
- Monetization or paywall of any kind (no $3/mo tier yet)
- Native iOS app for the *first* build — see Section 5 on build order

---

5. Suggested tech shape (for Replit build)

Build order: web first. This spec targets a lean full-stack web app; a native iOS build is a planned follow-on, not part of this v1 scope. Keep the backend/data model platform-agnostic (a plain REST/JSON API, no web-only assumptions baked into business logic) so the iOS build can reuse it later without a rewrite.

A reasonable default stack for a Replit build:

- **Frontend:** React (Next.js is fine) — mobile-first responsive layout, since most usage will be on phones at events.
- **Backend/DB/Auth:** Supabase (or Replit's own DB + auth) — handles email auth, Postgres for users/posts/follows/reactions, and storage for audio files in one place.
- **Transcription:** ElevenLabs — needs to return raw transcript fast enough to feel instant (under ~5–10 seconds for a 90-second clip is the target).
- **Transcript cleanup + agent Q&A:** OpenAI via Replit's integration — one call to clean the raw transcript into publish-ready text, and a separate lightweight retrieval step (pull that user's transcripts, pass as context) to answer agent questions.
- **Audio storage:** object storage (Supabase Storage or S3-compatible) — store the raw audio file, serve via signed/public URL from the post.

Data model (minimum)

- `users`: id, name, handle, bio, email, created_at
- `posts`: id, user_id, audio_url, transcript_raw, transcript_clean, created_at
- `follows`: follower_id, followed_id
- `reshuuts`: id, user_id, original_post_id, created_at
- `reactions`: post_id, user_id, emoji_type (one of: goat, rocket, laughing_crying, confused, thumbs_down), created_at — one reaction per user per post, changeable but not stackable
- Agent Q&A can run at query time directly against a user's `posts.transcript_clean` rows — no separate vector store needed at this scale; revisit if/when post volume makes that slow.

---

6. Sharing to X / WhatsApp — behavior detail

- Trigger: appears once, immediately after a post successfully publishes. Also available later from the post itself (small share icon), in case someone wants to re-share an older post.
- X: open a pre-filled tweet composer (via X's web intent URL) with the excerpt + link. Don't post on the user's behalf — they review and send from X's own UI.

- WhatsApp: open WhatsApp's `wa.me` share link with the same pre-filled text, letting the user pick who/which chat to send to.
- No auto-posting, no stored API credentials for either platform in v1 — both are just pre-filled deep links, which keeps this a same-day build with no OAuth work.

---

7. Decisions locked

- **Transcription:** ElevenLabs (existing credits available).
- **LLM (cleanup + agent Q&A):** OpenAI via Replit's built-in integration.
- **"Everyone" unfiltered feed tab:** included in v1 — recommended given a cold-start seed audience with few mutual follows yet.
- **Moderation / engagement mechanism:** an emoji reaction set replaces both moderation-by-absence and classic likes — 🐐 (goat), 🚀 (rocket), 😂 (laughing/crying), 😕 (confused), 👎 (thumbs down). One reaction per user per post. This is not a reporting/flagging tool on its own — 👎 signals disagreement or a miss, not abuse. **Still open:** whether a high volume of 👎 on one post should trigger any action (visibility reduction, review queue) or remain purely informational. Recommend deciding this before launch rather than after the first contentious post.

-