

Getting Started with R

James Ashby

2026-09-30

Goals

1. Load the packages we need
2. Load a data file

If this document renders without errors, your setup works.

Click **Render** at the top of this pane to run everything. To run one chunk at a time, click the green arrow at its top right.

Background reading: [Experimentology](#), [Appendix C](#).

(1) Load packages

Run this once, by hand, if you have never installed these. It is set to `eval: false` so it does not run every time you render.

```
install.packages(c("tidyverse", "here"))
```

```
library(tidyverse)
library(here)
```

(2) Load the data

`here()` builds file paths starting from the top of your project — the folder holding `getting-started-with-r.Rproj`. That is why you open the project by double-clicking the `.Rproj` file, and why you never need `setwd()`.

```
here()
```

```
[1] "/Users/jamesashby/Documents/GitHub/R-Tutorial"
```

Paths built this way work on any computer, and keep working if you later move this file into a subfolder.

```
rt_data <- read_csv(here("data", "example_rt_data.csv"), show_col_types = FALSE)

glimpse(rt_data)
```

```
Rows: 48
```

```
Columns: 5
```

```
$ participant <chr> "s01", "s01", "s02", "s02", "s03", "s03", "s04", "s04", "s~
$ age_group  <chr> "child", "child", "adult", "adult", "child", "child", "adu~
$ condition  <chr> "congruent", "incongruent", "congruent", "incongruent", "c~
$ rt_ms      <dbl> 800, 976, 496, 582, 803, 924, 401, 609, 690, 808, 515, 627~
$ accuracy   <dbl> 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 0, 1, 1, 1, 1~
```

Simulated reaction times from a made-up Stroop-like task: `participant`, `age_group` (child/adult), `condition` (congruent/incongruent), `rt_ms`, and `accuracy` (1 = correct).

If you see 48 rows above, you are set up correctly.