

Introduction	Motivation	Time Series	Modeling Methodology	Data Methodology	Results	Conclusions	References
0000	0000	0000000000	0000	00000000	000000000000	00	

Using Time Series Models for Defect Prediction in Software Release Planning

James Tunnell
Central Washington University
Computational Science Program

March 30, 2015

Introduction	Motivation	Time Series	Modeling Methodology	Data Methodology	Results	Conclusions	References
0000	0000	0000000000	0000	00000000	000000000000	00	

Outline

- 1 Introduction
- 2 Motivation
- 3 Time Series
- 4 Modeling Methodology
- 5 Data Methodology
- 6 Results
- 7 Conclusions
- 8 References

Introduction	Motivation	Time Series	Modeling Methodology	Data Methodology	Results	Conclusions	References
0000	0000	0000000000	0000	00000000	000000000000	00	

Introduction

Introduction	Motivation	Time Series	Modeling Methodology	Data Methodology	Results	Conclusions	References
●000	0000	0000000000	0000	00000000	000000000000	00	

Release Planning Objectives

- Two primary objectives of software release planning are:
 - Improving functionality
 - Maintaining quality
- Both of these objectives are constrained by limits on development time and cost.

Introduction	Motivation	Time Series	Modeling Methodology	Data Methodology	Results	Conclusions	References
●●00	0000	0000000000	0000	00000000	000000000000	00	

Quality Control

- Software defects (bugs) are inevitable
- Sufficient time should be available to ensure good quality (by testing and bug-fixing)
- Otherwise, there is a risk of
 - Low quality (failure to meet objective)
 - Schedule slip (failure to respect constraint)
- This quality control (QC) time can be allowed for by limiting the scope of work in the planned release

Introduction	Motivation	Time Series	Modeling Methodology	Data Methodology	Results	Conclusions	References
●●●0	0000	0000000000	0000	00000000	000000000000	00	

Quality Control (cont'd)

- To support release planning, QC time can be estimated
- Assumption: QC time depends (at least partly) on the number of software defects introduced
- Then, a basis for estimating QC time would be the predicted number of defects

Introduction
Motivation
Time Series
Modeling Methodology
Data Methodology
Results
Conclusions
References

Defect Prediction

- Approaches to defect prediction tend to focus on either
 - Code analysis
 - Lines of code
 - Number of decisions
 - Code churn
 - Historical information
 - Regression analysis
 - Time series modeling
- A multivariate time series model with exogenous inputs was chosen

Introduction
Motivation
Time Series
Modeling Methodology
Data Methodology
Results
Conclusions
References

Motivation

Introduction
Motivation
Time Series
Modeling Methodology
Data Methodology
Results
Conclusions
References

Release Plan Optimization

- A release plan is formed by selecting features and improvements to work on
- Release plans can be compared by the expected revenue they will generate
- This optimization problem is posed as The Next Release Problem (NRP)

Introduction
Motivation
Time Series
Modeling Methodology
Data Methodology
Results
Conclusions
References

Release Plan Optimization (cont'd)

- The NRP is an abstract optimization problem
- In practice, QC time should be considered to ensure constraints are respected
- With the help of a defect prediction model, QC time can be estimated
- In this context, release plans are being compared
- For a defect prediction model to be useful, it should depend in some way on the basic elements of the release plan (planned new features and improvements)

Introduction
Motivation
Time Series
Modeling Methodology
Data Methodology
Results
Conclusions
References

Explanatory Model

- Assumption: the number of defects in the future depends on more than just the number of defects in the past
- A defect prediction model that depends only on previous numbers of defects is not explanatory
- Such a non-explanatory model would always predict the same number of defects

```

graph TD
    RP1[Release Plan 1] --> NEM[Non-explanatory Model]
    RP2[Release Plan 2] --> NEM
    Dots[...] --> NEM
    RPN[Release Plan N] --> NEM
    NEM --> PD[Predicted Defects]
  
```

Figure : A non-explanatory model.

Introduction
Motivation
Time Series
Modeling Methodology
Data Methodology
Results
Conclusions
References

Explanatory Model (cont'd)

- A model could also depend on the key factors of a release plan
- This would be an explanatory model structure
- Such a model can potentially predict a different number of defects for every release plan

```

graph TD
    RP1[Release Plan 1] --> EM[Explanatory Model]
    RP2[Release Plan 2] --> EM
    Dots[...] --> EM
    RPN[Release Plan N] --> EM
    EM --> PD1[Predicted Defects 1]
    EM --> PD2[Predicted Defects 2]
    EM --> Dots2[...]
    EM --> PDN[Predicted Defects N]
  
```

Figure : An explanatory model.

Introduction 0000	Motivation 0000	Time Series 0000000000 0000	Modeling Methodology 0000	Data Methodology 00000000	Results 000000000000 00	Conclusions	References
----------------------	--------------------	---------------------------------------	------------------------------	------------------------------	----------------------------	-------------	------------

Time Series Modeling

Introduction 0000	Motivation 0000	Time Series ●00000000 0000	Modeling Methodology 0000	Data Methodology 00000000	Results 000000000000 00	Conclusions	References
----------------------	--------------------	--------------------------------------	------------------------------	------------------------------	----------------------------	-------------	------------

Time Series

- A time series is a collection of observations that occur in order
- The process underlying a time series is assumed to be stochastic (non-deterministic)
- Each observation might depend on one or more previous observations
- This dependence is termed *autocorrelation*

Introduction 0000	Motivation 0000	Time Series ●00000000 0000	Modeling Methodology 0000	Data Methodology 00000000	Results 000000000000 00	Conclusions	References
----------------------	--------------------	--------------------------------------	------------------------------	------------------------------	----------------------------	-------------	------------

Autoregressive Models

- A basic autoregressive (AR) model is a linear combination of previous values
- A white noise term accounts for stochastic fluctuation
- An $AR(p)$ model for predicting a value X at time t is

$$X_t = c + \sum_{i=1}^p \phi_i X_{t-i} + \epsilon_t \quad (1)$$

where $\phi_1, \phi_2, \dots, \phi_p$ are the p parameters, c is a constant, and ϵ_t is the white noise term

Introduction 0000	Motivation 0000	Time Series ●00000000 0000	Modeling Methodology 0000	Data Methodology 00000000	Results 000000000000 00	Conclusions	References
----------------------	--------------------	--------------------------------------	------------------------------	------------------------------	----------------------------	-------------	------------

Autoregressive Models (cont'd)

- Extending the AR model to be multivariate results in a Vector AR (VAR) model
- This model can support time series for defect count, improvements, and new features

Introduction 0000	Motivation 0000	Time Series 000●000000 0000	Modeling Methodology 0000	Data Methodology 00000000	Results 000000000000 00	Conclusions	References
----------------------	--------------------	---------------------------------------	------------------------------	------------------------------	----------------------------	-------------	------------

Endogeneity and Exogeneity

Endogeneity

- Under a VAR model, the behavior of each time series is explained by both its own past values and the past values of the other time series
- This makes the variables *endogenous*

Exogeneity

- An alternative to this is when a variable is not explained at all by a model
- Rather, the variable is used to explain other time series
- This type of explanatory variable is called *exogenous*

Introduction 0000	Motivation 0000	Time Series 000●000000 0000	Modeling Methodology 0000	Data Methodology 00000000	Results 000000000000 00	Conclusions	References
----------------------	--------------------	---------------------------------------	------------------------------	------------------------------	----------------------------	-------------	------------

Endogeneity and Exogeneity (cont'd)

- The desired model does not need to explain features and improvements
- Instead, these are used to explain defects
- Planned features and improvements can be made exogenous
- By also considering exogenous variables, a VAR model would become a VARX model

- A stationary time series has time-invariant statistics

- Stationary can be determined by testing for trends

- A time series with a deterministic trend has a non-constant mean

- Such a time series is said to be stationary around a deterministic trend




Figure : Time series with a deterministic trend.

- A stochastic trend shows permanent effects due to random variations

- Differencing can be used to remove a stochastic trend




Figure : Time series with a stochastic trend.

- A pure AR model of a time series with stochastic trend contains a unit

- A unit-root test starts with the null hypothesis that an AR model has a

- On the other hand is a stationarity test

- If the test statistic is above some significance level, this shows that the

Modeling Methodology

Introduction

Motivation

Time Series

Modeling Methodology

Data Methodology

Results

Conclusions

References

0000

0000

0000000000

0000

00000000

000000000000

00

Data Collection

- *MongoDB* uses *JIRA* for issue tracking and project management
- Issue data was exported from the project's JIRA web interface as XML data
- Issue data was extracted from the XML, and the following fields were kept:
 - Creation date
 - Resolution date
 - Type
 - Priority

Introduction

Motivation

Time Series

Modeling Methodology

Data Methodology

Results

Conclusions

References

0000

0000

0000000000

0000

00000000

000000000000

00

Data Cleansing

- Not all of the data was preserved for modeling
- No-change issues
 - Only issues with resolution *fixed*, *complete*, or *done* were kept
 - Other issues did not result in any change, and were not included
- Orphan sub-tasks
 - Issues that are sub-tasks are first converted to be the same type as the parent issue
 - Sub-tasks whose parent issue is not in the dataset are considered orphans, and discarded
 - Orphan sub-tasks can not be identified as improvement or new feature
 - 20 (0.28%) orphaned sub-tasks were in the dataset

Introduction

Motivation

Time Series

Modeling Methodology

Data Methodology

Results

Conclusions

References

0000

0000

0000000000

0000

00000000

000000000000

00

Data Sampling

- The dataset was operated on to prepare it for time series modeling
- First, data was sampled at regular intervals, measuring
 - Number of bugs created
 - Number of improvements resolved
 - Number of new features resolved
- A 7-day sampling period was used

Introduction

Motivation

Time Series

Modeling Methodology

Data Methodology

Results

Conclusions

References

0000

0000

0000000000

0000

00000000

000000000000

00

Data Sampling (cont'd)

Figure : Sampling example issue data.

Period	Improvements Resolved	New Features Resolved	Bugs Created
1	0	0	1
2	1	1	1
3	1	0	1

Table : Results of sampling example issues.

Introduction

Motivation

Time Series

Modeling Methodology

Data Methodology

Results

Conclusions

References

0000

0000

0000000000

0000

00000000

000000000000

00

Establishing Stationarity

- Establish stationarity by testing
 - ADF unit root test
 - KPSS stationariy test
- If test results agree, then no differencing is necessary
- Otherwise, difference data and retest

Introduction

Motivation

Time Series

Modeling Methodology

Data Methodology

Results

Conclusions

References

0000

0000

0000000000

0000

00000000

000000000000

00

Time Windowing

- Assumption: the software development process underlying a given project might change over time
- The VARX model does not accommodate a changing process
- To account for a changing process, data will be time windowed
- Data will be used for modeling only if it occurs within the time window
- This should limit the amount of process change the model is exposed to

Introduction
Motivation
Time Series
Modeling Methodology
Data Methodology
Results
Conclusions
References

Results

Introduction
Motivation
Time Series
Modeling Methodology
Data Methodology
Results
Conclusions
References

MongoDB Time Series Data

Time series data was obtained by sampling the *MongoDB* dataset with a 7-day sample period




Figure : MongoDB time series data

Introduction
Motivation
Time Series
Modeling Methodology
Data Methodology
Results
Conclusions
References

Stationarity & Differencing

- At first, ADF and KPSS test results disagreed
- After differencing, test results agreed




Figure : MongoDB time series data after differencing

Introduction
Motivation
Time Series
Modeling Methodology
Data Methodology
Results
Conclusions
References

Time Windowing

- A 78-week time window (approximately 18 months) was chosen
- Three of these windowed periods, non-overlapping, were used for modeling
- Since the data is being differenced, the first sample (week) is skipped
- These windowed periods are denoted W_{2-79} , W_{80-157} , and $W_{158-235}$
- Modeling methodology is applied to each

Introduction
Motivation
Time Series
Modeling Methodology
Data Methodology
Results
Conclusions
References

Model Specification, Estimation, and Diagnostic Checking

- Using $K_{min} = 4$, maximum model order is obtained by
$$p_{max} = \left\lfloor \frac{78}{(3)(4)} \right\rfloor = [6.5] = 6 \quad (3)$$
- Models of order 1 through $p_{max} = 6$ were estimated for diagnostic checking
- All models were found to be stable
- Several model orders were found to be inadequate by the Ljung-Box test:
 - Orders 1-2 for period W_{2-79}
 - Order 5 for period $W_{158-235}$

Introduction
Motivation
Time Series
Modeling Methodology
Data Methodology
Results
Conclusions
References

Model Selection

- Models found to be stable and not inadequate were considered for selection
- A different model was selected for each windowed period
- Lower AIC score is better

Model order	AIC score		
	W_{2-79}	W_{80-157}	$W_{158-235}$
1	N/A	429.8	477.9
2	N/A	439.3	482.4
3	400.8	440.9	489.7
4	400.3	450.2	499.9
5	404.0	456.7	N/A
6	414.9	461.7	508.8

Table : Results of model selection, using AIC score to compare models of different order.

Introduction
Motivation
Time Series
Modeling Methodology
Data Methodology
Results
Conclusions
References

0000
0000
0000000000
0000
00000000
00000000
000000000000
00

One-step Predictions

The fit for each selected model is demonstrated by plotting one-step predictions along with actual values.

Figure : Actual values (solid) vs. one-step predictions (dotted), for each model selected by AIC score.

Introduction
Motivation
Time Series
Modeling Methodology
Data Methodology
Results
Conclusions
References

0000
0000
0000000000
0000
00000000
00000000
000000000000
00

Forecasting Results

- A range of hypothetical future values for improvements and new features were used to make defect predictions
- This simulates the use of defect prediction for release planning
- Single-step, out-of-sample forecast
- Inputs were differenced, and difference was removed from output
- Results include 75% and 90% confidence intervals
- Forecast results are shown only for the first time window, W_{2-79}

Introduction
Motivation
Time Series
Modeling Methodology
Data Methodology
Results
Conclusions
References

0000
0000
0000000000
0000
00000000
00000000
000000000000
00

Forecasting Results (cont'd)

- The actual number of improvements and features was 4 and 0
- Actual number of bugs was 18
- For the actual input values, the 90% confidence interval does not include 18

Table : Forecasting at the end of the first time window, W_{2-79} .

Improvements	Features	90% low	75% low	Mean	75% high	90% high
2	0	5.61	6.72	9.31	11.89	13.00
2	1	5.54	6.66	9.24	11.82	12.93
2	2	5.48	6.59	9.17	11.75	12.86
2	3	5.41	6.52	9.1	11.69	12.8
4	0	6.4	7.51	10.09	12.68	13.79
4	1	6.33	7.44	10.03	12.61	13.72
4	2	6.27	7.38	9.96	12.54	13.65
4	3	6.2	7.31	9.89	12.48	13.59

Introduction
Motivation
Time Series
Modeling Methodology
Data Methodology
Results
Conclusions
References

0000
0000
0000000000
0000
00000000
00000000
000000000000
00

Forecasting Results (cont'd)

- Low accuracy for the predictions is concerning
- For the next window, W_{80-157} , the actual number of future bugs was 17
- This was inside the 90% confidence interval, which spanned from 13.38 to 18.00
- This result conflicts with that of the previous window

Introduction
Motivation
Time Series
Modeling Methodology
Data Methodology
Results
Conclusions
References

0000
0000
0000000000
0000
00000000
00000000
000000000000
00

Sliding Window Forecasts

- How useful is the VARX model in general, considering these conflicting results?
- To find out, a sliding 78-week window was used
- The sliding window started at the first sample period, and was shifted by one sample period after modeling
- Only the actual number of improvements and features were used in this forecasting

Introduction
Motivation
Time Series
Modeling Methodology
Data Methodology
Results
Conclusions
References

0000
0000
0000000000
0000
00000000
00000000
000000000000
00

Sliding Window Forecasts (cont'd)

- Errors between the mean forecasted and actual number of bugs is shown as a histogram
- The histogram appears to be normally distributed (good)
- The variability is quite large (bad)
- The actual number of bugs was inside the 90% confidence interval for 23.87% of the sliding window ranges

Figure : Histogram of errors in forecast mean obtained using a 78-week sliding window.




Conclusion & Future Work

- The VARX modeling methodology was successfully applied to the time series data collected from the *MongoDB* project
- Models were created for each of three time windows
- A model was selected for each window
- Forecast results using the models were inconclusive
- A better picture of the prediction performance was obtained using a sliding window
- This resulted in a normally distributed error in the mean forecasted values
- A low proportion (23.87%) of the sliding window ranges included the actual number of bugs in the 90% confidence interval
- These results may indicate that a VARX model will not be useful to make predictions for the the MongoDB dataset



Future Work

Having applied the VARX time series model to one project dataset, a next step is to apply the methodology to other software project data sets, such as *Eclipse* or *Mozilla*, to more conclusively determine the model's usefulness.

References II

-  J. E. Gaffney.
Estimating the number of faults in code.
Software Engineering, IEEE Transactions on,
SE-10(4):459–464, July 1984.
-  S. Henry and D. Kafura.
The evaluation of software systems' structure using
quantitative software metrics.
Software: Practice and Experience, 14(6):561–573, 1984.
-  P. L. Li, M. Shaw, J. Herbsleb, B. Ray, and P. Santhanam.
Empirical evaluation of defect projection models for
widely-deployed production software systems.
SIGSOFT Softw. Eng. Notes, 29(6):263–272, Oct. 2004.

References III

-  N. Nagappan and T. Ball.
Use of relative code churn measures to predict system defect density.
In *Software Engineering, 2005. ICSE 2005. Proceedings. 27th International Conference on*, pages 284–292. IEEE, 2005.
-  L. L. Singh, A. M. Abbas, F. Ahmad, and S. Ramaswamy.
Predicting software bugs using arima model.
In *Proceedings of the 48th Annual Southeast Regional Conference*, page 27. ACM, 2010.