

EECS 484 Winter 2019: Project 4

Import and Query MongoDB Database

Due on Apr. 19th, 2019 by 11:55PM

Late day policy refer to Grading policies at the end of the spec

Overview

In this project, we will be using the same dataset as in Project 2 FakeBook and explore the capability of MongoDB (NOSQL). You will first export FakeBook Database to JSON format using JDBC, and then implement nine MongoDB queries in JavaScript. This spec will give you an introduction to MongoDB syntax.

1. The Environment

You have to work in CAEN environment for **Part A: Export Oracle Database to JSON**. Because our Oracle Database server is only accessible from the University of Michigan network, you need to either be on-campus, or connected to [UM VPN](#) whenever you run the program.

For **Part B: MongoDB Queries**, we have set up MongoDB account in CAEN for every student registered in this class. To login, refer to section 4 instruction.

If you choose to install MongoDB on your personal computer, refer to the MongoDB installation document for instructions. You can connect to `eeecs484.eecs.umich.edu` server from your PC only when you are on-campus or connected to [UM VPN](#). Make sure to test your code on CAEN environment before submission.

2. Files Provided to You

On Canvas you will find `startfile.tar.gz` containing files provided to you for project4.

To complete **Part A: Export Oracle database to JSON**, start with the 2 Java files: `Main.java` and `GetData.java`. We have also provided 3 jar packages: `ojdbc6.jar`, `json_simple-1.1.jar`, `json-20151123.jar`. Put all the above files in the same folder with `Makefile`.

To complete **Part B: MongoDB Queries**, set up your MongoDB database using `Makefile`. Implement MongoDB query in 8 JavaScript files `query1.js` to `query8.js`. The file `test.js` can be used to check partial correctness of your query results.

1) Main.java

This file provides the main function for running Part A. You can use it to run your program, but you don't need to turn it in.

Please only modify the `oracleUserName` and `password` static variables, replacing them with your own Oracle username and password.

```
13 public class Main {
14
15     static String dataType = "PUBLIC";
16     static String oracleUserName = "username"; //replace with your Oracle account name
17     static String password = "password"; //replace with your Oracle password
```

2) GetData.java

This file contains the function you need to implement for Part A. Query USERS, FRIENDS, CITIES tables to export data from Oracle Database to JSON format. An output file named `output.json` should be generated in the folder where your Java files are. Your `output.json` is expected to contain the same data, but can be in entirely different order from `sample.json`. An introduction to JSON format is covered in the spec for Part A.

3) Makefile

To compile, execute `make` in the terminal. Or you can use the following command:

```
javac -Xlint:-unchecked -cp
"ojdbc6.jar:json-20151123.jar:json_simple-1.1.jar:" Main.java
GetData.java
```

To run, execute `make run` in the terminal. Or you can use the following command:

```
java -cp "ojdbc6.jar:json-20151123.jar:json_simple-1.1.jar:" Main
```

To setup or clear MongoDB database for Part B, please substitute `<uniquename>` and `<password>` with your MongoDB account information (NOT UM account) in `Makefile`. **The**

default MongoDB password is your username. Please login and change your password following Section 4 Part B instructions.

To prepare tar.gz file for submission, execute `make submit` via the terminal.

4) sample.json

This file contains the JSON data from running our official implementation of GetData. Please DO NOT `diff output.json sample.json` because JSON arrays are likely to come in entirely different order between any two runs.

Part A and Part B in this project do not have dependencies on each other. You may setup your database for Part B using `sample.json` to test MongoDB queries. The AutoGrader testing on Part B **does not** rely on correct results from Part A.

5) test.js

In Part B, you will implement 8 queries in the given JavaScript files. The file `test.js` contains one **simple** test on each of the query. You may use it to check **partial correctness** of your implementation. Notice an output saying “test1 correct!” does not assure your query1 will score full on the AutoGrader. Use `Make mongoquerytest` to feed the test file into MongoDB, or put the following command into a CAEN terminal (use your mongodb account and password):

```
mongo <username> -u <username> -p <password> --host  
eecs484.eecs.umich.edu < test.js
```

3. Part A: Export Oracle database to JSON

1) Introduction to JSON

JSON (JavaScript Object Notation) is a key-value representation, in which values can also be JSON objects. Different from `std::map` in C++, the values does not have to be consistent in terms of data types. Here is an example of JSON object (initialized in JavaScript):

```
var student1 = {"Name": "John Doe", "Age": 21, "Major": ["CS", "Math"]}
```

Name, Age and Major are the keys. Their corresponding values are string, integer and array of strings. An example of calling certain field of value is shown below:

```
student1[ "Name"];           // gives John Doe
```

With multiple JSON objects, we can create a JSON array in JavaScript:

```
var students = [  
    {"Name": "John Doe", "Age": 21, "Major": ["CS", "Math"]},  
    {"Name": "Richard Roe", "Age": 22, "Major": ["CS"]},  
    {"Name": "Joe Public", "Age": 21, "Major": ["CE"]}];  
students[0][ "Name"];        // gives John Doe
```

2) Export to JSON

From Project 2 FakeBook Database, you need to use JDBC to query USERS, FRIENDS, CITIES and other relevant tables to export comprehensive information on each user. The results should be a JSONArray `users_info`, containing 800 JSONObject for 800 users. It is suggested that you use multiple queries to achieve all the information. Each JSONObject should include:

- user_id
- first_name
- last_name
- gender
- YEAR_OF_BIRTH
- MONTH_OF_BIRTH
- DATE_OF_BIRTH
- hometown (JSONObject) that contains:
 - city
 - state

```
{  
  "first_name": "Frodo",  
  "friends": [  
    184,  
    214,  
    240,  
    242,  
    244,  
    255  
  ],  
  "hometown": {  
    "state": "Gondor",  
    "country": "Middle Earth",  
    "city": "Edhellond"  
  },  
  "current_city": {  
    "state": "Gondor",  
    "country": "Middle Earth",  
    "city": "Edhellond"  
  },  
  "DOB": 28,  
  "MOB": 12,  
  "last_name": "Baggins",  
  "gender": "male",  
  "YOB": 547,  
  "user_id": 163  
}
```

- Country
- current_city (JSONObject) that contains:
 - city
 - state
 - Country
- friends (JSONArray) that contains: all of the user_ids of users who are friends with the current user, and has larger user_id than the current user

Note: It is possible that a user might have no information regarding his\her hometown or current city in our database. In this case **put an empty JSONObject({})** as value under key “hometown” or “current_city”

See the file `sample.json` for an example valid output.

4. Part B: MongoDB Queries

1) Introduction to MongoDB

MongoDB is a document-oriented database program. It's comparable to SQL Oracle Databases in many aspects. Each document in MongoDB is one JSON object, with key-value pairs of data, just like a tuple in SQL has fields of data; each collection in MongoDB is one JSON array of multiple JSON objects, just like a table/relation in SQL has multiple tuples. Refer to the following table for concepts of document and collection in MongoDB, as well as queries to select certain columns and rows.

SQL	MongoDB
Tuple	Document. JSON object
Relation/Table	Collection. Initialized using a JSON array
SELECT * FROM users;	db.users.find();
SELECT * FROM users WHERE name = 'John' and age = 50;	db.users.find({name: 'John', age: 50});
SELECT user_id, addr FROM users WHERE name = 'John';	db.users.find({name: 'John', {user_id: 1, addr: 1, _id: 0}});

<https://docs.mongodb.com/manual/reference/sql-comparison/> is a document comparing MongoDB with SQL.

2) Log in to MongoDB

To perform the MongoDB queries, you will need to login to Mongo Shell. The following instructions apply to CEAN environment. **The default MongoDB password is your username.**

```
$ module load mongodb/3.6.8
```

This command allows you to connect to our mongodb server hosted on `eecs484.eecs.umich.edu` via mongo shell in you CAEN computer.

```
$ mongo <username> -u <username> -p <password> --host  
eecs484.eecs.umich.edu
```

You can update password with the following command:

```
> db.updateUser("<username>", {pwd : "<newpassword>"})
```

The new password takes effect when you logout (Ctrl+D).

3) Import JSON to MongoDB

Open the terminal in the folder where you have `sample.json` and/or `output.json` and `Makefile`. Remember to load module each time you open a new terminal to perform any MongoDB operations. Modify `Makefile` with your updated **MongoDB account** information and put `make setupsampled` in the terminal to load database from `sample.json`, or `make setupmydb` to load database from your `output.json`.

Alternatively, put one of the following commands in the terminal:

```
$ mongoimport --host eeecs484.eecs.umich.edu --username <username>  
--password <password> --collection users --db <username> --file  
sample.json --jsonArray
```

```
$ mongoimport --host eecs484.eecs.umich.edu --username <username>
--password <password> --collection users --db <username> --file
output.json --jsonArray
```

Please do not modify the `-collection users` field.

On success, you should have imported 800 user documents. **Notice `mongoimport` command is accumulative, meaning you will have another 800 user objects imported next time you use `mongoimport`.** To clear up data in the database, use `make dropdatabase` to drop.

There's no need to repetitively load and drop database for each query.

4) Queries

Query 1: Townsman

In this query, we want to find all users whose hometown city is the specified 'city'. The result is to be returned as a JavaScript array of `user_ids`, in which the order of `user_ids` does not matter.

You may find `cursor.forEach()` helpful:

<https://docs.mongodb.com/v3.0/reference/method/cursor.forEach/>

Query 2: flat_users

In Part A, we have created a `friends` array using JDBC. Each user (JSON object) has `friends` (JSON array) that contains all `user_ids`, who are friends to the current user and has a larger `user_id`. In this query, we want to restore the friendship information to pairs.

Create a collection called `flat_users`. Documents in the collection follow the schema:

```
{"user_id": xxx, "friends": xxx}
```

For example, if we have the following user in the `users` collection:

```
{"user_id": 100, "first_name": "John", ... "friends": [ 120, 200, 300 ]}
```

The query would produce 3 documents (JSON objects) and keep them in the collection

`flat_users`:

```
{"user_id": 100, "friends": 120},
```

```
{"user_id": 100, "friends": 200},
```

```
{"user_id": 100, "friends": 300},
```

You do not need to return anything for this query.

Hint: You may find this link on MongoDB \$unwind helpful:

<https://docs.mongodb.org/manual/reference/operator/aggregation/unwind/>

You may use \$project and \$out to create the collection, or you may insert tuples into flat_users iteratively.

Query 3: Hometown Cities collection

Similar to query 1, we want to create a collection named cities. Each document in the collection should contain two fields: _id field holding the city name, and users field holding an array of user_ids who live in that city.

For example, if users 10, 20 and 30 live in Bucklebury, the following document will be in the collection cities:

```
{"_id": "Bucklebury", "users": [ 10, 20, 30]}
```

You should not return anything for this query.

Query 4: Suggest friends

Find all user_id pairs (A, B) that meet the following requirements:

- i. user A is a male and user B is a female
- ii. their Year_Of_Birth difference is less than year_diff, an argument passed in to the query
- iii. user A and user B are not friends
- iv. user A and user B are from the same city

Your query should return a JSON array of pairs; each pair is an array with two user_ids.

Hint: You may use cursor.forEach() useful.

You may use `array.indexOf()` in JavaScript to check for the non-friend constraints.

```
16 function suggest_friends(year_diff, dbname) {
17     db = db.getSiblingDB(dbname);
18     var pairs = [];
19     // TODO: implement suggest friends
20     // Return an array of arrays.
21     return pairs;
22 }
23
```

Query 5: Find the oldest friend

Find the oldest friend for each user who has friends. For simplicity, use only year of birth to determine age. In case of a tie, return the friend with smallest `user_id`.

Notice in the `users` collection, each user has only information on friends whose `user_id` is greater than his/hers. You will need to consider all existing friendships. The idea of Query2 and 3 may be useful.

Your query should return a JSON object: key is the `user_id` and the value is his/her oldest friend's `user_id`. The order does not matter. The schema should look like the following:

{ `user_id1`: `user_idx`, `user_id2`: `user_idxxx`, ... }

The number of keys should equal the number of users who have friends.

```
9 function oldest_friend(dbname){
10     db = db.getSiblingDB(dbname);
11     var results = {};
12     // TODO: implement oldest friends
13     // return an javascript object described above
14     return results
15 }
16
```

Query 6: Find average friend count

Find the average number of friends a user owns in the `users` collection and return a decimal number. The average friend count on users should take into consideration those who have 0 friends. In order to make this easier, we're treating the number of friends that a user has as equal to the number of friends in their friend list (we aren't counting users with lower ids, since they aren't in the friend list). DO NOT round the result to an integer.

```

6  function find_average_friendcount(dbname){
7      db = db.getSiblingDB(dbname)
8      // TODO: return a decimal number of average friend count
9  }
10

```

Query 7: Find count of user born in each months using MapReduce

MapReduce is a powerful yet simple parallel data processing paradigm. We have set up the MapReduce calling point in the test.js and you need to implement the mapper, reducer and finalizer.

In this query, we are asking you to use MapReduce to find the number of users born in each month. **Hint:** You need to emit a JSON object from your mapper and return a JSON object of the exact same form from your reducer.

Note that after running test.js, running `db.born_each_month.find()` in Mongo Shell allows you to bring up the collection with users born in each month. For example, if there are 200 users born in September, the document below would be in the collection:

```
{ "_id": 9, "value": 200 }
```

You may find the following document helpful: <https://docs.mongodb.com/v3.2/core/map-reduce/>

Query 8: Find city-average friend count using MapReduce

In this query, we are asking you to use MapReduce to find average friend count per user where the users belong to the same city. Instead of getting only one number for all users' average friend count, we will get have an average friend count for each hometown city.

Hint: You need to emit a JSON object from your mapper and return a JSON object of the exact same form from your reducer. The average calculation should be performed in the finalizer.

```

6  var city_average_friendcount_mapper = function() {
7    // implement the Map function of average friend count
8  };
9
10 var city_average_friendcount_reducer = function(key, values) {
11   // implement the reduce function of average friend count
12 };
13
14 var city_average_friendcount_finalizer = function(key, reduceVal) {
15   // We've implemented a simple forwarding finalize function. This implementation
16   // is naive: it just forwards the reduceVal to the output collection.
17   // Feel free to change it if needed. However, please keep this unchanged:
18   // the var ret should be the average friend count per user of each city.
19   var ret = reduceVal;
20   return ret;
21 };
22

```

Note that after running test.js, running `db.friend_city_population.find()` in Mongo Shell allows you to bring up the collection with per city average friend count. For example, if Bucklebury has average friend count 15.23, the document below would be in the collection:

```
{ "_id": "Bucklebury", "value": 15.23 }
```

5. Submission and Grading

To submit on AG, join a team first and then run `make submit` to generate a `project4.tar.gz`. Ensure that the tar.gz file contains all of the following files and no others:

1. `GetData.java`
2. `query[1-8].js`

Grading policies:

Late day policy:

Project 4 is due on Apr. 19th, 2019 at 11:55 pm EST. If you do not turn in your project by this date, or you are unhappy with your work, you may re-submit until 4 days after the due date. Each late day (or part thereof) on which you submit incurs a 1% deduction to your **overall course grade** at the end of the semester. These deductions are cumulative for all course projects, and the first two deductions (overall, not per project) will be reprieved.

- If you **fail to join your group before submitting to the grading system**, we will assume that you are submitting on your own and any resemblance to others' solutions will be considered ***violation of the honor code***, which will be reported, and you will ***get 0 points*** in the project.