

Stop: no block-pass meets the frozen canopy-span floor

RULING — Do not begin Gate A from the current package. Across five selected native-grid passes, 13,210 block-passes have at least 60 complete cells, but 0 reach the frozen 0.20 canopy p10–p90 span. No Stage-1 coefficient, spatial SE, or required-N value is estimable.

Five selected passes

Pass	Complete native cells	Candidate block-passes	Converged	Stable
phoenix:27963	632,264	2,760	0	0
phoenix:28024	639,363	2,651	0	0
phoenix:28706	684,388	2,807	0	0
phoenix:28828	684,389	2,807	0	0
phoenix:28909	493,309	2,185	0	0

Why the model stopped

The pass selection and all thresholds were frozen in D011 before the run. Candidate cell counts range from 60 to 450 (median 210). Canopy-span p25/median/p75 are 0.021918/0.043041/0.065816; the maximum is 0.185551. Every row therefore stops before regression and spatial resampling. The requested SE, leverage, residual Moran's I and stability columns remain blank/false with the same explicit failure code.

Sealed boundary

The canonical sealed file contains the required header and zero coefficient rows. SHA-256: 146b16f85aa89c486d174121d1e3e781ded685d8940f0dc6037e238b090d6004. It was hashed but not opened after creation. Open tables contain no point-estimate field.

This is a real failure, but not a final-study effect result

Acceptance status

Passed: exactly five outcome-blind-selected native passes; one candidate row per block-pass; native LST was not resampled; sealed/open separation and row identities passed. Failed/not estimable: one slope per block-pass, spatially robust SEs, observed sigma, and numerical detection/equivalence N. The 48-row planning table keeps both criteria, three reliabilities, all eight D1b combinations, and their available counts, but leaves required N blank rather than inventing it.

Immediate next action

Obtain the annual raw Science TCC 2019–2025 stack and repeat the canopy-span screen without opening thermal data. If that conforming nonthermal screen still produces no eligible block-passes, stop or reframe. If it materially changes eligibility, obtain supervisor approval before another five-pass thermal run. Gate A is not authorized.

Files

tables/d1d_stage1_se.csv · tables/d1d_n_required.csv · figures/d1d_se_distribution.png · figures/d1d_n_required.png · sealed/d1d_coefficients_SEALED.csv

Precision-only deviations

This free check uses Collection-2 rather than final Collection-3 LST; inherited modified-NLCD canopy rather than annual Science TCC; the LSTE height layer rather than USGS 3DEP; NLCD-derived distance to water; and a 10 m subgrid approximation for building fraction. These were frozen and disclosed before the run. None may be promoted to the final exposure, context stack, or study sample.

Required cautions

1. A Stage-1 SE would be a measurement-error floor, not the Stage-2 residual SD.
2. Connected block-passes—not all rows—define usable support.
3. Passes sharing one HLS acquisition are dependent.
4. D1b counts are optimistic historical upper bounds and cannot rescue zero Stage-1-eligible block-passes.

Scope consequence

The result stops the current D1d/Gate-A package. It does not establish that the conforming Science TCC stack will also fail, because the inherited canopy input is explicitly prohibited for the final v6.2 study. No coefficient sign or value was used in this ruling.