

Digital Signal Processing

Instituto Superior Técnico

Lab assignment 5 – Image Segmentation

Author: Margarida Silveira and Jorge Salvador Marques.

Introduction

In this assignment, we will address image segmentation using Maximum Likelihood Estimation. The goal is to compare several distributions for the image intensity and to use the one that best fits the given image data to perform segmentation.

Notes

For this lab assignment, only short answers to the questions below and the Matlab code written to answer those questions are required. The deadline for submission in fenix is one week after the day of the respective lab session at 23:59. The items that you should address are marked in bold font, e.g. **R1.a**).

In this assignment, you'll often find between brackets, as in {`command`}, suggestions of Matlab commands that may be useful to perform the requested tasks. You should use Matlab's help, when necessary, to obtain a description of how to use these commands.

Experimental work

1. Maximum Likelihood Estimators

- R1.a)** Find the log-likelihood function and the Maximum Likelihood estimate of the unknown parameter(s) for each of the following univariate distributions:
 - a) Exponential distribution. b) Rayleigh distribution. c) Normal distribution.
- R1.b)** Load the image data {`sar_image`} which contains a Synthetic Aperture Radar (SAR) Image depicting ice and ocean. Visualize the image. {`imagesc`, `colormap`}
- R1.c)** Crop two image regions, as large as possible, one in the ice area and the other in the water area. Use the pixels intensity in each of the cropped regions as observations and estimate the unknown parameter(s) that best fit your data, for the designated distributions. Indicate the parameters you obtained. {`imcrop`}
- R1.d)** Plot each of the estimated distributions and compare with the histogram of the image data, properly normalized, in both regions (water and ice). Which distribution do you think is the best? {`histogram(data,'Normalization','pdf')`}

2. Image Segmentation

- R2.a)** Use the parameters you estimated for the best distribution to perform segmentation of the image by assigning each image pixel to the region (water or ice) with maximum log-likelihood. Show the segmentation results superimposed on the image. {`imcontour`}
- R2.b)** Repeat R2.a) but now assign each image pixel to the region (water or ice) with maximum log-likelihood, considering the average value of a 5x5 patch around that pixel. Assume the pixels in the patch are independent. *Suggestion:* Start by obtaining a smoothed version of the original image by applying a moving average filter with a 5x5 window. {`conv2(data, kernel, 'same')`}
- R2.c)** Compare the previous approaches visually and by computing their rate of correct decisions in the regions used for parameter estimation. Comment.