Benchmark notes on the non-dominated points project

5D–10D serial, MPI and worst-case measurements, and the questions they leave open

Arundinesh

24 October 2026

Working notes. Everything below was measured on my laptop with the code in this repository, unless I say otherwise. Where a number comes from the cluster I keep it separate and never mix the two — that mistake is easy to make and it silently inflates the result by a factor of twenty.

1 Why I re-ran all of this

The plots I had were fine as pictures and weak as evidence. Each configuration was one run with a median and nothing else, the million-point datasets had never been touched, every parallel number came from the cluster, and the quadratic baseline had only ever been measured on random data — the case where it gets to exit early. I could not answer three questions a reviewer asks immediately: how much do the numbers move between runs, what does the recipe cost per point, and what happens when the input is not friendly.

So I re-ran the serial suite for 5D–10D, measured the baseline on the same datasets, added a million-point and peak-memory run, timed the MPI decomposition on the same machine as the sequential code, and built an input on which nothing can be pruned. Then I added a phase timer to the MPI program, because the strong-scaling story did not add up on its own and I wanted to know which part of the merge was refusing to scale. This document is what came out, including the parts I cannot explain yet.

2 The setup, and what the timers actually contain

One machine: Apple silicon laptop, AppleClang, `-O3 -DNDEBUG`, warnings promoted to errors. Serial timings are the median of ten repetitions with the minimum and maximum stored next to them; MPI timings are the median of five. The CSVs keep microseconds (serial) or seconds (MPI), and the plotting scripts convert — that mismatch is a trap I have fallen into before.

Which timer covers what matters because the figures put the curves on the same axes:

- `MAXIMA2`: input copy, the sort of the working buffer, the whole recursion, and the final `resize`. The input is `const`, so one copy is unavoidable.
- Brute force: the double loop only. The input is already in memory.
- `MPI_Marrygomethod`: starts after `MPI_Scatterv` and a barrier, so reading the file and distributing it are excluded, and gathering the result is outside the region too. Inside it, the time is split into local brute force, cross-filter, the four blocking `Sendrecv` calls per round and the barrier that closes each round.

One caveat about the new instrumentation: it adds a barrier at the end of every round, so the totals from the instrumented build are a few percent above the plain ones (10D/10^5 at eight

processes: 0.97 s now against 0.93 s before). The insertion is on purpose — without it the per-round waits get attributed to whatever call happens to be next — but it means old and new MPI totals should not be mixed in one table.

Datasets are the ones in `DataSets/`: `Test1`–`Test6` with 50, 100, 500, 1 000, 10 000 and 100 000 uniformly random points, `Test7` with a million. All six dimensions use the same sizes, and the maxima counts agree for every shared configuration, which is the cross-check that both drivers solve the same problem.

3 The serial numbers

Table 1: Medians of ten repetitions. Ratio is baseline time divided by `MAXIMA2` time; below 1 the baseline is still faster. "Maxima" is the size of the output and the fraction is maxima/N.

d	$N = 10\,000$			$N = 100\,000$			maxima
	MAXIMA2 (ms)	brute force (ms)	ratio	MAXIMA2 (ms)	brute force (ms)	ratio	(100k)
5	4.55	36.0	7.9	35.5	789	22.2	847 (0.8 %)
6	5.40	60.0	11.1	63.6	1 927	30.3	2 251 (2.3 %)
7	9.13	105.0	11.5	116.2	4 067	35.0	5 218 (5.2 %)
8	14.79	189.8	12.8	193.5	6 491	33.6	8 970 (9.0 %)
9	20.32	258.1	12.7	317.9	10 584	33.3	16 083 (16.1 %)
10	26.24	315.4	12.0	477.3	16 294	34.1	25 921 (25.9 %)




Figure 1: Runtime against input size for all six dimensions: `MAXIMA2`, the brute-force baseline and the MPI marry-go-round at eight processes.

The shape of this table is easy to explain and I want to write it down properly because I have quoted the ratio without the explanation before. At $N = 10^5$ the output is 0.8 % of the input in 5D and 25.9 % in 10D. The baseline is a loop that exits as soon as it finds a dominator; when almost nothing survives, there is almost nothing to find, so in ten dimensions it does close to the full $N^2 d$ work. That is why the advantage grows from 22× to 34× at fixed N as d goes from 5 to 10, and why it is the maxima fraction rather than N that predicts it.

Per point is the more honest way to read the growth. In 5D `MAXIMA2` costs 0.36–0.41 μs per point from 1 000 to 100 000 points, i.e. flat. In 10D it climbs from 0.91 to 4.77 μs. Fitting $t \propto N^p$ over $N = 1\,000 \ldots 100\,000$ gives $p = 0.95$ (5D) rising to 1.36 (10D), against 1.33–1.89 implied by

the bound $N \log_2^{d-2} N$ over the same interval. On i.i.d. uniform data `FILTER` prunes far more than the worst case assumes. The bound is an upper bound on a pruning argument, not a forecast, and presenting it as the latter makes the measurements look suspiciously good. Section 7 is me finally testing that sentence instead of asserting it.

About the crossover: in 5D the baseline is still 1.2× faster at $N = 50$ and $N = 100$, and `MAXIMA2` takes the lead at $N = 500$. In 6D–10D it is already ahead at $N = 50$. Those small-N ratios come from measurements of 4–9 μs with a spread of up to ±100 %, so I would not quote a crossover point below 500 points at all; "no measurable difference" is the honest version.

4 A million points, and what it costs in memory

Table 2: $N = 10^6$ (`Test7`), median of five repetitions; p is fitted between $N = 10^5$ and $N = 10^6$. Peak memory is the process high-water mark including the input; "added" is what the run contributed on top of the loaded set.

d	time (ms)	p	peak (MB)	added (MB)	maxima
5	426	1.07	139.5	69.0	1 766
6	758	1.06	139.5	69.0	5 671
7	1 366	1.05	170.1	84.3	13 120
8	2 457	1.08	170.1	84.3	31 371
9	4 269	1.11	201.4	99.9	58 565
10	7 033	1.15	201.4	100.0	99 079




Figure 2: Peak resident memory against input size, one line per dimension. The working copy of the input accounts for the growth: one `Item` per point plus its coordinate vector.

The memory column is the one I am most confident in, because it matches the arithmetic to within bytes: N times a vector header plus d doubles, plus allocator overhead. 139–201 MB for a million points, of which 69–100 MB is the run itself. That is what the in-place rewrite

was supposed to achieve — one working copy, no per-level allocations — and it is nice that the number says so without me having to trust the code reading. For the MPI program the same figure applies per rank to its N/P share, which is why the cluster runs at twenty processes fit comfortably.

Worth noting while I am here: in 10D a million points produce 99 079 maxima. Ten percent of the input is output. That is a data-structure question as much as an algorithm question, and if I ever need another factor of two in 10D I will find it in how the output is accumulated before I find it in the comparison loop.

5 One core of the algorithm against eight processes of brute force

Table 3: Sequential `MAXIMA2` (Table 1) against the MPI brute force at 1, 2, 4 and 8 processes on the same machine, median of three repetitions. The last column is an extrapolation from the observed gain per doubling, not a measurement.

configuration	MAXIMA2	$P = 1$	$P = 2$	$P = 4$	$P = 8$	parity at
5D, $N = 10\,000$	4.6 ms	15.1 ms	6.3 ms	2.9 ms	3.4 ms	$P \approx 4$
10D, $N = 10\,000$	26.2 ms	207.8 ms	78.0 ms	31.1 ms	29.5 ms	$P \approx 9$
10D, $N = 100\,000$	477 ms	11 795 ms	4 059 ms	1 677 ms	930 ms	$P \approx 16$–20

This is the number the thesis actually needs and it had never been measured. In 10D at 100 000 points the parallel baseline needs 0.93 s against 0.477 s for one core of `MAXIMA2`; at 10 000 points it needs 29.5 ms against 26.2 ms. Eight processes are not enough. Only in 5D at 10 000 points does the parallel program win, and there $P = 8$ is slower than $P = 4$.

The maxima counts match the sequential runs exactly in all three cases (535, 5 233 and 25 921), so the decomposition is not quietly dropping points — the comparison is between two correct programs, which is the only kind worth making.

Two things I want to be careful about when this goes into the thesis. First, the cluster speed-up curve is superlinear by construction: each rank brute-forces N/P points, so per-rank work falls as $(N/P)^2$ and $T(1)/T(P)$ exceeds P. At twenty processes the cluster data shows about 72×, an efficiency of 3.6. That is a true measurement of that decomposition, but it is not parallel efficiency and it should not be described as better-than-linear scaling. The honest efficiency is $T(1)/(P\,T(P))$, which for the local 10D/10^5 run is $11.8/(8 \times 0.93) = 1.6$ — still above one, still for the same reason.

Second, cluster and laptop numbers cannot be divided by each other. The cluster's single-process time for 10D/10^5 is 233.5 s; mine is 11.8 s for the same program and the same dataset. That is a hardware factor of 19.8. Any ratio that mixes the two — and "233 s parallel against 0.477 s sequential" is the tempting one — is comparing machines.

6 Where the time actually goes in the merge

I added the phase timer because the eight-process results made no sense to me. Doubling from four to eight processes cut the local brute force by almost a factor of four at 10D/10^4 and the wall time by nine percent. Something was absorbing the gain, and I wanted to know what.

Now it makes sense, and the answer is not the one I expected. Communication is not the problem: the busiest rank moves 3.7 MB at two processes and 7.0 MB at eight at 10D/10^5, which costs 38–53 ms, four to five percent of the run. The problem is that the cross-filter does not scale at all. It costs 413 ms at $P = 2$, 405 ms at $P = 4$ and 359 ms at $P = 8$ — flat — while the local phase falls from 11.76 s to 0.52 s over the same range, a factor of 22.7 for eight processes (superlinear, because per-rank work is quadratic). At eight processes the cross-filter is 37 % of the wall time; at sixteen it would be about two thirds.

Table 4: Phase breakdown of the merge, medians in milliseconds over five repetitions. Local work, cross-filter and barrier are the critical rank's; communication is the busiest rank's, so the columns need not add up exactly.

P	total (ms)	local (ms)	cross-filter (ms)	communication (ms)	barrier (ms)	cross-filter share
5D, $N = 10\,000$						
1	15.0	15.0	–	–	–	–
2	5.8	5.1	0.15	0.5	0.00	3 %
4	2.3	1.8	0.14	0.3	0.04	6 %
8	2.3	0.6	0.13	1.0	0.5	6 %
10D, $N = 10\,000$						
1	207.5	207.5	–	–	–	–
2	76.2	58.4	15.1	2.6	0.02	20 %
4	31.6	16.2	12.4	1.8	0.5	39 %
8	28.9	4.2	11.2	5.4	8.3	39 %
10D, $N = 100\,000$						
1	11 758.9	11 758.9	–	–	–	–
2	4 055.5	3 616.2	412.6	43.2	2.6	10 %
4	1 716.4	1 296.3	404.6	53.0	14.1	24 %
8	969.7	517.5	358.6	37.9	106.5	37 %




Figure 3: The same breakdown as a picture, with the composition underneath. The dotted line is the busiest rank's exchange; it is consistently larger than the critical rank's, because the root sends whole halves while a middle rank sends one.

The structure explains it. Every round, every rank compares its surviving half against a neighbour's half, and the number of survivors per rank does not fall as fast as the number of ranks rises. So there is a ceiling: if the cross-filter stays at its measured 0.36 s, no process count takes 10D/10^5 below $11.76/0.36 \approx 33\times$, and the measured 12.1× at eight processes is about a third of it. I find that a more useful statement than "the speed-up is 12×", because it says where the next improvement has to come from — fewer rounds, reuse of the previous round's comparisons, or a different merge topology — rather than more processes.

The fourth row of each block is the price of synchronisation. 5D/10^4 at eight processes spends 69 % of its wall time on exchanges and barriers, which is exactly why it is no faster than at four. At 10D/10^4 the barrier alone costs 8.3 ms out of 28.9 ms. Any write-up that quotes only message time understates the cost of the decomposition by an order of magnitude.

7 What happens when nothing can be pruned

Up to here every dataset is uniformly random, which is the easy case: 0.8 % of the input survives in 5D. The opposite endpoint is an antichain, where no point dominates another and every point belongs to the output.

Building one exactly is easy once you see the trick. Draw $d-1$ integer cuts uniformly in $[0, 10^6]$, sort them, and use the d gaps plus the two ends as coordinates. Every point then has the same coordinate sum, and a point that dominated another would need a larger sum, so domination is impossible by construction — no tolerance, no floating-point luck, nothing to tune. `worst_case_benchmark` refuses to write a row unless the number of maxima equals N, and it passed that check for all 66 configurations.

Table 5: Uniform data against the antichain, medians in milliseconds. The baseline is stopped at 10^4 points: on this input it has no early exit left and is quadratic in full.

	MAXIMA2, $N = 10^4$			brute force, $N = 10^4$			MAXIMA2, $N = 10^5$		
d	uniform (ms)	anti-chain (ms)	ratio	uniform (ms)	anti-chain (ms)	ratio	uniform (ms)	anti-chain (ms)	ratio
5	4.6	16.5	3.6	36.0	444.0	12.3	35.5	343.7	9.7
6	5.4	23.3	4.3	60.0	462.5	7.7	63.6	584.1	9.2
7	9.1	28.8	3.2	105.0	483.0	4.6	116.2	816.3	7.0
8	14.8	31.9	2.2	189.8	489.2	2.6	193.5	997.8	5.2
9	20.3	35.5	1.7	258.1	499.2	1.9	317.9	1 130.3	3.6
10	26.2	36.6	1.4	315.4	503.8	1.6	477.3	1 224.8	2.6

Four things I take from this.

The penalty is largest where pruning helps most. `MAXIMA2` is 3.6× slower at 5D/10^4 and 9.7× slower at 5D/10^5, but only 1.4× and 2.6× in 10D, because in high dimensions uniform data is already close to the worst case and there is less left to lose.

The growth moves onto the bound. The fitted exponent rises from 0.95–1.36 on uniform data to 1.31–1.55 on the antichain, against 1.33–1.89 implied by $N \log_2^{d-2} N$. In 5D–7D the antichain is within 0.02–0.04 of the bound's exponent, so the bound is tight there; in 10D the measurement is 0.34 below it. That is what a worst-case bound should look like, and it is now measured rather than assumed — which is the difference between a citation and a result.

The baseline becomes exactly quadratic: exponent 1.99–2.07, and 444–504 ms at 10^4 points in every dimension. The near-independence from d surprised me until I thought about it: it is bound by streaming the points, not by the coordinate comparisons, and the dimension loop is short enough to be vectorised.

The algorithmic advantage survives the worst case. At 10^4 points the baseline is 27× slower in 5D and 14× slower in 10D on this input, against 8× and 12× on uniform data. The pruning




Figure 4: Left: runtime on the antichain for all three programs in 10D, the MPI curve at eight processes. Right: how much slower `MAXIMA2` is on the antichain than on uniform data of the same size, one line per dimension.

argument is not an artefact of random data. It also sets a bound on how much any single runtime number means: up to an order of magnitude depends on the distribution, and that should be said whenever one number is quoted.

8 Odd things I cannot fully explain

The first dataset of a run is slow. The 5D rows at $N = 50$ and $N = 100$ are two to two-and-a-half times slower than the corresponding 6D rows for `MAXIMA2`, and 16–79 % slower for the baseline, although fewer dimensions must be cheaper. It reproduces across runs, so it is not noise; a cold process (page faults, frequency ramp) hits the first configuration of each driver invocation, and 5D is the first dimension in the suite. Rows at $N \leq 500$ should be re-measured with a warm-up run discarded before anyone gives them weight.

Small-N timings move between runs. Re-running three configurations gave 10D/500: 0.210 ms recorded, then 0.94, 0.55 and 0.58 ms on three repeats; 10D/1 000: 0.991 ms recorded, then 1.45, 1.28 and 1.16 ms. Only 5D/50 was stable (4.1–4.4 μs). A median of ten inside one process does not capture frequency scaling, cache state or background load between runs, so the wiggles at small N in the runtime plots are not signal, whatever they look like.

The antichain at $10\text{D}/10^4$ is slower than uniform by only 1.4×, although the output is nearly twice as large (10 000 points instead of 5 233). My guess is that the extra surviving points cost less than the pruning they prevent, because the partition phase still separates them cheaply. I have not verified that, and it is the kind of thing that is cheap to get wrong by reasoning about it.

The MPI CSV appends. Unlike the serial drivers, which replace the row for a configuration, the MPI program appends a row per repetition — on purpose, so the plotting script can take a median — but it means a second campaign on the same cluster would silently mix two generations of measurements. Either rotate the file per campaign or make the driver upsert like `saveBenchmark` does. I left the behaviour alone because the existing cluster data depends on it, and the new timing CSV is local-only.

Cluster and laptop differ by an order of magnitude. Not an anomaly, but it makes the 72× headline meaningless as a hardware-independent claim, and I would rather write the factor down than be asked about it in a defence.

9 What I still do not know

- Whether the suite reproduces between runs. Everything above rests on one run per configuration; the min–max inside it says nothing about frequency scaling between invocations. Five whole-suite repetitions on an idle machine would settle it, and it is cheap.
- How `MAXIMA2` behaves on the cluster. It has never been timed there, so the one genuinely comparative statement — algorithm against decomposition on the same hardware — exists only for my laptop.
- What tie-heavy and pre-sorted inputs cost. The differential test covers correctness there; the timings do not. Pre-sorted input matters because the sort is inside the timer.
- How much of the serial runtime is the sort, the recursion and the output handling. The MPI program now separates its phases; `MAXIMA2` still reports one number, and at a million points in 10D ten percent of the output is new data.
- Whether the million-point speed-up is what the extrapolation says. The baseline cannot run 10^6 points; growing its measured 10D/10^5 time by the measured 10^5-to-10^4 factor gives about fourteen minutes, roughly 2×10^2 times the 7.0 s `MAXIMA2` needs. That is an extrapolation and has to be labelled as one.

10 What I would do next, in order

Repeat the serial suite five times and report the spread between runs. It is an afternoon and it protects every other claim here.

Measure the parity point instead of extrapolating it (P = 12, 16, 20 on the laptop). The cross-filter ceiling says parity is not the interesting number anyway; what matters is where the curve bends, and 16–20 is the region.

Run `Maxima_method` on the cluster with the same job script as the MPI program, so the comparison is hardware-matched. Everything else about the parallel story is already measured.

Put the cross-filter at the top of the optimisation list if more speed is needed. The local phase is still 53 % of that run, but making it infinitely fast would at best halve the wall time, because the cross-filter and the barriers would remain; the cross-filter is the part that does not move.

Add the serial phase timer and the tie-heavy and pre-sorted inputs. The first answers the question reviewers ask first; the second is the remaining adversarial case.

11 What changed in the code

`MPI_Marrygomethod` now writes a second CSV, `mpi_marry_go_round_timing.csv`, with the phase split, the exchanged bytes and a load-imbalance ratio, alongside the unchanged summary file. The breakdown belongs to the rank that determined the wall time, so its parts add up to that rank's total; the busiest rank's communication is stored separately, because taking the maximum of each phase independently lets the parts exceed the whole. `scripts/mpi_timing_sweep.sh` reproduces the local sweep.

`worst_case_benchmark` generates the antichain in memory and times one algorithm per process, so the memory and timing of a configuration belong to that run alone. The sweep behind Table 5 is a shell script in `scripts/`. Two plotting scripts came with the new material, one for the MPI breakdown and one for the worst case.

Also, from the earlier pass: `scripts/mpi_marry_go.sh` used to compile the MPI binary itself with `-O2` while the CMake target uses `-O3`, so cluster timings came from a differently optimised binary. That compile line is gone; the script uses the CMake build, which its own error message already assumed.

12 Reproducing this

```
cmake -S . -B build -DNDP_WARNINGS_AS_ERRORS=ON
cmake --build build -j
cd build && ctest --output-on-failure   # algorithms, pipeline, MPI

./Maxima_method 5D_Data                 # serial suite, 5D..10D
./brute_force ../DataSets/10D_Data      # quadratic baseline, same datasets

# one dataset per process, so the memory high-water mark is per run
./large_benchmark ../plots/data/memory_and_large_n.csv \
                  ../DataSets/10D_Data/Test7.txt

# worst case: antichain, every point maximal
./worst_case_benchmark ../plots/data/worst_case_all_maxima.csv 10 10000 maxima2
cd .. && scripts/worst_case_sweep.sh build/worst_case_benchmark \
                                     plots/data/worst_case_all_maxima.csv

# MPI phase breakdown, from a build directory whose parent has results/
cd build && ../scripts/mpi_timing_sweep.sh      # NP="1 2 4 8" REPS=5
cd ../plots && python3 plot_results.py && python3 plot_analysis.py \
             && python3 plot_mpi_timing.py && python3 plot_worst_case.py
```

The figures read the two serial CSVs in `results` and the measurement files in `plots/data`: the memory and large-N table, the local MPI comparison, the MPI phase breakdown and the antichain table. The cluster series in `results` comes from your campaign and was not re-measured for this document.