

STANDARD OPERATING PROCEDURE FOR CUT TO LENGTH (CTL)

CTL OPERATION

- Relevant personal protective equipment to be used by operator
- Identify the coil with sticker
- From the raw material area, the coil is lifted with the help of overhead crane.
- While handling the coil no one should present on the path way.
- The coil is feed into the mandrel end expand the mandrel.
- The narrow width coil safety guard should be provided
- And the snubber roll is operated by operator at control desk.
- Snubber roll comes contact to the coil and binding strip is removed from the coil by using cutter tool manually, operator should stand side only
- The lead end of the coil is then placed in pinch rollers for further movement of sheet.
- The sheet is then pass through the flatness rollers where the flatness of sheet can be done.
- Then sheet pass through loop pit table.
- The sheet then pass through the Quadratic table with rollers and guide rolls to guide the sheet for further movement.
- Again the sheet pass through the lower the feed roll g which help the sheet
- Start the line where the rollers supplies the required length of the sheet as per programme fed using PLC.
- Shear will operate and cut the sheet. Then again feeder is started for second cut
- The cut down sheets then pass through the conveyor belt.
- At the end of the conveyor belt the sheet reaches the trolley sheets level adjustment done on trolley only
- Pallet placed upon that on the trolley and sheet is packed and covered with polyethylene cover and binded together with binding strips, mention work order number and customer details
- Operator should not sit on pallet stacking table in machine operation
- Write the production report.