

SAFE OPERATING PROCEDURE FOR COLLECTION, Handling, STORING & DISPOSAL OF Oil soaked cotton waste

- 1. Purpose:** To provide guidelines for easy process for Collect, handle, store disposal of Oil soaked cotton waste
- 2. Scope:** This procedure is applicable to collect, handle, store disposal of oil soaked cotton waste
- 3. Responsibility:** In-Charge-Stores, and In-charges of all sectional are responsible to implement the instructions.

4. Procedure

- a) Oil soaked cotton waste will be collected into bins provided at respective work areas. Oil soaked cotton waste will be packed into HDPE bags.
- b) Respective sectional in-charge will send oil soaked cotton waste bags to stores periodically with weighment slip or written note.
- c) Stores section in-charge will issue acknowledgement note of receipt material to respective sectional in-charge.
- d) Respective sectional will keep acknowledgement note given by stores as a proof of receiving material.
- e) Stores department has already identified customers who are authorized by respective pollution control boards.
- f) Oil soaked cotton waste will be disposed off for the internal use for pre heating purpose and to the authorized operators only.
- g) The stores will maintain the necessary documents to meet legal requirements. They are Form - 3, Form – 11, Form - 12, & Form - 13.
- h) Stores personnel will maintain appropriate records for receipts, disposal and stocks.
- i) Store in a metal safety can with a tight-fitting lid
- j) Label the container "Contaminated Waste"
- k) Keep containers away from ignition sources
- l) Store in a designated area with a proper slope and spillage collection pit
- m) Remove from the site as soon as possible
- n) Empty individual containers into a larger drum with a lid at the end of each day
- o) Keep drums and containers securely closed and locked
- p) Hand over to a Hazardous Waste Treatment, Storage, and Disposal Facility (TSDF)
- q) Hand over to an authorized recycler.

- r) Maintain proper fire extinguishing equipment and smoke detectors
- s) If there is a small fire, use dry chemical, CO2, sand, earth, water spray, or regular foam
- t) If there is a large fire, use water spray, fog, or regular foam
- u) Ensure that personnel wear protective gas masks when opening drums
- v) Provide exhaust/suction blowers in the area where drums are opened



SOP NO.: PTC/PROD/ REV.00