

**Exp No: 6****Handling JSON data using HDFS and Python****AIM:**

To handle JSON data using HDFS and python.

**PROCEDURE:****Step 1: Create json file on bash & save as emp.json**

nano emp.json ; Paste the below content on it

```
[  
  {"name": "John Doe", "age": 30, "department": "HR", "salary": 50000},  
  {"name": "Jane Smith", "age": 25, "department": "IT", "salary": 60000},  
  {"name": "Alice Johnson", "age": 35, "department": "Finance", "salary": 70000},  
  {"name": "Bob Brown", "age": 28, "department": "Marketing", "salary": 55000},  
  {"name": "Charlie Black", "age": 45, "department": "IT", "salary": 80000}  
]
```

A screenshot of a terminal window with a dark background. It shows the same JSON array as the previous block, with each line of the array on a new line. The text is color-coded: strings are in red, numbers are in green, and keys are in blue. The array is enclosed in square brackets with commas separating the objects.

```
[  
  {"name": "John Doe", "age": 30, "department": "HR", "salary": 50000},  
  {"name": "Jane Smith", "age": 25, "department": "IT", "salary": 60000},  
  {"name": "Alice Johnson", "age": 35, "department": "Finance", "salary": 70000},  
  {"name": "Bob Brown", "age": 28, "department": "Marketing", "salary": 55000},  
  {"name": "Charlie Black", "age": 45, "department": "IT", "salary": 80000}  
]
```

**Step 2 : Check json is readable or any error by giving**

install jq by sudo apt-get install jq

hadoop@Ubuntu:~\$ jq . emp.json

```
osboxes@fedora:~$ cd Downloads/  
osboxes@fedora:~/Downloads$ jq . emp.json  
[  
  {  
    "name": "John Doe",  
    "age": 30,  
    "department": "HR",  
    "salary": 50000  
  },  
  {  
    "name": "Jane Smith",  
    "age": 25,  
    "department": "IT",  
    "salary": 60000  
  },  
  {  
    "name": "Alice Johnson",  
    "age": 35,  
    "department": "Finance",  
    "salary": 70000  
  },  
]
```

**Step 3: Install pandas and hdfs dependencies for python.**

**Step 4: Create process\_data.py file**

```
from hdfs import InsecureClient
```

```
import pandas as pd
```

```
import json
```

```
# Connect to HDFS
```

```
hdfs_client = InsecureClient('http://localhost:9870', user='hdfs')
```

```
# Read JSON data from HDFS
```

```
try:
```

```
    with hdfs_client.read('/home/hadoop/emp.json', encoding='utf-8') as reader:
```

```
        json_data = reader.read() # Read the raw data as a string
```

```
        if not json_data.strip(): # Check if data is empty
```

```
            raise ValueError("The JSON file is empty.")
```

```
        print(f"Raw JSON Data: {json_data[:1000]}") # Print first 1000 characters for debugging
```

```
        data = json.loads(json_data) # Load the JSON data
```

```
except json.JSONDecodeError as e:
```

```
print(f'JSON Decode Error: {e}')
exit(1)
except Exception as e:
    print(f'Error reading or parsing JSON data: {e}')
    exit(1)

# Convert JSON data to DataFrame
try:
    df = pd.DataFrame(data)
except ValueError as e:
    print(f'Error converting JSON data to DataFrame: {e}')
    exit(1)

# Projection: Select only 'name' and 'salary' columns
projected_df = df[['name', 'salary']]

# Aggregation: Calculate total salary
total_salary = df['salary'].sum()

# Count: Number of employees earning more than 50000
high_earners_count = df[df['salary'] > 50000].shape[0]

# Limit: Get the top 5 highest earners
top_5_earners = df.nlargest(5, 'salary')

# Skip: Skip the first 2 employees
skipped_df = df.iloc[2:]

# Remove: Remove employees from a specific department
filtered_df = df[df['department'] != 'IT']
```

```
# Save the filtered result back to HDFS
filtered_json = filtered_df.to_json(orient='records')

try:
    with hdfs_client.write('/home/hadoop/filtered_employees.json', encoding='utf-8', overwrite=True) as writer:
        writer.write(filtered_json)

    print("Filtered JSON file saved successfully.")
except Exception as e:
    print(f"Error saving filtered JSON data: {e}")
    exit(1)

# Print results
print(f"Projection: Select only name and salary columns")
print(f"{projected_df}")

print(f"Aggregation: Calculate total salary")

print(f"Total Salary: {total_salary}")
print(f"\n")

print(f"# Count: Number of employees earning more than 50000")

print(f"Number of High Earners (>50000): {high_earners_count}")
print(f"\n")
print(f"limit Top 5 highest salary")

print(f"Top 5 Earners: \n{top_5_earners}")
print(f"\n")
print(f"Skipped DataFrame (First 2 rows skipped): \n{skipped_df}")
```

```
print(f'\n')  
print(f'Filtered DataFrame (Sales department removed): \n{filtered_df}')
```

**Step 5: run the file by**

bash: python3 process\_data.py

```
Top 5 Earners:  
   name  age department  salary  
4  Charlie Black   45         IT   80000  
2  Alice Johnson   35        Finance   70000  
1    Jane Smith   25         IT   60000  
3    Bob Brown   28       Marketing   55000  
0    John Doe    30          HR   50000  
  
Skipped DataFrame (First 2 rows skipped):  
   name  age department  salary  
2  Alice Johnson   35        Finance   70000  
3    Bob Brown   28       Marketing   55000  
4  Charlie Black   45         IT   80000  
  
Filtered DataFrame (Sales department removed):  
   name  age department  salary  
0    John Doe    30          HR   50000  
2  Alice Johnson   35        Finance   70000  
3    Bob Brown   28       Marketing   55000
```

**RESULT:**

Experiment has been successfully executed and output has been verified.