

```
1 #include <stdio.h>
2 int main()
3 {
4     int N,oddsum=0,evensum=0;
5     scanf("%d",&N);
6     for(int i=1;i<=N;i++)
7     {
8         if(i%2==0)
9             evensum+=i;
10        else
11            oddsum+=i;
12    }
13    printf("%d\n%d",oddsum,evensum);
14    return 0;
15 }
16
```

```
1 #include <stdio.h>
2 int main()
3 {
4     int n,i;
5     scanf("%d",&n);
6     for(i=1;i<=n;i++)
7         printf("%d",i);
8     return 0;
9 }
```

```
1 #include <stdio.h>
2 int main()
3 {
4     int n,i =1,sum=0;
5     scanf("%d",&n);
6     while(i<=n)
7     {
8         sum=sum+i;
9         i++;
10    }
11    printf("%d",sum);
12    return 0;
13 }
```

```
1 #include <stdio.h>
2 int main()
3 {
4     int n,i;
5     scanf("%d",&n);
6     for(i=1;i<=10;i++)
7     {
8         printf("%d x %d=%d\n",&n,&i,&n*i);
9     }
10 }
11 return 0;
12
13 }
```

```
1 #include <stdio.h>
2 int main()
3 {
4     int n,i=2,prime=1;
5     scanf("%d",&n);
6     if(n<=1)
7         prime=0;
8     while(i<n){
9         if(n%i==0){
10             prime=0;
11             break;
12         }
13         i++;
14     }
15     if(prime)
16         printf("prime number");
17     else
18         printf("not a prime number");
19     return 0;
20
21 }
```

```
1 #include <stdio.h>
2 int main()
3 {
4     char str[100];
5     int i,count=0;
6     scanf("%s",str);
7     for(i=0,str[i]!='\a';i++)
8     {
9         if(str[i]=='a' || str[i]=='e' || str[i]=='i' || str[i]=='o' || str[i]=='u' || str[i]=='A' || str[i]=='E' || str[i]=='I' || str[i]=='O' || str[i]=='U')
10             count++;
11     }
12     printf("%d",count);
13     return 0;
14
15
16 }
```

```
1 #include <stdio.h>
2 int main()
3 {
4     int n,a=0,b=1,c;
5     scanf("%d",&n);
6     while(a<=n)
7     {
8         printf("%d",a);
9         c=a+b;
10        a=b;
11        b=c;
12
13    }
14    return 0;
15 }
```

```
1 #include <stdio.h>
2
3 int main()
4 {
5     int n, i;
6     long long fact = 1;
7
8     scanf("%d", &n);
9
10    for (i = 1; i <= n; i++)
11        fact = fact * i;
12
13    printf("%lld", fact);
14
15    return 0;
16 }
```



```
1 #include <stdio.h>
2 int main()
3 {
4     int i,j,n;
5     scanf("%d",&n);
6     for(i=1;i<=n;i++)
7     {
8         for(j=1;j<=1;j++)
9         {
10             printf("*");
11
12         }
13         printf("\n");
14     }
15     return 0;
16 }
```

```
1 #include <stdio.h>
2 int main()
3 {
4     int i,j,n;
5     scanf("%d",&n);
6     for(i=1;i<=n;i++){
7         for(j=1;j<=n;j++)printf(" ");
8         for(j=1;j<=2*i-1;j++)printf("*");
9         printf("\n");
10    }
11    for(i=n-1;i>=1;i--){
12        for(j=1;j<=n-i;j++) printf(" ");
13        for(j=1;j<=2*i-1;j++)printf("*");
14        printf("\n");
15    }
16    return 0;
17 }
```

```
1 #include <stdio.h>
2 int main()
3 {
4     int i,j,n;
5     scanf("%d",&n);
6     for(i=1;i<=n;i++){
7         for(j=1;j<=i;j++)
8             printf("*");
9         printf("\n");
10    }
11    return 0;
12 }
```

```
1 #include <stdio.h>
2 int main()
3 {
4     int i,j,n;
5     scanf("%d",&n);
6     for(i=1;i<=n;i++){
7         for(j=1;j<=n;j++)
8             if(i==1||i==n||j==1||j==n) printf("*");
9             else
10                 printf(" ");
11         printf("\n");
12     }
13     return 0;
14 }
```

```
1 #include <stdio.h>
2 int main()
3 {
4     int n=5,i,j;
5     for(i=1;i<=n;i++){
6         for(j=1;j<=n-i;j++) printf("*");
7         for(j=1;j<=2*i-1;j++) printf(j==1||j==2*i-1?"*":" ");
8         printf("\n");
9     }
10    for(i=n-1;i>=1;i--){
11        for(j=1;j<=n-1;j++) printf(" ");
12        for(j=1;j<=2*i-1;j++) printf(j==1||j==2*i-1?"*":" ");
13        printf("\n");
14    }
15 }
16 return 0;
17 }
```

```
1 #include <stdio.h>
2 int main()
3 {
4     int i,j,n=5,c;
5     for(i=0;i<n;i++){
6         c=1;
7         for(j=0;j<=i;j++){
8             printf("%d",c);
9             c=c*(i-j)/(j+1);
10
11         }
12         printf("\n");
13     }
14     return 0;
15 }
```

```
1 #include <stdio.h>
2 int main()
3 {
4     int i,j,n=9;
5     for(i=1;i<=3;i++){
6         for(j=1;j<=n;j++)
7             if((i+j)%4==0||(i==2 && j%4==0))
8                 printf("*");
9         else
10             printf(" ");
11         printf("\n");
12
13     }
14     return 0;
15 }
```

```
1 #include <stdio.h>
2 int main()
3 {
4     int a[10][10],n=1,t=0,b=3,I=0,r=3,i,j,k=1;
5     while(t<=b&&I<=r){
6         for(i=1;i<=r;i++)a[t][i]=k++; t++;
7         for(i=t;i<=b;i++)a[i][r]=k++; r--;
8         for(i=r;i>=I;i--)a[b][i]=k++; b--;
9         for(i=b;i>=t;i--)a[i][I]=k++; I++;
10
11     }
12     for(i=0;i<n;i++){
13         for(j=0;j<n;j++)
14             printf("%2",a[i][j]);
15         printf("\n");
16     }
17     return 0;
18 }
```



```
1 #include <stdio.h>
2 int main()
3 {
4     int n,temp,rem,sum=0;
5     scanf("%d",&n);
6     temp=n;
7     while(temp!=0)
8     {
9         rem=temp%10;
10        sum=sum+rem*rem*rem;
11        temp=temp/10;
12    }
13    if(sum==n)
14        printf("Armsrong number");
15    else
16        printf("not an armsrong");
17    return 0;
18 }
```

```
1 #include <stdio.h>
2 int main()
3 {
4     int n,i,s=0;
5     scanf("%d",&n);
6
7     for(i=1;i<n;i++)
8         if(n%i==0) s+=i;
9     if(s==n)
10         printf("perfect number");
11     else
12         printf("not perfect number");
13     return 0;
14 }
```