

```
1 #include <stdio.h>
2 int add(int a, int b){
3     return a+b;
4 }
5 int main(){
6     int x,y;
7     scanf("%d%d",&x,&y);
8     printf("%d",add(x,y));
9     return 0;
10 }
```

```
1 #include <stdio.h>
2 float area(float r){
3     return 3.14*r*r;
4 }
5 int main(){
6     float r;
7     scanf("%f",&r);
8     printf("%.2f",area(r));
9     return 0;
10 }
```

```
1 #include <stdio.h>
2 float celsius(float f){
3     return (f-32)*5/9;
4 }
5 int main(){
6     float f;
7     scanf("%f",&f);
8     printf("%.2f",celsius(f));
9     return 0;
10 }
```

```
1 #include <stdio.h>
2 int prime(int n){
3     int i;
4     if(n<2)
5         return 0;
6     for(i=2;i<n;i++)
7         if(n%i==0)
8             return 0;
9     return 1;
10 }
11 int main(){
12     int n;
13     scanf("%d",&n);
14     if(prime(n))
15         printf("prime");
16     else
17         printf("Not prime");
18     return 0;
19 }
```

```
1 #include <stdio.h>
2 int fact(int n){
3     if(n == 0 || n == 1)
4         return 1;
5     return n*fact(n-1);
6 }
7 int main(){
8     int n;
9     scanf("%d",&n);
10    printf("%d",fact(n));
11    return 0;
12 }
```

```
1 #include <stdio.h>
2 int largest(int a[],int n){
3     int i,max=a[0];
4     for(i=1;i<n;i++)
5         if(a[i]>max)
6             max=a[i];
7     return max;
8
9 }
10 int main(){
11     int a[100],n,i;
12     scanf("%d",&n);
13     for(i=0;i<n;i++)
14         scanf("%d",&a[i]);
15     printf("%d",largest(a,n));
16     return 0;
17 }
```

```
1 #include <stdio.h>
2 void swap(int a,int b){
3     int t=a;
4     a=b;
5     b=t;
6     printf("%d %d",a,b);
7 }
8 int main(){
9     int x,y;
10    scanf("%d%d",&x,&y);
11    swap(x,y);
12    return 0;
13
14 }
```

```
1 #include <stdio.h>
2 void sort(int a[],int n){
3     int i,j,t;
4     for(i=0;i<n-1;i++)
5         for(j=i+1;j<n;j++)
6             if(a[i]>a[j]){
7                 t=a[i];
8                 a[i]=a[j];
9                 a[j]=t;
10
11             }
12     for(i=0;i<n;i++)
13         printf("%d ",a[i]);
14 }
15 int main(){
16     int a[100],n,i;
17     scanf("%d",&n);
18     for(i=0;i<n;i++)
19         scanf("%d",&a[i]);
20     sort(a,n);
21     return 0;
```



```
1 #include <stdio.h>
2 int area(int I,int b){
3     return I*b;
4
5 }
6 int main(){
7     int I,b;
8     scanf("%d%d",&I,&b);
9     printf("%d",area(I,b));
10    return 0;
11 }
```

```
1 #include <stdio.h>
2 int gcd(int a,int b){
3     while(b != 0){
4         int t=b;
5         b=a % b;
6         a=t;
7
8     }
9     return a;
10
11 }
12 int main(){
13     int a,b;
14     scanf("%d%d",&a,&b);
15     printf("%d",gcd(a, b));
16     return 0;
17 }
```

```
1 #include <stdio.h>
2 int vowels(char s[]){
3     int i,count =0;
4     for(i=0;s[i] !='\0';i++)
5         if(s[i]=='a' || s[i]=='e' || s[i]=='i' || s[i]=='o' || s[i]=='u' || s[i]=='A' || s[i]=='E' || s[i]=='I' || s[i]=='O' || s[i]=='U')
6             count++;
7     return count;
8 }
9 int main(){
10     char s[100];
11     scanf("%s",s);
12     printf("%d",vowels(s));
13     return 0;
14 }
15
```

```
1 #include <stdio.h>
2
3 int sumArray(int arr[], int n) {
4     int sum = 0;
5
6     for (int i = 0; i < n; i++)
7         sum += arr[i];
8
9     return sum;
10 }
11
12 int main() {
13     int n, arr[100];
14
15     printf("Enter number of elements: ");
16     scanf("%d", &n);
17
18     printf("Enter array elements:\n");
19     for (int i = 0; i < n; i++)
20         scanf("%d", &arr[i]);
21
```

```
1 #include <stdio.h>
2
3 int secondSmallest(int arr[], int n) {
4     int smallest, second;
5
6     smallest = second = 999999;
7
8     for (int i = 0; i < n; i++) {
9         if (arr[i] < smallest) {
10             second = smallest;
11             smallest = arr[i];
12         } else if (arr[i] < second && arr[i] != smallest) {
13             second = arr[i];
14         }
15     }
16
17     return second;
18 }
19
20 int main() {
21     int n, arr[100];
```

```
1 #include <stdio.h>
2
3 int Palindrome(char str[]) {
4     int i, j, length = 0;
5
6     while (str[length] != '\0')
7         length++;
8
9     i = 0;
10    j = length - 1;
11
12    while (i < j) {
13        if (str[i] != str[j])
14            return 0;
15
16        i++;
17        j--;
18    }
19
20    return 1;
21 }
```

```
1 #include <stdio.h>
2 #include <stdlib.h>
3 #include <time.h>
4
5 int randomNumber(int min, int max) {
6     return min + rand() % (max - min + 1);
7 }
8
9 int main() {
10     int min, max, result;
11
12     printf("Enter two numbers: ");
13     scanf("%d %d", &min, &max);
14
15     srand(time(0));
16
17     result = randomNumber(min, max);
18
19     printf("Random number = %d\n", result);
20
21     return 0;
```

```
1 #include <stdio.h>
2
3 int power(int base, int exponent) {
4     int result = 1;
5
6     for (int i = 0; i < exponent; i++)
7         result *= base;
8
9     return result;
10 }
11
12 int main() {
13     int base, exponent;
14
15     printf("Enter base and exponent: ");
16     scanf("%d %d", &base, &exponent);
17
18     printf("Power = %d\n", power(base, exponent));
19
20     return 0;
21 }
```



```
1 #include <stdio.h>
2
3 void sortStrings(char str[][100], int n) {
4     char temp[100];
5
6     for (int i = 0; i < n - 1; i++) {
7         for (int j = i + 1; j < n; j++) {
8             int k = 0;
9
10            while (str[i][k] == str[j][k] && str[i][k] != '\0')
11                k++;
12
13            if (str[i][k] > str[j][k]) {
14                int x = 0;
15
16                while (str[i][x] != '\0') {
17                    temp[x] = str[i][x];
18                    x++;
19                }
20                temp[x] = '\0';
21
```

```
1 #include <stdio.h>
2
3 int binaryToDecimal(int binary) {
4     int decimal = 0;
5     int base = 1;
6     int remainder;
7
8     while (binary > 0) {
9         remainder = binary % 10;
10        decimal = decimal + remainder * base;
11        binary = binary / 10;
12        base = base * 2;
13    }
14
15    return decimal;
16 }
17
18 int main() {
19     int binary;
20
21     printf("Enter a binary number: ");
```

```
1 #include <stdio.h>
2
3 void fibonacci(int n) {
4     int a = 0, b = 1, c;
5
6     for (int i = 0; i < n; i++) {
7         printf("%d ", a);
8         c = a + b;
9         a = b;
10        b = c;
11    }
12 }
13
14 int main() {
15     int n;
16
17     printf("Enter n: ");
18     scanf("%d", &n);
19
20     printf("Fibonacci series: ");
21     fibonacci(n);
```

```
1 #include <stdio.h>
2
3 void findMaxMin(int arr[], int n, int *max, int *min) {
4     *max = arr[0];
5     *min = arr[0];
6
7     for (int i = 1; i < n; i++) {
8         if (arr[i] > *max)
9             *max = arr[i];
10
11         if (arr[i] < *min)
12             *min = arr[i];
13     }
14 }
15
16 int main() {
17     int arr[100], n, max, min;
18
19     printf("Enter number of elements: ");
20     scanf("%d", &n);
21
```