

```
1 #include <stdio.h>
2
3 union Data {
4     int i;
5     float f;
6     char c;
7 };
8
9 int main() {
10     union Data d;
11
12     d.i = 10;
13     printf("Integer: %d\n", d.i);
14
15     d.f = 25.5;
16     printf("Float: %.2f\n", d.f);
17
18     d.c = 'A';
19     printf("Character: %c\n", d.c);
20
21     return 0;
```

```
1 #include <stdio.h>
2
3 union Data
4 {
5     int i;
6     float f;
7 };
8
9 int main()
10 {
11     union Data d;
12     int a;
13     float b;
14
15     scanf("%d", &a);
16     d.i = a;
17     printf("%d\n", d.i);
18
19     scanf("%f", &b);
20     d.f = b;
21     printf("%.2f", d.f);
```

```
1 #include <stdio.h>
2
3 union Data
4 {
5     int i;
6     float f;
7     char c;
8 };
9
10 int main()
11 {
12     union Data d;
13
14     d.i = 10;
15     printf("Integer: %d\n", d.i);
16
17     d.f = 20.5;
18     printf("Float: %.2f\n", d.f);
19
20     d.c = 'A';
21     printf("Character: %c\n", d.c);
```

```
1 #include <stdio.h>
2
3 union Data
4 {
5     char c;
6     int i;
7     float f;
8 };
9
10 int main()
11 {
12     union Data d;
13     int choice;
14
15     scanf("%d", &choice);
16
17     if (choice == 1)
18     {
19         scanf(" %c", &d.c);
20         printf("%c", d.c);
21     }
```

```
1 #include <stdio.h>
2
3 union Data
4 {
5     float result;
6 };
7
8 int main()
9 {
10     union Data d;
11     float a, b;
12     int choice;
13
14     scanf("%f %f", &a, &b);
15     scanf("%d", &choice);
16
17     switch(choice)
18     {
19         case 1:
20             d.result = a + b;
21             printf("%.2f", d.result);
```