

```
1 #include <stdio.h>
2
3 int main()
4 {
5     int a, b, temp;
6     int *p, *q;
7
8     scanf("%d %d", &a, &b);
9
10    p = &a;
11    q = &b;
12
13    temp = *p;
14    *p = *q;
15    *q = temp;
16
17    printf("%d %d", a, b);
18
19    return 0;
20 }
```

```
1 #include <stdio.h>
2
3 int main()
4 {
5     int a[100], n, i, max;
6     int *p;
7
8     scanf("%d", &n);
9
10    for(i = 0; i < n; i++)
11        scanf("%d", &a[i]);
12
13    p = a;
14    max = *p;
15
16    for(i = 1; i < n; i++)
17    {
18        if(*(p + i) > max)
19            max = *(p + i);
20    }
21
```

```
1 #include <stdio.h>
2
3 int main()
4 {
5     char str1[100], str2[100];
6     char *p, *q;
7
8     scanf("%99s", str1);
9     scanf("%99s", str2);
10
11     p = str1;
12     q = str2;
13
14     while (*p != '\0')
15         p++;
16
17     while (*q != '\0')
18     {
19         *p = *q;
20         p++;
21         q++;
```

```
1 #include <stdio.h>
2
3 int main()
4 {
5     int a[100], n, i, even = 0, odd = 0;
6     int *p;
7
8     scanf("%d", &n);
9
10    for(i = 0; i < n; i++)
11        scanf("%d", &a[i]);
12
13    p = a;
14
15    for(i = 0; i < n; i++)
16    {
17        if(*(p + i) % 2 == 0)
18            even++;
19        else
20            odd++;
21    }
```

```
1 #include <stdio.h>
2
3 int main()
4 {
5     int a[100], n, i, sorted = 1;
6     int *p;
7
8     scanf("%d", &n);
9
10    for(i = 0; i < n; i++)
11        scanf("%d", &a[i]);
12
13    p = a;
14
15    for(i = 0; i < n - 1; i++)
16    {
17        if(*(p + i) > *(p + i + 1))
18        {
19            sorted = 0;
20            break;
21        }
```

```
1 #include <stdio.h>
2
3 int main()
4 {
5     int a[100], n, i, temp;
6     int *p, *q;
7
8     scanf("%d", &n);
9
10    for(i = 0; i < n; i++)
11        scanf("%d", &a[i]);
12
13    p = a;
14    q = a + n - 1;
15
16    while(p < q)
17    {
18        temp = *p;
19        *p = *q;
20        *q = temp;
21
```

```
1 #include <stdio.h>
2
3 int main()
4 {
5     char str1[100], str2[100];
6     char *p, *q;
7
8     scanf("%99s", str1);
9
10    p = str1;
11    q = str2;
12
13    while (*p != '\0')
14    {
15        *q = *p;
16        p++;
17        q++;
18    }
19
20    *q = '\0';
21
```

```
1 #include <stdio.h>
2
3 int main() {
4     int a[10][10], rows, cols;
5     int i, j, sum = 0;
6     int *ptr;
7
8     scanf("%d %d", &rows, &cols);
9
10    for (i = 0; i < rows; i++) {
11        for (j = 0; j < cols; j++) {
12            scanf("%d", &a[i][j]);
13        }
14    }
15
16    ptr = &a[0][0];
17
18    for (i = 0; i < rows * cols; i++) {
19        sum += *(ptr + i);
20    }
21
```



```
1 #include <stdio.h>
2
3 int main() {
4     char str[100];
5     char *ptr;
6     int length = 0;
7
8     scanf("%99s", str);
9
10    ptr = str;
11
12    while (*ptr != '\0') {
13        length++;
14        ptr++;
15    }
16
17    printf("%d", length);
18
19    return 0;
20 }
```

```
1 #include <stdio.h>
2
3 int main() {
4     int a[100], n, i, j, temp;
5     int *ptr;
6
7     scanf("%d", &n);
8
9     for (i = 0; i < n; i++) {
10         scanf("%d", &a[i]);
11     }
12
13     ptr = a;
14
15     for (i = 0; i < n - 1; i++) {
16         for (j = i + 1; j < n; j++) {
17             if (*(ptr + i) > *(ptr + j)) {
18                 temp = *(ptr + i);
19                 *(ptr + i) = *(ptr + j);
20                 *(ptr + j) = temp;
21             }
22         }
23     }
24 }
```