

```
1 #include <stdio.h>
2
3 int main() {
4     char str[100];
5     int length = 0;
6
7     printf("Enter a string: ");
8     fgets(str, sizeof(str), stdin);
9
10    while (str[length] != '\0' && str[length] != '\n') {
11        length++;
12    }
13
14    printf("Length of the string = %d\n", length);
15
16    return 0;
17 }
```

```
1 #include <stdio.h>
2
3 int main() {
4     char str1[200], str2[100];
5     int i = 0, j = 0;
6
7     printf("Enter first string: ");
8     scanf("%s", str1);
9
10    printf("Enter second string: ");
11    scanf("%s", str2);
12
13    while (str1[i] != '\0') {
14        i++;
15    }
16
17    while (str2[j] != '\0') {
18        str1[i] = str2[j];
19        i++;
20        j++;
21    }
```

```
1 #include <stdio.h>
2
3 int main() {
4     char str[100];
5     int i = 0;
6
7     printf("Enter a string: ");
8     fgets(str, sizeof(str), stdin);
9
10    while (str[i] != '\0') {
11        if (str[i] >= 'a' && str[i] <= 'z') {
12            str[i] = str[i] - 32;
13        }
14        i++;
15    }
16
17    printf("Uppercase string: %s", str);
18
19    return 0;
20 }
```

```
1 #include <stdio.h>
2
3 int main() {
4     char str[100];
5     int len = 0, i;
6     char temp;
7
8     printf("Enter a string: ");
9     scanf("%99s", str);
10
11     while (str[len] != '\0') {
12         len++;
13     }
14
15     for (i = 0; i < len / 2; i++) {
16         temp = str[i];
17         str[i] = str[len - 1 - i];
18         str[len - 1 - i] = temp;
19     }
20
21     printf("Reversed string: %s\n", str);
22 }
```

```
1 #include <stdio.h>
2
3 int main() {
4     char str[200];
5     int i = 0, count = 0, in_word = 0;
6
7     printf("Enter a string: ");
8     fgets(str, sizeof(str), stdin);
9
10    while (str[i] != '\0') {
11        if (str[i] != ' ' && str[i] != '\t' && str[i] != '\n' && str[i] != '\r') {
12            if (in_word == 0) {
13                in_word = 1;
14                count++;
15            }
16        } else {
17            in_word = 0;
18        }
19        i++;
20    }
```

```
1 #include <stdio.h>
2
3 int main() {
4     char str1[100], str2[100];
5     int count[256] = {0};
6     int i = 0, is_anagram = 1;
7
8     printf("Enter first string: ");
9     scanf("%99s", str1);
10
11    printf("Enter second string: ");
12    scanf("%99s", str2);
13
14    while (str1[i] != '\0') {
15        count[(unsigned char)str1[i]]++;
16        i++;
17    }
18
19    i = 0;
20    while (str2[i] != '\0') {
21        count[(unsigned char)str2[i]]--;
```

```
1 #include <stdio.h>
2
3 int main()
4 {
5     char str[100];
6     int i, j, count;
7
8     scanf("%99s", str);
9
10    for(i = 0; str[i] != '\0'; i++)
11    {
12        count = 0;
13
14        for(j = 0; str[j] != '\0'; j++)
15        {
16            if(str[i] == str[j])
17            {
18                count++;
19            }
20        }
21    }
```

```
1 #include <stdio.h>
2
3 int main()
4 {
5     char str[100];
6     char old, new;
7     int i;
8
9     scanf("%99s", str);
10    scanf(" %c", &old);
11    scanf(" %c", &new);
12
13    for(i = 0; str[i] != '\0'; i++)
14    {
15        if(str[i] == old)
16        {
17            str[i] = new;
18        }
19    }
20
21    printf("%s", str);
```



```
1 #include <stdio.h>
2
3 int main()
4 {
5     char str[100];
6     int start, length, i;
7
8     scanf("%99s", str);
9     scanf("%d", &start);
10    scanf("%d", &length);
11
12    for(i = start; i < start + length; i++)
13    {
14        printf("%c", str[i]);
15    }
16
17    return 0;
18 }
```

```
1 #include <stdio.h>
2
3 int main()
4 {
5     char str[100];
6     int i, j, length = 0, flag = 1;
7
8     scanf("%99s", str);
9
10    while(str[length] != '\0')
11    {
12        length++;
13    }
14
15    i = 0;
16    j = length - 1;
17
18    while(i < j)
19    {
20        if(str[i] != str[j])
21        {
```

```
1 #include <stdio.h>
2
3 int main()
4 {
5     char str[100];
6     int i;
7
8     fgets(str, sizeof(str), stdin);
9
10    for(i = 0; str[i] != '\0'; i++)
11    {
12        if(str[i] != ' ')
13        {
14            printf("%c", str[i]);
15        }
16    }
17
18    return 0;
19 }
```

```
1 #include <stdio.h>
2
3 int main()
4 {
5     char str[100];
6     int i, j, count;
7
8     scanf("%99s", str);
9
10    for(i = 0; str[i] != '\0'; i++)
11    {
12        count = 1;
13
14        if(str[i] == '*')
15            continue;
16
17        for(j = i + 1; str[j] != '\0'; j++)
18        {
19            if(str[i] == str[j])
20            {
21                count++;
```

```
1 #include <stdio.h>
2
3 int main()
4 {
5     char str[100];
6     int i, j, k;
7
8     scanf("%99s", str);
9
10    for(i = 0; str[i] != '\0'; i++)
11    {
12        for(j = i + 1; str[j] != '\0'; j++)
13        {
14            if(str[i] == str[j])
15            {
16                for(k = j; str[k] != '\0'; k++)
17                {
18                    str[k] = str[k + 1];
19                }
20                j--;
21            }
22        }
23    }
```

```
1 #include <stdio.h>
2
3 int main()
4 {
5     char str[100][50], temp[50];
6     int n, i, j, k;
7
8     scanf("%d", &n);
9
10    for(i = 0; i < n; i++)
11    {
12        scanf("%99s", str[i]);
13    }
14
15    for(i = 0; i < n - 1; i++)
16    {
17        for(j = i + 1; j < n; j++)
18        {
19            k = 0;
20
21            while(str[i][k] != '\0' && str[j][k] != '\0' &&
```

```
1 #include <stdio.h>
2
3 int main()
4 {
5     char str[100];
6     int i, vowels = 0, consonants = 0;
7
8     scanf("%99s", str);
9
10    for(i = 0; str[i] != '\0'; i++)
11    {
12        if(str[i] == 'a' || str[i] == 'e' || str[i] == 'i' ||
13            str[i] == 'o' || str[i] == 'u' ||
14            str[i] == 'A' || str[i] == 'E' || str[i] == 'I' ||
15            str[i] == 'O' || str[i] == 'U')
16        {
17            vowels++;
18        }
19        else
20        {
21            consonants++;
22        }
23    }
24}
```

```
1 #include <stdio.h>
2
3 int main()
4 {
5     char str[200], old[50], new[50], result[300];
6     int i, j, k, match;
7
8     scanf("%99s", str);
9     scanf("%99s", old);
10    scanf("%99s", new);
11
12    i = 0;
13    k = 0;
14
15    while(str[i] != '\0')
16    {
17        j = 0;
18        match = 1;
19
20        while(old[j] != '\0')
21        {
```



```
1 #include <stdio.h>
2
3 int main()
4 {
5     char str[200];
6     int i;
7
8     fgets(str, sizeof(str), stdin);
9
10    for(i = 0; str[i] != '\0'; i++)
11    {
12        if((str[i] >= 'A' && str[i] <= 'Z') ||
13            (str[i] >= 'a' && str[i] <= 'z') ||
14            (str[i] >= '0' && str[i] <= '9') ||
15            str[i] == ' ')
16        {
17            printf("%c", str[i]);
18        }
19    }
20
21    return 0;
```

```
1 #include <stdio.h>
2
3 int main()
4 {
5     char str[200];
6     int i, newWord = 1;
7
8     fgets(str, sizeof(str), stdin);
9
10    for(i = 0; str[i] != '\0'; i++)
11    {
12        if(str[i] == ' ')
13        {
14            newWord = 1;
15        }
16        else if(newWord == 1)
17        {
18            if(str[i] >= 'a' && str[i] <= 'z')
19                str[i] = str[i] - 32;
20
21            newWord = 0;
```

```
1 #include <stdio.h>
2
3 int main()
4 {
5     char str[200];
6     int i, length = 0;
7     int maxLength = 0, start = 0, maxStart = 0;
8
9     fgets(str, sizeof(str), stdin);
10
11     for(i = 0; ; i++)
12     {
13         if(str[i] != ' ' && str[i] != '\0' && str[i] != '\n')
14         {
15             length++;
16         }
17         else
18         {
19             if(length > maxLength)
20             {
21                 maxLength = length;
```