MINGW64:/c/Users/janas/my-project/git-demo

```
bash: exoprt: command not found

janas@AsusA15 MINGW64 ~ (master)
$ git config --global user.name "Sujan"

janas@AsusA15 MINGW64 ~ (master)
$ git config --global user.email "janasujan3636@gmail.com"

janas@AsusA15 MINGW64 ~ (master)
$ mkdir my-project
cd my-project
git init
Initialized empty Git repository in C:/Users/janas/my-project/.git/

janas@AsusA15 MINGW64 ~/my-project (master)
$ git clone https://github.com/janasujan3636-stack/git-demo.git
Cloning into 'git-demo'...
remote: Enumerating objects: 3, done.
remote: Counting objects: 100% (3/3), done.
remote: Compressing objects: 100% (3/3), done.
remote: Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
Receiving objects: 100% (3/3), done.

janas@AsusA15 MINGW64 ~/my-project (master)
$ cd git-demo

janas@AsusA15 MINGW64 ~/my-project/git-demo (main)
$ touch file.txt

janas@AsusA15 MINGW64 ~/my-project/git-demo (main)
$ git add file.txt

janas@AsusA15 MINGW64 ~/my-project/git-demo (main)
$ git commit -m "add file.txt"
[main e7c2848] add file.txt
 1 file changed, 0 insertions(+), 0 deletions(-)
 create mode 100644 file.txt

janas@AsusA15 MINGW64 ~/my-project/git-demo (main)
$
```

MINGW64:/c/Users/janas/my-project/git-demo

```
janas@AsusA15 MINGW64 ~/my-project (master)
$ cd git-demo

janas@AsusA15 MINGW64 ~/my-project/git-demo (main)
$ git remote add origin https://github.com/janasujan3636-stack/git-demo.git
error: remote origin already exists.

janas@AsusA15 MINGW64 ~/my-project/git-demo (main)
$ git push -u origin main
Enumerating objects: 4, done.
Counting objects: 100% (4/4), done.
Delta compression using up to 4 threads
Compressing objects: 100% (2/2), done.
Writing objects: 100% (3/3), 297 bytes | 297.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
To https://github.com/janasujan3636-stack/git-demo.git
   8679d3f..e7c2848  main -> main
branch 'main' set up to track 'origin/main'.

janas@AsusA15 MINGW64 ~/my-project/git-demo (main)
$ git pull origin main
From https://github.com/janasujan3636-stack/git-demo
 * branch            main       -> FETCH_HEAD
Already up to date.

janas@AsusA15 MINGW64 ~/my-project/git-demo (main)
$ git checkout -b new-branch
Switched to a new branch 'new-branch'

janas@AsusA15 MINGW64 ~/my-project/git-demo (new-branch)
$ git push -u origin new-branch
Total 0 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
remote:
remote: Create a pull request for 'new-branch' on GitHub by visiting:
remote:      https://github.com/janasujan3636-stack/git-demo/pull/new/new-branch
remote:
To https://github.com/janasujan3636-stack/git-demo.git
 * [new branch]      new-branch -> new-branch
branch 'new-branch' set up to track 'origin/new-branch'.

janas@AsusA15 MINGW64 ~/my-project/git-demo (new-branch)
$ git pull origin main
remote: Enumerating objects: 8, done.
remote: Counting objects: 100% (8/8), done.
remote: Compressing objects: 100% (4/4), done.
remote: Total 7 (delta 0), reused 0 (delta 0), pack-reused 0 (from 0)
Unpacking objects: 100% (7/7), 2.83 KiB | 107.00 KiB/s, done.
From https://github.com/janasujan3636-stack/git-demo
 * branch            main       -> FETCH_HEAD
   e7c2848..e7b7918  main       -> origin/main
Updating e7c2848..e7b7918
Fast-forward
 .github/workflows/main.yml | 1 +
 1 file changed, 1 insertion(+)
 create mode 100644 .github/workflows/main.yml

janas@AsusA15 MINGW64 ~/my-project/git-demo (new-branch)
$ git add .

janas@AsusA15 MINGW64 ~/my-project/git-demo (new-branch)
$ git commit -m "Resolve merge conflicts"
On branch new-branch
Your branch is ahead of 'origin/new-branch' by 3 commits.
  (use "git push" to publish your local commits)

nothing to commit, working tree clean

janas@AsusA15 MINGW64 ~/my-project/git-demo (new-branch)
$
```

