

QA-Deployment with K8S

How to deploy multiple QA environments with the help of K8S

Jan Baer

27. Juli 2020

What we had before

- 3 independent QA environments
- 3 cloned Bamboo plans for deployment
- 3 configuration files with fixed host-urls
- Docker-compose with 68 containers running inside on each host
- Very difficult to add more QA environments
- Hard to investigate when a feature was not deployed correctly

QA Deployment

QA1 VERBU-6224

Build #1283

Progress: 100%

Time: 3 Minutes and 2 seconds

Status: **Successful**

Assigned to

Assigned today at 09:28

UN-ASSIGN

VERBU-JIRA number

↓ DEPLOY TO QA1

QA2 VERBU-6051

Build #1203

Progress: 100%

Time: 2 Minutes and 30 seconds

Status: **Successful**

Environment free

ASSIGN TO ME

VERBU-JIRA number

↓ DEPLOY TO QA2

QA3 VERBU-6166

Build #1254

Progress: 100%

Time: 2 Minutes and 18 seconds

Status: **Successful**

Environment free

ASSIGN TO ME

VERBU-JIRA number

↓ DEPLOY TO QA3

What we wanted to reach

- At least 6 parallel QA environments
- Easier scalable
- Only one config for QA
- Better management and error investigation

QA Deployment

VERBU-JIRA number

CREATE NEW DEPLOYMENT

Feature: [VERBU-6051 \(active\)](#) Created on: 20.07.2020 15:23 (vor einem Tag) Created by:

[BU-DESKTOP](#) [CUSTOMER AREA](#) [GF-DESKTOP](#) [MOBILE](#) [GF MOBILE](#) [CUSTOMER AREA](#) [BUBOT](#) [BU-TARIFF ADMIN](#) [GF-TARIFF ADMIN](#)

[TEMPLE](#) [WALLET](#)

[SHOW DETAILS](#)

Feature: [VERBU-6264 \(active\)](#) Created on: 21.07.2020 11:53 (vor 5 Stunden) Created by:

[BU-DESKTOP](#) [CUSTOMER AREA](#) [GF-DESKTOP](#) [MOBILE](#) [GF MOBILE](#) [CUSTOMER AREA](#) [BUBOT](#) [BU-TARIFF ADMIN](#) [GF-TARIFF ADMIN](#)

[TEMPLE](#) [WALLET](#)

[SHOW DETAILS](#)

Feature: [VERBU-6119 \(active\)](#) Created on: 21.07.2020 14:31 (vor 5 Stunden) Created by:

[BU-DESKTOP](#) [CUSTOMER AREA](#) [GF-DESKTOP](#) [MOBILE](#) [GF MOBILE](#) [CUSTOMER AREA](#) [BUBOT](#) [BU-TARIFF ADMIN](#) [GF-TARIFF ADMIN](#)

[TEMPLE](#) [WALLET](#)

[HIDE DETAILS](#)

communicator	nexus.intern.bu.check24.de:5000/docker/communicator:VERBU-6119_latest	restartCount: 0	status: active
desktop-wui	nexus.intern.bu.check24.de:5000/docker/desktop-apt:VERBU-6119_latest	restartCount: 0	status: active
desktop-app	nexus.intern.bu.check24.de:5000/docker/desktop-app:VERBU-6119_latest	restartCount: 0	status: active
wallet	nexus.intern.bu.check24.de:5000/docker/wallet:master_latest	restartCount: 0	status: active
u-tipper	nexus.intern.bu.check24.de:5000/docker/u-tipper:master_latest	restartCount: 0	status: active
tofu	nexus.intern.bu.check24.de:5000/docker/tofu:master_latest	restartCount: 0	status: active

K3s is a fully compliant Kubernetes distribution with the following enhancements:


- Packaged as a single binary. (less than 100 MB.)
- Lightweight storage backend based on sqlite3 as the default storage mechanism. etcd3, MySQL, Postgres also still available.
- Wrapped in simple launcher that handles a lot of the complexity of TLS and options.
- Secure by default with reasonable defaults for lightweight environments.

- Simple but powerful “batteries-included” features have been added, such as: a local storage provider, a service load balancer, a Helm controller, and the Traefik ingress controller.
- Operation of all Kubernetes control plane components is encapsulated in a single binary and process. This allows K3s to automate and manage complex cluster operations like distributing certificates.
- External dependencies have been minimized (just a modern kernel and cgroup mounts needed).

- Containerd
- Flannel
- CoreDNS
- CNI
- Host utilities (iptables, socat, etc)
- Ingress controller (traefik)
- Embedded service loadbalancer
- Embedded network policy controller

- Uses per default Containerd as container-engine
- Can use alternatively Docker, but it's not required
- Run's as a Server and a Node on the same machine
- But also as Server(s) and Node(s) on separate machines
- You need at least one Server and one Node
- For high availability K3s supports a cluster of multiple servers

The architecture of K3s



Install K3s is very easy

Install the server

```
3 K3S_DATA_DIR=/data/k3s ↵
4 ↵
5 export K3S_KUBECONFIG_MODE=644 ↵
6 export K3S_TOKEN="qa-k3s-cluster-1" ↵
7 ↵
8 export INSTALL_K3S_EXEC="server --docker --data-dir ${K3S_DATA_DIR}"
9 ↵
10 curl -sL https://get.k3s.io | sh - ↵
```

Install the agent

```
export K3S_TOKEN="qa-k3s-cluster-1" ↵
↵
K3S_URL="https://10.10.10.1:6443" ↵
K3S_DATA_DIR=/data/k3s ↵
↵
export INSTALL_K3S_EXEC="agent --server ${K3S_URL} --data-dir ${K3S_DATA_DIR} --docker"
↵
curl -sL https://get.k3s.io | sh ↵
```

K3s will be installed as Systemd service

Server

```
• k3s.service - Lightweight Kubernetes
  Loaded: loaded (/etc/systemd/system/k3s.service; enabled; vendor preset: enabled)
  Active: active (running) since Sat 2020-07-11 12:32:12 CEST; 2 weeks 2 days ago
    Docs: https://k3s.io
  Main PID: 1232 (k3s-server)
    Tasks: 0
   CGroup: /system.slice/k3s.service
           └─1232 /usr/local/bin/k3s server --docker --node-label agent-type=server --data-dir /data/k3s
```


Agent

```
• k3s-agent.service - Lightweight Kubernetes
  Loaded: loaded (/etc/systemd/system/k3s-agent.service; enabled; vendor preset: enabled)
  Active: active (running) since Fri 2020-07-24 15:50:56 CEST; 3 days ago
    Docs: https://k3s.io
  Main PID: 1328 (k3s-agent)
    Tasks: 0
   CGroup: /system.slice/k3s-agent.service
           └─1328 /usr/local/bin/k3s agent --docker --node-label agent-type=worker --data-dir /data/k3s
```

The whole K3s cluster

<input type="checkbox"/> State	Name	Roles	Version	CPU	RAM	Pods
<input type="checkbox"/> Active	bu-int-k8s-node-01 172.30.136.197 <small>agent-type=worker</small>	Worker	v1.18.3-k3s1 <small>19.3.11</small>	0.9/4 Cores	1.7/7.8 GiB	36/110
<input type="checkbox"/> Active	bu-int-k8s-node-02 172.30.136.198 <small>agent-type=worker</small>	Worker	v1.18.3-k3s1 <small>19.3.11</small>	0.9/4 Cores	1.6/7.8 GiB	34/110
<input type="checkbox"/> Active	bu-int-k8s-node-03 172.30.136.199 <small>agent-type=worker</small>	Worker	v1.18.3-k3s1 <small>19.3.11</small>	0.9/4 Cores	1.1/7.8 GiB	24/110
<input type="checkbox"/> Active	bu-int-k8s-node-04 172.30.136.200 <small>agent-type=worker</small>	Worker	v1.18.3-k3s1 <small>19.3.11</small>	0.8/4 Cores	1.7/7.8 GiB	37/110
<input type="checkbox"/> Active	bu-int-k8s-node-05 172.30.136.205 <small>agent-type=worker</small>	Worker	v1.18.3-k3s1 <small>19.3.11</small>	0.6/4 Cores	1/7.8 GiB	23/110
<input type="checkbox"/> Active	bu-int-k8s-server-01 172.30.136.196 <small>agent-type=server</small>	Control Plane	v1.18.3-k3s1 <small>19.3.11</small>	0.1/2 Cores	0.1/3.9 GiB	7/110

How is it working together



What problems we had to solve

- Dynamic creation of urls
- Improve first-deployment and update and cleanup times
- Waiting for depending services (NSQ)
- Find the right limits
- Rewriting urls

Dynamic creation of urls

Use placeholders in config files

```
{
  "env": "qa",
  "origin": "https://services- $\{feature\}$ .qa.bu.check24-test.de",
  "services": {
    "auth": "https://services- $\{feature\}$ .qa.bu.check24-test.de/auth",
    "ripple": "https://services- $\{feature\}$ .qa.bu.check24-test.de/ripple",
    "miami": "https://services- $\{feature\}$ .qa.bu.check24-test.de/miami",
    "customerActivities": "https://services- $\{feature\}$ .qa.bu.check24-test"
  }
}
```

Set feature as environment variable

Environment Variables Environment Variables that were added at creation.	
Key ↕	Value ↕
NODE_MAX_PROCESSES	1
NODE_ENV	qa
FQDN	services-verbu-6202.qa.bu.check24-test.de
FEATURE	verbu-6202

Improve deployment times

- First deployment takes a while because it requires to deploy ~70 Pods
- Only update what has changed

Feature: VERBU-6202 (active) Created on: 23.07.2020 16:53 (vor 4 Tagen) Created by: Teresa Heiss

UPDATE DEPLOYMENT REMOVE DEPLOYMENT

BU-DESKTOP CUSTOMER AREA GF-DESKTOP MOBILE GF MOBILE CUSTOMER AREA BLBOT BU-TARIFF ADMIN GF-TARIFF ADMIN

TEMPLATE WALLET

HIDE DETAILS

buBot insurance-application-requests	nexus.intern.bu.check24.de:5000/docker/buBot-insurance-application-requests-VERBU-6202_latest	restartCount: 0	status: updating
desktop-api	nexus.intern.bu.check24.de:5000/docker/desktop-api-VERBU-6202_latest	restartCount: 0	status: updating
desktop-web	nexus.intern.bu.check24.de:5000/docker/desktop-api-VERBU-6202_latest	restartCount: 0	status: updating
insurance-application-requests-api	nexus.intern.bu.check24.de:5000/docker/insurance-application-requests-api-VERBU-6202_latest	restartCount: 0	status: updating
latest	nexus.intern.bu.check24.de:5000/docker/insurance-application-requests-api-VERBU-6202_latest	restartCount: 0	status: updating
mobile-app	nexus.intern.bu.check24.de:5000/docker/mobile-app-VERBU-6202_latest	restartCount: 0	status: updating
tda	nexus.intern.bu.check24.de:5000/docker/tda-VERBU-6202_latest	restartCount: 0	status: updating
wallet	nexus.intern.bu.check24.de:5000/docker/wallet-master_latest	restartCount: 0	status: active
u-ripper	nexus.intern.bu.check24.de:5000/docker/u-ripper-master_latest	restartCount: 0	status: active

- No graceful shutdown reduces deletion time
- ```
terminationGracePeriodSeconds: 0
```

# Waiting for dependent services

- Some of the services requiring a running NSQ service

```
<% if (requiresNsq) { %>
initContainers:
- - - name: wait-for-nsq
- - - image: subfuzion/netcat
- - - command: ['sh', '-c', 'while ! nc -z nsqd 4151; do sleep 0.5; done']
<% } %>
```

| State           | Name                           | Image                                                     | Restarts |
|-----------------|--------------------------------|-----------------------------------------------------------|----------|
| Waiting         | brain                          | nexus.intern.bu.check24.de:5000/docker/brainmaster_latest | 0        |
| PodInitializing |                                |                                                           |          |
| Waiting         | wait-for-nsq<br>Init Container | subfuzion/netcat                                          | 0        |
| PodInitializing |                                |                                                           |          |

# Finding the right limits

- Observe a deployment to know what resources are required

```
➤ watch -n 2 -t kubectl top pods -n verbu-6202
```

| NAME                                                  | CPU(cores) | MEMORY(bytes) |
|-------------------------------------------------------|------------|---------------|
| accounting-api-5588fc9678-pd57h                       | 2m         | 65Mi          |
| acid-6c84c7dff-cdm52                                  | 1m         | 63Mi          |
| addressservice-5b5bf7f4c7-4npfw                       | 1m         | 97Mi          |
| auth-cb4c45b5b-522f5                                  | 9m         | 62Mi          |
| auth-ui-6cccc7b664-kwgq5                              | 1m         | 80Mi          |
| brain-5c85f89b47-l6hlw                                | 2m         | 64Mi          |
| bu-cleanup-fd45f8b85-4x75f                            | 1m         | 68Mi          |
| bubot-748c6b76cb-tpwqx                                | 12m        | 110Mi         |
| bubot-accounting-55bf8c85cf-7fc9w                     | 1m         | 70Mi          |
| bubot-appointments-6796479ccb-khst9                   | 1m         | 93Mi          |
| bubot-consulting-process-6646dd9665-t9fzp             | 1m         | 88Mi          |
| bubot-documents-5fcd6f856-ksc5g                       | 24m        | 105Mi         |
| bubot-insurance-application-requests-66b787796b-97rzd | 1m         | 96Mi          |
| bubot-mailing-5666f7dcc5-vvmxk                        | 1m         | 88Mi          |
| bubot-rivo-586dd8f69b-zgxx7                           | 1m         | 71Mi          |
| bubot-salary-6cf7f5d85f-lh929                         | 1m         | 67Mi          |
| bus-5b86d84798-8xpfg                                  | 1m         | 49Mi          |
| coachman-94d74db9c-vd4sz                              | 22m        | 76Mi          |
| communicator-7cd7d4968b-zk7rp                         | 1m         | 74Mi          |
| consulting-process-api-549fcb8986-r8zzb               | 5m         | 66Mi          |

## Some urls has to be changed

- Remove /eventbus from the url before forwarding to NSQ service

```
apiVersion: networking.k8s.io/v1beta1
kind: Ingress
metadata:
 annotations:
 kubernetes.io/ingress.class: traefik
 traefik.frontend.rule.type: PathPrefixStrip
 name: ingress-eventbus
 namespace: <%= namespace %>
spec:
 rules:
 - host: <%= host %>
 http:
 paths:
 - backend:
 serviceName: <%= name %>
 servicePort: <%= port %>
 path: <%= path %>
 tls:
 - hosts:
 - <%= host %>
```

- One MongoDB per feature deployment
- Improve visualisation of the deployment state

## Which problems we still have

- Too many pods for every feature deployment
- Deployment becomes unstable after the 6th deployment and it's unclear why

Questions?

Thank you!