

file_188_189.docx

eigenpal/docx-editor

Project Charter & Contributor Agreement

npm [@eigenpal/docx-js-editor](#)

github [eigenpal/docx-editor](#)

1. What this is

An open-source WYSIWYG .docx editor for React. Drop in `<DocxEditor documentBuffer={file} />` and your users can open, edit, and save Word documents entirely in the browser — no backend required —, no document data leaving the client.

Most editors serialise to HTML and back: `DOCX → HTML → edits → HTML → DOCX`. Every hop loses formatting, tracked changes, and styles. This library skips it — OOXML is the canonical format throughout.

```
import { DocxEditor } from '@eigenpal/docx-js-editor'
import '@eigenpal/docx-js-editor/styles.css'

function App({ file }: { file: ArrayBuffer }) {
  return (
    <DocxEditor
      documentBuffer={file}
      onSave={({buffer}) => uploadToServer(buffer)}
    />
  )
}
```

2. Collaboration — Tracked Changes & Comments

Both features round-trip through OOXML so documents open correctly in Word, LibreOffice, and Google Docs.

Suggestion mode

Toggle between **Editing** **Strikethrough** **Blue Demo** and **Suggesting** via the toolbar dropdown. In Suggesting mode, every edit becomes a tracked insertion (**green underline**) or deletion (**red strikethrough**). Consecutive keystrokes group into a single change. Accept or reject individually or all at once.

This document uses Editing mode with strikethrough and blue font color.

Blue strikethrough in Editing mode marks deleted content for revision.

Serialises to `<w:ins />` the same OOXML markup Word uses. Tracked changes survive a save/reload cycle and are reviewable in Word with full accept/reject UI.

Comments

Select text and click the floating button on the page edge to add a comment anchored to that selection. A Google Docs-style sidebar shows threaded cards positioned at their anchor point in the document. Reply, resolve, reopen, or delete inline.

Serialises to `<comments.xml>` with `<w:commentRangeStart />` `<w:commentRangeEnd>` markers. Comments and reply threads are preserved on round-trip.

Agent-friendly

Because tracked changes and comments are native OOXML, an AI agent can write `<w:ins />` `<w:del />` `<w:comment>` markup directly into a document and hand it to `<DocxEditor />` for human review — no custom diff format, no proprietary API.

3. Props

Pass `author="Your App"` to set the author name for comments and tracked changes. Toggle suggestion mode via the toolbar dropdown.

Prop	Type	Default	Description
documentBuffer	ArrayBuffer	—	.doex file contents to load
readOnly	boolean	false	Preview mode — no editing UI
showToolbar	boolean	true	Show formatting toolbar
author	string	'User'	Author name for comments and tracked changes
onChange	function	—	Called on every document change
onSave	function	—	Called on save, receives ArrayBuffer
onError	function	—	Called on error

Ref methods

```
const ref = useRef<DocxEditorRef>(null)

await ref.current.save() // ArrayBuffer of the .docx
ref.current.getDocument() // current document object
ref.current.setZoom(1.5) // set zoom to 150%
ref.current.scrollToPage(3) // scroll to page 3
ref.current.print() // print
```

4. Contributing

Read [docs/PLUGINS.md](#) before opening a pull request that touches the plugin API.

Ground rules

- Every PR must pass the round-trip test: load a .docx, apply an edit, export, reload — content and formatting must be stable on unchanged content.
- Run `bun test` and `bun run test:e2e` locally before pushing.
- Avoid intermediate HTML serialisation where possible.
- Tracked changes and comments must survive a full OOXML round-trip — save, open in Word, verify changes are reviewable, reload in the editor.

Dev setup

```
bun install
bun run dev // Vite demo on localhost:5173
```

Sign-off

EigenPal

Maintainer: eigenpal.com

Contributor

on behalf of the community

signature — date

signature — date