

file 147 146.docx

Bold Underline Highlight Demo

This document shows bold, underline, and yellow highlight combined.

This triple combination is used for critical review

annotations. eigenpal/docx-editor

Project Charter & Contributor Agreement

npm [@eigenpal/docx-js-editor](#)

github [eigenpal/docx-editor](#)

1. What this is

An open-source WYSIWYG .docx editor for React. Drop in `<DocxEditor documentBuffer={file} />` and your users can open, edit, and save Word documents entirely in the browser — no backend required —, no document data leaving the client.

Most editors serialise to HTML and back: `DOCX → HTML → edits → HTML → DOCX`. Every hop loses formatting, tracked changes, and styles. This library skips it — OOXML is the canonical format throughout.

```
import { DocxEditor } from '@eigenpal/docx-js-editor'
import '@eigenpal/docx-js-editor/styles.css'

function App({ file }: { file: ArrayBuffer }) {
  return (
    <DocxEditor
      documentBuffer={file}
      onSave={({buffer}) => uploadToServer(buffer)}
    />
  )
}
```

2. Collaboration — Tracked Changes & Comments

Both features round-trip through OOXML so documents open correctly in Word, LibreOffice, and Google Docs.

Suggestion mode

Toggle between Editing and Suggesting via the toolbar dropdown. In Suggesting mode, every edit becomes a tracked insertion (green underline) or deletion (red underline).

~~red strikethrough~~). Consecutive keystrokes group into a single change. Accept or reject individually or all at once.

Serialises to ~~w:ins~~ / ~~w:del~~ the same OOXML markup Word uses. Tracked changes survive a save/reload cycle and are reviewable in Word with full accept/reject UI.

Comments

Select text and click the floating button on the page edge to ~~add a comment anchored to that selection~~. A Google Docs-style sidebar shows threaded cards positioned at their anchor point in the document. Reply, resolve, reopen, or delete inline.

Serialises to ~~comments.xml~~ with ~~w:commentRangeStart~~ / ~~w:commentRangeEnd~~ markers. Comments and reply threads are preserved on round-trip.

Agent-friendly

Because tracked changes and comments are native OOXML, an AI agent can write ~~w:ins~~ / ~~w:del~~ / ~~w:comment~~ markup directly into a document and hand it to `<DocxEditor />` for human review — no custom diff format, no proprietary API.

3. Props

Pass ~~author="Your App"~~ to set the author name for comments and tracked changes. Toggle suggestion mode via the toolbar dropdown.

Prop	Type	Default	Description
documentBuffer	ArrayBuffer	—	.doex file contents to load
readOnly	boolean	false	Preview mode — no editing UI
showToolbar	boolean	true	Show formatting toolbar
author	string	'User'	Author name for comments and tracked changes
onChange	function	—	Called on every document change
onSave	function	—	Called on save, receives ArrayBuffer
onError	function	—	Called on error

Ref methods

```
const ref = useRef<DocxEditorRef>(null)

await ref.current.save() // ArrayBuffer of the .docx
ref.current.getDocument() // current document object
ref.current.setZoom(1.5) // set zoom to 150%
ref.current.scrollToPage(3) // scroll to page 3
ref.current.print() // print
```

4. Contributing

2. Collaboration—Tracked Changes & Comments

Both features round-trip through OOXML so documents open correctly in Word, LibreOffice, and Google Docs.

Suggestion mode

Toggle between `Editing` and `Suggesting` via the toolbar dropdown. In Suggesting mode, every edit becomes a tracked insertion (`green underline`) or deletion (`red strikethrough`). Consecutive keystrokes group into a single change. Accept or reject individually or all at once.

Serialises to `w:ins` / `w:del` the same OOXML markup Word uses. Tracked changes survive a save/reload cycle and are reviewable in Word with full accept/reject UI.

Comments

Select text and click the floating button on the page edge to `add a comment anchored to that selection`. A Google Docs-style sidebar shows threaded cards positioned at their anchor point in the document. Reply, resolve, reopen, or delete inline.

Serialises to `comments.xml` with `w:commentRangeStart` / `w:commentRangeEnd` markers. Comments and reply threads are preserved on round-trip.

Agent-friendly

Because tracked changes and comments are native OOXML, an AI agent can write `w:ins` / `w:del` / `w:comment` markup directly into a document and hand it to `<DocxEditor />` for human review — no custom diff format, no proprietary API.

3. Props