

[file 4241.docx](#)

Blue Underline Combo Demo

This document combines blue font color with underline.

Blue underlinedOOXML w:b (bold) tester: ST_OnOff variants, rStyle-only cases, rStyle + inline overrides, and a linked style pair (paragraph+character) to verify behavior.

A) ST_OnOff values for <w:b> on a run:

— w:b w:val=(w:val omitted): **Sample text** resembles hyperlinks

— w:b w:val=true: **Sample text**

— w:b w:val=1: **Sample text**

— w:b w:val=on: **Sample text**

— w:b w:val=false: Sample text

— w:b w:val=0: Sample text

— w:b w:val=off: Sample text

B) rStyle-only cases (no inline <w:b>):

— rStyle='SD_BoldChar' (should be bold): **Sample via SD_BoldChar**

— rStyle='Strong' (built-in documents.bold): **Sample via Strong**

— rStyle='SD_PlainChar' (not bold): Sample via SD_PlainChar

C) rStyle + inline <w:b> combinations (inline overrides style):

— rStyle='SD_BoldChar' + <w:b w:val='0'> => expect NOT bold: Styled bold, overridden off

— rStyle='SD_BoldChar' + <w:b w:val='1'> => expect bold: **Styled bold, reinforced on**

— rStyle='SD_PlainChar' + <w:b w:val='on'> => expect bold: **Plain style, inline turns bold on**

— rStyle='Strong' + <w:b w:val='off'> => expect NOT bold: Strong style, explicit bold off

— rStyle='Strong' + <w:b w:val='true'> => expect bold: **Strong style, inline bold on**

D) Linked style (paragraph+character) demonstrations:

~~--rStyle='SD_LinkedHeadingChar' (character side of linked pair) => expect bold: **Linked Char style applied to run**~~

~~--rStyle='SD_LinkedHeadingChar' + <w:b w:val='0'> => expect NOT bold: Linked Char style overridden off~~

~~--pStyle='SD_LinkedHeading' + inline <w:b w:val='0'>: Paragraph style makes text bold, but inline turns it off here~~

~~--pStyle='SD_LinkedHeading' (no inline) => expect bold: All runs inherit bold from the paragraph style~~

Table examples (linked style + inline overrides):

rStyle='SD_LinkedHeadingChar' (no inline) **Should be bold**

rStyle='SD_LinkedHeadingChar' + w:b='0' Should NOT be bold