

Open Sans Bold Underline Demo

This document shows Open Sans font with bold and underline.

Open Sans bold underline creates a distinctive modern heading style.OOXML-w:b (bold) tester: ST_OnOff variants, rStyle-only cases, rStyle + inline overrides, and a linked style pair (paragraph+character) to verify behavior.

A) ST_OnOff values for <w:b> on a run:

—w:b w:val=(w:val omitted): **Sample text**

—w:b w:val=true: **Sample text**

—w:b w:val=1: **Sample text**

—w:b w:val=on: **Sample text**

—w:b w:val=false: Sample text

—w:b w:val=0: Sample text

—w:b w:val=off: Sample text

B) rStyle-only cases (no inline <w:b>):

—rStyle='SD_BoldChar' (should be bold): **Sample via SD_BoldChar**

—rStyle='Strong' (built-in bold): **Sample via Strong**

—rStyle='SD_PlainChar' (not bold): Sample via SD_PlainChar

C) rStyle + inline <w:b> combinations (inline overrides style):

—rStyle='SD_BoldChar' + <w:b w:val='0'>=> expect NOT bold: Styled bold, overridden off

—rStyle='SD_BoldChar' + <w:b w:val='1'>=> expect bold: **Styled bold, reinforced on**

—rStyle='SD_PlainChar' + <w:b w:val='on'>=> expect bold: **Plain style, inline turns bold on**

—rStyle='Strong' + <w:b w:val='off'>=> expect NOT bold: Strong style, explicit bold off

—rStyle='Strong' + <w:b w:val='true'>=> expect bold: **Strong style, inline bold on**

D) Linked style (paragraph+character) demonstrations:

—rStyle='SD_LinkedHeadingChar' (character side of linked pair) => expect bold: **Linked Char style applied to run**

—rStyle='SD_LinkedHeadingChar' + <w:b w:val='0'> => expect NOT bold: Linked Char style overridden off

—pStyle='SD_LinkedHeading' + inline <w:b w:val='0'>: Paragraph style makes text bold, but inline turns it off here

—pStyle='SD_LinkedHeading' (no inline) => expect bold: **All runs inherit bold from the paragraph style**

Table examples (linked style + inline overrides):

rStyle='SD_LinkedHeadingChar' (no inline)	Should be bold
rStyle='SD_LinkedHeadingChar' + w:b='0'	Should NOT be bold