

# eigenpal/docx-editor

## Project Charter & Contributor Agreement

|     |                                          |        |                                      |
|-----|------------------------------------------|--------|--------------------------------------|
| npm | <a href="#">@eigenpal/docx-js-editor</a> | github | <a href="#">eigenpal/docx-editor</a> |
|-----|------------------------------------------|--------|--------------------------------------|

### 1. What this is

An open-source WYSIWYG `.docx` editor for React. Drop in `<DocxEditor` `documentBuffer={file} />` and your users can open, edit, and save Word documents entirely in the browser — no backend required, no document data leaving the client.

Most editors serialise to HTML and back: `DOCX → HTML → edits → HTML → DOCX`. Every hop loses formatting, tracked changes, and styles. This library skips it — OOXML is the canonical format throughout.

```
import { DocxEditor } from '@eigenpal/docx-js-editor'
import '@eigenpal/docx-js-editor/styles.css'

function App({ file }: { file: ArrayBuffer }) {
  return (
    <DocxEditor
      documentBuffer={file}
      onSave={buffer => uploadToServer(buffer)}
    />
  )
}
```

### 2. Collaboration — Tracked Changes & Comments

Both features round-trip through OOXML so documents open correctly in Word, LibreOffice, and Google Docs.

#### Suggestion mode

Toggle between `Editing` and `Suggesting` via the toolbar dropdown. In Suggesting mode, every edit becomes a tracked insertion ( `green underline` ) or deletion ( `red strikethrough` ). Consecutive keystrokes group into a single change. Accept or reject individually or all at once.

Serialises to `w:ins` / `w:del` — the same OOXML markup Word uses. Tracked changes survive a save/reload cycle and are reviewable in Word with full accept/reject UI.

#### Comments

Select text and click the floating button on the page edge to **add a comment anchored to that selection**. A Google Docs-style sidebar shows threaded cards positioned at their anchor point in the document. Reply, resolve, reopen, or delete inline.

Serialises to `comments.xml` with `w:commentRangeStart` / `w:commentRangeEnd` markers. Comments and reply threads are preserved on round-trip.

Agent-friendly

Because tracked changes and comments are native OOXML, an AI agent can write `w:ins` / `w:del` / `w:comment` markup directly into a document and hand it to `<DocxEditor />` for human review — no custom diff format, no proprietary API.

3. Props

Pass `author="Your App"` to set the author name for comments and tracked changes. Toggle suggestion mode via the toolbar dropdown.

| Prop                        | Type                     | Default             | Description                                       |
|-----------------------------|--------------------------|---------------------|---------------------------------------------------|
| <code>documentBuffer</code> | <code>ArrayBuffer</code> | —                   | .docx file contents to load                       |
| <code>readOnly</code>       | <code>boolean</code>     | <code>false</code>  | Preview mode — no editing UI                      |
| <code>showToolbar</code>    | <code>boolean</code>     | <code>true</code>   | Show formatting toolbar                           |
| <code>author</code>         | <code>string</code>      | <code>'User'</code> | Author name for comments and tracked changes      |
| <code>onChange</code>       | <code>function</code>    | —                   | Called on every document change                   |
| <code>onSave</code>         | <code>function</code>    | —                   | Called on save, receives <code>ArrayBuffer</code> |
| <code>onError</code>        | <code>function</code>    | —                   | Called on error                                   |

Commented [1]: Just like that!

Commented [2]: Just like that!

### Ref methods

```
const ref = useRef<DocxEditorRef>(null)

await ref.current.save() // ArrayBuffer of the .docx
ref.current.getDocument() // current document object
ref.current.setZoom(1.5) // set zoom to 150%
ref.current.scrollToPage(3) // scroll to page 3
ref.current.print() // print
```

## 4. Contributing

Read [docs/PLUGINS.md](#) before opening a pull request that touches the plugin API.

### Ground rules

- Every PR must pass the round-trip test: load a .docx, apply an edit, export, reload — content and formatting must be stable on unchanged content.
- Run `bun test` and `bun run test:e2e` locally before pushing.
- Avoid intermediate HTML serialisation where possible.
- Tracked changes and comments must survive a full OOXML round-trip — save, open in Word, verify changes are reviewable, reload in the editor.

### Dev setup

```
bun install
bun run dev // Vite demo on localhost:5173
```

## Sign-off

### EigenPal

Maintainer · eigenpal.com

signature · date

### Contributor

on behalf of the community

signature · date