

~~This document demonstrates all valid OOXML `w:b` (bold) tester: ST_OnOff variants, rStyle-only cases, rStyle + inline overrides, and a linked style pair (paragraph+character) to verify behavior.~~

~~A) ST_OnOff values for the `<w:b (bold)>` on a run property in OOXML. Each line shows the exact w:val used and the resulting rendering.:~~

~~—w:b w:val=(~~w:val~~ omitted): **Sample text**~~

~~—w:b w:val=true: **Sample text**~~

~~—w:b w:val=1: **Sample text**~~

~~—w:b w:val=on: **Sample text**~~

~~—w:b w:val=false: Sample text~~

~~—w:b w:val=0: Sample text~~

~~—w:b w:val=off: Sample text~~

~~B) rStyle-only cases (no inline `<w:b>`):~~

~~—rStyle='SD_BoldChar' (should be bold): **Sample via SD_BoldChar**~~

~~—rStyle='Strong' (built-in bold): **Sample via Strong**~~

~~—rStyle='SD_PlainChar' (not bold): Sample via SD_PlainChar~~

~~C) rStyle + inline `<w:b>` combinations (inline overrides style):~~

~~—rStyle='SD_BoldChar' + `<w:b w:val='0'>` => expect NOT bold: Styled bold, overridden off~~

~~—rStyle='SD_BoldChar' + `<w:b w:val='1'>` => expect bold: **Styled bold, reinforced on**~~

~~—rStyle='SD_PlainChar' + `<w:b w:val='on'>` => expect bold: **Plain style, inline turns bold on**~~

~~—rStyle='Strong' + `<w:b w:val='off'>` => expect NOT bold: Strong style, explicit bold off~~

~~—rStyle='Strong' + `<w:b w:val='true'>` => expect bold: **Strong style, inline bold on**~~

~~D) Linked style (paragraph+character) demonstrations:~~

~~—rStyle='SD_LinkedHeadingChar' (character side of linked pair) => expect bold: **Linked Char style applied to run**~~

—~~rStyle='SD_LinkedHeadingChar' + <w:b w:val='0'>=> expect NOT bold: Linked Char style overridden off~~

—~~pStyle='SD_LinkedHeading' + inline <w:b w:val='0'>: Paragraph style makes text bold, but inline turns it off here~~

—~~pStyle='SD_LinkedHeading' (no inline)=> expect bold: All runs inherit bold from the paragraph style~~

Table examples: ~~(linked style + inline overrides):~~

<u>Omitted</u>	val='off' (not	Should be	<u>val='1' (bold)</u>
<u>(bold)</u>	rStyle='SD_LinkedHeadingChar' (no	bold)	
	inline)		

rStyle='SD_LinkedHeadingChar' + w:b='0'	Should NOT be bold
---	--------------------