

OOXML w:b (bold)highlight tester:—enumerates ST_OnOff variantsHighlightColor values, rStyle-only cases, rStyle +highlights, inline overrides, and a linked style pair (paragraph+character) to verify behaviorstyles.

A) ST_OnOff values for <w:b> on a runhighlight> values:

- w:bhighlight w:val=(='yellow': Highlight sample
- w:highlight w:val omitted): Sample text='green': Highlight sample
- w:bhighlight w:val=true: Sample text='cyan': Highlight sample
- w:bhighlight w:val=1: Sample text='magenta': Highlight sample
- w:bhighlight w:val=on: Sample text='blue': Highlight sample
- w:bhighlight w:val=false: Sample text='red': Highlight sample
- w:bhighlight w:val=0: Sample text='darkYellow': Highlight sample
- w:bhighlight w:val=off: Sample text='darkGreen': Highlight sample
- w:highlight w:val='darkCyan': Highlight sample
- w:highlight w:val='darkMagenta': Highlight sample
- w:highlight w:val='darkBlue': Highlight sample
- w:highlight w:val='darkRed': Highlight sample
- w:highlight w:val='darkGray': Highlight sample
- w:highlight w:val='lightGray': Highlight sample
- w:highlight w:val='black': Highlight sample
- w:highlight w:val='white': Highlight sample
- w:highlight w:val='none': Highlight sample

B) rStyle-only cases (no inline <w:b>):(character style sets highlight):

- rStyle='SD_BoldChar' (should be bold): Sample via SD_BoldCharHighlightYellowChar': Styled yellow highlight
- rStyle='Strong' (built-in bold): Sample via Strong
- rStyle='SD_PlainChar' (not bold): Sample via SD_PlainCharHighlightLightGrayChar': Styled lightGray highlight

—rStyle='SD_HighlightNoneChar': Styled none (no highlight)

C) rStyle + inline <w:b> combinationshighlight> (inline overrides style):

- rStyle='SD_BoldChar' + <w:b w:val='0'>HighlightYellowChar' + inline 'none' => expect NOT bold: Styled bold, no highlight: Yellow style overridden offto none

- rStyle='SD_BoldChar' + <w:b w:val='1'> => expect bold: Styled bold, reinforced on

- rStyle='SD_PlainChar' + <w:b w:val='on'> => expect bold: Plain style, inline turns bold on

- rStyle='Strong' + <w:b w:val='off'> => expect NOT bold: Strong style, explicit bold off

- rStyle='Strong' + <w:b w:val='true'> => expect bold: StrongHighlightNoneChar' + inline 'darkBlue' => expect darkBlue: None style, inline bold onoverridden to darkBlue

D) Linked style pair (paragraph+character) demonstrationswith highlight:

- rStyle='SD_LinkedHeadingChar' (character side of linked pair) => expect boldLinkedHighlightHeadingChar' => yellow: Linked Char style applied to run

- rStyle='SD_LinkedHeadingChar' + <w:b w:val='0'> => expect NOT bold: Linked Char style overridden off

- pStyle='SD_LinkedHeading'LinkedHighlightHeading' (lightGray) + inline <w:b w:val='0'>: Paragraph style makes text bold, but inline turns it off here

- pStyle='SD_LinkedHeading' (no inline) => expect bold: All runs inherit bold from the 'red' on a run: This part should be red highlight overriding paragraph style

Table examples (linked style + inline overridesmixed highlight):

rStyle='SD_LinkedHeadingChar' (no inline)Yellow Should be boldYellow cell

rStyle='SD_LinkedHeadingChar' + w:b='0'None Should NOT be boldDarkMagenta cell
+ inline darkMagenta