



DATA CAPABILITY STATEMENT v2.0

ADISA Data Capability Statement *This table shows the Data Sanitisation Capabilities of the service provider being audited. These capabilities have been verified as being able to be delivered by the service provider themselves. This does not make these services approved as each customer should specify their preferred data sanitisation process after a risk assessment process.*

<u>On client site</u>		<u>Media Type</u>	<u>At processing facility</u>	
<u>Reuse</u>	<u>Destruction</u>	-	<u>Reuse</u>	<u>Destruction</u>
<u>Here you would add what software tool , version number of the product used to sanitise the assets on client site</u> -	<u>Here you would add what method used to destroy the assets the assets on client site eg. Shred to 6mm</u>	<u>Magnetic Hard Disk Drives</u>	<u>Here you would add what software tool, version number of the product used to sanitise the assets at your facility</u>	<u>Here you would add what method used to destroy the assets at your facility eg. Shred to 6mm</u>
		<u>Solid State Hard Drives</u>		
-		<u>Smart Phones</u>		
		<u>Hybrid Disk Drives</u>		
-		<u>Networking Devices such as Switches, Routers etc</u>		
	-	<u>Printers, Copiers and Multi-function devices</u>		
-		<u>Magnetic Tapes</u>		

-		<u>Optical Disks</u>		
-		<u>Removable Media such as USB</u>		

Combi-Steamer with 10 levels 2/1 GN electric

Description:

Combi-steamer according to DIN 18866 for most cooking methods used in commercial kitchens for the optional use of steam and convection, individually, sequentially or combined. Capacity 2/1, 1/1 GN-containers

Technical design:

- ~~Convection mode from 30°C to 300°C.~~
- ~~Steam mode from 30°C to 130°C.~~
- ~~Combination of Convection and steam from 30°C to 300°C.~~
- ~~Steam generator with automatic cleaning and descaling.~~
- ~~Automatic cooking system with time or core temperature-controlled processes, load detection and load-dependent adaption of the cooking process.~~
- ~~Automatic cooking processes for low temperature cooking, delta-T cooking and braising with automatic individual holding.~~
- ~~Individual control of each rack level with specific timer or core temperature.~~
- ~~Display of food which can be cooked in a mixed load.~~
- ~~Percentage-accurate humidity measurement, setting and control from 30°C to 300°C.~~
- ~~Actual humidity in the cooking cabinet can be set and called up on the control panel.~~
- ~~Cooking cabinet dehumidification without manual intervention.~~
- ~~Adjustable air speeds in the cooking cabinet with clocked fan wheel for gentle air flow.~~
- ~~Quick humidification of the cooking cabinet via water injection.~~
- ~~Core temperature probe with minimum 3 measuring points and automatic error correction of incorrect positioning of the core temperature probe.~~
- ~~Support function to find the right core temperature for the respective food and selection in the display.~~
- ~~Presetting of frequently used cooking temperatures and times for quick selection during operation.~~
- ~~Individual programming of more than 1.000 cooking programs with any number of steps and programmable intermediate messages.~~
- ~~Programmable proofing step.~~
- ~~Rapid cool down of cooking cabinet without door opening.~~
- ~~Customizable display with automatic, clear arrangement of the remaining functions for different users.~~
- ~~Automatic cleaning system for cooking cabinet and steam generator, independent of main pressure.~~

- Adaptation of the cleaning process depending on the degree of soiling in the cooking cabinet.
- Soiling detection with soiling-dependent cleaning suggestion.
- Unattended cleaning, even overnight.
- Display of the consumption of water, energy, and cleaning chemicals.
- Automatic adjustment of boiling temperature to the sea level of the installation location.
- Operation without water softening system and without additional manual descaling.
- Lengthwise loading.
- Removable hinged racks with rail spacing 67mm.
- Appliance door with rear-ventilated double-glass pane and hinged inner pane.
- Hand shower with automatic return.
- USB Interface.
- Maximum insertion height 1.60 m when using an original base cabinet.
- Height adjustable feet for easy leveling of the appliance.
- Fixed wastewater connection approved in accordance with SVGW.
- Separate solenoid valves for normal and soft water
- Appliance approved for unsupervised operation in accordance with VDE.
- Splash and jet water protection IP X5.
- Material inside and outside stainless steel DIN 1.4301.
- 150-300 meals per day

~~Technical data:~~

- Weight : 190 kg
- Dimensions (W x D x L) : 1,042 x 976 x 1,075 mm
- Connected load: 35.6 kW
- Fuse: 3x63 A
- Voltage: 400V