

This document demonstrates all valid OOXML ~~w:b (bold) tester~~: ST_OnOff variants, rStyle-only cases, rStyle + inline overrides, and a linked style pair (paragraph+character) to verify behavior.

A) ST_OnOff values for the <w:b (bold)> on a run property in OOXML. Each line shows the exact w:val used and the resulting rendering.:

~~—w:b w:val=(w:val omitted):~~ **Sample text**

~~—w:b w:val=true:~~ **Sample text**

~~—w:b w:val=1:~~ **Sample text**

~~—w:b w:val=on:~~ **Sample text**

~~—w:b w:val=false:~~ Sample text

~~—w:b w:val=0:~~ Sample text

~~—w:b w:val=off:~~ Sample text

B) ~~rStyle-only cases (no inline <w:b>):~~

~~—rStyle='SD_BoldChar' (should be bold):~~ **Sample via SD_BoldChar**

~~—rStyle='Strong' (built-in bold):~~ **Sample via Strong**

~~—rStyle='SD_PlainChar' (not bold):~~ Sample via SD_PlainChar

C) ~~rStyle + inline <w:b> combinations (inline overrides style):~~

~~—rStyle='SD_BoldChar' + <w:b w:val='0'>=> expect NOT bold:~~ Styled bold, overridden off

~~—rStyle='SD_BoldChar' + <w:b w:val='1'>=> expect bold:~~ **Styled bold, reinforced on**

~~—rStyle='SD_PlainChar' + <w:b w:val='on'>=> expect bold:~~ **Plain style, inline turns bold on**

~~—rStyle='Strong' + <w:b w:val='off'>=> expect NOT bold:~~ Strong style, explicit bold off

~~—rStyle='Strong' + <w:b w:val='true'>=> expect bold:~~ **Strong style, inline bold on**

D) ~~Linked style (paragraph+character) demonstrations:~~

~~—rStyle='SD_LinkedHeadingChar' (character side of linked pair)=> expect bold:~~ **Linked Char style applied to run**

- `rStyle='SD_LinkedHeadingChar' + <w:b w:val='0'>` => expect NOT bold: Linked Char style overridden off
- `pStyle='SD_LinkedHeading' + inline <w:b w:val='0'>`: Paragraph style makes text bold, but inline turns it off here
- `pStyle='SD_LinkedHeading' (no inline)` => expect bold: All runs inherit bold from the paragraph style

Table examples: ~~(linked style + inline overrides):~~

<u>Omitted</u>	<u>val='off' (not</u>	<u>Should be</u>	<u>val='1' (bold)</u>
<u>(bold)</u>	<code>rStyle='SD_LinkedHeadingChar' (no</code>	<code>bold)</code>	
	<code>inline)</code>		
	<code>rStyle='SD_LinkedHeadingChar' + w:b='0'</code>	<code>Should NOT be bold</code>	