

OOXML w:rFonts tester — inline attributes (ascii/hAnsi/eastAsia/cs, theme*, hint), i (italic) test: ST_OnOff variants and rStyle-only based cases. Direct run properties (<w:i>) should override character styles, inline overrides, and a linked paragraph/character pair. Includes Latin, Japanese, and Arabic samples. (<w:rStyle>).

A) Direct ST_OnOff values for <w:rFonts> on runs a run:

- ascii/hAnsi='Times New Roman' (Latin): The quick brown fox 123

- ascii/hAnsi='Arial' (Latin): The quick brown fox 123

- eastAsia='MS Mincho' (Japanese): 日本語のサンプルテキスト

- eastAsiaTheme='majorEastAsia' (Japanese, theme): 日本語のサンプル テキスト

- cs='Times New Roman' (Arabic): العربية تجربة نصية

- ascii='Calibri' + cs='Times New Roman' + hint='cs' (Latin text, CS hint): The quick brown fox 123

- asciiTheme='majorAscii', hAnsiTheme='minorHAnsi' (Latin theme): The quick brown fox 123

- csTheme='majorBidi' (Arabic theme): العربية تجربة نصية

- Mixed scripts with explicit rFonts per run: The quick brown fox 123 | 日本語のサンプル テキスト | العربية تجربة نصية

— ~~w:i w:val=(w:val omitted): Sample text~~

— ~~w:i w:val=true: Sample text~~

— ~~w:i w:val=1: Sample text~~

— ~~w:i w:val=on: Sample text~~

— ~~w:i w:val=false: Sample text~~

— ~~w:i w:val=0: Sample text~~

— ~~w:i w:val=off: Sample text~~

B) rStyle-only (character styles set <w:rFonts>): cases (no <w:i> direct formatting):

- rStyle='SD_RFonts Ascii Arial' (Latin): The quick brown fox 123

- rStyle='SD_RFonts EastAsia Mincho' (Japanese): 日本語のサンプル テキスト

-ItalicStyle' (should render italic): Sample via rStyle='SD_RFonts_CS_TNR' (Arabic): العربية تجربة نصية
italic

- rStyle='SD_RFonts Theme MajorAscii' (Latin theme): The quick brown fox 123'Strong' (bold, not italic): **Sample via rStyle Strong**

C) rStyle + inline <w:rFonts>i> combinations (inline overrides stylewins):

- rStyle='SD_RFonts Ascii Arial' + inline ascii/hAnsi='Times New Roman' (Latin): The quick brown fox 123

- rStyle='SD_RFonts EastAsia Mincho' + inline eastAsiaTheme='majorEastAsia' (Japanese): 日本語のサンプル テキスト

—rStyle='SD_ItalicStyle' + <w:i w:val='0'>=> expect NOT italic: *Styled italic, overridden off*

- rStyle='SD_RFonts_CS_TNR' + inline cs='Arial' (Arabic): العربية تجربة نصيةItalicStyle' + <w:i w:val='1'>=> expect italic: *Styled italic, reinforced on*

- rStyle='SD_RFonts Theme MajorAscii' + PlainStyle' + <w:i w:val='on'>=> expect italic: *Plain style, inline ascii/hAnsi='Courier New' (Latin): The quick brown fox 123turns italic on*

D) Linked style pair (paragraph+character) with <w:rFonts>:

- rStyle='SD_LinkedRFontsHeadingChar' across scripts: The quick brown fox 123 | 日本語のサンプル テキスト | العربية تجربة نصية

- pStyle='SD_LinkedRFontsHeading' + inline ascii='Courier New' on part: The quick brown fox 123 (inline Courier New)

E) —rStyle='Strong' + <w:i w:val='off'>=> expect NOT italic: **Strong style, explicit italic off**

—rStyle='Strong' + <w:i w:val='true'>=> expect bold + italic: ***Strong style, italic turned on inline***

Table samples (Latin / Japanese / Arabicexamples (rStyle + inline overrides):

rStyle=Ascii Arial (Latin)

The quick brown fox 123

rStyle=EastAsia Mincho + 'SD_ItalicStyle' (no inline eastAsiaTheme=majorEastAsia)

日本語のサンプル テキスト Should be italic

rStyle=CS TNR + inline cs='Arial"SD_ItalicStyle' العربية تجرية نصية Should NOT be italic
+ w:i='0'