

OOXML `w:sz` `rFonts` tester – demonstrates font size via half-points (`<w:sz w:val='...'>`), — inline attributes (`ascii/hAnsi/eastAsia/cs, theme*, hint`), `rStyle`-only `sizes` character styles, inline overrides, and a linked `styles/paragraph/character` pair. Includes Latin, Japanese, and Arabic samples.

A) Direct `<w:sz>` sizes (pt shown; XML uses half-points): `rFonts` on runs:

- `w:sz 8pt (w:val='16')`: Sample size text

- `w:sz 10pt (w:val='20')`: Sample size text

- `w:sz 11pt (w:val='22')`: Sample size text

- `w:sz 12pt (w:val='24')`: Sample size text

- `w:sz 14pt (w:val='28')`: Sample size text

- `w:sz 18pt (w:val='36')`: Sample size text

- `w:sz 24pt (w:val='48')`: Sample size text

- `w:sz 36pt (w:val='72')`: Sample size text

~~— `ascii/hAnsi='Times New Roman'` (Latin): The quick brown fox 123~~

~~— `ascii/hAnsi='Arial'` (Latin): The quick brown fox 123~~

~~— `eastAsia='MS Mincho'` (Japanese): 日本語のサンプルテキスト~~

~~— `eastAsiaTheme='majorEastAsia'` (Japanese, theme): 日本語のサンプルテキスト~~

~~— `cs='Times New Roman'` (Arabic): العربية تجربة نصية~~

~~— `ascii='Calibri' + cs='Times New Roman' + hint='cs'` (Latin text, CS hint): The quick brown fox 123~~

~~— `asciiTheme='majorAscii', hAnsiTheme='minorHAnsi'` (Latin theme): The quick brown fox 123~~

~~— `csTheme='majorBidi'` (Arabic theme): العربية تجربة نصية~~

~~— Mixed scripts with explicit `rFonts` per run: The quick brown fox 123 | 日本語のサンプルテキスト | العربية تجربة نصية~~

B) rStyle-only sizes (no inline(character styles set <w:szrFonts>)):

- rStyle='SD_Sz12ptChar' => 12pt: Styled 12pt text~~RFonts_Ascii_Arial' (Latin): The quick brown fox 123~~

- rStyle='SD_Sz24ptChar' => 24pt: Styled 24pt text~~RFonts_EastAsia_Mincho' (Japanese): 日本語のサンプルテキスト~~

- rStyle='SD_Sz18ptChar' => 18pt: Styled 18pt text~~RFonts_CS_TNR' (Arabic): العربية تجريبية نصية~~

→ rStyle='SD_RFonts_Theme_MajorAscii' (Latin theme): The quick brown fox 123

C) rStyle + inline <w:szrFonts> (inline overrides style):

- rStyle='SD_Sz24ptChar' + inline 12pt => expect 12pt: 24pt style overridden to 12pt

- rStyle='SD_Sz12ptChar'RFonts_Ascii_Arial' + inline ascii/hAnsi='Times New Roman' (Latin): The quick brown fox 123

→ rStyle='SD_RFonts_EastAsia_Mincho' + inline 36pt => expect 36pt: 12pt

style overridden to

36pt~~eastAsiaTheme='majorEastAsia' (Japanese): 日本語のサンプルテキスト~~

→ rStyle='SD_RFonts_CS_TNR' + inline cs='Arial' (Arabic): العربية تجريبية نصية

→ rStyle='SD_RFonts_Theme_MajorAscii' + inline ascii/hAnsi='Courier New' (Latin): The quick brown fox 123

D) Linked style pair (paragraph+character) with sizes:<w:rFonts>:

- rStyle='SD_LinkedSizeHeadingChar' => 18pt: Linked Char size

~~--rStyle='SD_LinkedRFontsHeadingChar' across scripts: The quick brown fox 123 | 日本語のサンプル
ルテキスト | العربية تجربة نصية~~

- pStyle='SD_LinkedSizeHeading'
(24pt)LinkedRFontsHeading' + inline

36ptascii='Courier New' on a run: This

part should be 36pt

overriding paragraph size: ~~The
quick brown fox 123 (inline
Courier New)~~

E) Table examples (size mix) ~~samples (Latin / Japanese / Arabic):~~

rStyle=Sz18Ascii_Arial (Latin)

18pt ~~The quick brown fox 123~~

rStyle=Sz12EastAsia_Mincho + inline
36pteastAsiaTheme=majorEastAsia

36pt ~~日本語のサンプルテキスト~~

rStyle=CS_TNR + inline cs='Arial'

~~العربية تجربة نصية~~