



BOLETÍN DE PRENSA

Oficina de Comunicación Social

Pasto, 26 de septiembre de 2025

Boletín de prensa No. 345

Alcaldía de Pasto ha puesto en funcionamiento el botón PSE para realizar el pago de las contribuciones

La Secretaría de Infraestructura y Valorización de la Alcaldía de Pasto ha puesto en funcionamiento el botón PSE para realizar el pago de las contribuciones, esto con la finalidad de facilitarle al ciudadano hacer sus aportes por las obras que benefician a su sector. A través de este botón se podrá realizar el trámite de manera rápida, fácil y segura.

"El botón es permanente para el uso en el momento en que ustedes requieran para poder hacer el pago de su contribución. Para el caso de sectores como Pandiaco o Morasurco se puede hacer el pago mediante abonos o en su totalidad hasta el 31 de diciembre sin intereses", señaló la subsecretaria de Valorización, Mónica Esparza.

Adicionalmente, la funcionaria comentó que las ventajas que brinda la activación del botón PSE es que los ciudadanos podrán realizar sus pagos desde cualquier lugar con acceso a internet, sin necesidad de desplazarse a las oficinas de la Alcaldía o al banco. Así mismo, se garantiza la seguridad y confiabilidad de los pagos en línea, reduciendo el riesgo de errores o extravíos de pagos.

"Estamos complacidos de lanzar este nuevo servicio de la Alcaldía de Pasto. Nuestro objetivo es facilitar el pago de las contribuciones de los contribuyentes", concluyó la funcionaria.

Engineer: _____

Contractor: _____



Prepared By: _____ Date: _____

Model: _____ Indoor/Outdoor: _____ MBTUH Input: _____

- ◆ 100% Factory Fire Tested
- ◆ Thermal Efficiency: Up to 85%
- ◆ Versa IC® Controller with LCD Display
- ◆ Maximum Setpoint: 150°F
- ◆ Maximum Outlet Temperature: 200°F
- ◆ Minimum Non-Condensing Inlet Temperature: 105°F
- ◆ Thermal Shock Proof Heat Exchanger
- ◆ Limited Twenty-Year Thermal Shock Warranty
- ◆ Limited Ten-Year Cupro-Nickel Heat Exchanger Warranty
- ◆ Limited Five-Year Copper Heat Exchanger Warranty

Hi Delta FlexGas® -Type WH

—Dual Fuel Water Heaters
Models 302CD-902CD



Carrera 28 No. 16-05 Parque San Andrés
Teléfono: (602) 7244326 - Ext 01 comunicaciones@pasto.gov.co



/Alcaldía de Pasto

- ◆ **Full Safety Diagnostics with Fault History**
- ◆ **PolyTuf Powder Coated Cabinet**
- ◆ **No Combustible Floor Shield Required**
- ◆ **Fan-Assisted**
- ◆ **Patented Burner Security Blanket**
- ◆ **Ultra-Low NO_x—SCAQMD 1146.2 Certified**
- ◆ **Cascade up to 4 Heaters—No External Sequencer Required**

Patent Nos. 6,904,873 & 7,044,124;
other patents pending



Proudly Assembled in the USA

Heat Exchanger

- Headers
 - ☐ Brass—Standard
 - ☐ A-2 Glass-Lined Cast Iron
- ASME Inspected and HLW Stamped
160 PSIG Working Pressure
- National Board Approved
- Fin Tubing
 - ☐ Copper (Std.) 85%
 - ☐ Cupro-Nickel 83.1%
- ASME Steel Tube Sheet
- Silicone High Temp. O-Rings
- ASME Pressure Relief Valve
 - ☐ 125 PSIG—Standard
 - ☐ _____ PSIG—Optional
- Temperature and Pressure Gauge
- Water Connections
 - ☐ Left—Standard
 - ☐ A-6 Right Hand

Controls

- 120V, 60Hz, 1Ø Power Supply
- 120/24V 60Hz Transformer
- Versa-IC® Integrated Control
- 100% Shut Off/Lockout
- Hot Surface Ignition
- Ignition Module
 - ☐ 3-Try—Standard
 - ☐ C-6 Single-Try
- Remote Flame Sensor
- Fixed High Limit, Manual Reset 240°F
- On/Off Power Switch
- Flow Switch
- Blocked Vent Pressure Switch
- Combustion Air Proving Switch
- Programmable Pump Time Delays
 - Heater
 - Recirculation
- Enable/Disable

- Powder Coat Finish
- CSA Low Lead Certified ($\leq$.25% Lead)

Venting

- Vent Category I/III Cupro-Nickel
- Vent Category II/IV Copper
- Vent Location
 - ☐ Top—Standard
 - ☐ D-14 Rear
- Vent Termination Cap
 - ☐ D-11 Outdoor
 - ☐ D-15 Indoor, Horizontal
 - ☐ Indoor, Vertical (by others)
- Combustion Air
 - ☐ D-17 In-Line Filter Kit (TruSeal only)
 - ☐ D-16 Air Intake Elbow

Venting—cont.

- Extractor—Optional
 - ☐ By others
 - ☐ Not required

Burner

- Ultra-Low NO_x: Less Than 20 PPM

Options

- ☐ C-6—Ignition Module, Manual Reset
- ☐ D-21—TruSeal® Direct Vent
- ☐ F-10—Low Water Cut-Off, Remote Probe
- ☐ I-1—High Limit Control, Auto-Reset
- ☐ P—Pump Bronze
 - _____ HP, 120V, 1Ø, 60Hz
 - _____ Water Hardness _____ GPG
 - ☐ Mounted ☐ Loose
 - ☐ Front ☐ Rear
- ☐ P—Cold Water Run (See 1000-19)
- ☐ S-1—Low Gas Pressure Switch, Manual
- ☐ S-2—High Gas Pressure Switch, Manual
- ☐ X-1—SureRack® Kit
- ☐ X-2—SureRack® Add-on

Additional Options or Accessories

- ☐ _____

Multi-Boiler Temperature Controllers

- ☐ TempTracker Mod+ Hybrid
 - ☐ B-36, 2-4 Heaters
 - ☐ B-37, 5-10 Heaters
 - ☐ B-38, 11-16 Heaters
 - ☐ B-39 EMS 4-20mA Remote Setpoint Interface Module
 - ☐ B-62 BACnet MS/TP Interface

Controls—cont.

- LCD Display: Status, Fault and Diagnostics
- Cold Water Protection Function
 - ☐ Optional CWR Variable-Speed Pump (See Cat. 6000-73)
- Modbus RTU BMS Port (Up to 115K Baud,
 - ☐ B-85—BMS Gateway—BACnet MS/TP, BACnet IP, N2 Metasys or Modbus TCP
 - ☐ B-86—BMS Gateway—LonWorks

Gas Train

- Manual Gas Shut-Off Valve(s)
- Gas Pressure Regulator
- Safety Shut-off Valve
- Firing Control Valve
- Firing Mode: 2-Stage (WH3)
- Natural/Propane Gas
- Gas Connection
 - ☐ Left—Standard
 - ☐ Z-1 Right
- Design-Certified—ANSI Z21.10.3/CSA 4.3

Construction

- Indoor/Outdoor Construction
- Enclosed Front Controls




For Metric inform



Oficina de Comunicación Social

et



Carrera 28 No. 16-05 Parque San Andrés
Teléfono: (602) 7244326 - Ext 01 comunicaciones@pasto.gov.co



/Alcaldía de Pasto

□ 902CD	900	765	748	78	1-1/4	8	36	7	740
---------	-----	-----	-----	----	-------	---	----	---	-----

* Without

pump

- NOTES: 1. Dimensions are in inches.
 2. Rates shown are for natural or propane gas, and elevations up to 4,500 feet. For installation above 4,500 feet, please contact manufacturer.
 3. Required natural gas pressure is 7 — 10.5" WC. Required propane gas pressure is 11 — 13" WC.

Hi Delta Flex Gas — Type WH Models 302CD-902CD

Mod

el

Model	83.1% System Flow and Head Loss													
	3-4 Grains Per Gallon					5-15 Grains Per Gallon					16-25** Grains Per Gallon			
	ΔT (°F)	GPM	ΔP (FT WC)	MTS (IN)	SHL (FT WC)	ΔT (°F)	GPM	ΔP (FT WC)	MTS (IN)	SHL (FT WC)	ΔT (°F)	GPM	ΔP (FT WC)	SHL (FT WC)
□ 302CD	13	40	2.0	2	5.1	10	50	3.0	2	7.7	6	90	9.8	23.7
□ 402CD	17	40	2.0	2	5.1	13	52	3.4	2	8.4	7	90	10.0	23.8
□ 502CD	21	40	2.1	2	5.2	16	52	3.5	2	8.6	9	90	10.4	24.2
□ 652CD	27	40	2.2	2	5.3	21	52	3.7	2	8.7	12	90	10.8	24.7
□ 752CD	28	45	3.0	2	6.8	23	55	4.4	2	9.9	14	90	11.3	25.1
□ 902CD	28	54	4.3	2	9.7	24	73	7.8	2	17.2	17	90	11.7	25.5

SHL includes 50 ft of tubing each way (100 total)

** Must use optional cupro-nickel tubes. For hardness exceeding 25 GPG, must use water softener
 Basis for minimum flow is 40 GPM or 30°F ΔT, 90 GPM for maximum flow

Model	85% System Flow and Head Loss													
	3-4 Grains Per Gallon					5-15 Grains Per Gallon					16-25** Grains Per Gallon			
	ΔT (°F)	GPM	ΔP (FT WC)	MTS (IN)	SHL (FT WC)	ΔT (°F)	GPM	ΔP (FT WC)	MTS (IN)	SHL (FT WC)	ΔT (°F)	GPM	ΔP (FT WC)	SHL (FT WC)
□ 302CD	13	40	2.0	2	5.1	10	50	3.0	2	7.7	6	90	9.8	23.7
□ 402CD	17	40	2.0	2	5.1	13	52	3.4	2	8.4	8	90	10.0	23.8
□ 502CD	21	40	2.1	2	5.2	17	52	3.5	2	8.6	10	90	10.4	24.2
□ 652CD	28 SHL includes 50 ft of tubing each way (100 total)	40	2.2	2	5.3	21	52	3.7	2	8.7	12	90	10.8	24.7
□ 752CD	28 Basis for minimum flow is 40 GPM or 30°F ΔT, 90 GPM for maximum flow	45	3.0	2	6.8	23	55	4.4	2	9.9	14	90	11.3	25.1



ALCALDÍA
DE PASTO

BOLETÍN DE PRENSA

Oficina de Comunicación Social

	902CD	29	54	4.3	2	9.7	24	73	7.8	2	17.2	17	90	11.7	2	25.5
--	-------	----	----	-----	---	-----	----	----	-----	---	------	----	----	------	---	------

Model	83.1% Recovery Rates								
	20°	30°	40°	50°	60°	70°	80°	90°	100°
302CD	1511	1007	755	604	504	432	378	336	302
402CD	2010	1340	1005	804	670	574	502	447	402
502CD	2518	1679	1259	1007	839	709	630	560	504
652CD	3274	2182	1637	1309	1091	935	818	727	655
752CD	3777	2518	1889	1511	1259	1079	944	839	755
902CD	4533	3022	2266	1813	1511	1295	1133	1007	907

Model	85 % Recovery Rates								
	20°	30°	40°	50°	60°	70°	80°	90°	100°
302CD	1545	1030	773	618	515	442	386	343	309
402CD	2055	1370	1028	822	685	587	514	457	411
502CD	2576	1717	1288	1030	859	736	644	572	515
652CD	3348	2232	1674	1339	1116	957	837	744	670
752CD	3864	2576	1932	1545	1288	1104	966	859	773
902CD	4636	3091	2318	1855	1545	1325	1159	1030	927

