

OOXML w:b (bold) tester: ST_OnOff variants, rStyle-only cases, rStyle + inline overrides, and a linked style pair (paragraph+character) to verify behavior.

A) ST_OnOff values for <w:b> on a run:

- w:b w:val=(w:val omitted): **Sample text**

- w:b w:val=true: **Sample text**

- w:b w:val=1: **Sample text**

- w:b w:val=on: **Sample text**

- w:b w:val=false: Sample text

- w:b w:val=0: Sample text

- w:b w:val=off: Sample text

B) rStyle-only cases (no inline <w:b>):

- rStyle='SD_BoldChar' (should be bold): **Sample via SD_BoldChar**

- rStyle='Strong' (built-in bold): **Sample via Strong**

- rStyle='SD_PlainChar' (not bold): Sample via SD_PlainChar

C) rStyle + inline <w:b> combinations (inline overrides style):

- rStyle='SD_BoldChar' + <w:b w:val='0'> => expect NOT bold: **Styled bold, overridden off**

- rStyle='SD_BoldChar' + <w:b w:val='1'> => expect bold: **Styled bold, reinforced on**

- rStyle='SD_PlainChar' + <w:b w:val='on'> => expect bold: **Plain style, inline turns bold on**

- rStyle='Strong' + <w:b w:val='off'> => expect NOT bold: **Strong style, explicit bold off**

- rStyle='Strong' + <w:b w:val='true'> => expect bold: **Strong style, inline bold on**

D) Linked style (paragraph+character) demonstrations:

- rStyle='SD_LinkedHeadingChar' (character side of linked pair) => expect bold: **Linked Char style applied to run**

- rStyle='SD_LinkedHeadingChar' + <w:b w:val='0'> => expect NOT bold: Linked Char style overridden off

- pStyle='SD_LinkedHeading' + inline <w:b w:val='0'>: Paragraph style makes text bold, but inline turns it off here

- pStyle='SD_LinkedHeading' (no inline) => expect bold: All runs inherit bold from the paragraph style

Table examples (linked style + inline overrides):

<u>rStyle='SD_LinkedHeadingChar' (no inline)</u>	Should be bold
--	-----------------------

<u>rStyle='SD_LinkedHeadingChar' + w:b='0'</u>	<u>Should NOT be bold</u>
--	---------------------------

Num words: 0

Num chars: 0

Num pages: 4

| test

|

