

## SD-2672 RTL

OOXML w:i (italic) test: ST\_OnOff variants and rStyle-based cases. Direct run properties (<w:i>) should override character styles (<w:rStyle>).

A) ST\_OnOff values for <w:i> on a run:

—w:i w:val=(w:val omitted): *Sample text*

—w:i w:val=true: *Sample text*

—w:i w:val=1: *Sample text*

—w:i w:val=on: *Sample text*

—w:i w:val=false: Sample text

—w:i w:val=0: Sample text

—w:i w:val=off: Sample text

B) rStyle-only cases (no <w:i> direct formatting):

—rStyle='SD\_ItalicStyle' (should render italic): *Sample via rStyle italic*

—rStyle='Strong' (bold, not italic): **Sample via rStyle Strong**

C) rStyle + inline <w:i> combinations (inline wins):

—rStyle='SD\_ItalicStyle' + <w:i w:val='0'>=> expect NOT italic: ~~Styled italic, overridden off~~

—rStyle='SD\_ItalicStyle' + <w:i w:val='1'>=> expect italic: *Styled italic, reinforced on*

—rStyle='SD\_PlainStyle' + <w:i w:val='on'>=> expect italic: *Plain style, inline turns italic on*

—rStyle='Strong' + <w:i w:val='off'>=> expect NOT italic: **Strong style, explicit italic off**

—rStyle='Strong' + <w:i w:val='true'>=> expect bold + italic: ***Strong style, italic turned on inline***

Table examples (rStyle + inline overrides):

|                 |                                                |                                                               |
|-----------------|------------------------------------------------|---------------------------------------------------------------|
| <u>rtl-r0c2</u> | <b><u>rtl-r0c1</u></b> <i>Should be italic</i> | <b><u>rtl-r0c0</u></b> rStyle='SD_ItalicStyle'<br>(no inline) |
| <u>rtl-r1c2</u> | <b><u>rtl-r1c1</u></b> Should NOT be italic    | <u>rtl-r1c0</u><br>rStyle='SD_ItalicStyle'+<br>'w:i='0        |