

Combi-Steamer with 10 levels 2/1 GN electric

Description:

Combi steamer according to DIN 18866 for most cooking methods used in commercial kitchens for the optional use of steam and convection, individually, sequentially or combined. Capacity 2/1, 1/1 GN containers

Technical design:

- Convection mode from 30°C to 300°C.
- Steam mode from 30°C to 130°C.
- Combination of Convection and steam from 30°C to 300°C.
- Steam generator with automatic cleaning and descaling.
- Automatic cooking system with time or core temperature-controlled processes, load detection and load-dependent adaption of the cooking process.
- Automatic cooking processes for low temperature cooking, delta-T cooking and braising with automatic individual holding.
- Individual control of each rack level with specific timer or core temperature.
- Display of food which can be cooked in a mixed load.
- Percentage-accurate humidity measurement, setting and control from 30°C to 300°C.
- Actual humidity in the cooking cabinet can be set and called up on the control panel.
- Cooking cabinet dehumidification without manual intervention.
- Adjustable air speeds in the cooking cabinet with clocked fan wheel for gentle air flow.
- Quick humidification of the cooking cabinet via water injection.
- Core temperature probe with minimum 3 measuring points and automatic error correction of incorrect positioning of the core temperature probe.
- Support function to find the right core temperature for the respective food and selection in the display.
- Presetting of frequently used cooking temperatures and times for quick selection during operation.
- Individual programming of more than 1.000 cooking programs with any number of steps and programmable intermediate messages.
- Programmable proofing step.
- Rapid cool down of cooking cabinet without door opening.
- Customizable display with automatic, clear arrangement of the remaining functions for different users.
- Automatic cleaning system for cooking cabinet and steam generator, independent of main pressure.
- Adaptation of the cleaning process depending on the degree of soiling in the cooking cabinet.
- Soiling detection with soiling-dependent cleaning suggestion.
- Unattended cleaning, even overnight.
- Display of the consumption of water, energy, and cleaning chemicals.
- Automatic adjustment of boiling temperature to the sea level of the installation location.
- Operation without water softening system and without additional manual descaling.
- Lengthwise loading
- Removable hinged racks with rail spacing 67mm.
- Appliance door with rear-ventilated double glass pane and hinged inner pane.
- Hand shower with automatic return.
- USB-Interface.
- Maximum insertion height 1.60 m when using an original base cabinet.
- Height adjustable feet for easy leveling of the appliance.
- Fixed wastewater connection approved in accordance with SVGW.
- Separate solenoid valves for normal and soft water
- Appliance approved for unsupervised operation in accordance with VDE.
- Splash and jet water protection IP X5.
- Material inside and outside stainless-steel DIN 1.4301.
- 150-300 meals per day

Technical data:

- Weight : 190 kg
- Dimensions (W x D x L) : 1,042 x 976 x 1,075 mm
- Connected load: 35.6 kW
- Fuse: 3x63 A
- Voltage: 400V