

OOXML w:i (italic) test: ST\_OnOff variants and rStyle-based cases. Direct run properties (<w:i>) should override character styles (<w:rStyle>).

A) ST\_OnOff values for <w:i> on a run:

- w:i w:val=(w:val omitted): *Sample text*
- w:i w:val=true: *Sample text*
- w:i w:val=1: *Sample text*
- w:i w:val=on: *Sample text*
- w:i w:val=false: Sample text
- w:i w:val=0: Sample text
- w:i w:val=off: Sample text

B) rStyle-only cases (no <w:i> direct formatting):

- rStyle='SD\_ItalicStyle' (should render italic): *Sample via rStyle italic*
- rStyle='Strong' (bold, not italic): **Sample via rStyle Strong**

C) rStyle + inline <w:i> combinations (inline wins):

- rStyle='SD\_ItalicStyle' + <w:i w:val='0'> => expect NOT italic: *Styled italic, overridden off*
- rStyle='SD\_ItalicStyle' + <w:i w:val='1'> => expect italic: *Styled italic, reinforced on*
- rStyle='SD\_PlainStyle' + <w:i w:val='on'> => expect italic: *Plain style, inline turns italic on*
- rStyle='Strong' + <w:i w:val='off'> => expect NOT italic: **Strong style, explicit italic off**
- rStyle='Strong' + <w:i w:val='true'> => expect bold + italic: ***Strong style, italic turned on inline***

Table examples (rStyle + inline overrides):

|                                     |                         |
|-------------------------------------|-------------------------|
| rStyle='SD_ItalicStyle' (no inline) | <i>Should be italic</i> |
| rStyle='SD_ItalicStyle' + w:i='0'   | Should NOT be italic    |