

SECTION 102800
TOILET, BATH, AND LAUNDRY ACCESSORIES - ASI

PART 1 GENERAL

1.01 SECTION INCLUDES

- A. Paper towel combination units.

1.02 RELATED REQUIREMENTS

1.03 REFERENCE STANDARDS

- A. ADA Standards - 2010 ADA Standards for Accessible Design; 2010.
B. ICC A117.1 - Accessible and Usable Buildings and Facilities; 2017.

1.04 SUBMITTALS

- A. See Section 013000 - Administrative Requirements for submittal procedures.
B. Manufacturer's Installation Instructions: Indicate special procedures and conditions requiring special attention.

PART 2 PRODUCTS

2.01 MANUFACTURERS

- A. Basis of Design Manufacturer: American Specialties, Inc: www.americanspecialties.com/#sle.
B. Other Acceptable Manufacturers:
1. Products by listed manufacturers are subject to compliance with specified requirements found in specification and in Technical Data Sheet of selected ASI model and prior approval of Architect.
C. Substitutions: See Section 016000 - Product Requirements.
1. All proposed substitutions (clearly delineated as such) must be submitted in writing for approval by Architect minimum of 10 working days prior to bid date and must be made available to all bidders. Proposed substitutes must be accompanied by review of specification and ASI Technical Data Sheets noting compliance on line-by-line basis.

2.02 PAPER TOWEL COMBINATION UNITS

- A. Combination Towel Dispenser/Waste Receptacle: Stainless steel; seamless wall flanges, continuous heavy-duty stainless steel multi-staked piano hinges, tumbler locks on upper and lower doors.
1. Mounting: As indicated in product listing.
2. Stainless Steel Thickness: As indicated on Technical Data Sheet for selected ASI model.
3. Waste Receptacle Liner: Reusable, heavy-duty vinyl.
4. Towel Type: As indicated in product listing.
5. Folded Towel Dispenser Capacity: As indicated in product listing.
6. Waste Receptacle Capacity: As indicated in product listing.
7. Products:
a. Model 0469-ND - Recessed - Traditional Collection - Paper Towel Dispenser and Waste Receptacle - No Door - 12 gal (45.4 L).
b. Substitutions: Section 016000 - Product Requirements.

2.03 MATERIALS

- A. Accessories - General: Shop assembled, free of dents and scratches and packaged complete with anchors and fittings, steel anchor plates, adapters, and anchor components for installation.

2.04 FABRICATION

- A. Traditional Collection:

--	--	--

1. Basic Construction Requirements:

- a. Doors: Type 304, 22 gauge, 0.0312 inch (0.79 mm) stainless steel, double pan construction, with 1/4 inch (6 mm) thick structural fiberboard core.
- b. Cabinets: Type 304, 22 gauge, 0.0312 inch (0.79 mm) stainless steel, formed perimeter trim with 1/4 inch (6 mm) return to wall four sides; joints welded, sight-exposed welds finished to match sheet finish.
- c. Hinges: Heavy-duty stainless steel multi-staked piano hinge, 3/16 inch (5 mm) diameter barrel, full length of cabinet; hinge leaves spot-welded to door and cabinet body.
- d. Locks: Tumbler locks, keyed alike other toilet accessory locks, with one key for each lock.
- e. Cabinet and Door Finish: No.4 satin finish.

2.05 FINISHES

- A. Shop Primed Ferrous Metals: Pretreat and clean, spray apply one coat primer and bake.
- B. Back paint components where contact is made with building finishes to prevent electrolysis.

PART 3 EXECUTION

3.01 EXAMINATION

- A. Verify existing conditions before starting work.
- B. Verify exact location of accessories for installation.

3.02 PREPARATION

- A. Deliver inserts and rough-in frames to site for timely installation.
- B. Provide templates and rough-in measurements as required.

3.03 INSTALLATION

- A. Install accessories in accordance with manufacturers' instructions in locations indicated on drawings.
- B. Mounting Heights: As required by accessibility regulations, unless otherwise indicated.
 - 1. Other Accessories: As indicated on drawings.

3.04 PROTECTION

- A. Protect installed accessories from damage due to subsequent construction operations.

END OF SECTION ~~Injury event—place of
occurrence, code (ICD-10-AM 8th edn)
ANN{.N[N]}~~

Exported from METEOR

(AIHW's Metadata Online Registry)

--	--	--

© Australian Institute of Health and Welfare 2024

This product, excluding the AIHW logo, Commonwealth Coat of Arms and any material owned by a third party or protected by a trademark, has been released under a Creative Commons BY 4.0 (CC BY 4.0) licence. Excluded material owned by third parties may include, for example, design and layout, images obtained under licence from third parties and signatures. We have made all reasonable efforts to identify and label material owned by third parties.

You may distribute, remix and build on this website's material but must attribute the AIHW as the copyright holder, in line with our attribution policy. The full terms and conditions of this licence are available at <https://creativecommons.org/licenses/by/4.0/>.

Enquiries relating to copyright should be addressed to info@aihw.gov.au.

Enquiries or comments on the METEOR metadata or download should be directed to the METEOR team at meteor@aihw.gov.au.

--	--	--

~~Injury event—place of occurrence, code (ICD-10-AM 8th edn) ANN{.N[N]}~~

~~Identifying and definitional attributes~~

Metadata item type:	Data Element
Short name:	Place of occurrence of external cause of injury (ICD-10-AM)
METEOR identifier:	514302
Registration status:	<u>Health, Superseded 13/11/2014</u>
Definition:	The place where the external cause of injury, poisoning or adverse effect occurred, as represented by a code.
Data Element Concept:	<u>Injury event—place of occurrence</u>
Value Domain:	<u>Place of occurrence (ICD-10-AM 8th edn) ANN{.N[N]}</u>

~~Value domain attributes~~

~~Representational attributes~~

Classification scheme:	<u>International Statistical Classification of Diseases and Related Health Problems, Tenth Revision, Australian Modification 8th edition</u>
Representation class:	Code
Data type:	String

--	--	--

Format: ANN{.N{N}}

Maximum character length: 6

Data element attributes

Collection and usage attributes

Guide for use: Admitted patient:
 External cause codes in the range V00 to Y89 must be accompanied by a place of occurrence code.
 External cause codes V00 to Y34 must be accompanied by an activity code.

Comments: Enables categorisation of injury and poisoning according to factors important for injury control. Necessary for defining and monitoring injury control targets, injury costing and identifying cases for in-depth research.

Source and reference attributes

Origin: National Centre for Classification in Health
 AIHW National Injury Surveillance Unit
 National Data Standards for Injury Surveillance Advisory Group

Relational attributes

Related metadata references: Supersedes Injury event — place of occurrence, code (ICD-10 AM 7th edn)
ANN{.N{N}}
Health, Superseded 02/05/2013

--	--	--

~~Has been superseded by Injury event—place of occurrence, code (ICD-10-AM 9th edn) ANN(.N[N])~~

~~Health, Superseded 05/10/2016~~

~~Tasmanian Health, Superseded 10/07/2017~~

Implementation in
Data-Set
Specifications:

~~Admitted patient care NMDS 2013-14~~

~~Health, Superseded 11/04/2014~~

~~**Implementation start date:** 01/07/2013~~

~~**Implementation end date:** 30/06/2014~~

~~**DSS specific information:** To be used with ICD-10-AM external cause codes.~~

~~Admitted patient care NMDS 2014-15~~

~~Health, Superseded 13/11/2014~~

~~**Implementation start date:** 01/07/2014~~

~~**Implementation end date:** 30/06/2015~~

~~**DSS specific information:** To be used with ICD-10-AM external cause codes.~~

~~Injury surveillance NBPDS 2013-~~

~~Health, Standard 02/05/2013~~

~~**Implementation start date:** 01/07/2013~~