

- List item 1
- List item 2
 - o Indentation 1
- Back

1. Numbered 1
2. Num 2
 - a. With indend 1

lastOOXML w:i (italic) test: ST_OnOff variants and rStyle-based cases. Direct run properties (<w:i>) should override character styles (<w:rStyle>).

A) ST_OnOff values for <w:i> on a run:

- w:i w:val=(w:val omitted): *Sample text*
- w:i w:val=true: *Sample text*
- w:i w:val=1: *Sample text*
- w:i w:val=on: *Sample text*
- w:i w:val=false: Sample text
- w:i w:val=0: Sample text
- w:i w:val=off: Sample text

B) rStyle-only cases (no <w:i> direct formatting):

- rStyle='SD_ItalicStyle' (should render italic): *Sample via rStyle italic*
- rStyle='Strong' (bold, not italic): **Sample via rStyle Strong**

C) rStyle + inline <w:i> combinations (inline wins):

- rStyle='SD_ItalicStyle' + <w:i w:val='0'>=> expect NOT italic: *Styled italic, overridden off*
- rStyle='SD_ItalicStyle' + <w:i w:val='1'>=> expect italic: *Styled italic, reinforced on*
- rStyle='SD_PlainStyle' + <w:i w:val='on'>=> expect italic: *Plain style, inline turns italic on*
- rStyle='Strong' + <w:i w:val='off'>=> expect NOT italic: **Strong style, explicit italic off**
- rStyle='Strong' + <w:i w:val='true'>=> expect bold + italic: ***Strong style, italic turned on inline***

Table examples (rStyle + inline overrides):

rStyle='SD_ItalicStyle' (no inline)

Should be italic

rStyle='SD_ItalicStyle' + w:i='0'

Should NOT be italic

3.