

OOXML w:b (bold)highlight tester: ~~—enumerates ST_OnOff variants HighlightColor values, rStyle-only cases, rStyle + highlights, inline overrides, and a linked style pair (paragraph+character) to verify behavior~~ styles.

A) ST_OnOff values for <w:b> on a runhighlight> values:

- w:bhighlight w:val=(='yellow': Highlight sample
- ~~—w:highlight w:val omitted): Sample text='green': Highlight sample~~
- w:bhighlight w:val=true: Sample text'cyan': Highlight sample
- w:bhighlight w:val=1: Sample text'magenta': Highlight sample
- w:bhighlight w:val=on: Sample text'blue': Highlight sample
- w:bhighlight w:val=false: Sample text'red': Highlight sample
- w:bhighlight w:val=0: Sample text'darkYellow': Highlight sample
- w:bhighlight w:val=off: Sample text'darkGreen': Highlight sample
- ~~—w:highlight w:val='darkCyan': Highlight sample~~
- ~~—w:highlight w:val='darkMagenta': Highlight sample~~
- ~~—w:highlight w:val='darkBlue': Highlight sample~~
- ~~—w:highlight w:val='darkRed': Highlight sample~~
- ~~—w:highlight w:val='darkGray': Highlight sample~~
- ~~—w:highlight w:val='lightGray': Highlight sample~~
- ~~—w:highlight w:val='black': Highlight sample~~
- ~~—w:highlight w:val='white': Highlight sample~~
- ~~—w:highlight w:val='none': Highlight sample~~

B) rStyle-only cases (no inline <w:b>):(character style sets highlight):

- rStyle='SD_BoldChar' (should be bold): Sample via SD_BoldCharHighlightYellowChar': Styled yellow highlight
- rStyle='Strong' (built-in bold): Sample via Strong
- rStyle='SD_PlainChar' (not bold): Sample via SD_PlainCharHighlightLightGrayChar': Styled lightGray highlight

-- rStyle='SD_HighlightNoneChar': Styled none (no highlight)

C) rStyle + inline <w:b> combinations highlight> (inline overrides style):

- rStyle='SD_BoldChar' + <w:b w:val='0'>HighlightYellowChar' + inline 'none' => expect NOT bold: Styled bold, no highlight: Yellow style overridden off to none

- rStyle='SD_BoldChar' + <w:b w:val='1'> => expect bold: **Styled bold, reinforced on**

- rStyle='SD_PlainChar' + <w:b w:val='on'> => expect bold: **Plain style, inline turns bold on**

- rStyle='Strong' + <w:b w:val='off'> => expect NOT bold: Strong style, explicit bold off

- rStyle='Strong' + <w:b w:val='true'> => expect bold: **StrongHighlightNoneChar' + inline 'darkBlue' => expect darkBlue: None style, inline bold on overridden to darkBlue**

D) Linked style pair (paragraph+character) demonstrations with highlight:

- rStyle='SD_LinkedHeadingChar' (character side of linked pair) => expect boldLinkedHighlightHeadingChar' => yellow: Linked Char style applied to run

- rStyle='SD_LinkedHeadingChar' + <w:b w:val='0'> => expect NOT bold: Linked Char style overridden off

- pStyle='SD_LinkedHeading'LinkedHighlightHeading' (lightGray) + inline <w:b w:val='0'>: Paragraph style makes text bold, but inline turns it off here

- pStyle='SD_LinkedHeading' (no inline) => expect bold: All runs inherit bold from the 'red' on a run: **This part should be red highlight overriding paragraph style**

Table examples (linked style + inline overrides mixed highlight):

rStyle='SD_LinkedHeadingChar' (no inline)Yellow **Should be bold**Yellow cell

rStyle='SD_LinkedHeadingChar' + w:b='0'None **Should NOT be bold**DarkMagenta cell
+ inline darkMagenta