

file_146¹⁴⁵.docx

[eigenpal/docx-editor](#)

[Project Charter & Contributor Agreement](#)

[npm](#) [@eigenpal/docx-js-editor](#)

[github](#) [eigenpal/docx-editor](#)

1. What this is

An open-source WYSIWYG [.docx](#) editor for React. Drop in [<DocxEditor](#)
[documentBuffer={file}](#) /> and your users can open, edit, and save Word documents
entirely in the browser — no backend required, no document data leaving the client.

Most editors serialise to HTML and back: [DOCX → HTML → edits → HTML → DOCX](#).
Every hop loses formatting, tracked changes, and styles. This library skips it — OOXML is the
canonical format throughout.

```
import { DocxEditor } from '@eigenpal/docx-js-editor'
import '@eigenpal/docx-js-editor/styles.css'

function App({ file }: { file: ArrayBuffer }) {
  return (
    <DocxEditor
      documentBuffer={file}
      onSave={ (buffer) => uploadToServer(buffer) }
    />
  )
}
```

2. Collaboration — Tracked Changes & Comments

Both features round-trip through OOXML so documents open correctly in Word, LibreOffice, and Google Docs.

Suggestion mode

Toggle between `Editing` and `Suggesting` via the toolbar dropdown. In `Suggesting` mode, every edit becomes a tracked insertion (`green underline`) or deletion (`red strikethrough`). Consecutive keystrokes group into a single change. Accept or reject individually or all at once.

Serialises to `w:ins` / `w:del` — the same OOXML markup Word uses. Tracked changes survive a save/reload cycle and are reviewable in Word with full accept/reject UI.

Comments

Select text and click the floating button on the page edge to `add a comment anchored to that selection` . A Google Docs-style sidebar shows threaded cards positioned at their anchor point in the document. Reply, resolve, reopen, or delete inline.

Commented [1]: Just like that!

Serialises to `comments.xml` with `w:commentRangeStart` / `w:commentRangeEnd` markers. Comments and reply threads are preserved on round-trip.

Agent-friendly

Because tracked changes and comments are native OOXML, an AI agent can write `w:ins` / `w:del` / `w:comment` markup directly into a document and hand it to `<DocxEditor />` for human review — no custom diff format, no proprietary API.

3. Props

Pass `author="Your App"` to set the author name for comments and tracked changes. Toggle suggestion mode via the toolbar dropdown.

Prop	Type	Default	Description
------	------	---------	-------------

[Docx Editor: Project Charter & Contributor Agreement](#)

documentBuffer	ArrayBuffer	=	.docx file contents to load
readOnly	boolean	false	Preview mode — no editing UI
showToolbar	boolean	true	Show formatting toolbar
author	string	'User'	Author name for comments and tracked changes
onChange	function	=	Called on every document change
onSave	function	=	Called on save, receives ArrayBuffer
onError	function	=	Called on error

Ref methods

```
const ref = useRef<DocxEditorRef>(null)

await ref.current.save() // ArrayBuffer of the .docx
ref.current.getDocument() // current document object
ref.current.setZoom(1.5) // set zoom to 150%
ref.current.scrollToPage(3) // scroll to page 3
ref.current.print() // print
```

4. Contributing

2. Collaboration — Tracked Changes & Comments

Both features round-trip through OOXML so documents open correctly in Word, LibreOffice, and Google Docs.

Suggestion mode

Toggle between `Editing` and `Suggesting` via the toolbar dropdown. In `Suggesting` mode, every edit becomes a tracked insertion (`green underline`) or deletion (`red strikethrough`). Consecutive keystrokes group into a single change. Accept or reject individually or all at once.

Serialises to `w:ins` / `w:del` — the same OOXML markup Word uses. Tracked changes survive a save/reload cycle and are reviewable in Word with full accept/reject UI.

Comments

Select text and click the floating button on the page edge to `add a comment anchored to that selection`. A Google Docs-style sidebar shows threaded cards positioned at their anchor point in the document. Reply, resolve, reopen, or delete inline.

Commented [2]: Just like that!

Serialises to `comments.xml` with `w:commentRangeStart` / `w:commentRangeEnd` markers. Comments and reply threads are preserved on round-trip.

Agent-friendly

Because tracked changes and comments are native OOXML, an AI agent can write `w:ins`
`/ w:del / w:comment` markup directly into a document and hand it to
`<DocxEditor />` for human review — no custom diff format, no proprietary API.

3. Props

Pass `author="Your App"` to set the author name for comments and tracked changes.
Toggle suggestion mode via the toolbar dropdown.

Prop	Type	Default	Description
<code>documentBuffer</code>	<code>ArrayBuffer</code>	<code>-</code>	<code>.docx</code> file contents to load
<code>readOnly</code>	<code>boolean</code>	<code>false</code>	Preview mode — no editing UI
<code>showToolbar</code>	<code>boolean</code>	<code>true</code>	Show formatting toolbar
<code>author</code>	<code>string</code>	<code>'User'</code>	Author name for comments and tracked changes
<code>onChange</code>	<code>function</code>	<code>-</code>	Called on every document change
<code>onSave</code>	<code>function</code>	<code>-</code>	Called on save, receives <code>ArrayBuffer</code>
<code>onError</code>	<code>function</code>	<code>-</code>	Called on error

[Ref methods](#)

```
const ref = useRef<DocxEditorRef>(null)

await ref.current.save() // ArrayBuffer of the .docx
ref.current.getDocument() // current document object
ref.current.setZoom(1.5) // set zoom to 150%
ref.current.scrollToPage(3) // scroll to page 3
ref.current.print() // print
```

[4. Contributing](#)

Read [docs/PLUGINS.md](#) before opening a pull request that touches the plugin API.

[Ground rules](#)

- [Every PR must pass the round-trip test: load a .docx, apply an edit, export, reload — content and formatting must be stable on unchanged content.](#)
- [Run `bun test` and `bun run test:e2e` locally before pushing.](#)
- [Avoid intermediate HTML serialisation where possible.](#)
- [Tracked changes and comments must survive a full OOXML round-trip — save, open in Word, verify changes are reviewable, reload in the editor.](#)

[Dev setup](#)

```
bun install
bun run dev // Vite demo on localhost:5173
```

[Sign-off](#)

[EigenPal](#)

Maintainer · [eigenpal.com](#)

[Contributor](#)

on behalf of the community

[signature · date](#)

[signature · date](#)

Sign-off

EigenPal

[Maintainer · eigenpal.com](#)

Contributor

[on behalf of the community](#)

[signature · date](#)

[signature · date](#)

Heading 4 Right Italic Demo

***Heading 4 style with right alignment and italic formatting.
This creates unique stylized subheadings for document sections.***