

✓ CSST 106

Verdad, Jane Benneth Dione

BSCS-4B

September 09, 2024

Exercise 1

1. Install OpenCV

```
!pip install opencv-python-headless
```

Requirement already satisfied: opencv-python-headless in /usr/local/lib/python3.10/dist-packages (4.10.0.84)
Requirement already satisfied: numpy>=1.21.2 in /usr/local/lib/python3.10/dist-packages (from opencv-python-headless) (1.26.4)

2. Import Libraries

```
import cv2
import numpy as np
import matplotlib.pyplot as plt

def display_image(img, title="Image"):
    plt.imshow(cv2.cvtColor(img, cv2.COLOR_BGR2RGB))
    plt.title(title)
    plt.axis('off')
    plt.show()

def display_images(img1, img2, title1="Image 1", title2="Image 2 "):
    plt.subplot(1,2,1)
    plt.imshow(cv2.cvtColor(img1, cv2.COLOR_BGR2RGB))
    plt.title(title1)
    plt.axis('off')

    plt.subplot(1,2,2)
    plt.imshow(cv2.cvtColor(img2, cv2.COLOR_BGR2RGB))
    plt.title(title2)
    plt.axis('off')

    plt.show()
```

3. Load Image

```
from google.colab import files
from io import BytesIO
from PIL import Image

uploaded = files.upload()

image_path = next(iter(uploaded))
image = Image.open(BytesIO(uploaded[image_path]))
image = cv2.cvtColor(np.array(image), cv2.COLOR_BGR2RGB)

display_image(image, "Original Image")
```



Choose Files Verdad.jpg

- **Verdad.jpg**(image/jpeg) - 273352 bytes, last modified: 9/9/2024 - 100% done
Saving Verdad.jpg to Verdad.jpg

Original Image



Exercise 1: Scaling and Rotation

```
def scale_image(image, scale_factor):  
    height, width = image.shape[:2]  
    scale_image = cv2.resize(image, (int(width * scale_factor), int(height * scale_factor)), interpolation=cv2.INTER_LINEAR)  
    return scale_image  
  
scaled_image = scale_image(image, 0.5)  
  
def rotate_image(image, angle):  
    height, width = image.shape[:2]  
    center = (width // 2, height // 2)  
    matrix = cv2.getRotationMatrix2D(center, angle, 1.0)  
    rotated_image = cv2.warpAffine (image, matrix, (width, height))  
    return rotated_image  
  
rotated_image = rotate_image(image, 45)  
  
# Display images side by side  
plt.figure(figsize=(6, 6))  
  
plt.subplot(1, 2, 1)  
plt.imshow(cv2.cvtColor(scaled_image, cv2.COLOR_BGR2RGB))  
plt.title("Scaled Image (50%)")  
plt.axis('off')  
  
plt.subplot(1, 2, 2)  
plt.imshow(cv2.cvtColor(rotated_image, cv2.COLOR_BGR2RGB))  
plt.title("Rotated Image (45°)")  
plt.axis('off')  
  
plt.show()
```



Scaled Image (50%)



Rotated Image (45°)



Exercise 2: Blurring Techniques and Side by Side Comparison

```
gaussian_blur = cv2.GaussianBlur(image, (25,25),0)
median_blur = cv2.medianBlur(image, 25)
bilateral_filter = cv2.bilateralFilter(image, 50, 100, 150)

# Display the side by side results for comparison
plt.figure(figsize=(11, 5))

plt.subplot(1, 3, 1)
plt.imshow(cv2.cvtColor(gaussian_blur, cv2.COLOR_BGR2RGB))
plt.title("Gaussian Blur")
plt.axis('off')

plt.subplot(1, 3, 2)
plt.imshow(cv2.cvtColor(median_blur, cv2.COLOR_BGR2RGB))
plt.title("Median Blur")
plt.axis('off')

plt.subplot(1, 3, 3)
plt.imshow(cv2.cvtColor(bilateral_filter, cv2.COLOR_BGR2RGB))
plt.title("Bilateral Filter")
plt.axis('off')

plt.show()
```



Gaussian Blur

Median Blur

Bilateral Filter




Exercise 3: Edge Detection using Canny

```
edges = cv2.Canny(image, 50, 100)
display_image(edges, "Canny Edge Detection")
```



Canny Edge Detection



September 16, 2024

Other Blurring Techniques and Side by Side Comparison

```
#BOX FILTER
def box_blur(img):
    box = cv2.boxFilter(img, -1, (20, 10))
    return box
# Apply Box filter to the uploaded image
box_blurred = box_blur(image)

#MOTION BLUR
def motion_blur(img):
    # Create motion blur kernel (size 15x15)
    kernel_size = 15
    kernel = np.zeros((kernel_size, kernel_size))
    kernel[int((kernel_size - 2) / 2), :] = np.ones(kernel_size)
    kernel = kernel / kernel_size
    # Apply motion blur
    motion_blurred = cv2.filter2D(img, -2, kernel)
    return motion_blurred
# Apply Motion blur to the uploaded image
motion_blurred = motion_blur(image)

#UNSHARP MASKING (SHARPENING)
def unsharp_mask(img):
    # Create a Gaussian blur version of the image
    blurred = cv2.GaussianBlur(img, (15, 15), 10.0)
    # Sharpen by adding the difference between the original and the blurred image
    sharpened = cv2.addWeighted(img, 1.5, blurred, -0.5, 0)
    return sharpened
# Apply Unsharp Masking to the uploaded image
sharpened_image = unsharp_mask(image)

# Display the results for comparison
plt.figure(figsize=(10, 5))

plt.subplot(1, 3, 1)
plt.imshow(cv2.cvtColor(box_blurred, cv2.COLOR_BGR2RGB))
plt.title("Box Filter")
plt.axis('off')

plt.subplot(1, 3, 2)
plt.imshow(cv2.cvtColor(motion_blurred, cv2.COLOR_BGR2RGB))
plt.title("Motion Blur")
plt.axis('off')

plt.subplot(1, 3, 3)
plt.imshow(cv2.cvtColor(sharpened_image, cv2.COLOR_BGR2RGB))
plt.title("Unsharp Mask (Sharpening)")
plt.axis('off')

plt.show()
```



Box Filter



Motion Blur



Unsharp Mask (Sharpening)



Exercise 5: Other Edge Detection and Comparison

```
# Sobel Edge Detection
def sobel_edge_detection(image):
    # Convert to grayscale
    gray = cv2.cvtColor(image, cv2.COLOR_BGR2GRAY)
    # Sobel edge detection in the x direction
    sobelx = cv2.Sobel(gray, cv2.CV_64F, 1, 0, ksize=5)
    # Sobel edge detection in the y direction
    sobely = cv2.Sobel(gray, cv2.CV_64F, 0, 1, ksize=5)
    # Combine the two gradients
    sobel_combined = cv2.magnitude(sobelx, sobely)
    # Convert to 8-bit for display
    sobel_combined = cv2.convertScaleAbs(sobel_combined)
    return sobel_combined
# Apply Sobel edge detection to the uploaded image
sobel_edges = sobel_edge_detection(image)

# Laplacian Edge Detection
def laplacian_edge_detection(img):
    # Convert to grayscale
    gray = cv2.cvtColor(img, cv2.COLOR_BGR2GRAY)
    # Apply Laplacian operator
    laplacian = cv2.Laplacian(gray, cv2.CV_64F)
    # Convert to 8-bit for display
    laplacian = cv2.convertScaleAbs(laplacian)
    return laplacian
# Apply Laplacian edge detection to the uploaded image
laplacian_edges = laplacian_edge_detection(image)

# Prewitt Edge Detection
def prewitt_edge_detection(img):
    # Convert to grayscale
    gray = cv2.cvtColor(img, cv2.COLOR_BGR2GRAY)
    # Prewitt operator kernels for x and y directions
    kernelx = np.array([[1, 0, -1], [1, 0, -1], [1, 0, -1]], dtype=int)
    kernely = np.array([[1, 1, 1], [0, 0, 0], [-1, -1, -1]], dtype=int)
    # Applying the Prewitt operator
    prewittx = cv2.filter2D(gray, cv2.CV_64F, kernelx)
    prewitty = cv2.filter2D(gray, cv2.CV_64F, kernely)
    # Combine the x and y gradients by converting to floating point
    prewitt_combined = cv2.magnitude(prewittx, prewitty)
    # Convert to 8-bit for display
    prewitt_combined = cv2.convertScaleAbs(prewitt_combined)
    return prewitt_combined
# Apply Prewitt edge detection to the uploaded image
prewitt_edges = prewitt_edge_detection(image)

# Display the results for comparison
plt.figure(figsize=(13, 5))

plt.subplot(1, 3, 1)
plt.imshow(sobel_edges, cmap='gray')
plt.title("Sobel Edge Detection")
plt.axis('off')

plt.subplot(1, 3, 2)
plt.imshow(laplacian_edges, cmap='gray')
plt.title("Laplacian Edge Detection")
plt.axis('off')

plt.subplot(1, 3, 3)
plt.imshow(prewitt_edges, cmap='gray')
plt.title("Prewitt Edge Detection")
plt.axis('off')


plt.show()
```



Sobel Edge Detection



Laplacian Edge Detection



Prewitt Edge Detection



Exercise 4: Basic Image Processor (Interactive)

```
def process_image(image, action):
    if action == 'Scale':
        return scale_image(image, 0.5)
    elif action == 'Rotate':
        return rotate_image(image, 45)
    elif action == 'Gaussian':
        return cv2.GaussianBlur(image, (25, 25), 0)
    elif action == 'Median':
        return cv2.medianBlur(image, 25)
    elif action == 'Bilateral':
        return cv2.bilateralFilter(image, 50, 100, 150)
    elif action == 'Canny':
        return cv2.Canny(image, 50, 100)
    elif action == 'Sobel':
        return sobel_edge_detection(image)
    elif action == 'Laplacian':
        return laplacian_edge_detection(image)
    elif action == 'Prewitt':
        return prewitt_edge_detection(image)
    elif action == 'Box':
        return box_blur(image)
    elif action == 'Motion':
        return motion_blur(image)
    elif action == 'Unsharp':
        return unsharp_mask(image)
    else:
        return image
```


```
action = input("Enter action (Scale, Rotate, Gaussian, Median, Bilateral, Canny, Sobel, Laplacian, Prewitt, Box, Motion, Unsharp): ")
processed_image = process_image(image, action)
display_images(image, processed_image, "Original Image", f"Processed Image ({action})")
```

Enter action (Scale, Rotate, Gaussian, Median, Bilateral, Canny, Sobel, Laplacian, Prewitt, Box, Motion, Unsharp): Sobel

Original Image



Processed Image (Sobel)



COMPARISON OF ALL PROCESSED IMAGE

```
# Display the Original Image
display_image(image, "Original Image")
```



Original Image



Blurring Techniques

```
# Display the Blurring Techniques results for comparison
plt.figure(figsize=(13,5))

plt.subplot(1, 3, 1)
plt.imshow(cv2.cvtColor(gaussian_blur, cv2.COLOR_BGR2RGB))
plt.title("Gaussian Blur")
plt.axis('off')

plt.subplot(1, 3, 2)
plt.imshow(cv2.cvtColor(median_blur, cv2.COLOR_BGR2RGB))
plt.title("Median Blur")
plt.axis('off')

plt.subplot(1, 3, 3)
plt.imshow(cv2.cvtColor(bilateral_filter, cv2.COLOR_BGR2RGB))
plt.title("Bilateral Filter")
plt.axis('off')

plt.figure(figsize=(13, 5))
plt.subplot(1, 3, 1)
plt.imshow(cv2.cvtColor(box_blurred, cv2.COLOR_BGR2RGB))
plt.title("Box Filter")
plt.axis('off')

plt.subplot(1, 3, 2)
plt.imshow(cv2.cvtColor(motion_blurred, cv2.COLOR_BGR2RGB))
plt.title("Motion Blur")
plt.axis('off')

plt.subplot(1, 3, 3)
plt.imshow(cv2.cvtColor(sharpened_image, cv2.COLOR_BGR2RGB))
plt.title("Unsharpened Mask")
plt.axis('off')

plt.show()
```



Gaussian Blur



Box Filter

Median Blur



Motion Blur

Bilateral Filter



Unsharpened Mask



Edge Detection Compilation

```
# Display the Edge Detection results for comparison
plt.figure(figsize=(15, 10))
plt.subplot(1, 4, 1)
plt.imshow(cv2.cvtColor(edges, cv2.COLOR_BGR2RGB))
plt.title("Canny Edge Detection")
plt.axis('off')
plt.subplot(1, 4, 2)
plt.imshow(cv2.cvtColor(sobel_edges, cv2.COLOR_BGR2RGB))
plt.title("Sobel Edge Detection")
plt.axis('off')
plt.subplot(1, 4, 3)
plt.imshow(cv2.cvtColor(laplacian_edges, cv2.COLOR_BGR2RGB))
plt.title("Laplacian Edge Detection")
plt.axis('off')
plt.subplot(1, 4, 4)
plt.imshow(cv2.cvtColor(rewitt_edges, cv2.COLOR_BGR2RGB))
plt.title("Prewitt Edge Detection")
plt.axis('off')
plt.show()
```




Canny Edge Detection



Sobel Edge Detection



Laplacian Edge Detection



Prewitt Edge Detection

